



NASA SP-7037 (31)

N73-26991

AERONAUTICAL ENGINEERING

A SPECIAL BIBLIOGRAPHY

WITH INDEXES

Supplement 31

MAY 1973

CASE FILE
COPY

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

ACCESSION NUMBER RANGES

Accession numbers cited in this Supplement fall within the following ranges:

IAA (A-10000 Series)	A73-18893—A73-21844
----------------------	---------------------

STAR (N-10000 Series)	N73-15978—N73-17998
-----------------------	---------------------

This bibliography was prepared by the NASA Scientific and Technical Information Facility operated for the National Aeronautics and Space Administration by Informatics Tisco, Inc.

The Administrator of the National Aeronautics and Space Administration has determined that the publication of this periodical is necessary in the transaction of the public business required by law of this Agency. Use of funds for printing this periodical has been approved by the Director of the Office of Management and Budget through July 1, 1974.

AERONAUTICAL ENGINEERING

A Special Bibliography

Supplement 31

A selection of annotated references to unclassified reports and journal articles that were introduced into the NASA scientific and technical information system and announced in April 1973 in

- *Scientific and Technical Aerospace Reports (STAR)*
- *International Aerospace Abstracts (IAA).*



This Supplement is available from the National Technical Information Service (NTIS), Springfield, Virginia 22151, for \$3.00. For copies mailed to addresses outside the United States, add \$2.50 per copy for handling and postage.

INTRODUCTION

Under the terms of an interagency agreement with the Federal Aviation Administration this publication has been prepared by the National Aeronautics and Space Administration for the joint use of both agencies and the scientific and technical community concerned with the field of aeronautical engineering. The first issue of this bibliography was published in September 1970 and the first supplement in January 1971. Since that time, monthly supplements have been issued.

This supplement to *Aeronautical Engineering—A Special Bibliography* (NASA SP-7037) lists 307 reports, journal articles, and other documents originally announced in April 1973 in *Scientific and Technical Aerospace Reports (STAR)* or in *International Aerospace Abstracts (IAA)*.

The coverage includes documents on the engineering and theoretical aspects of design, construction, evaluation, testing, operation, and performance of aircraft (including aircraft engines) and associated components, equipment, and systems. It also includes research and development in aerodynamics, aeronautics, and ground support equipment for aeronautical vehicles.

Each entry in the bibliography consists of a standard bibliographic citation accompanied in most cases by an abstract. The listing of the entries is arranged in two major sections, *IAA Entries* and *STAR Entries*, in that order. The citations, and abstracts when available, are reproduced exactly as they appeared originally in *IAA* or *STAR*, including the original accession numbers from the respective announcement journals. This procedure, which saves time and money, accounts for the slight variation in citation appearances.

Three indexes—subject, personal author, and contract number—are included.

An annual cumulative index will be published.

AVAILABILITY OF CITED PUBLICATIONS

IAA ENTRIES (A73-10000 Series)

All publications abstracted in this Section are available from the Technical Information Service, American Institute of Aeronautics and Astronautics, Inc., (AIAA), as follows: Paper copies are available at \$5.00 per document up to a maximum of 20 pages. The charge for each additional page is 25 cents. Microfiche⁽¹⁾ are available at the rate of \$1.00 per microfiche for documents identified by the # symbol following the accession number. A number of publications, because of their special characteristics, are available only for reference in the AIAA Technical Information Service Library. Minimum airmail postage to foreign countries is \$1.00. Please refer to the accession number, e.g., A73-10468, when requesting publications.

STAR ENTRIES (N73-10000 Series)

A source from which a publication abstracted in this Section is available to the public is ordinarily given on the last line of the citation, e.g., Avail: NTIS. The following are the most commonly indicated sources (full addresses of these organizations are listed at the end of this introduction):

Avail: NTIS. Sold by the National Technical Information Service as indicated:

Currently Announced Documents. Facsimile (reproduced on demand) copies are sold for \$3.00 plus 25 cents for every 5 pages over 20 pages, effective for all documents having the accession number N72-22991 (the first accession in 1972 STAR 14) or higher. The full price is shown in the citation.

Printed NASA Documents. Documents such as NASA Technical Reports, Technical Notes, Special Publications, Contractor Reports, Technical Memorandums (numbered below 50,000), and Technical Translations (below 8,000) are priced at \$3.00 for documents of 300 pages or less; \$6.00 for those in the 301-600 page range, \$9.00 for those having 601-900 pages; and individually priced above 900 pages. Documents available from both the Superintendent of Documents (SOD), Government Printing Office, and from NTIS have the SOD price. All prices are shown in the citation.

Documents Announced Between July 1970 and July 1972. All documents with accession numbers between N70-27805 and N72-22990 are sold at the previously announced standard price, whether printed copy or facsimile is supplied. If "Avail: NTIS" appears in the citation, the document is sold at \$3.00. Any other price is shown in the citation.

Documents Announced Prior to July 1970. A surcharge of \$3.00 is applied to each document that, as of STAR Issue 14, 1972, is two years old from the time of its announcement, i.e., to all documents with an accession number lower than N70-27805 (the first accession number in Issue 14, 1970, of STAR), but not to more recently issued documents. Therefore, documents with older accession numbers of 300 pages or less are priced at a total of \$6.00. Since no surcharge is applied to documents with over 300 pages, documents in the 301- to 600-page range are also sold for \$6.00 in hard copy, and those in the 601- to 900-page range are sold at \$9.00. Those exceeding 900 pages are priced by NTIS on an individual basis, except when priced by SOD. These prices do not change with time.

(1) A microfiche is a transparent sheet of film, 105 x 148 mm in size, containing as many as 60 to 98 pages of information reduced to micro images (not to exceed 24:1 reduction).

Microfiche. Microfiche is available from NTIS at a standard price of 95 cents (regardless of age) for those documents identified by the # sign following the accession number (e.g., N73-10281#) and having an NTIS availability shown in the citation. Standing orders for microfiche of (1) the full collection of NTIS-available documents announced in *STAR* with the # symbol, (2) NASA reports only (identified by an asterisk (*)), (3) NASA-accessioned non-NASA reports only (for those who wish to maintain an integrated microfiche file of aerospace documents by the "N" accession number), or (4) any of these classes within one or more *STAR* categories, also may be placed with NTIS at greatly reduced prices per title (e.g., 35 cents) over individual requests. Inquiries concerning NTIS Selective Categories in Microfiche should be addressed to the Subscription Unit, National Technical Information Service.

Deposit Accounts and Customers Outside U.S. NTIS encourages its customers to open deposit accounts to facilitate the purchase of its documents now that prices vary so greatly.

NTIS customers outside the United States are reminded that they should add the following handling and postage charges to the standard or announced prices: hard (paper) copy, \$2.50 each document; microfiche, \$1.50 each document. For subscribers outside the United States who receive microfiche through the Selective Categories in Microfiche program, NTIS will add 15 cents for each title shipped.

Avail: SOD (or GPO). Sold by the Superintendent of Documents, U.S. Government Printing Office, in hard copy. The price is given following the availability line. (An order received by NTIS for one of these documents will be filled at the SOD price if hard copy is requested. NTIS will also fill microfiche requests, at the standard 95 cent price, for those documents identified by a # symbol.)

Avail: NASA Public Document Rooms. Documents so indicated may be examined at or purchased from the National Aeronautics and Space Administration, Public Documents Room (Room 126), 600 Independence Ave., S.W., Washington, D.C. 20546, or public document rooms located at each of the NASA research centers, the Mississippi Test Facility, and the NASA Pasadena Office at the Jet Propulsion Laboratory.

Avail: NASA Scientific and Technical Information Office. Documents with this availability are usually news releases or informational brochures available without charge in paper copy.

Avail: AEC Depository Libraries. Organizations in U.S. cities and abroad that maintain collections of U.S. Atomic Energy Commission reports, usually in microfiche form, are listed in *Nuclear Science Abstracts*. Services available from the USAEC and its depositories are described in a booklet, *Science Information Available from the Atomic Energy Commission* (TID-4550), which may be obtained without charge from the USAEC Technical Information Center.

Avail: Univ. Microfilms. Documents so indicated are dissertations selected from *Dissertation Abstracts*, and are sold by University Microfilms as xerographic copy (HC) at \$10.00 each and microfilm at \$4.00 each, regardless of the length of the manuscript. Handling and shipping charges are additional. All requests should cite the author and the Order Number as they appear in the citation.

Avail: HMSO. Publications of Her Majesty's Stationery Office are sold in the U.S. by Pendragon House, Inc., (PHI), Redwood City, California. The U.S. price (including a service charge) is given, or a conversion table may be obtained from PHI.

Avail: National Lending Library, Boston Spa, England. Sold by this organization at the price shown. (If none is given, an inquiry should be addressed to NLL.)

Avail: ZLDI. Sold by the Zentralstelle für Luftfahrtokumentation und -Information, Munich, Federal Republic of Germany, at the price shown in deutschmarks (DM).

Avail: Issuing Activity, or Corporate Author, or no indication of availability: Inquiries as to the availability of these documents should be addressed to the organization shown in the citation as the corporate author of the document.

Avail: U.S. Patent Office. Sold by Commissioner of Patents, U.S. Patent Office, at the standard price of \$.50 each, postage free.

Other availabilities: If the publication is available from a source other than the above, the publisher and his address will be displayed entirely on the availability line or in combination with the corporate author line.

GENERAL AVAILABILITY

All publications abstracted in this bibliography are available to the public through the sources as indicated in the *STAR Entries* and *IAA Entries* sections. It is suggested that the bibliography user contact his own library or other local libraries prior to ordering any publication inasmuch as many of the documents have been widely distributed by the issuing agencies, especially NASA. A listing of public collections of NASA documents is included on the inside back cover.

SUBSCRIPTION AVAILABILITY

This publication is available on subscription from the National Technical Information Service (NTIS). The annual subscription rate for the monthly supplements, excluding the annual cumulative index, is \$18.00. All questions relating to subscriptions should be referred to the NTIS.

ADDRESSES OF ORGANIZATIONS

American Institute of Aeronautics
and Astronautics
Technical Information Service
750 Third Ave.
New York, N.Y. 10017

Commissioner of Patents
U.S. Patent Office
Washington, D.C. 20231

Engineering Sciences Data Unit Ltd.
251-259 Regent Street
London W1R 7AD, England

ESRO/ELDO Space Documentation Service
European Space Research Organization
114, av. Charles de Gaulle
92-Neuilly-sur-Seine, France

Her Majesty's Stationery Office
P.O. Box 569, S.E. 1
London, England

NASA Scientific and Technical Information
Facility
P.O. Box 33
College Park, Maryland 20740

National Aeronautics and Space
Administration
Scientific and Technical Information
Office (KSI)
Washington, D.C. 20546

National Lending Library for Science
and Technology
Boston Spa, Yorkshire, England

National Technical Information Service
Springfield, Virginia 22151

Pendragon House, Inc.
899 Broadway Avenue
Redwood City, California 94063

Superintendent of Documents
U.S. Government Printing Office
Washington, D.C. 20402

University Microfilms, Inc.
A Xerox Company
300 North Zeeb Road
Ann Arbor, Michigan 48106

University Microfilms, Inc.
Tylers Green
London, England


U.S. Atomic Energy Commission
Technical Information Center
P.O. Box 62
Oak Ridge, Tennessee 37830

Zentralstelle für Luftfahrt-doku-
mentation und-Information
8 München 86
Postfach 880
Federal Republic of Germany


TABLE OF CONTENTS


	Page
IAA Entries	143
STAR Entries	157
Subject Index	A-1
Personal Author Index	B-1
Contract Number Index	C-1

TYPICAL CITATION AND ABSTRACT FROM STAR



TYPICAL CITATION AND ABSTRACT FROM IAA





AERONAUTICAL ENGINEERING

A Special Bibliography (Suppl. 31)

MAY 1973

IAA ENTRIES

A73-18899 Systems for collision avoidance. J. H. Reed (U.S. Department of Transportation, National Transportation Safety Board, Washington, D.C.). (*Air Traffic Control Association, Annual Meeting, 17th, Chicago, Ill., Oct. 8-11, 1972.*) *Journal of Air Traffic Control*, vol. 15, Jan.-Feb. 1973, p. 5-7.

Evaluation of midair collision accident data and near collision data over the past several years indicates that there is no single remedial solution to the midair collision hazard. Assessments indicated that 49% of the accidents could have been avoided if all aircraft had been radio equipped and adhered to improved procedures requiring mandatory position calls in the vicinity of uncontrolled airport areas. It was also indicated that 24% of the accidents could have been avoided if there had been published standard traffic patterns at all airports. F.R.L.

A73-18900 Ground based CAS versus Airborne CAS. R. E. Erickson (Honeywell, Inc., Minneapolis, Minn.). (*Air Traffic Control Association, Annual Meeting, 17th, Chicago, Ill., Oct. 8-11, 1972.*) *Journal of Air Traffic Control*, vol. 15, Jan.-Feb. 1973, p. 10-13.

It is considered that there is a growing need for air-derived collision prevention systems in airspace that is not under positive control. Honeywell's interrogator/transponder concept has been proven in the operation and flight evaluation of systems delivered to the U.S. Army. An operational pilot warning indicator, a tested, advanced proximity warning indicator which includes relative bearing information, and a prototype collision warning system which has successfully undergone an extensive Army flight evaluation are described. Any system within this family of devices will communicate and function operationally with any of the others. F.R.L.

A73-19088 Damping configurations that have a stabilizing influence on nonconservative systems. G. T. S. Done (Edinburgh, University, Edinburgh, Scotland). *International Journal of Solids and Structures*, vol. 9, Feb. 1973, p. 203-215. 15 refs.

A73-19097 Analysis of internally generated sound in continuous materials. III - The momentum potential field description of fluctuating fluid motion as a basis for a unified theory of

internally generated sound. P. E. Doak (Southampton, University, Southampton, England). *Journal of Sound and Vibration*, vol. 26, Jan. 8, 1973, p. 91-120. 5 refs. Contract No. F33615-71-C-1663.

A73-19099 * The status of engineering knowledge concerning the damping of built-up structures. E. E. Ungar (Bolt Beranek and Newman, Inc., Cambridge, Mass.). *Journal of Sound and Vibration*, vol. 26, Jan. 8, 1973, p. 141-154. 35 refs. Contract No. NAS1-9557-17.

The importance of the effects of structural joints on the damping of built-up structures is pointed out, and the energy dissipation mechanisms associated with squeezing, rocking, and shearing motions are discussed for simple joints that are dry, lubricated, or provided with viscoelastic inserts. The damping mechanisms and behaviors of built-up beams and of skin-stringer structures are discussed as far as they are currently understood, and available damping estimation methods are summarized. Difficulties in defining and measuring the damping of skin-stringer structures are indicated, and it is pointed out that particularly the high-frequency damping of built-up beams and the low-frequency damping of skin-stringer configurations require further investigation. (Author)

A73-19141 # The Aeronautical Satellite Programme - ATC aspects. M. O'Hagan (Plessey Radar, Ltd., Weybridge, Surrey, England). (*British Interplanetary Society, Symposium on Communications Satellites, University of Southampton, Southampton, England, Sept. 19, 20, 1972.*) *British Interplanetary Society, Journal*, vol. 26, Feb. 1973, p. 90-96.

In this paper the current practice in oceanic Air Traffic Control (ATC) is reviewed, the facilities offered by the Aerosat system are discussed, and some of the operational effects of its introduction are identified. (Author)

A73-19182 # Collection and processing of data for the establishment of route charges. L. Putz. *Eurocontrol*, vol. 2, no. 6, 1972, p. 4-8. Translation.

A73-19183 # The experimental data processor. W. D. Miller. *Eurocontrol*, vol. 2, no. 6, 1972, p. 9-12.

Description of an experimental data processor intended as a test bed on which the concepts implied by ATC systems could be proven both technically and operationally. This data processor is a scale working model of a semiautomatic digital ATC en route control system and incorporates most advanced computer techniques. A two-level concept of main processors and display processors is employed. The task of the main processors is to create and maintain up to date an internal image of the total ATC system in the form of a data bank using plan, radar, and associating plan/radar logics. The

A73-19184

display processors act, on the one hand, as the display message filter and switching system ensuring that the data are steered to the correct controller at the correct time, and, on the other, as the handler of controller input commands for system control purposes. A.B.K.

A73-19184 * # Automated radar terminal systems (ARTS). A. R. Ridenour. *Eurocontrol*, vol. 2, no. 6, 1972, p. 22-25.

Description of the design and operation of a new automated radar terminal system (ARTS III) which simplifies the acquisition and maintenance of radar identification of aircraft on the radar display and provides the controller with beacon-derived altitude data to help reduce verbal coordination and communications workload. In the basic ARTS III beacon-tracking level system, individual tags of alphanumeric data are written on the controller's display. The tags are kept tied to their appropriate beacon target by the computer tracking program. Communication from the controller to the ARTS III computer is accomplished with data entry devices provided at each control position. The actual sequence of operation with ARTS III is described, and numerous improvements in the conditions of air traffic control at Chicago's O'Hare International Airport since ARTS III became fully operational at that facility are noted. A.B.K.

A73-19188 * # Approximate analysis of containment/deflection ring responses to engine rotor fragment impact. R. W. H. Wu and E. A. Witmer (MIT, Cambridge, Mass.). *Journal of Aircraft*, vol. 10, Jan. 1973, p. 28-37. 21 refs. Grant No. NGR-22-009-339.

The transient responses of containment and/or deflection rings to impact from an engine rotor-blade fragment are analyzed. Energy and momentum considerations are employed in an approximate analysis to predict the collision-induced velocities which are imparted to the fragment and to the affected ring segment. This collision analysis is combined with the spatial finite-element representation of the ring and a temporal finite-difference solution procedure to predict the resulting large transient elastic-plastic deformations of containment/deflection rings. Some comparisons with experimental data are given. (Author)

A73-19189 * # Hypersonic flows in large-scale inlet models. W. R. Seebaugh (Fairchild Industries, Inc., Farmingdale, N.Y.). *Journal of Aircraft*, vol. 10, Jan. 1973, p. 38-44. 9 refs. Contracts No. NAS2-5052; No. NAS2-5719.

Analytical and experimental investigations were conducted to determine the characteristics of the internal flows in model passages representative of inlets for a typical Mach 12 hypersonic cruise vehicle and also sufficiently large for reliable data to be obtained. Three large-scale inlet models, each having a different internal compression ratio, were designed to provide maximum performance at the throat stations. Tests were conducted in the Mach 7.4 nozzle of the NASA Ames 3.5-foot hypersonic wind tunnel at a nominal test Reynolds number of 2,700,000 per ft. The experimental results revealed that a high level of total pressure recovery, approximately 0.85 (relative to the inlet-entrance conditions) for the core flow of the internal passage, was achieved for each inlet design. (Author)

A73-19191 * # Model tests on unsteady rotor wake effects. K. H. Hohenemser and S. T. Crews (Washington University, St. Louis, Mo.). *Journal of Aircraft*, vol. 10, Jan. 1973, p. 58-60. 6 refs. Contract No. NAS2-4151.

A qualitative model of unsteady asymmetric wake effects is considered, taking into account a progressing blade flapping mode in which each blade flaps in a rotating frame of reference. The rotor model used for the tests is two bladed. The experimental data are compared with an analytical flapping response. It is found that the

steady wake effects are largest at zero advance ratio and low collective pitch. The effects remain significant at higher advance ratios and collective pitch settings. G.R.

A73-19192 * # Conformal mapping for potential flow about airfoils with attached flap. V. J. Rossow (NASA, Ames Research Center, Moffett Field, Calif.). *Journal of Aircraft*, vol. 10, Jan. 1973, p. 60-62. 6 refs.

The conformal mapping sequence presented transforms the potential flow about a circle into that about an airfoil with an attached flap or spoiler. It is found that adequate versatility of the flap shape for a given airfoil can usually be obtained with the indicated functions, although other transformations would expand the variety of possible flap shapes. G.R.

A73-19193 # Aircraft wing-tip vortex modification. P. O. Jarvinen (Sanders Associates, Inc., Nashua, N.H.). *Journal of Aircraft*, vol. 10, Jan. 1973, p. 63, 64. 10 refs.

The results of a low speed experimental wind tunnel study of the modification of a wing tip vortex are discussed, taking into account a tip mounted, upstream facing jet. Smoke flow visualization photographs show substantial enlargement of the vortex with increases in the jet momentum coefficient. Vorticity meter data are shown in a graph as a function of the jet momentum coefficient. G.R.

A73-19197 The effect of the degree of turbulence on the aerodynamic characteristics of planar decelerating cascades (Einfluss des Turbulenzgrads auf die aerodynamischen Eigenschaften von ebenen Verzögerungsgittern). R. Kiock (Deutsche Forschungs- und Versuchsanstalt für Luft- und Raumfahrt, Institut für Aerodynamik, Braunschweig, West Germany). *Forschung im Ingenieurwesen*, vol. 39, no. 1, 1973, p. 17-28. 36 refs. In German. Research supported by the Deutsche Forschungsgemeinschaft.

The efficiency of the blading of a turbomachine depends mainly on the flow in the boundary layer at the blades and the separation characteristics. The flow in the boundary layer is significantly affected by the turbulence of the flow to the cascade, particularly in the case of small Reynolds numbers. The calculation of the frictionless degree of turbulence on the basis of the velocity distribution behind the cascade is considered, taking into account the potential theory. The computed degree of turbulence is compared with measured data obtained for various stages of an axial-flow compressor. G.R.

A73-19205 Calculation of the potential flow about axisymmetrical fuselages, annular profiles, and propulsion system inlets (Berechnung der Potentialströmung um rotationssymmetrische Rümpfe, Ringprofile und Triebwerkseinläufe). W. Geissler (Aerodynamische Versuchsanstalt, Göttingen, West Germany). (*Deutsche Gesellschaft für Luft- und Raumfahrt, Jahrestagung, 4th, Baden-Baden, West Germany, Oct. 11-13, 1971.*) *Zeitschrift für Flugwissenschaften*, vol. 20, Dec. 1972, p. 457-462. 9 refs. In German.

The calculation of the potential flow about bodies of revolution (closed bodies, inlets, cowlings) is done by a method using surface distributions of sources, sinks and vortices. This method deals with the case of an arbitrary flow about the body. Besides of axisymmetric flows and flows at incidence to the body axis it is possible to take care of the flow field induced by another body (interference problem). A panel method is used for the numerical solution of the

problem. In the case of an axisymmetric body the surface elements are frustrums of cones of small axial length. For different types of bodies the results of this method are compared with measurements. (Author)

A73-19347 # The pre-flight handling of inertial navigation systems. K. R. Brown and W. H. McKinlay. (Ferranti, Ltd., Holinwood, Lancs., England). *Journal of Navigation*, vol. 26, Jan. 1973, p. 13-20.

The accuracy afforded by inertial navigation systems is strongly affected by correct handling of the unit prior to takeoff. Basic system requirements and some detailed engineering considerations that affect operations taking place in an inertial navigator during the initial or preflight alignment sequence are explained in an attempt at evaluating possibilities for more rapid alignment. Recent studies show that it is possible to align the system with the instruments at the temperature existing at switch-on and with the wheel at low speed. Rapid heating is then applied when the system is navigating, and the wheels are accelerated to full speed at this time. The procedure results in considerable time savings. T.M.

A73-19348 # The growth of aircraft movements by 1985. (International Air Transport Association, Technical Conference, 19th, Dublin, Ireland, Oct. 1972.) *Journal of Navigation*, vol. 26, Jan. 1973, p. 26-32.

Forecast of the 1985 volume of aircraft traffic between selected city pairs and at individual terminal areas in Europe, North America, South America, and the Far East. Details of the forecasting technique are explained, and the tabulated results are examined in relation to the magnitude of the traffic handling task which can be expected to face the airline industry by 1985. T.M.

A73-19349 # Air traffic control by programmed navigation. K. Ramsayer (Stuttgart, Universität, Stuttgart, West Germany). (International Air Transport Association, Technical Conference, 19th, Dublin, Ireland, Oct. 1972.) *Journal of Navigation*, vol. 26, Jan. 1973, p. 33-36.

Description of a general scheme for automatic control and navigation of commercial air traffic in the future. Each aircraft is to fly according to a prescribed flight plan elaborated by a central air traffic control station and transmitted by data link to an airborne computer which monitors the navigation of the aircraft. The flight plan specifies positions, altitudes, and time within prescribed tolerances, and the navigation itself is based on an integrated inertial-DME system. T.M.

A73-19350 # A precision position and time service for the air traffic of the future. L. F. Fehlner and T. A. McCarty (Johns Hopkins University, Baltimore, Md.). (International Air Transport Association, Technical Conference, 19th, Dublin, Ireland, Oct. 1972.) *Journal of Navigation*, vol. 26, Jan. 1973, p. 37-54. 26 refs.

Extended Loran-C coverage is proposed as the key element of a precision position and time reference system for terminal and area navigation in a future air traffic control network. Maps show locations of 1.6-MW transmitters providing ground-wave coverage of the continental U.S. (17 stations) and Europe (19 stations). A Loran-C receiver in the aircraft measures the horizontal coordinates, and a calibrated digital barometric altimeter measures the vertical coordinate in the common grid system. The airborne navigation computer can be tied by data link to a ground-based central air-traffic control computer that elaborates and updates the flight plans. Sky-wave coverage over the North Atlantic provides control in that area. It is argued that the system cannot be saturated by increasing air traffic volume, and the well developed Loran-C technology offers reliable precision at substantial savings. T.M.

A73-19351 How can we use area navigation in the terminal area. N. H. Hughes (Royal Aircraft Establishment, Farnborough, Hants., England). (International Air Transport Association, Technical Conference, 19th, Dublin, Ireland, Oct. 1972.) *Journal of Navigation*, vol. 26, Jan. 1973, p. 55-60.

It is argued that currently available area navigation systems are incompatible with present terminal ATC approach sequencing procedures. Benefits which may result from the integration of area navigation systems with terminal ATC systems do not necessarily include increased traffic density since runway capacity is restricted by trailing-vortex and runway occupancy-time constraints. Such integration is only possible if computer assistance to the approach controller is combined with a data link between the ATC computer and the aircraft navigation system. The use of vertical navigation is suggested as a valuable first step to combined area and terminal control. T.M.

A73-19352 # The capacity of a single-runway S.T.O.L./R.T.O.L. airport. V. W. Attwooll and C. P. Hayfield. (International Air Transport Association, Technical Conference, 19th, Dublin, Ireland, Oct. 1972.) *Journal of Navigation*, vol. 26, Jan. 1973, p. 61-74. 7 refs.

The arrival and departure operations of three different types (100, 180, and 400 seats) of hypothetical STOL aircraft at a single-runway airport are examined in order to delineate factors affecting the traffic handling capacity. It is assumed that the airport operates without interference from conventional takeoff and landing (CTOL) aircraft. It is shown that separation requirements produced by turbulent-wake effects could strongly reduce the handling capacity. Aircraft design solutions to the turbulent-wake problem are particularly urged for the heavier versions of STOL aircraft. T.M.

A73-19403 # Calculation of the reliability of electronic components in an 'aeronautics' environment shaped by the operational service routines of onboard equipment devices used by Air France (Calcul de la fiabilité de composants électroniques dans l'environnement 'aviation' à partir du suivi d'exploitation d'équipements de bords utilisés par la compagnie Air-France). D. Levy (CNET, Centre de Fiabilité, Bagneux, Hauts-de-Seine, France). In: National Congress on Reliability; Perros-Guirec, Côtes-du-Nord, France, September 20-22, 1972, Text of the Lectures.

Paris, Centre National d'Etudes des Télécommunications, 1972, p. 41-47. In French.

A73-19468 # Mathematical model of nonstationary linear aeroautoelasticity (Matematicheskaya model' nestatsionarnoi lineinoi aeroavtougosti). S. M. Belotserkovskii. *Akademiia Nauk SSSR, Doklady*, vol. 27, Nov. 21, 1972, p. 557-559. In Russian.

The behavior of an elastic flight body is analyzed that moves through a continuous medium. The study of its flight control involves the combined solution of problems of aerodynamics, automatic control, and elasticity theory. This problem complex is therefore termed aeroautoelasticity. The analysis uses a rigorous approach based on linear nonstationary theory. M.V.E.

A73-19554 How practical are lab-oriented solid film lubricants. B. K. Gabel (U.S. Naval Material Command, Naval Air Development Center, Warminster, Pa.). In: Assessment of lubricant technology; Proceedings of the Annual Spring Lubrication Symposium, Boston, Mass., June 6-8, 1972. New York, American Society of Mechanical Engineers, 1972, p. 15-19. 7 refs.

Discussion of some of the problems associated with the use of

solid-film lubrication on aircraft components. Special attention is given to surface precleaning and roughening, lubricant-film application and curing, and susceptibility to contamination and corrosion. Aerosol applicability, extended shelf life, and the development of corrosion-preventive properties are also reviewed. M.V.E.

A73-19563 The influence of lubricants on turbine engine design. T. E. Russell and J. E. Methlie (General Electric Co., Cincinnati, Ohio). In: Assessment of lubricant technology; Proceedings of the Annual Spring Lubrication Symposium, Boston, Mass., June 6-8, 1972. New York, American Society of Mechanical Engineers, 1972, p.135-142. 6 refs.

This paper addresses the problem of predicting the influence of lubricants on advanced gas turbine engine design and stresses the system's concept. Presented are discussion and supporting analytical techniques to indicate the relative importance of several lubricant properties as they pertain to the operation of a gas turbine engine. The properties considered are bulk oil stability, hot spot stability, vapor pressure, autoignition temperature, pumpability, gear load capacity and bearing life. Potential deficiencies in current criteria as applied to possible future high temperature designs and areas for further research are also indicated. (Author)

A73-19575 # Minimum performance standards - Airborne distance measuring equipment /DME/ operating within the radio-frequency range of 960-1215 megahertz. Washington, D.C., Radio Technical Commission for Aeronautics (Document No. DO-151), 1972. 61 p. \$6.00.

A73-19578 # The steady and unsteady aerodynamic coefficients for the rolling motion of slender wings (Über die stationären und instationären aerodynamischen Beiwerte für die Rollbewegung schlanker Flügel). F. Schlottmann. Bochum, Ruhr-Universität, Abteilung für Maschinenbau und Konstruktiven Ingenieurbau, Dr.-Ing. Dissertation, 1972. 120 p. 86 refs. In German. Research supported by the Nordrhein-Westfalen Landesamt für Forschung.

A test installation was developed for determining the aerodynamic forces acting on airfoils in the case of steady and unsteady rolling motions in a low-speed wind tunnel. The principles of operation of the test installation are described together with the measurement instruments employed. The rolling moment produced by the motion was determined as a function of roll angular velocity, its temporal derivative, and the angle of attack. The experimental results are compared with theoretical values obtained on the basis of linear and nonlinear steady airfoil theory or with the aid of linear unsteady theory. The occurrence of nonlinear effects is observed.

G.R.

A73-19604 # Hydraulic systems of modern aircraft. II (Układy hydrauliczne współczesnych samolotów. II). J. Filip. *Technika Lotnicza i Astronautyczna*, vol. 27, Dec. 1972, p. 15-17, 34. In Polish.

Description of hydraulic drive and control systems used for landing-gear retraction and extension on the Piper Cherokee Arrow and for main-wheel braking on the F-111. Some new applications of hydraulic drive systems for engine cranking and starting operations are also discussed. T.M.

A73-19605 # Development trends in aircraft-engine compressor design methods. III (Kierunki rozwoju metod projektowania sprężarek silników lotniczych. III). W. Kordzinski. *Technika Lotnicza i Astronautyczna*, vol. 27, Dec. 1972, p. 18, 25, 26. In

Polish.

Simplified methods (based on two-dimensional flow theory) for the design of vaneless and bladed diffusers in centrifugal compressors are critically evaluated. Emphasis is placed on the drawbacks of existing computational procedures, and it is noted that the lack of systematic research on centrifugal compressors results in a situation where final performance characteristics depend on the intuition and luck of the designer. T.M.

A73-19625 An investigation of the intensity of turbulence in the region of the inflow of a jet of secondary air into the firing tube of a gas turbine engine chamber. G. M. Gorbunov, A. V. Peshkov, I. L. Khristoforov, and M. V. Emmil'. (*Aviatsionnaia Tekhnika*, vol. 14, no. 4, 1971, p. 38-43.) *Fluid Mechanics - Soviet Research*, vol. 1, Sept.-Oct. 1972, p. 170-175. 7 refs. Translation.

The intensity of mixing processes resulting from the crosswind injection of a system of circular jets is governed by the jet parameters, the depth of jet penetration, and the turbulence induced by jet wakes. Hot-wire anemometers were used to measure turbulence intensity near the inlet of a single jet and behind several jets of secondary air injected into the flame tube of a gas turbine engine. Results show that the use of optimally spaced transverse jets with a given depth of penetration makes it possible to attain a high level of turbulence that ensures active mixing of air and fuel. T.M.

A73-19942 A description of two low cost turbo-compressors built for powered lift research. J. A. Conway and K. A. J. Lockwood (de Havilland Aircraft of Canada, Ltd., Downsview, Ontario, Canada). (*Canadian Aeronautics and Space Institute, Annual General Meeting, Toronto, Canada, May 18, 19, 1972.*) *Canadian Aeronautics and Space Journal*, vol. 18, Dec. 1972, p. 319, 320, M-2 to M-4.

A73-19952 * # Second derivatives of the flutter velocity and the optimization of aircraft structures. C. S. Rudisill (Clemson University, Clemson, S.C.) and K. G. Bhatia (NASA, Langley Research Center, Hampton, Va.). *AIAA Journal*, vol. 10, Dec. 1972, p. 1569-1572. Grant No. NGR-41-001-027.

Equations for the second partial derivatives of the eigenvalues of the flutter equation along with the equations for finding the second partial derivatives of the flutter velocity of an aircraft structure with respect to the structural parameters are derived. These partial derivatives are used to develop expressions for the step size in a projected gradient search along a constant mass hyperplane. A projected gradient search along with a gradient mass and a gradient velocity search is used to minimize the mass of a box beam which supports a lifting surface. (Author)

A73-19954 # Flow in the wake of a cascade of oscillating airfoils. W. P. Jones and J. A. Moore (Texas A & M University, College Station, Tex.). *AIAA Journal*, vol. 10, Dec. 1972, p. 1600-1605. 11 refs. Grant No. DA-ARO(D)-31-124-71-G153.

A study has been made of the amplitude and phase of the vertical oscillations in the wake behind (1) a cascade of airfoils oscillating in phase and (2) a cascade of airfoils at zero incidence with oscillating flaps. It was found that in both cases the amplitude of the flow oscillations in the wake remained approximately constant downstream for the values of frequency parameter and airfoil spacing considered. From the results of some preliminary experimental work it appears that sinusoidal gusts could be reproduced in an open jet wind tunnel with either system, but the second type of airfoil-flap arrangement is preferable in practice. The difficulties resulting from flow separation and early stalling which arise with the first system do not appear until much higher angular amplitudes are used when only the flaps are oscillated. (Author)

A73-19955 # Boundary-layer separation on rotating blades in forward flight. W. H. Young, Jr. and J. C. Williams (North Carolina State University, Raleigh, N.C.). *AIAA Journal*, vol. 10, Dec. 1972, p. 1613-1619. 16 refs. Grant No. DAAJ02-69-C-0086.

A study has been made to determine the effects of rotation, forward flight, angle of attack, lift, and downflow on the laminar boundary-layer separation on an idealized rigid blade of infinite extent. As a result of the method of analysis it is possible to isolate the effects of angle of attack, forward flight, and downflow velocity. In general, separation is delayed on the inboard portion of the blade as a result of rotation. This effect has been noted previously. For forward flight without downflow the separation point, at a given spanwise location, oscillates about the no-forward-flight separation point. In addition, the location of the separation point in this case is 90 deg out of phase with the velocity at the edge of the boundary layer. When both forward flight and downflow are included in the solution, the oscillations of the separation line are amplified and the separation line undergoes an additional phase shift in azimuthal angle. The larger the angle of attack, the more exaggerated are the amplifications of the oscillation in the separation line. (Author)

A73-19956 * # Multiple element airfoils optimized for maximum lift coefficient. A. I. Ormsbee (Illinois, University, Urbana, Ill.) and A. W. Chen (Illinois, University, Urbana, Ill.; NASA, Langley Research Center, Hampton, Va.). *AIAA Journal*, vol. 10, Dec. 1972, p. 1620-1624. Grant No. NGR-14-005-144.

Optimum airfoils in the sense of maximum lift coefficient are obtained for incompressible fluid flow at large Reynolds number. The maximum lift coefficient is achieved by requiring that the turbulent skin friction be zero in the pressure rise region on the airfoil upper surface. Under this constraint, the pressure distribution is optimized. The optimum pressure distribution is a function of Reynolds number and the trailing edge velocity. Geometries of those airfoils which will generate these optimum pressure distributions are obtained using a direct-iterative method which is developed in this study. This method can be used to design airfoils consisting of any number of elements. Numerical examples of one- and two-element airfoils are given. The maximum lift coefficients obtained range from 2 to 2.5. (Author)

A73-19964 # A correction to 'lifting-line theory as a singular perturbation problem.' K. P. Kerney (U.S. Naval Material Command, Ship Research and Development Center, Bethesda, Md.). *AIAA Journal*, vol. 10, Dec. 1972, p. 1683, 1684. 6 refs. Navy-supported research. Navy Task J-15090.

The formula given by Van Dyke (1964) for the lift-curve slope of a high-aspect-ratio elliptical wing in incompressible inviscid uniform flow is investigated with respect to its accuracy and proved to be incorrect. A corrected version of the formula is presented.

M.V.E.

A73-20014 # Vapor pressure of supersonic aircraft fuels (O davlennii parov topliva dlia sverkhzvukovykh samoletov). Ia. B. Chertkov and P. M. Kolobova. *Khimiia i Tekhnologiia Toplivi i Masel*, vol. 18, no. 1, 1973, p. 46, 47. 7 refs. In Russian.

Vapor pressures and distillation fractions suitable for supersonic airliner fuels are discussed. A nomogram is proposed for the determination of boiling point vs temperature and absolute pressure in such fuels. A boiling point of 165 to 168 C for speeds of up to 2.5 M, and distillation fraction contents corresponding to Soviet T-8 fuel and western grade A fuel are suggested for supersonic airliners. V.Z.

A73-20077 # Flight control with incomplete information (Upravlenie poletom pri nepolnoi informatsii). G. I. Kostychev. *Aviatsionnaia Tekhnika*, vol. 15, no. 3, 1972, p. 12-15. In Russian.

A flight control algorithm is proposed for situations where the equations of motion contain a random quantity whose dispersion decreases with time due to incoming information, as under conditions of limited visibility. The algorithm yields a solution for an infinitesimal time interval in contrast to ordinary solutions in problems without information inflow, which provide controls averaged over the entire time of controlled operation. V.Z.

A73-20086 # Investigation of the heat transfer between the gas and casing in the area of the apertures between the nozzle diaphragm blades and guide vanes of turbines (Issledovanie teplootdachi mezhdru gazom i korpusom v raione mezhlopatochnykh kanalov soplovykh i napravliaiushchikh apparatov turbin). V. I. Lokai, M. N. Bodunov, V. A. Podgornov, and A. G. Karimova. *Aviatsionnaia Tekhnika*, vol. 15, no. 3, 1972, p. 62-67. 8 refs. In Russian.

A73-20094 # Calculation of the aerodynamic characteristics of a rectangular wing with tip plates moving at a low subsonic speed in the proximity of a screen (Raschet aerodinamicheskikh kharakteristik priamougol'nogo kryla s kontsevyimi shaybami, dvizhushchegosia s maloi dozvukovoi skorost'iu vblizi ekrana). S. D. Ermolenko, Iu. A. Rogozin, and G. V. Rogachev. *Aviatsionnaia Tekhnika*, vol. 15, no. 3, 1972, p. 105-112. In Russian.

A73-20095 # Accelerations of points on a flight vehicle during short-period motion (Uskorenniia tochek letatel'nogo apparata v korotkoperiodicheskom dvizhenii). B. D. Shneider. *Aviatsionnaia Tekhnika*, vol. 15, no. 3, 1972, p. 113-117. In Russian.

Demonstration that a point situated at some distance in front of the center of mass of a flight vehicle has minimum vertical accelerations during flight vehicle pitching. Considerations are given for determining the position of that point by measurements during flight. It is recommended that acceleration sensors of automatic pilots be positioned at that point. V.Z.

A73-20124 Advances in the design of electric three-phase machines for air and land vehicles (Fortschritte im Bau elektrischer Drehstrommaschinen für Luft- und Landfahrzeuge). P.-G. Sperling (Siemens AG, Nuremberg, West Germany). *Siemens-Zeitschrift*, vol. 46, Aug. 1972, p. 686-692. 6 refs. In German.

Developments in the technology, design, and cooling of three-phase machines are described which have led to new solutions in the construction of reliable efficient generators and motors for aircraft and land vehicles. The impact of semiconductor technology on the design of brushless generators is noted. One of the principal advances in aircraft generator design is the substantial reduction in the power-to-weight ratio. V.P.

A73-20157 Predicting light flashes due to alpha-particle flux on SST planes. P. S. Young (Mississippi State University, State College, Miss.) and K. Fukui (USAF, Cambridge Research Laboratories, Bedford, Mass.). *Nature*, vol. 241, Jan. 12, 1973, p. 112, 113. 11 refs.

Experiments conducted to determine the causes of the phenomenon experienced by the astronauts during the Apollo Lunar Missions confirm that the flashes were caused either by direct interaction between energetic heavy primary cosmic rays or neutrons and the retina, or by Cerenkov radiation produced by muons. Because the alpha-particle flux is much higher than that of heavy

nuclei in primary cosmic rays, the possibility of observing light flashes on SST aircraft owing to alpha-particles cannot be ruled out.
G.R.

A73-20171 A flight control system for STOL aircraft. G. Schänzer (Bodenseewerk Gerätetechnik GmbH, Überlingen, West Germany). *Interavia*, vol. 28, Jan. 1973, p. 66-68.

In order to avoid obstacles and to keep noise to a minimum, steep nonlinear approach profiles will be necessary in many cases when operating STOL aircraft. The deterioration of flight characteristics can be overcome by means of a suitable control system. For exact control of flight path and aerodynamic flow, altitude deviations and angle of attack deviations should be kept as low as possible. At least two independent control possibilities are necessary to control flight path and angle of attack independently. Spoilers are necessary for very precise landings.
F.R.L.

A73-20200 # On a particular case of conformal representation of multiconnected domains. W. J. Prosnak (Warszawa, Politechnika, Warsaw, Poland). *Académie Polonaise des Sciences, Bulletin, Série des Sciences Techniques*, vol. 20, no. 11, 1972, p. 11 (917)-17 (923). 5 refs. Research supported by the Zakłady Sprzetu Lotnictwa Sportowego.

Conformal representation of two profiles symmetric with respect to the real axis onto two such circles is considered in the paper. The mapping function is assumed in the form of a series of rational functions, and relations between coefficients of this series and coordinates of the profiles are established.
(Author)

A73-20214 A computerized flutter solution procedure. Y. T. Phoa (Technology, Inc., Dayton, Ohio). (*National Symposium on Computerized Structural Analysis and Design, George Washington University, Washington, D.C., Mar. 27-29, 1972.*) *Computers and Structures*, vol. 3, Jan. 1973, p. 195-204.

An approach has been developed to solve flutter equations completely automatically. The method consists of a computerized search for the flight speed, vibration frequency, and air density values which satisfy all conditions imposed by the flutter problem. Control theory concepts are used for the presentation and the aeroelastic system involved can be extended to include any type of linear feedback control device.
(Author)

A73-20244 Icing testing in the large Modane wind-tunnel on full-scale and reduced scale models (Essais de givrage dans la grande soufflerie de Modane sur maquettes à échelle grandeur et échelle réduite). F. Charpin and G. Fasso (ONERA, Châtillon-sous-Bagneux, Hauts-de-Seine, France). (*Conférence sur la Protection Contre le Givrage, London, England, May 10, 1972.*) *L'Aéronautique et l'Astronautique*, no. 38, 1972, p. 23-31. 10 refs. In French.

A73-20246 Fatigue life of aircraft structures (Durée en fatigue des structures des avions). W. Barrois (Centre de Documentation de l'Armement, Paris; Société Nationale Industrielle Aérospatiale, Châtillon-sous-Bagneux, Hauts-de-Seine, France). (*NATO, AGARD, Symposium on Random Load Fatigue, Lyngby, Denmark, Apr. 13, 1972.*) *L'Aéronautique et l'Astronautique*, no. 38, 1972, p. 46-63. 26 refs. In French.

A brief review of the current methods for forecasting the fatigue life of aircraft structures according to the fatigue test results obtained on parts, assemblies, and structures under constant amplitude loads is presented. Following a discussion on the utilization

of the test results obtained under programmed loadings, the possibilities of using the tests under random loads in the range of slow fatigue are then studied. As a conclusion, it appears that the definition of a random loading by its root mean square value is not adequate to the forecasting of the lifetime of a structure subjected to fatigue even when the loading power spectrum pattern is known, barring the case of comparative forecasting where the sole variable is the intensity of a loading spectrum. The possibility of speeding up the test runs by a general increase of the load level has been contemplated.
(Author)

A73-20248 Basic specification research for the main instruments of light aircraft (Recherche de spécifications de base pour les instruments principaux destinés aux avions légers). R. Tiercelin. *L'Aéronautique et l'Astronautique*, no. 38, 1972, p. 73-80. In French.

A73-20249 India's wind tunnels (Die Windkanäle Indiens). A. Klein. *DGLR Mitteilungen*, vol. 6, Jan. 1973, p. 2-5. 11 refs. In German.

Review of the wind tunnel test facilities currently operating in India. After briefly outlining the current state of the Indian aircraft industry, descriptions are given of the low-velocity wind tunnels of the Indian Institute of Science, Hindustan Aeronautics Limited, and the Indian Institute of Technology, the high-velocity wind tunnel at the Indian Institute of Science, and two high-velocity wind tunnels at the National Aeronautical Laboratory, one of which, the large 120 x 120 cm wind tunnel is described in particular detail.
A.B.K.

A73-20350 Earlier programs spawned TF34. M. L. Yaffee. *Aviation Week and Space Technology*, vol. 98, Feb. 5, 1973, p. 56-60.

The TF34-GE-2 turbofan engine being produced for the Navy/Lockheed S-3A anti-submarine warfare aircraft is described, together with the TF34-GE-100 turbofan engine being developed for the USAF's close support AX aircraft built by Boeing. The principal components and characteristic features of these engines are examined. Both engines are designed on the basis of the technology developed for the TF39/CF6 and T64 engines.
V.P.

A73-20359 Emissions from and within an Allison J-33 combustor. A. M. Mellor, R. D. Anderson, R. A. Altenkirch, and J. H. Tuttle (Purdue University, Lafayette, Ind.). *Combustion Science and Technology*, vol. 6, Nov. 1972, p. 169-176. 11 refs. U.S. Environmental Protection Agency Contract No. 68-04-0001; Grant No. DAAE07-69-C-0756.

Gas temperature, carbon monoxide, and nitric oxide concentration profiles measured as a function of axial and radial position inside an Allison J-33 combustor with unheated inlet air are reported. In addition, the isolated effects of combustor pressure, overall equivalence ratio, and air flow rate on combustor exit plane emissions are investigated. A consistent model of the combustion process in this combustor is presented on the basis of the results.
(Author)

A73-20375 Air-terminal queues under time-dependent conditions. B. O. Koopman (Arthur D. Little, Inc., Cambridge, Mass.). *Operations Research*, vol. 20, Nov.-Dec. 1972, p. 1089-1114. 20 refs.

The queues formed by aircraft in stacks awaiting landing clearance have usually been treated either by machine simulation, or

analytically as stochastic processes with time-independent transition probabilities (possessing stationary solutions). In contrast to such methods, the present paper regards the queue-developing process in question as strongly time-dependent, often with a diurnal (24-hour) periodicity. The formulation and treatment are entirely analytic and make use of machines only to solve the equations for the probabilities, by economical deterministic steps, using the coefficients as given in tabular form. Time-varying Poisson arrivals are assumed, and also an upper limit to queue length. Two laws of servicing are used: Poisson and fixed service time; these extremes are found to lead to numerically close results in the realistic case.

(Author)

A73-20376 # Methods and equipment for in-flight aircraft strength tests (Metody i tekhnika letnykh ispytaniy samoletov na prochnost'). A. I. Gudkov and P. S. Leshakov. Moscow, Izdatel'stvo Mashinostroenie, 1972. 248 p. 39 refs. In Russian.

In-flight test methods for estimating the strength of aircraft and helicopters are presented. The main types of modern equipment for measuring vibrations, stress, temperature, and other parameters are described, and recommendations are made concerning the preparation and calibration of the equipment. Brief information is presented concerning laboratory strength tests of aircraft structures. Methods of in-flight strength testing involving load and vibration measurements are considered. Methods of analyzing measurement data on the basis of the special features of aircraft loading are outlined. The main types of automatic devices used for treating and analyzing measurement results are described.

A.B.K.

A73-20377 # Problems of passenger aircraft design (Problemy proektirovaniia passazhirskikh samoletov). V. M. Sheinin and V. I. Kozlovskii. Moscow, Izdatel'stvo Mashinostroenie, 1972. 312 p. 128 refs. In Russian.

A number of problems of passenger aircraft design are considered which are of interest from the standpoint of increasing the technical and economic efficiency of the aircraft and of the transport system as a whole. The trends of development of jet-powered passenger aircraft which tend to increase their profitability are noted, a detailed analysis is made of the concept of the airbus, problems of weight and size of a passenger aircraft are considered, the special features of designing aircraft with aft-mounted engines are indicated, and problems of optimal design are discussed. Also considered are some unsolved problems concerning takeoff and landing, flight range, and reliability.

A.B.K.

A73-20378 # Onboard distance-measuring systems (Bortovye distantsionno-izmeritel'nye sistemy). Iu. M. Pul'er. Moscow, Izdatel'stvo Mashinostroenie, 1972. 288 p. 47 refs. In Russian.

A study is made of onboard continuously operating and pulsed distance-measuring devices and measuring modulators. A general mathematical method is given for engineering calculation and error analysis of distance-measuring systems and individual measuring elements. The noise fluctuations of a servo microdrive and the effect of residual stress on its resolution are considered. The general principles of design of electromechanical measuring modulators - including those based on standard induction and logic electronic elements - are outlined. Calculations of specific measuring systems which have been used in flight vehicles are presented.

A.B.K.

A73-20381 # Control of aircraft and helicopter flight (Upravlenie poletom samoletov i vertoletov). V. T. Borodin and G. I. Ryl'skii. Moscow, Izdatel'stvo Mashinostroenie, 1972. 240 p. 136 refs. In Russian.

Analysis and systematization of the main results of non-Soviet research on the creation of promising means of automating aircraft and helicopter flight control. Structural diagrams and descriptions of control systems are presented for modern aircraft and helicopters, nonrigid flight vehicles, and adaptive (self-adjusting, variable-structure, and self-organizing) aircraft systems. Bionic principles of adaptation and the possibility of using them in flight vehicle control systems are considered, as well as problems involved in the automation of landings, flights at low and maximally low altitudes, and the creation of onboard equipment complexes. Methods of displaying piloting and navigational information to the pilot are described, as well as semiautomatic control systems, collision warning systems, landing systems, profile flight systems, and modern onboard equipment complexes.

A.B.K.

A73-20382 # System analysis of the air-ground transportation interface problem at Bangkok International Airport. C.-R. Wang. Bangkok, Asian Institute of Technology, Master of Engineering Thesis, 1971. 120 p. 15 refs.

The characteristics of passenger flows throughout the various facilities of the passenger and baggage handling system of the airport are studied. Because of the time-dependent nature of the demand for service, deterministic queueing models are considered to be appropriate for describing the passenger and baggage handling operations. From these results, applications are made to determine the effect of jumbo jet flights on the level of service in the future. The study includes the departure check-in counter, immigration and public health, the departure lounge, the arrival lounge, immigration check-in, and the baggage claim and customs inspection area.

F.R.L.

A73-20394 # Cost and economic factors in aerospace system development. A. H. Flax (Institute for Defense Analysis, Washington, D.C.). In: Management in science and technology. Porz-Wahn, Deutsche Forschungs- und Versuchsanstalt für Luft- und Raumfahrt, 1971, p. 176-209. 13 refs.

The cost of high-performance military and major transport aircraft has been growing exponentially over the past fifty years at about the rate of a tenfold increase every eighteen years. This increase in unit cost has been accompanied in recent years by an even sharper rate of increase in the cost of development. It will be increasingly necessary to recognize that the costs of development and production of aerospace systems are strongly dependent on the rate at which new technology is introduced.

G.R.

A73-20407 Superconducting a.c. machines - An approach to development. D. F. Warne and M. E. Hadlow (Electrical Research Association, Leatherhead, Surrey, England). In: International Cryogenic Engineering Conference, 4th, Eindhoven, Netherlands, May 24-26, 1972, Proceedings. Guildford, Surrey, England, IPC Science and Technology Press, Ltd., 1972, p. 239-242.

The findings are reviewed of a study concerned with the evolution and evaluation of alternative configurations of superconducting ac machines, the comparison, in terms of weight, cost, and volume, with conventional machines at various points in the power spectrum, and an appraisal of the justification for development expenditure in the commercial (or market potential) context. It is shown that planar air gap machines are attractive (particularly in terms of specific volume) for medium power machines (about 20 MW), while cylindrical air gap machines show potential advantages across the full power spectrum.

V.P.

A73-20408 Superconducting generators for aircraft. J. T. Hayden (Cranfield Institute of Technology, Cranfield, Beds., England). In: International Cryogenic Engineering Conference, 4th, Eindhoven, Netherlands, May 24-26, 1972, Proceedings.

Guildford, Surrey, England, IPC Science and Technology Press, Ltd., 1972, p. 253-255. 6 refs.

The specific weights and performance characteristics of 400-Hz alternators employing superconducting field windings are calculated, and the general features of such alternators are discussed. It is shown that the main advantage which accrues from the use of superconducting field windings is the possibility of using high flux densities without the necessity of a heavy iron core. Some problems which must be resolved to obtain superconducting alternators suitable for use in aircraft are examined. V.P.

A73-20451 # Moving radiography. D. A. W. Pullen (Atomic Energy Research Establishment, Harwell, Berks., England). *Non-Destructive Testing Society of Great Britain, Annual Conference and Exhibition on Non-Destructive Testing, 9th, Loughborough University of Technology, Loughborough, Leics., England, Sept. 12-15, 1972, Paper. 13 p. 5 refs.*

The application of radiographic techniques to investigate dynamic events is becoming more widely used as engineers and others become increasingly aware of the unique facility it offers in recording for analysis details of motion which cannot be seen or photographed in the normal way. The motion may be transient or cyclic in nature, and the type of equipment necessary to obtain satisfactory radiographs varies from subject to subject. This paper reviews current methods of moving radiography with particular reference to the radiography of aero gas turbines under dynamic conditions, a development with which the author is closely involved. (Author)

A73-20452 # The corrosion problem in aircraft structures. P. F. Jowitt. *Non-Destructive Testing Society of Great Britain, Annual Conference and Exhibition on Non-Destructive Testing, 9th, Loughborough University of Technology, Loughborough, Leics., England, Sept. 12-15, 1972, Paper. 5 p.*

A historical overview of the aircraft corrosion problem and an assessment of the aircraft corrosion behavior of today. The subjects considered include corrosion in pressurized aircraft due to condensation, duralumin-related corrosion incidents, fatigue failures, magnesium-related corrosion failures, electrolytic corrosion, and anticorrosion plating. Nonexistence of corrosion on aircraft is urged as a necessity for safe flying. V.Z.

A73-20458 * Acoustic results obtained with upper-surface-blowing lift-augmentation systems. U. von Glahn, M. Reshotko, and R. Dorsch (NASA, Lewis Research Center, Cleveland, Ohio). *Acoustical Society of America, Meeting, 84th, Miami Beach, Fla., Nov. 28-Dec. 1, 1972, Paper. 25 p. 16 refs.*

The noise caused by the interaction of the jet exhaust and a wing was measured under static conditions for several versions of a small-scale STOL engine-over-the-wing configuration. Three basic nozzles were used in the tests; a circular nozzle, a 5:1 aspect ratio slot nozzle, and a 10:1 aspect ratio slot nozzle. Various flow attachment devices were included in the study. The wing included a flap that could be positioned for nominal takeoff or approach flap settings. Far field noise data are presented for the flyover mode. The data are discussed in terms of sound power and sound pressure spectra. (Author)

A73-20487 # Aerodynamic characteristics of thin asymmetric wing profiles in supersonic flow (Aerodynamische

Profileigenschaften der unsymmetrischen dünnen Flügel in der Überschallströmung). Y. Morikawa (Osaka University, Osaka, Japan), K. Nakabe (Osaka University, Osaka; Japan Monopoly Corp., Japan), S. Tada (Osaka University, Osaka; Hakodate Technical High School, Hakodate, Japan), and K. Nakamura (Osaka University, Osaka; Izumi Technical High School, Izumi, Japan). *Osaka University, Technology Reports*, vol. 22, Oct. 1972, p. 687-710. In German.

Expressions are derived for the lift, drag, and rolling-moment coefficients of a wing profile asymmetric with respect to the wing cord in three-dimensional flow. The influence of the profile configuration on the supersonic aerodynamic characteristics is studied by Busemann's approximate method as a function of the aspect ratio. V.P.

A73-20502 # A possible approach to the probabilistic estimation of the vibration strength of turbomachine components (Ob odnom vozmozhnom podkhode k veroiatnostnoi otsenke vibratsionnoi prochnosti detalei turbomashin). B. F. Shorr, E. A. Lokshtanov, and Iu. M. Khalatov (Tsentr'nyi Nauchno-Issledovatel'skii Institut Aviatsionnogo Motorostroeniia, Moscow, USSR). *Problemy Prochnosti*, vol. 4, Nov. 1972, p. 11-14. 7 refs. In Russian.

A method of assessing the vibration strength of turbine components on the basis of a safety factor calculated from the statistically maximal values of the variable acting and breaking stresses is proposed. The statistically maximum stresses are determined with allowance for certain random factors which influence the nature of the stress distribution near a dissipation center. The advantage of using statistically maximum stresses instead of maximal measured stresses is demonstrated. V.P.

A73-20503 # Designing turbomachine blades for forced vibrations under various excitation conditions (Raschet lopatok turbomashin na vynuzhdennye kolebaniia pri razlichnykh tipakh vozbuzhdeniia). Iu. S. Vorob'ev and N. G. Medvedev (Akademiia Nauk Ukrainskoi SSR, Institut Tekhnicheskoi Teplofiziki, Kiev, Ukrainian SSR). *Problemy Prochnosti*, vol. 4, Nov. 1972, p. 15-19. 6 refs. In Russian.

The problem of the forced vibrations of rotor blades is solved by a variational method on the basis of an improved vibration theory for twisted rods which takes into account the influence of aerodynamic damping and inelastic internal resistance. The vibration modes and the distribution of internal forces, moments, and stresses along the blades are determined for loads varying arbitrarily in time over the blade length. V.P.

A73-20546 # System for in-flight recording of the rotational speed of the turbine of a jet engine (Uklad do rejestracji obrotow turbiny silnika odrzutowego w czasie lotu samolotu). R. Kudelski (Wojska Lotnicze, Instytut Techniczny, Warsaw, Poland). In: Measurement of dynamic mechanical quantities; Scientific-Engineering Conference, 3rd, Warsaw, Poland, October 26-28, 1972, Summaries. Warsaw, Instytut Lotnictwa, 1972, p. 244-246.

In Polish.

A73-20586 Recent advances and applications in the prediction of pilot acceptance of aircraft flying qualities. J. R. Stone and F. R. Naylor (USAF, Flight Dynamics Laboratory, Wright-Patterson AFB, Ohio). In: Conference on Decision and Control and Symposium on Adaptive Processes, 11th, New Orleans, La., December 13-15, 1972, Proceedings. New York, Institute of Electrical and Electronics Engineers, Inc., 1972, p. 262-265. 16 refs.

A recently developed digital computer program capable of predicting pilot-vehicle performance, pilot model parameters, and pilot acceptance (in terms of Cooper ratings) is used to study the longitudinal flying qualities of a large aircraft. The predictions are then compared with actual in-flight simulation data and with

fixed-base pilot describing function measurements. The complete package represents the largest and most recent set of data available for the pitch axis control task. The results are very promising and clearly demonstrate the utility of modern optimization techniques and identification methods. (Author)

A73-20588 * Nonlinear programming in design of control systems with specified handling qualities. A. A. Schy (NASA, Langley Research Center, Hampton, Va.). In: Conference on Decision and Control and Symposium on Adaptive Processes, 11th, New Orleans, La., December 13-15, 1972, Proceedings. New York, Institute of Electrical and Electronics Engineers, Inc., 1972, p. 272-279.

A method is described for using nonlinear programming in the computer-aided design of aircraft control systems. It is assumed that the quality of such systems depends on many criteria. These criteria are included in the constraints vector, and the design proceeds through a sequence of nonlinear programming solutions in which the designer varies the specification of sets of requirements levels. The method is applied to design of a lateral stability augmentation system (SAS) for a fighter aircraft, in which the requirements vector is chosen from the official handling-qualities specifications. Results are shown for several simple SAS configurations designed to obtain desirable handling qualities over all design flight conditions with minimum feedback gains. (Author)

A73-20600 Distributed control of air traffic. W. M. Hollister and R. W. Simpson (MIT, Cambridge, Mass.). In: Conference on Decision and Control and Symposium on Adaptive Processes, 11th, New Orleans, La., December 13-15, 1972, Proceedings. New York, Institute of Electrical and Electronics Engineers, Inc., 1972, p. 576-581. 10 refs.

Performance measures for the evaluation of advanced Air Traffic Control concepts are developed and applied to a number of proposed systems. Distributed control has the potential for reducing cost, increasing capacity and reducing risk relative to centralized systems. The concept requires that traffic information be available in the cockpit. (Author)

A73-20618 # Mass air travel is definitely possible (Visst ar folkflyget mojligt). O. Ljungstrom (Styrelsen for Teknisk Utveckling, Stockholm, Sweden). *Teknisk Tidskrift*, vol. 103, Jan. 19, 1973, p. 15-19. In Swedish.

Outline of proposed air traffic developments to make possible a mass ridership in Sweden. The existing situation with respect to air travel in Sweden is reviewed, and criticism is made of the poor scheduling, unduly long travel times, and high fares which have resulted in a smaller percentage of the public traveling by air in Sweden than in Norway and Denmark. A scheme is then proposed to increase the air ridership in Sweden through the immediate introduction of jet aircraft on lines which are still using propeller-driven aircraft and the eventual introduction of the so-called QSTOLs or QTOLs around 1980. In addition, a new fare structure is proposed which would make fares for longer distances lower than at present while simultaneously increasing fares for short distances. A.B.K.

A73-20677 Computer-controlled software diagnosis of an airborne computer. E. D. Smally (MIT, Cambridge, Mass.). In: Automatic support systems for advanced maintainability; Symposium, Philadelphia, Pa., November 13-15, 1972, Record.

New York, Institute of Electrical and Electronics Engineers, Inc., 1972, p. 17-21. 10 refs. Navy-supported research.

The effort required and the important concepts involved in developing a single software diagnostic package for an airborne guidance computer are described in this paper. The paper is an attempt by the author to share some of the knowledge gained in planning, developing, and in using the diagnostics. The diagnostic

philosophy, diagnostic methods, test generation methods, and test validation methods used to develop the diagnostics are briefly described. (Author)

A73-20679 Some UK military views on the development and procurement of AIDS, BIT and ATE for avionics. M. H. Walshaw (Royal Aircraft Establishment, Farnborough, Hants., England). In: Automatic support systems for advanced maintainability; Symposium, Philadelphia, Pa., November 13-15, 1972, Record.

New York, Institute of Electrical and Electronics Engineers, Inc., 1972, p. 50-56.

The paper first deals with the applications of AIDS and BIT, and comments on several specific aspects, including integrated avionics and flight control systems, before putting forward an overall view on the philosophy of on-aircraft monitoring and maintenance testing. The use of ATE for off-aircraft avionics testing is considered, and computerised ATE and software are discussed. The latter discussion covers the use of standard high-level languages, such as ATLAS, for test-specification writing and the relative merits of some compiling schemes. One such scheme could employ a new intermediate-level language called IDA, which has been designed to ease the problems which arise in compiling. (Author)

A73-20680 AUTOMATE - A self-contained automatic test system. T. L. Rothwell (Hughes Aircraft Co., Culver City, Calif.). In: Automatic support systems for advanced maintainability; Symposium, Philadelphia, Pa., November 13-15, 1972, Record.

New York, Institute of Electrical and Electronics Engineers, Inc., 1972, p. 61-70.

AUTOMATE is a remarkably flexible and cost-effective computer-controlled automatic test system, developed by Hughes for use in its manufacturing plants. It is self-contained and designed to handle different products with widely different production rates. ATLAS is used for both analog and digital testing. Key system features include the use of a central computer/satellite test station concept, an ATLAS compiler resident on the central computer which is accessible in real-time from the test station for on-line ATLAS program development, and the maximum use of low-cost, low-risk commercial equipment. The result is a user-oriented system easily applied by test engineers and technicians and operable by lower skilled personnel. The AUTOMATE system, its software, and some of the user experience are described. Extensions of the design to other applications are covered briefly. (Author)

A73-20683 Test techniques for advanced avionics displays. J. W. Kenney (General Dynamics Corp., Convair Aerospace Div., Fort Worth, Tex.). In: Automatic support systems for advanced maintainability; Symposium, Philadelphia, Pa., November 13-15, 1972, Record.

New York, Institute of Electrical and Electronics Engineers, Inc., 1972, p. 89-94.

Some displays testing problems are examined, with emphasis on some unique techniques which are described in detail. Their flexibilities and shortcomings are discussed. Because many of the displays requiring functional and fault isolation testing were exceedingly complex, it was decided that automated (as opposed to manual) testing would be required. Video position measurements, manual visual testing with a programmable cursor, moving map display testing, complex video display testing, and automatic video testing with programmable video are considered. Attention is given to current limitations and future needs. F.R.L.

A73-20687 ATE support software system concept. C. H. Kozin and R. F. Huggard (PRD Electronics, Inc., Syosset, N.Y.). In: Automatic support systems for advanced maintainability; Symposium, Philadelphia, Pa., November 13-15, 1972, Record.

New York, Institute of Electrical and Electronics Engineers, Inc., 1972, p. 141-151. 5 refs. Navy-supported research.

A73-20688

Description of a system concept for the definition and development of support software for automatic test equipment (ATE). The essential objective of an automatic test system is the capability for the user to generate a test program once and repeatedly use it thereafter for maintaining his equipment. The user's performance in the generation of a test program depends heavily on the ATE system support software. The basic support software to the test program developer is the translation system (i.e., language, translator, and operating system) which allows him to clearly express his test requirements. The features of the language, the translator, and the operating system as elements of a closed-loop ATE system are described, and the rationale for allocation of the ATE system requirements to a particular element of the support software is presented. (Author)

A73-20688 Extension of the VAST software system. D. J. Zingg (Lockheed-California Co., Burbank, Calif.). In: Automatic support systems for advanced maintainability; Symposium, Philadelphia, Pa., November 13-15, 1972, Record. New York, Institute of Electrical and Electronics Engineers, Inc., 1972, p. 161-165.

One of the major problems encountered in the design and development of avionics test program sets for the versatile avionics shop test (VAST) system are with the VITAL compiler and lack of useful 'on-station' debug aids that are available to the user. While some of these problems are peculiar to the VAST software system itself, many are of a general nature and apply to program development on any automatic test system. This paper cites some of the major problems in the use of the compiler, how many of these problems are alleviated with an 'on-station' program patching capability, and the features of the compiler that should be carefully considered when designing any future ATE software systems. (Author)

A73-20692 Crew station lighting - Commercial aircraft. SAE Aerospace Recommended Practice, ARP 1161, May 1972. 25 p.

A practical set of requirements is given for lighting systems to illuminate crew station areas and displays on commercial aircraft and aerospace vehicles. The requirements pertain to display color; light control; instrument lighting systems; readability; lightplates; circuit breaker lighting; warning, caution and advisory systems lighting; and factors affecting human perception. V.Z.

A73-20693 Comparison of ground-runup and flyover noise levels. SAE Aerospace Information Report, AIR 1216, Apr. 1972. 28 p.

Sound pressure level measurements were made on 707-320C four-engine jet transport and 727-100 three-engine jet transport during concrete-surface runup, grassy surface runup, and overfly. The differences between composite one-third-octave-band spectra of noise were determined under these conditions. Comparisons were also made of the differences between maximum one-third-octave-band sound pressure levels measured during the ground runups over the concrete surface and over the grassy surface and projected to a 400 ft sideline distance. The projections included corrections for inverse-square loss and atmospheric absorption. Distinct differences were established in the results for the two aircraft. V.Z.

A73-20694 General requirements for aerospace powered mobile ground support equipment. SAE Aerospace Recommended Practice, ARP 1247, Apr. 1972. 18 p.

A73-20696 Gas turbine engine transient performance presentation for digital computer programs. SAE Aerospace Recommended Practice, ARP 1257, June 1972. 22 p. 5 refs.

A technique is set forth for the presentation of gas turbine engine transient performance as obtained by programmed digital computer calculations. The presentation is compatible with that given in issue 681 and is intended to assist program users as a readily computer-adaptable aid. V.Z.

A73-20698 Aircraft noise research needs. SAE Aerospace Information Report, AIR 1079, May 1972. 4 p.

The following research areas are identified as basic to aircraft noise control: noise from components of power sources; duct treatment materials and technologies for noise minimization in ducts and nacelles; noise propagation in the atmosphere and over the ground; and community and cabin noise. Continued improvement in these areas is suggested as a prerequisite for quiet operation of future commercial aircraft. V.Z.

A73-20718 # Unsteady thin-airfoil theory for subsonic flow. C. Osborne (Cornell University, Ithaca, N.Y.). AIAA Journal, vol. 11, Feb. 1973, p. 205-209. 13 refs. USAF-supported research.

An approximate theory has been developed for the unsteady motion of a two-dimensional thin airfoil in subsonic flow. Closed-form expressions are presented for the forces on, the circulation about, and the strength of the vortex wake emanating from a two-dimensional thin airfoil subjected to the general class of oscillating upwash distribution whose x dependence may be expanded in a cosine series. Expressions are also set down for three particularly important examples of this upwash distribution - namely, the Kemp-type upwash, the convected sinusoidal gust, and the flutter case. Some preliminary comparisons of the present method with the few existing theories for the sinusoidal-gust case reveals good agreement up to at least $M = 0.6$. (Author)

A73-20938 # Conically cambered triangular wings with reflex spanwise curvature. V. S. Holla, T. N. Krishnaswamy (Indian Institute of Science, Bangalore, India), and S. M. Ramachandra (Hindustan Aeronautics, Ltd., Bangalore, India). Aeronautical Society of India, Journal, vol. 24, Aug. 1972, p. 321-338. 16 refs.

A systematic study of conically cambered triangular wings with reflex spanwise curvature is made in this paper. The wings considered are those having subsonic leading edges and supersonic trailing edge with zero load along the leading edge at the design condition. It is shown through numerical examples that these wings have good aerodynamic characteristics, comparable to those of plane triangular wings with leading edge suction. (Author)

A73-20939 # Aerodynamic experimental investigation of annular cascade of gas turbine nozzle blade in subsonic and supersonic flow. K. L. Yadao (Government Engineering College, Jabalpur, Madhya Pradesh, India). Aeronautical Society of India, Journal, vol. 24, Aug. 1972, p. 339-343. 7 refs.

A73-20947 # Optimisation in construction of the Jaguar and other military aircraft. I. C. Taig and R. I. Kerr (British Aircraft Corp., Ltd., Military Aircraft Div., Preston, Lancs., England). Aircraft Engineering, vol. 45, Jan. 1973, p. 9-11. 6 refs.

A73-20958 # Expectation of contract incentives. J. A. Finchum, Jr. (Standard Oil Co., Chicago, Ill.). Naval Research Logistics Quarterly, vol. 19, June 1972, p. 389-397. 11 refs.

The application of statistical expectation to risk density

functions and fee/incentive-element relationships is shown to be useful in structuring contract incentives. A mathematical procedure for calculating the expected value of fee for a given risk/incentive arrangement is described along with cost examples and related sensitivity analyses. The structuring of equivalent incentives is demonstrated by the use of the contracting procedure used for procuring the C-5A aircraft. (Author)

A73-21000 # Benefit-cost analysis of delay reduction with STOL. J. B. Barriage (FAA, Aircraft and Noise Abatement Div., Washington, D.C.) and S. P. E. Price (U.S. Department of Transportation, Urban Mass Transportation Administration, Washington, D.C.). (*American Society of Civil Engineers, National Transportation Engineering Meeting, Seattle, Wash., July 26-30, 1971, Preprint 1507.*) ASCE, *Transportation Engineering Journal*, vol. 99, Feb. 1973, p. 43-52. 10 refs.

Various strategies for investment in STOL fleets have been evaluated with the aid of a heuristic computer model of the decision process which tallies incremental investment costs and incremental resulting benefits. The model is composed of about 700 FORTRAN statements and requires about one minute of running time on a CDC 6600 computer. The model was run with projected demand and capacity conditions for 1975. The outcome of STOL fleet and runway investments specified by the model is graphically portrayed as a series of city-pair STOL fleet costs (investments) and corresponding benefits (reduced costs of delay). T.M.

A73-21087 Applications of the infrared to navigation (*Applications de l'infrarouge à la navigation*). C. Lemonon (Thomson-CSF, Corbeville, Essonne, France). *Navigation* (Paris), vol. 21, Jan. 1973, p. 32-46. 7 refs. In French.

The infrared systems most appropriate as navigational aids are highly sensitive image formation radiometers. The essential characteristics of an image-forming radiometer are the image rate, the number of points resolved in the image, and the thermal sensitivity. These characteristics are closely related, and it is not possible to obtain simultaneously a high sensitivity at a rapid rate, and high resolution. The use of the radiometer for blind landing, for aerial reconnaissance over land and sea, for horizon detection, and for detection of obstacles at sea are discussed. Brief comment is made on the use of ultraviolet radiation for navigation. F.R.L.

A73-21088 Evolution and actual aspect of air navigation (*Evolution et aspect actuel de la navigation aérienne*). P. Fombonne (Thomson-CSF, Paris, France). *Navigation* (Paris), vol. 21, Jan. 1973, p. 63-75. In French.

The development of air navigation over the past twenty years is reviewed, with discussion of requirements and methods. A major factor has been the great increase in air traffic. A crucial event was the appearance of civil jet aircraft about 1960. The technical key to air navigation has been the progress of electronics during the period. Many innovations, such as the semiconductor revolution, have made it possible to construct apparatus which would have been impractical in 1953 on account of size and cost. Various navigational systems are described, and future possibilities are discussed. F.R.L.

A73-21180 Measurement of the pressure distribution at the surface of an aerodynamic body using a special interrogator. O. R. Cheranovskii and V. B. Zozulia (Khar'kovskii Aviatsionnyi Institut, Kharkov, Ukrainian SSR). (*Gidromekhanika*, no. 15, 1969, p. 65-69.) *Fluid Mechanics - Soviet Research*, vol. 1, Nov.-Dec. 1972, p. 51-54. Translation.

Description of a device proposed for measuring the pressure distribution over a profile by means of a pneumatically activated inductive sensor. By means of an interrogator switch, pressure measurements at 50 points of the profile can be obtained during 1 sec. V.P.

A73-21235 Welding and fabrication of non-ferrous metals; Proceedings of the International Conference, Eastbourne, Sussex, England, May 2, 3, 1972. Volume 1. Conference sponsored by the Welding Institute and Institute of Metals. Cambridge, Welding Institute, 1972. 132 p. Members, \$10.42; nonmembers, \$15.63.

Welding process parameters, participating reactions and mechanisms, weld properties, and inspection techniques are described in papers dealing with the fabrication and welding of aluminum, copper, zirconium, and other nonferrous alloys. Topics examined include hot crack formation during welding of aluminum and its alloys, problems in electron-beam welding of nonferrous metals, argon-nitrogen gas metal-arc welding of nonferrous metals, friction-welding experiments, cold-pressure welding of aluminum, explosive and implosive welding of duplex metal cylinders, welding of titanium alloy airframe structures with the aid of tensile loading to overcome distortion, and fatigue properties of welded high-temperature alloys. T.M.

A73-21240 Welding airframe structures in titanium alloys using tensile loading as a means of overcoming distortion. A. Stanhope, R. H. Hazelhurst, and B. M. Swann (Hawker Siddeley Aviation, Ltd., Kingston on Thames, England). In: *Welding and fabrication of non-ferrous metals; Proceedings of the International Conference, Eastbourne, Sussex, England, May 2, 3, 1972. Volume 1.* Cambridge, Welding Institute, 1972, p. 72-82.

The traditional method of stiffening aircraft wing or fuselage panels is by attaching longitudinal stiffeners or 'stringers' or alternatively machining integrally stiffened structure from the solid. There are obvious advantages in welding the stringers to the skin, and design studies have suggested that a U section would often be the most efficient structurally. Fusion welding such a joint invariably leads to considerable distortion. This distortion is caused by stresses locked into the welded zone as solidification proceeds. The present work shows how these normal residual stresses can be balanced out by the application of a relatively large tensile prestrain to the parts prior to welding. The panels produced by this method have been shown to be perfectly flat and distortion-free. The case for using titanium alloys as materials for aircraft construction is put forward, together with some problems associated with welding these materials. (Author)

A73-21249 A proposed design for the construction of a VTOL simulator (*Ricerca di progetto a realizzazione del simulatore per un velivolo a decollo verticale*). A. Folchini and M. Grande. *Rivista Aeronautica*, vol. 48, Dec. 1972, p. 2011-2028. In Italian.

Development of a design for a VTOL aircraft capable of fulfilling transport, training, and combat functions, giving particular attention to the construction of a simulator for predicting the effective behavior of this aircraft in flight. Among the design problems considered are the lift augmentation system, the architecture of the aircraft, the weight distribution, size limitations within the fuselage, flight safety, and aircraft stability and control. In connection with the simulator, a detailed description is given of the principle of operation and the circuitry employed. Also described is a proposed scheme for providing the pilot with the maximum information possible concerning the outside world using only a visual screen (an oscilloscope) and qualitative data concerning speed, attitude, and altitude. The results of preliminary tests carried out with the aid of the simulator are illustrated graphically. A.B.K.

A73-21495 Flow in the vicinity of a trailing edge (*Ecoulement au voisinage d'un bord de fuite*). J.-P. Guiraud (ONERA, Châtillon-sous-Bagneux, Hauts-de-Seine; Paris VI, Université, Service de Mécanique, Paris, France). *Académie des Sciences (Paris), Comptes Rendus, Série A - Sciences Mathématiques*, vol. 276, no. 5, Jan. 29, 1973, p. 399-401. 5 refs. In French.

The triple layer method conceived by Stewartson and Williams (1969) and utilized in various applications by Stewartson (1969),

Brown and Stewartson (1970), and Riley and Stewartson (1969) is considered for further uses. It is applied to the study of the three-dimensional flow of an incompressible, viscous fluid in the vicinity of the trailing edge of a thin wing. The advantages and limitations of the method are pointed out. M.V.E.

A73-21529 ONERA will put a large anechoic chamber with a wind tunnel in service in 1975 (L'ONERA mettra en service in 1975 une grande chambre sourde avec soufflerie). J. Morisset. *Air et Cosmos*, vol. 10, Feb. 10, 1973, p. 23-25. In French.

The major feature of the anechoic chamber is an open aerodynamic circuit, or pseudo wind tunnel, consisting of an air inlet, a free jet test chamber, and an outlet with two fans driven by variable frequency electric motors. The pseudo wind tunnel will accomplish total soundproofing, will optimize the aerodynamics of the sound absorbing elements, and will achieve a very good flow without turbulence. The installation will make it possible to study jets with or without reheating, the blowers of turbojets at various rates of dilution, helicopter rotors, and models of V/STOL aircraft using jets for lift-off. F.R.L.

A73-21574 L-1011 TriStar - Design development. J. B. Beach (Lockheed-California Co., Burbank, Calif.). *Esso Air World*, vol. 25, no. 2, 1972, p. 36-41.

A distinct improvement in handling qualities for large transport aircraft was a major objective in the design of the L-1011. The 'flying stabilizer' augmented by elevators linked to the stabilizer motion was evolved so as to camber the stabilizer surface as a function of stabilizer deflection. Variations in center of gravity have a very small effect on the feel of the airplane. Avionics flight control and automatic landing systems, structure and corrosion protection, hydromechanical systems, and aspects of maintenance and noise abatement are discussed. F.R.L.

A73-21611 # Discrete vortex scheme of a wing of finite span (O diskretnoi vikhrevoi skheme kryla konechnogo razmakha). N. F. Vorob'ev (Akademiia Nauk SSSR, Institut Teoreticheskoi i Prikladnoi Mekhaniki, Novosibirsk, USSR). *Akademiia Nauk SSSR, Sibirskoe Otdelenie, Izvestiia, Seriya Tekhnicheskikh Nauk*, Oct. 1972, p. 59-68. 5 refs. In Russian.

The flow of an inviscid incompressible gas past the lifting surface of a wing is analyzed. A vortex surface is substituted for the wing surface, and the trailing vortex sheet is represented by a vortex surface whose axes coincide with the stream lines. The introduction of the trailing vortex sheet helps to ensure the condition of a finite velocity at the trailing edges. The calculation of the aerodynamic characteristics of the wing is reduced to the solution of a system of algebraic equations. It is shown that, if the discrete vortices are properly selected and certain conditions are satisfied, the algebraic sums which represent the velocities induced by the discrete vortices, reduce with increasing number of the vortices to integrals. The convergence of the integrals is proved. V.P.

A73-21656 Contribution to the study of the total energy. III (Contribution à l'étude de l'énergie totale. III). J. M. Clément. *Aero-Revue*, Feb. 1973, p. 91-93. In French.

A rate of climb indicator for a glider is described. The perfect total energy developed in gliding flight passes by an accelerometric compensation. The application of a theoretical C sub p equals -1 leads to an unusable rate of climb indicator because it is apparently overcompensated at the beginning of the reclimb and indicates delays of several seconds, which must be added to the delay of the instrument itself. It is possible to artificially compensate the accelerometric error by undercompensating the rate of climb indicator by a quantity diminishing with the speed. F.R.L.

A73-21670 Analytical predictions of emissions from and within an Allison J-33 combustor. D. C. Hammond, Jr. and A. M. Mellor (Purdue University, Lafayette, Ind.). *Combustion Science and Technology*, vol. 6, Jan. 1973, p. 279-286. 20 refs. Grant No. DAAE07-69-C-0756.

An analytical model which considers gas-phase processes has been developed for gas turbine combustors. In the model the fluid mechanics of combustors are rather crudely approximated for reasons of mathematical tractability, and the perfectly stirred reactor constitutes the basic computational component of the model. The analytical model was used to make predictions, for an actual combustor, which were then compared with internal and exit plane measurements of temperature, carbon monoxide concentration, and nitric oxide concentration. The internal data could be reasonably well approximated by the predictions, but the variations in exit plane values for certain changes in the operating conditions were incorrectly predicted. These discrepancies were shown to result, at least partially, from heterogeneous effects. (Author)

A73-21683 * # A summary of wind tunnel research on tilt-rotors from hover to cruise flight. Ph. Poisson-Quinton (ONERA, Châtillon-sous-Bagneux, Hauts-de-Seine, France) and W. L. Cook (NASA, Ames Research Center Advanced Aircraft Programs Office, Moffett Field, Calif.). (NATO, AGARD, Réunion sur l'Aérodynamique des Voilures Tournantes, Marseille, France, Sept. 13-15, 1972.) *ONERA, TP* no. 1133, 1972. 18 p.

A73-21687 Olympus in Concorde /Twenty-fifth Louis Bleriot Lecture/. J. Devriese (Société Européenne de Propulsion, Paris, France) and P. H. Young (Rolls-Royce, Ltd., Bristol Engine Div., Bristol, England). (*L'Aéronautique et l'Astronautique*, no. 37, 1972, p. 5-22.) *Aeronautical Journal*, vol. 76, Dec. 1972, p. 683-694. 6 refs.

It has been demonstrated during flight tests that the Olympus engine cycle, eight years after it was designed, is perfectly suited to supersonic operation. Engineering improvements such as: intake casing assembly, annular combustion chamber, modern means of soundness monitoring, etc., were introduced to maintain the engine in the lead of advanced technology while satisfying pollution requirements. Noise reduction is being subjected to extensive research, with continuous improvements being introduced. The use of reheat - with a ratio increased to 18 per cent - was extended to transonic flight operation. Increased payload is ensured by the new type of secondary nozzle, which also contributes to noise abatement. Further engine developments are being considered. (Author)

A73-21688 Advanced materials for aircraft brakes. J. V. Weaver (Dunlop, Ltd., Aviation Div., Foleshill, Coventry, England). *Aeronautical Journal*, vol. 76, Dec. 1972, p. 695-698.

Material requirements for aircraft brakes are explained, and the thermal and mechanical properties of some advanced materials are outlined to demonstrate applications in solving problems encountered with recent brake design developments. Friction and wear characteristics, density, oxidation resistance, and mechanical strength are discussed for beryllium, steel, electrographite, nuclear grade graphite, high-density mechanical carbon, pyrolytic graphite, and carbon-fiber/carbon-matrix materials. T.M.

A73-21689 Formula one air racing. R. J. Hardy (Southampton, University, Southampton, England). *Aeronautical Journal*, vol. 76, Dec. 1972, p. 699-703.

The history of formula-one air racing in the United States and Great Britain is reviewed in terms of major competitive events, successful aircraft designs, and important design requirements. Specifications are given for a racer aircraft (Hobbit) offering simple low-cost construction by amateurs along with good racing and touring characteristics. T.M.

A73-21692 A linearised theory of parachute opening dynamics. H. G. Heinrich (Minnesota, University, Minneapolis, Minn.). *Aeronautical Journal*, vol. 76, Dec. 1972, p. 723-731. 19 refs.

The present analysis of parachute inflation dynamics introduces a refined inflow function and corrects a conceptual error appearing in the analytical method for calculating parachute opening time and opening shock described by Heinrich and Bhateley (1961). Calculated values of opening time and force obtained by the present improved method are in good agreement with available field test data. Effects of drag coefficients, inflation altitude, and volume of the inflated canopy are indicated.

T.M.

A73-21710 * The utility of a low flying aircraft or helicopter when collecting ground data for regional resource surveys. D. T. Lauer (California, University, Berkeley, Calif.). In: American Society of Photogrammetry and American Congress of Surveying and Mapping, Fall Convention, Columbus, Ohio, October 11-14, 1972, Proceedings. Falls Church, Va., American Society of Photogrammetry, 1972, p. 367-383. 6 refs. NASA-supported research. NASA Order R-03-038-002.

A73-21725 # Nonstationary load distribution on an arbitrary-planform wing in supersonic motion (Nestatsionarnye raspredelennye nagruzki na kryle, imeiushchem proizvol'noi formu v plane, pri sverkhzvukovom dvizhenii). R. A. Mezhlumian (GosNII Glavavtomatika, Moscow, USSR) and R. Sh. Solomonian (Akademiia Nauk Armianskoi SSR, Nauchno-Issledovatel'skii Institut Avtomatiki, Kirovakan, Armenian SSR). *Akademiia Nauk Armianskoi SSR, Izvestiia, Mekhanika*, vol. 25, no. 3, 1972, p. 41-59. 7 refs. In Russian.

A73-21837 Civil aviation development - A policy and operations analysis. R. C. Fraser, A. D. Donheiser, and T. G. Miller, Jr. (Arthur D. Little, Inc., Cambridge, Mass.). Research supported by the U.S. Department of Transportation; Contract No. DOT-OS-00083. New York, Praeger Publishers, Inc., 1972. 213 p. \$12.50.

Research findings are synthesized and enumerated, and the most comprehensive constraints and broad classes of options are discussed, followed by examination in greater detail of more specific constraints and options. The R & D problem is defined, and ways are indicated in which government and industry are not meeting the research challenge. The commercial airlines industry and its key interfaces with government are examined in order to evaluate the R & D implications of an historically close-knit private-public sector operation. The question of airport development is discussed. An examination of commercial helicopter operations, air cargo, STOL, and general aviation provides numerous examples of the difficulties facing civil aviation R & D.

F.R.L.

A73-21839 Aircraft structures for engineering students. T. H. G. Megson. London, Edward Arnold (Publishers), Ltd., 1972. 493 p. 76 refs. \$15.63.

This unified course considers the fundamentals of elasticity and aircraft structural analysis, and the associated topics of airworthiness and aeroelasticity. Sufficient elasticity theory is included to provide the basic tools of structural analysis. An attempt is made to clarify the use of energy methods of analysis and to present a consistent but general approach to the various types of structural problems for which energy methods are employed. The analysis of the thin-walled cellular type of structure is extensively treated. An introduction to computational methods of structural analysis is presented which also includes some elementary work on the finite element method for continuum structures.

F.R.L.

STAR ENTRIES

N73-15978 Engineering Sciences Data Unit, London (England).
**INFORMATION ON THE USE OF DATA ITEMS ON ROLLING
MOMENT DERIVATIVES OF AN AEROPLANE**
1972 2 p

(ESDU-Aircraft-06.01.00) Avail: Issuing Activity

Rolling moment derivatives of an aircraft due to rolling, yawing, and sideslip are discussed. The rolling moments are due to asymmetrical changes in the air flow over the aircraft and the consequent changes in pressure distribution. Procedure is based on principle of calculating effects of various components of the aircraft separately and adding the part derivatives to obtain the overall effect. Author

N73-15980 Engineering Sciences Data Unit, London (England).
**EFFECT OF WING ON ROLLING MOVEMENT DUE TO
YAWING**

Sep. 1972 19 p refs Supersedes ESDU-Aero-A.06.01.02 and ESDU-Aero-A.06.01.08 Sponsored by Roy. Aeron. Soc.

ESDU-72021; ESDU-Aero-A.06.01.02;

ESDU-Aero-A.06.01.08) Copyright. Avail: Issuing Activity CSCL 01A

A method for estimating the contribution of a straight tapered swept wing to the rolling moment derivative due to yawing at lift coefficients for which the flow remains fully attached is presented. The flow is assumed to be subsonic over the whole wing. The basic planform contribution and the effects of dihedral, twist, and deflected trailing edge flaps are considered. Mathematical models are included to amplify the text. Author

N73-15981 Engineering Sciences Data Unit, London (England).
**AERODYNAMIC CHARACTERISTICS OF AEROFOILS IN
COMPRESSIBLE INVISCID AIRFLOW AT SUBCRITICAL
MACH NUMBERS**

Oct. 1972 25 p refs Sponsored by Roy. Aeron. Soc.

(ESDU-72024) Copyright. Avail: Issuing Activity CSCL 01A

A method for estimating a number of aerodynamic characteristics of any given airfoil in compressible inviscid airflow from a knowledge only of the thickness and camber line parameters is presented. The aerodynamic characteristics considered are: (1) lift-curve slope at zero lift, (2) zero-lift incidence, (3) zero-lift pitching moment coefficient, and (4) chordwise position of the aerodynamic center. The geometrical parameters required to obtain estimates for the aerodynamic characteristics are tabulated.

Author

N73-15982 Engineering Sciences Data Unit, London (England).
COMPARISONS WITH EXPERIMENTAL DATA

Sep. 1972 5 p refs

(ESDU-70011-Amend-A) Copyright. Avail: Issuing Activity

The development of aerodynamic coefficients for wings of small thickness in inviscid flow is discussed. The errors introduced by neglecting the effects of thickness and viscosity in determining the lift-curve slope and aerodynamic center position are analyzed.

The analysis is limited to wings at low incidence for Mach numbers up to 0.6. The data are presented as tables and graphs. Author

N73-15983 Pennsylvania Univ., Philadelphia.
**UNSTEADY AIRFOIL THEORY APPLIED TO CAMBERED
BLADES AND TO BLADE ROWS OF HIGH SOLIDITY Ph.D.**
Thesis

Helmut G. W. Naumann 1971 132 p

Avail: Univ. Microfilms Order No. 72-17403

In turbomachinery as rotor blades pass through the wakes of upstream stator blades each blade experiences pressure and lift fluctuations. The first problem discussed deals with the pressure and lift fluctuations of low solidity cascades where the mutual induction effect of blades of the same blade row becomes negligible. The second problem deals with high solidity cascades. Dissert. Abstr.

N73-16986*# Washington Univ., Seattle.

**A TWO-DIMENSIONAL ITERATIVE SOLUTION FOR THE
JET FLAP**

Alan Charles Herold Washington NASA Feb. 1973 48 p refs

(Grant NGL-48-002-010)

(NASA-CR-2190) Avail: NTIS HC \$3.00 CSCL 01A

A solution is presented for the jet-flapped wing in two dimensions. The main flow is assumed to be inviscid and incompressible. The flow inside the jet is considered irrotational and the upper and lower boundaries between the jet and free stream are assumed to behave as vortex sheets which allow no mixing. The solution is found to be in satisfactory agreement with two dimensional experimental results and other theoretical work for intermediate values of momentum coefficient, but the regions of agreement vary with jet exit angle. At small values of momentum coefficient, the trajectory for the jet, as computed by this method, has more penetration than that of other available data, while at high values of momentum coefficient this solution results in less penetration of the jet into the main flow. Author

N73-16987*# National Aeronautics and Space Administration, Washington, D.C.

ON PEAKY AIRFOIL SECTIONS

Junzo Sato Feb. 1973 43 p refs Transl. into ENGLISH from J. Jap. Soc. Aeronaut. Space Sci. (Japan), v. 18, no. 201, Oct. 1970 p 374-388

(NASA-TT-F-749) Avail: NTIS HC \$3.00 CSCL 01A

The development of airfoil configurations to provide shock-free flow at supersonic speeds is discussed. The airfoil design creates local supersonic regions on the surfaces of the airfoil sections. Expansion waves reflected at sonic lines come back to the airfoil surface as compression waves which decelerate the local supersonic flow isentropically to subsonic speeds. A characteristic of the airfoil section is that a negative pressure peak exists close to the leading edge. Schlieren photographs of the shock wave patterns on typical airfoil sections are provided. Graphs of the pressure distribution for various airfoil configurations and conditions of flight are included. P.N.F.

N73-15988*# National Aeronautics and Space Administration, Langley Research Center, Langley Station, Va.

**SUBSONIC CHARACTERISTICS OF A TWIN-JET SWEEP-
WING FIGHTER MODEL WITH MANEUVERING DEVICES**

Edward J. Ray and Eddie G. Hollingsworth (McDonnell Douglas Co., St. Louis, Mo.) Washington Jan. 1973 292 p refs

(NASA-TN-D-6921; L-8221) Avail: NTIS HC \$3.00 CSCL 01A

An investigation has been conducted at Mach numbers ranging from 0.08 to 0.94 to determine the effects of various combinations of leading-edge slat devices on the static aerodynamic characteristics of a twin-jet swept-wing fighter model. The study also included a determination of the effects of wing leading-edge droop.

trailing-edge chord-extensions, wing fences, and wing-planform and camber modifications. The angle-of-attack range generally extended from about minus 2 deg to 24 deg and the sideslip angles ranged from about minus 6 deg to 13 deg. Author

N73-15991# New York Univ., N.Y. Dept. of Aeronautics and Astronautics.

THE EFFECT OF INJECTION ON BASE DRAG AT TRANSONIC SPEED

Renzo Piva and Carlos Dejesus Jul. 1972 59 p refs
(Grant AF-AFOSR-2167-72; AF Proj. 9782)
(AD-751269; NYU-AA-72-19; AFOSR-72-2044TR) Avail:
NTIS CSCL 01/1

The problem concerning the possible reduction of the transonic drag for a high speed airplane has been studied. Attention has been focused on decreasing the drag forces on the aft portion of the vehicle. The effect of the injection of a small amount of air in the rear of the model has been experimentally investigated. The alteration of the transonic flow field in the shock-boundary layer interaction region, increases the average pressure on the aft section. The required amount of air was relatively low, because of the high sensitivity of the interaction region to any small change in the flow regime. GRA

N73-15992# West Virginia Univ., Morgantown. Dept. of Aerospace Engineering.

CIRCULATION CONTROL BY STEADY AND PULSED BLOWING FOR A CAMBERED ELLIPTICAL AIRFOIL

Richard E. Walters, Danny P. Myer, and Daniel J. Holt Jul. 1972 116 p refs
(Contract N00014-68-A-0512; NR Proj. 215-163)
(AD-751045; TR-32) Avail: NTIS CSCL 01/3

An experimental investigation was performed on the effectiveness of circulation control in producing additional lift and preventing separation on a cambered elliptical airfoil section with a rounded trailing edge. Steady blowing and pulsed blowing from a slot near the rear of the airfoil were used for circulation control. Downwash studies were conducted for the airfoil using potential flow theory, and Reynolds number effects were studied for the no blowing case. Airfoil surface-pressure distributions are presented for the various test conditions. Author (GRA)

N73-15993 Engineering Sciences Data Unit, London (England). **LOW SPEED LONGITUDINAL AERODYNAMIC CHARACTERISTICS OF AIRCRAFT IN GROUND EFFECT**

Oct. 1972 21 p refs Supersedes ESDU-Aero-A.01.01.01
Sponsored by Roy. Aeron. Soc.
(ESDU-72023; ESDU-Aero-A.01.01.01) Copyright. Avail:
Issuing Activity CSCL 01B

A method for estimating the changes in the lift curve, drag, tail lift, and downwash from the wing of an aircraft due to ground effect in incompressible flow is presented. Static treatment of the aerodynamics of aircraft flying in ground effect is defined. The changes in the free air conditions on approaching the ground at constant aircraft lift coefficient by changing incidence are examined. Author

N73-15994 Stanford Univ., Calif.

COMPUTATIONAL METHODS FOR THE SYNTHESIS OF ROTARY WING VTOL AIRCRAFT CONTROL SYSTEMS

Ph.D. Thesis
Wilton Earl Hall 1971 257 p
Avail: Univ. Microfilms Order No. 72-11564

A design procedure is developed which models a rotary-wing VTOL aircraft as two coupled rigid bodies which represent the rotor and fuselage respectively. Previous design approaches for the synthesis of VTOL aircraft controllers have treated rotor and fuselage as dynamically uncoupled systems, and generally the rotor dynamics have been neglected in synthesizing the fuselage controls. Only the low-speed flight regime around hover is considered for this design. The equations for the rotor dynamics and rotor forces on the fuselage are obtained from an analysis of blade motions. The controls-fixed dynamic response of the two rigid body approximation is determined for a typical vehicle

with an articulated rotor and also with a hingeless rotor. A controller has been designed for the two rigid body approximation using eigenvector decomposition of the Euler-Lagrange equations of quadratic synthesis. Dissert. Abstr.

N73-15995 Duke Univ., Durham, N.C.

DYNAMIC INTERACTIONS OF HIGH SPEED TRACKED AIR CUSHION VEHICLES WITH THEIR GUIDEWAYS: A PARAMETRIC STUDY

Ph.D. Thesis
Sherrill Bost Biggers, Jr. 1971 142 p
Avail: Univ. Microfilms Order No. 72-11066

A mathematical model of a tracked air cushion vehicle and its guideway is formulated in order to investigate the vertical dynamic response of the vehicle-guideway system due to high speed vehicle passage. The vehicle is modeled as an arbitrary number of mass systems traveling in tandem, each system consisting of a lower mass (air cushion housing and chassis) and an upper mass (passengers and isolated passenger compartment). A train of vehicles can be represented by using a large number of mass systems in tandem. The vehicle load is transmitted to the guideway as a uniform, distributed pressure which varies in magnitude according to the vehicle vertical accelerations. The guideway is modeled as a series of simply supported Bernoulli-Euler beams with provisions for an elastic subgrade, combined structural and external damping, and a uniform axial compressive force. Dissert. Abstr.

N73-15996 North Carolina State Univ., Raleigh.

DESIGN FOR IMPROVEMENTS TO STATIC PERFORMANCE AND LATERAL-DIRECTIONAL DYNAMIC STABILITY OF A CONSTANT ATTITUDE LIGHT AIRCRAFT

Ph.D. Thesis
Douglas Eugene Humphreys 1971 108 p
Avail: Univ. Microfilms Order No. 72-8939

A design study was conducted to improve static performance and lateral-directional dynamic stability for a light aircraft. Design modifications are developed for a PA28-235C Piper Cherokee to enable it to fly at constant pitch attitude during all modes of flight. Lift modulation over the flight profile is accomplished through the use of full-span Fowler flaps. Lateral control is also provided by these full-span flaps. Improvements in static performance are accomplished by reducing the wing area by 25 percent and making greater utilization of propeller performance. The lateral-directional dynamic stability is improved by the design of a stability augmentation system. This system utilizes sideslip and bank angle feedback. Fast acting servos and electrical compensator networks are used to provide rapid bank angle response and to eliminate unwanted disturbances from sidegusts. Dissert. Abstr.

N73-15997 Case Western Reserve Univ., Cleveland, Ohio.

AN OPTIMAL CONFIGURATION DESIGN OF LIFTING SURFACE TYPE STRUCTURES UNDER DYNAMIC CONSTRAINTS

Ph.D. Thesis
Hirokazu Miura 1972 222 p
Avail: Univ. Microfilms Order No. 72-18717

An optimization, intended to be used in the preliminary design stage, of the structural configuration for a simplified model of a supersonic airplane wing is undertaken. The simplified plan view shape, the wing depth distribution and the skin panel thickness distribution are determined so that an objective function composed of a linear combination of the weight of the wing and the aerodynamic drag is minimized. In addition to static constraints, (yield stress, displacement, angle of attack and the required gross lift), natural vibration frequency and supersonic flutter speed are considered as constraints. A wing is considered to be a sandwich plate of variable thickness. By smearing all inhomogeneities, the skin panels and the sandwiched core are considered to be orthotropic, homogeneous materials. Distinctly large masses such as engines are considered to be concentrated masses at specified points. Dissert. Abstr.

N73-15998# Massachusetts Inst. of Tech., Cambridge. Charles Stark Draper Lab.

SOME EFFECTS OF BIAS ERRORS IN REDUNDANT FLIGHT

CONTROL SYSTEMS

Robert F. Stengel Jun. 1972 12 p refs
(Contract NAS9-10268)

(NASA-CR-130354; E-2688) Avail: NTIS HC \$3.00 CSCI
01B

The controllability and steady-state response of parallel-redundant flight control systems are examined. It is found that state components which appear in the parallel signal paths, or individual actuator commands, are not controllable, although the sum of the command signals is well-behaved. If the response modes associated with these components are not stable, bias errors can cause the components to diverge, leading to the possibility of nuisance trips in failure detection/isolation logic and eventual control system lockup (at saturation). Combining the inputs to the control computers assures that sensor bias will not cause divergence, while cross-strapping control strings bounds divergent response to all bias error inputs. Results of numerical solutions confirm the problem and its solutions.

Author

N73-15999# National Transportation Safety Board, Washington D.C.

AIRCRAFT ACCIDENT REPORT: CAPITOL INTERNATIONAL AIRWAYS, INCORPORATED, DC-8-63F, N4909C; ANCHORAGE, ALASKA, 27 NOVEMBER 1970

29 Mar. 1972 48 p

(NTSB-AAR-72-12) Avail: NTIS HC \$4.50

A Douglas DC-8-63F aircraft crashed following an unsuccessful takeoff attempt from the Anchorage International Airport Anchorage, Alaska, on 27 Nov. 1970. The flight was being operated as a Military Airlift Command (MAC) contract flight from McChord Air Force Base, Tacoma, Washington, to Cam Ranh Bay, Republic of South Viet Nam, with en route fueling stops at Anchorage, Alaska, and Yokota Air Base, Japan. There were 219 military passengers and a crew of 10 aboard the aircraft. Forty-six passengers and one flight attendant received fatal injuries in the post-crash fire. At the time of the takeoff, precipitation, in the form of freezing drizzle, was occurring at the airport and the runway was covered with a light coating of ice. Evidence of tire skid marks, degraded rubber and shredded tire casings were found over most of the length of the runway. The probable cause of this accident was the failure of the aircraft to attain the necessary airspeed to effect liftoff during the attempted takeoff.

Author

N73-16000# National Transportation Safety Board, Washington, D.C. Bureau of Aviation Safety.

AIRCRAFT INCIDENT REPORT: EASTERN AIR LINES, INCORPORATED, BOEING 727-100, N8168G FLIGHT 9701, ATLANTA, GEORGIA, 21 DECEMBER 1971

26 Jul. 1972 18 p ref

(NTSB-AAR-72-22) Avail: NTIS HC \$3.00

A Boeing 727 aircraft struck portions of the approach light system during landing approach at Atlanta International Airport, Georgia on 21 December 1971. Minor damage occurred to the aircraft flaps and landing gear. The cause of the accident was stated as an unexpected and undetected divergence of the aircraft from the glide slope centerline induced by a malfunction of the automatic pilot. The divergence occurred at an altitude where safe recovery could have been made, however, the preoccupation of the pilots with establishing an outside visual reference precluded timely recognition of the divergence.

Author

N73-16001# National Transportation Safety Board, Washington, D.C.

AIRCRAFT ACCIDENT REPORTS: BRIEF FORMAT, US CIVIL AVIATION. ISSUE NO. 3: 1971 ACCIDENTS

29 Sep. 1972 485 p

(NTSB-BA-72-6) Avail: NTIS HC \$26.25

Selected aircraft accident reports, in brief format, occurring in U.S. Civil Aviation operations during calendar year 1971 are presented. The 900 General Aviation accidents contained in this publication represent a random selection. This publication is issued irregularly, normally six times each year. The brief format presents the facts, conditions, circumstances, and probable cause(s) for

each accident. Additional statistical information is tabulated by type of accident, phase of operation, kind of flying, injury index, aircraft damage, conditions of light, pilot certificate, injuries, and causal factors.

Author

N73-16002# National Transportation Safety Board, Washington, D.C.

AIRCRAFT ACCIDENT REPORTS: BRIEF FORMAT, US CIVIL AVIATION. ISSUE NO. 4: 1971 ACCIDENTS

4 Dec. 1972 512 p

(NTSB-BA-72-7) Avail: NTIS HC \$27.75

Selected aircraft accident reports, in brief format, occurring in U.S. Civil Aviation operations during calendar year 1971 are presented. The General Aviation accidents contained in this publication represent a random selection. The brief format presents the facts, conditions, circumstances, and probable cause(s) for each accident. Additional statistical information is tabulated by type of accident, phase of operation, kind of flying, injury index, aircraft damage, conditions of light, pilot certificate, injuries, and causal factors.

Author

N73-16003# National Transportation Safety Board, Washington, D.C.

AIRCRAFT ACCIDENT REPORT: ROSS AVIATION, INCORPORATED, BEECHCRAFT 86-B80, QUEEN AIR, N841NS, ALBUQUERQUE, NEW MEXICO, 19 MAY 1972

13 Dec. 1972 19 p

(NTSB-AAR-72-32) Avail: NTIS HC \$3.00

A Beechcraft Queen Air aircraft, on a scheduled air taxi flight, crashed shortly after takeoff at the Albuquerque, New Mexico airport on 19 May 1972. The aircraft was destroyed by impact forces and post-impact fire. The probable cause of the accident was inadvertent opening of the forward cargo compartment door with resulting damage to the left propeller. Loss of power from the left engine at a critical stage of flight caused the aircraft to crash.

Author

N73-16004# National Transportation Safety Board, Washington, D.C.

AIRCRAFT ACCIDENT REPORT: PUERTO RICO INTERNATIONAL AIRLINES (PRINAIR), INCORPORATED, DEHAVILLAND DH-114, N564PR, PONCE, PUERTO RICO, 24 JUNE 1972

20 Dec. 1972 13 p

(NTSB-AAR-72-34) Avail: NTIS HC \$3.00

A DeHavilland Heron DH-114 crashed on the Mercedita Airport, Ponce, Puerto Rico, during an attempted go-around after landing on Runway 29, on 24 June 1972. The probable cause of this accident was the presence of an unauthorized vehicle on the runway which caused the pilot to attempt a go-around after touchdown to avoid a collision. The maneuver resulted in an overrotation of the aircraft at too low an airspeed to sustain flight.

Author

N73-16005# National Transportation Safety Board, Washington, D.C.

AIRCRAFT ACCIDENT REPORT: EASTERN AIRLINES, INCORPORATED, DC-9-31, N8961E, FORT LAUDERDALE, FLORIDA, 18 MAY 1972

13 Dec. 1972 36 p

(NTSB-AAR-72-31) Avail: NTIS HC \$4.00

A DC-9 aircraft was involved in a landing accident on May 18, 1972, at approximately 1521 eastern daylight time, at the Fort Lauderdale-Hollywood International Airport, Fort Lauderdale, Florida. The accident occurred following a straight-in localizer approach when the aircraft touched down hard on the runway, resulting in the failure of the main landing gear and the separation of the tail section from the aircraft. The aircraft was destroyed by subsequent ground fire. At the time of the accident, heavy rainshowers, associated with thunderstorm activity, were occurring at the airport. The probable cause of this accident was the decision of the pilot to initiate and continue an instrument approach under weather conditions which precluded adequate visual reference and the faulty techniques used by the

pilot during the landing phase of that approach. The flightcrew's nonadherence to prescribed operational practices and procedures compromised the safe operation of the flight. Author

N73-16006# National Transportation Safety Board, Washington, D.C.

AIRCRAFT ACCIDENT REPORT: AERO TAXI, BEECH E18S, N42A, CLEVELAND, OHIO, 22 JUNE 1972

20 Dec. 1972 24 p
(NTSB-AAR-72-33) Avail: NTIS HC \$3.25

A Beech Aircraft, Model E18S, on an air taxi revenue cargo flight, crashed into a residential area at approximately 0840 eastern daylight time, June 22, 1972. The accident occurred shortly after takeoff from Cleveland-Hopkins International Airport, Cleveland, Ohio. The pilot, the only occupant of the aircraft, was fatally injured. Two houses were damaged by aircraft impact and fire, but no injuries were sustained by persons on the ground. The probable cause of this accident was the in-flight failure of the left wing which resulted from a preexisting fatigue crack in the left-wing lower spar cap. The fatigue crack was present during inspections of the spar cap for cracks conducted prior to the accident, but it was not detected during these inspections.

Author

N73-16007*# National Aeronautics and Space Administration, Ames Research Center, Moffett Field, Calif.

COMPUTER PROGRAMS FOR ESTIMATION OF STOL TAKEOFF, LANDING, AND STATIC PERFORMANCE

Susan E. Post Dec. 1972 66 p refs Prepared in cooperation with Army Air Mobility R and D Lab., Moffett Field, Calif.
(NASA-TM-X-62217) Avail: NTIS HC \$5.50 CSCL 01B

A set of computer programs has been developed for evaluating the performance of powered-lift STOL aircraft. Included are a static performance summary and dynamic calculations of takeoff and landing performance. The input, output, options, and calculations for each program are described. The programs are written in FORTRAN IV and are currently available on TSS 360. Three independent sections are presented corresponding to the three programs: (1) static performance, (2) takeoff performance, and (3) landing performance.

Author

N73-16008*# National Aeronautics and Space Administration, Flight Research Center, Edwards, Calif.

MODELING OF AIRPLANE PERFORMANCE FROM FLIGHT-TEST RESULTS AND VALIDATION WITH AN F-104G AIRPLANE

Robert T. Marshall and William G. Schweikhard Washington Feb. 1973 30 p refs
(NASA-TN-D-7137; H-723) Avail: NTIS HC \$3.00 CSCL 01B

A technique of defining an accurate performance model of an airplane from limited flight-test data and predicted aerodynamic and propulsion system characteristics is developed. With the modeling technique, flight-test data from level accelerations are used to define a 1g performance model for the entire flight envelope of an F-104G airplane. The performance model is defined in terms of the thrust and drag of the airplane and can be varied with changes in ambient temperature or airplane weight. The model predicts the performance of the airplane within 5 percent of the measured flight-test data. The modeling technique could substantially reduce the time required for performance flight testing and produce a clear definition of the thrust and drag characteristics of an airplane.

Author

N73-16009*# Aerospace Corp., El Segundo, Calif. Air Transportation Group.

STUDY OF V/STOL AIRCRAFT IMPLEMENTATION. VOLUME 2: APPENDICES

A. Androsky, S. C. Miller, J. A. Neiss, W. J. Portenier, and H. M. Webb Nov. 1972 315 p refs
(Contract NAS2-6473)
(NASA-CR-114518; ATR-73(7303)-1-Vol-2-App) Avail: NTIS HC \$17.75 CSCL 01B

An analysis of V/STOL aircraft implementation and utilization is presented. The subjects discussed are: (1) short-haul air

transportation requirements, (2) available aircraft technology, (3) aircraft production requirements, (4) airport requirements, (5) roles and responsibilities, and (6) cost and funding. Author

N73-16010*# National Aeronautics and Space Administration, Flight Research Center, Edwards, Calif.

EXPLICIT DETERMINATION OF LATERAL-DIRECTIONAL STABILITY AND CONTROL DERIVATIVES BY SIMULTANEOUS TIME VECTOR ANALYSIS OF TWO MANEUVERS

Glenn B. Gilyard Washington Feb. 1973 12 p refs
(NASA-TM-X-2722; H-751) Avail: NTIS HC \$3.00 CSCL 01B

An extension of the time vector technique for determining stability and control derivatives from flight data is formulated. The technique provides for explicit determination of derivatives by means of simultaneous analysis of two maneuvers which differ by a dependent control input. The control derivatives for the dependent input are also explicitly determined. This extended technique is preferable to the application of the time vector method to single maneuvers in that no estimates of derivatives are required. An example illustrating the application of the technique is given.

Author

N73-16011*# National Aeronautics and Space Administration, Lewis Research Center, Cleveland, Ohio.

LOW-FREQUENCY REAR QUADRANT NOISE OF A TURBOJET ENGINE WITH EXHAUST DUCT MUFFLING

Richard P. Woodward and Gene L. Minner Washington Feb. 1973 21 p refs
(NASA-TM-X-2718; E-7202) Avail: NTIS HC \$3.00 CSCL 20A

A J-65 engine was run with a tuned sound-absorbing exhaust duct to study the internal and jet components of rear quadrant noise. Full muffler, hard wall duct, and regular production engine configurations were tested. The jet exhaust velocities were subsonic. The use of the exhaust muffler extended the relation between the jet noise and the eighth power of the jet velocity to lower velocities than for the hard wall duct.

Author

N73-16012*# National Aeronautics and Space Administration, Langley Research Center, Langley Station, Va.

THE EFFECTS OF CONFIGURATION CHANGES ON THE AERODYNAMIC CHARACTERISTICS OF A FULL-SCALE MOCKUP OF A LIGHT TWIN ENGINE AIRPLANE

Marvin P. Fink, James P. Shivers, H. Douglas Greer, and James L. Megrail (Army Air Mobility Res. and Develop. Lab., Fort Eustis, Va.) Washington Sep. 1972 223 p refs
(NASA-TN-D-6896; L-8375) Avail: NTIS HC \$3.00 CSCL 01C

Wind tunnel tests of a full-scale model of a light twin engine aircraft were conducted. The angle of attack was varied from minus 4 degrees to plus 20 degrees. The sideslip range was plus or minus 8 degrees. Thrust coefficients were 0, 0.20, and 0.44. Tests were made with various nacelle configurations, modes of propeller rotation, orientation of the thrust axis, and airfoil section at Reynolds numbers of 2.96 times one million and 2.05 times one million.

Author

N73-16013*# Mount Auburn Research Associates, Inc., Newton Upper Falls, Mass.

GODUNOV METHOD AND COMPUTER PROGRAM TO DETERMINE THE PRESSURE AND FLOW FIELD ASSOCIATED WITH A SONIC BOOM FOCUS

Lee W. Parker and Robert G. Zalosh Washington NASA Jan. 1973 109 p refs
(Contract NAS1-10276)

(NASA-CR-2127) Avail: NTIS HC \$3.00 CSCL 20A

A computer method has been developed to calculate the flow field associated with sonic boom focusing. Solutions are obtained for focussing caused by localized cold spots in the atmosphere, as well as for N-waves with concave fronts. Results include focus factors and the length scales of the focal region. Both strong and weak shock waves are studied.

Author

N73-16014*# National Aeronautics and Space Administration, Ames Research Center, Moffett Field, Calif.
PITCH ATTITUDE, FLIGHT PATH, AND AIRSPEED CONTROL DURING APPROACH AND LANDING OF A POWERED LIFT STOL AIRCRAFT

James A. Franklin and Robert C. Innis Dec. 1972 68 p refs (NASA-TM-X-62203) Avail: NTIS HC \$5.50 CSCL 01C

Analytical investigations and piloted moving base simulator evaluations were conducted for manual control of pitch attitude, flight path, and airspeed for the approach and landing of a powered lift jet STOL aircraft. Flight path and speed response characteristics were described analytically and were evaluated for the simulation experiments which were carried out on a large motion simulator. The response characteristics were selected and evaluated for a specified path and speed control technique. These characteristics were: (1) the initial pitch response and steady pitch rate sensitivity for control of attitude with a pitch rate command/ attitude hold system, (2) the initial flight path response, flight path overshoot, and flight path-airspeed coupling in response to a change in thrust, and (3) the sensitivity of airspeed to pitch attitude changes. Results are presented in the form of pilot opinion ratings and commentary, substantiated where appropriate by response time histories and aircraft states at the point of touchdown. Author

N73-16015*# Massachusetts Inst. of Tech., Cambridge, Aeroelastic and Structures Research Lab.
INVESTIGATION OF SOME PARAMETERS AFFECTING THE STABILITY OF A HINGELESS HELICOPTER BLADE IN HOVER

Peretz Friedmann Aug. 1972 19 p refs

(Contract NAS2-6175)

(NASA-CR-114525; ASRL-TR-166-4) Avail: NTIS HC \$3.00 CSCL 01B

Equations of motion are used to investigate the effects of the choice of the mode shape and built-in coning angle on the stability boundaries of hingeless blades in hover. The results obtained indicate that the stability boundaries are dependent upon the mode shape to a considerable degree. It was also found that positive built-in coning is usually destabilizing while a negative amount of built-in coning can be quite stabilizing.

Author

N73-16016# Messerschmitt-Boelkow-Blohm G.m.b.H., Hamburg (West Germany).
RECENT STUDIES ON METEOROLOGICAL ICING PARAMETERS [NEUERE UNTERSUCHUNGEN AUF DEM GEBIET DER METEOROLOGISCHEN VEREISUNGSPARAMETER]

W. Kleuters 12 Sep. 1972 37 p refs In GERMAN Presented at the 5th DGLR Ann. Meeting, Berlin, 4-6 Oct. 1972 (MBB-UH-11-72-O; DGLR-Paper-72-109) Avail: NTIS HC \$4.00

Natural ice formation conditions were investigated during test flights of the Transall C-160, in 1969 and 1970. The meteorological icing parameters, free water content, drop diameter and temperature have been measured. A special device was used for measuring free water content, which was reliable at high temperature and high water content. The data were evaluated statistically according to NACA/TN2738 and the results compared with the values in FAR25, Appendix C. It is shown that for high temperature and water content there are great differences, which can be traced back to the measuring equipment used by NACA, a rotating multicylinder, which does not function satisfactorily for high water content.

Author (ESRO)

N73-16017# Messerschmitt-Boelkow-Blohm G.m.b.H., Hamburg (West Germany).
COMPARISON BETWEEN STOL AIRCRAFT WITH MECHANICAL HIGH-LIFT SYSTEMS AND STOL AIRCRAFT WITH BLOWN FLAP WINGS [STOL-FLUGZEUGE MIT MECHANISCHEN HOCHAUFTRIEBSYSTEMEN IM VERGLEICH ZU STOL-FLUGZEUGEN MIT BLASKLAPPENFLUEGELN]

E.-A. Bielefeldt 20 Sep. 1972 35 p refs In GERMAN Presented at the 5th DGLR Ann. Meeting, Berlin, 4-6 Oct. 1972

(MBB-UH-12-72-O; DGLR-Paper-72-057) Avail: NTIS HC \$3.75

The net lift of modern mechanical high lift devices and externally blown flaps applied to STOL aircraft is compared. The possibilities of achieving higher aerodynamic efficiencies with these high lift devices are discussed. Aerodynamic installation problems and influence of the installation weights of several devices on the net lift are surveyed. The net lift, of complex mechanical and blown flap systems is determined for a STOL aircraft, which has a wing loading of 370 kp/sq m and a maximal lift coefficient in trimmed situation of about 3.5. It is shown that for this case mechanical high lift devices are superior to blown flaps.

Author (ESRO)

N73-16018# Messerschmitt-Boelkow-Blohm G.m.b.H., Hamburg (West Germany).

INFLUENCE OF AIRWORTHINESS REGULATIONS ON TAKEOFF AND LANDING PERFORMANCE OF QSTOL AIRCRAFT [EINFLUSS VON LUFTTUECHTIGKEITSVORSCHRIFTEN AUF DIE START- UND LANDELEISTUNGEN VON QSTOL-FLUGZEUGEN]

Heinz G. Klug 20 Sep. 1972 25 p In GERMAN Presented at the 5th DGLR Ann. Meeting, Berlin, 4-6 Oct. 1972

(MBB-UH-13-72-O; DGLR-Paper-72-056) Avail: NTIS HC \$3.25

The decisive influence of the requirements and assumptions with regard to takeoff and landing performance on the design of QSTOL aircraft is shown by using a typical example of an aircraft with externally blown flaps. This aircraft would need less than 500 m runway length according to one set of rules, and according to another set nearly 1000 m. The influence of different regulations on the determination of the lowest allowable velocities in flying over obstacles is represented and explained. Aircraft with blown flaps are very sensitive to this, and the whole comparison between different concepts can be distorted. A physically based set of regulations is required.

Author (ESRO)

N73-16019# Dornier-Werke G.m.b.H., Friedrichshafen (West Germany).

STUDY OF FLIGHT DYNAMICS USING PROBLEM ORIENTED PROGRAM LANGUAGES [UNTERSUCHUNG DER FLUGZEUGDYNAMIK MIT HILFE BLOCKORIENTIERTER PROGRAMMIERSPRACHEN]

H. Friedrich, H. Munser, and W. Kohl Bonn Bundeswehramt 1972 159 p refs In GERMAN; ENGLISH summary Sponsored by Bundesmin. fuer Verteidigung (BMVg-FBWT-72-21) Avail: NTIS HC \$10.00; Bundeswehramt 25 DM

A problem oriented program was tested for its application to digital simulation in flight dynamics investigations. These investigations are based on conventional computing methods with small perturbations theory and on simulation. A digital simulation language is suggested as a link between the two methods. The possibilities of CSMP, a problem oriented IBM program, were examined with the aid of two reference aircraft, Fiat G-91 and Dornier Do-31. The programming and testing are described, and all the possibilities available in flight dynamics with this computing technique are demonstrated. Cost aspects are mentioned.

ESRO

N73-16020# Intermetrics, Inc., Cambridge, Mass.
PWI (PILOT WARNING INDICATORS) SYSTEMS SURVEY

Final Report, Apr. - Nov. 1971

James H. Flanders, Peter A. Grundy, and Neal A. Carlson Nov. 1971 151 p refs

(Contract DOT-TSC-188)

(PB-212496; DOT-TSC-188-2) Avail: NTIS HC \$3.00 CSCL 01B

The survey is presented, using a compilation, classification, and review of 176 documents related to PWI and CAS research and development. Subject categories include: CAS system references; PWI system references; proceedings and literature searches; facilities and programs; and atmospheric physics. A multidimensional classification code for CAS and PWI systems is also included.

Author (GRA)

N73-16021# Princeton Univ., N.J.
HELICOPTER STATION KEEPING Final Task Report, Sep. 1966 - 30 Dec. 1971

Theodor A. Duker Sep. 1972 95 p refs
 (Contract DA-28-043-AMC-02412(E); DA Proj. 1H1-62202-A-219)
 (AD-751459; ECOM-02412-9) Avail: NTIS CSCL 01/2

A discussion of all aspects of formation flight, from initiation to termination, leads to an emphasis on the station keeping control loop. The most essential topics are brought into focus in order to reveal and to emphasize the basic relationships which must be considered in decisions about formation flight system features and requirements. The significance of leader-to-follower data communication is explored in detail. Nominal station keeping trajectories are defined in terms of the motion of a nominal point coordinate system. The information available to the follower determines his ability to calculate the location and orientation of the nominal coordinate system, i.e., his position errors. The need to know the reference orientation at low speeds and hover is shown. Acceleration errors are estimated based on a simple model for the positioning control loop, and relatively narrow ranges of gains and bandwidth are found feasible. Improvements can be made if leader information is available and utilized.

Author (GRA)

N73-16022# Princeton Univ., N.J.
A DYNAMIC HELICOPTER PERFORMANCE AND CONTROL MODEL Final Task Report, 1 Sep. 1966 - 30 Dec. 1971

G. J. Born, D. Carico, and E. J. Durbin Aug. 1972 66 p refs
 (Contract DA-28-043-AMC-02412(E); DA Proj. 1H1-62202-A-219)
 (AD-751460; ECOM-02412-11) Avail: NTIS CSCL 01/3

The report gives the results of the development of a dynamic helicopter performance and control model. The dynamic performance model is obtained by using the force and rotor aerodynamic equations. This performance model together with the moment balance and control equations are used as a basis for a helicopter control model. This model can be used for over relatively large speed range and varying rotor rpm. As an example, an analog computer simulation is made for a UH-1C helicopter, performing a steep descent maneuver, close to autorotation boundary.

Author (GRA)

N73-16023# ARO, Inc., Arnold Air Force Station, Tenn.
POST-STALL TESTING OF AIRCRAFT WITH A WIND TUNNEL CAPTIVE SYSTEM Final Report, Feb. - Jun. 1972

J. R. Milillo AEDC Nov. 1972 21 p refs
 (Contract F40600-73-C-0004; ARO Proj. PW5284)
 (AD-751461; ARO-PWT-TR-72-115; AEDC-TR-72-126) Avail: NTIS CSCL 01/3

High-speed aircraft may have unsatisfactory stall characteristics and the aircraft may be lost because of the uncontrolled flight gyrations encountered in attempting to maneuver in the stalled flight regime. Results are presented of a study to determine the feasibility of using a captive technique in a wind tunnel to study aircraft post-stall characteristics and to define boundaries for maintaining controlled flight of the aircraft. The technique appears feasible but needs to be developed by conducting pilot tests in an existing facility.

Author (GRA)

N73-16024# Defense Documentation Center, Alexandria, Va.
AIRCRAFT LANDINGS Report Bibliography, Jan. 1970 Apr. 1972

Nov. 1972 156 p refs
 (AD-751800; DDC-TAS-72-50) Avail: NTIS CSCL 01/2

The bibliography contains unclassified references on Aircraft Landings. These references deal with carrier controlled radar, carrier landings, instrument landings, approach, night landings, ground controlled radar, landing lights, display systems, control systems, glide path systems, human factors, and landing lights. Corporate Author-Monitoring Agency, Subject, Personal Author and Title Indexes are provided.

Author (GRA)

N73-16025# Air Force Aero Propulsion Lab., Wright-Patterson AFB, Ohio.
FIRE DETECTION SYSTEM PERFORMANCE IN USAF

AIRCRAFT Final Technical Report, Mar. - Sep. 1971
 Charles Delaney Aug. 1972 26 p refs
 (AD-751346; AFAPL-TR-72-49) Avail: NTIS CSCL 01/3

The report is concerned with the determination of the performance of fire detection systems in USAF aircraft. Data on false fire warnings and aircraft engine nacelle fires were taken from Air Force accident/incident reports. These data included the time period 1965 through 1970 and is restricted to noncombat related accidents/incidents. Analysis of the data showed that false fire warnings are a major problem in the majority of USAF aircraft (83% of all reported alarms are false). These false fire warnings resulted in damage or destruction to aircraft as well as crew injuries/fatalities. In addition, it was found that in approximately 50% of the engine nacelle fires, where the performance of the detection system could be determined, the system did not provide an alarm. It was also found that the fire detection system in a number of aircraft had been partially or totally removed to reduce or eliminate the false fire warning problem. As a consequence the majority of the fires which occurred in these aircraft were not detected.

Author (GRA)

N73-16026# Dunlap and Associates, Inc., Darien, Conn.
PREDICTIVE AND ADAPTIVE PROCESSES IN THE CONTROL OF AIR FORCE SYSTEMS Final Report

Charles R. Kelley 30 Sep. 1972 19 p
 (Contract F44620-72-C-0006; AF Proj. 9778)
 (AD-751306; AFOSR-72-2037TR) Avail: NTIS CSCL 01/3

The project has been concerned with prediction and adaptation in control of systems such as military aircraft. The processes were explored in human operators, in adaptive displays for the human operator and in a means for coupling manual with automatic control. The latter development, termed automanual control, was mechanized and tested in the laboratory. Automanual control with a predictor instrument proved superior to four other modes of control to which it was compared.

Author (GRA)

N73-16027# Boeing Co., Morton, Pa. Vertol Div.
USE OF THE FINITE ELEMENT DAMPED FORCED RESPONSE STRAIN ENERGY DISTRIBUTION FOR VIBRATION REDUCTION

John J. Sciarra and Robert G. Ricks 1972 30 p refs Presented at AROD Mil. Theme Rev. The Helicopter and V/STOL Aircraft Res. Conf., Moffett Field, Calif., 26-27 Sep. 1972
 (Contract DAHC04-71-C-0048)
 (AD-751809; AROD-9621-1-E) Avail: NTIS CSCL 01/3

Expressions for the vibratory strain energy distribution using the damped forced response (DFR) are developed. The modes above and below the excitation frequency are analyzed separately. The results are then combined to establish criteria for structural optimization. A helicopter forward pylon structural model is used to demonstrate the advantages of the DFR strain energy concept for structural vibrational optimization.

Author (GRA)

N73-16028# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.
COORDINATE STABILIZATION FOR A FLEXIBLE AIRCRAFT DURING FLIGHT IN A TURBULENT ATMOSPHERE

V. V. Udilov 8 Sep. 1972 13 p refs Transl. into ENGLISH from the mono. "Primenenie Invariantnykh Sistem Avtomaticheskogo Upravleniya" Moscow, Izd-vo Nauka, 1970 p 221-231
 (AD-751148; FTD-HT-23-863-72) Avail: NTIS CSCL 01/4

The problem is considered of automatically controlling aircraft altitude and pitch angle in the duck system. The aircraft dynamics are described by a system of linear differential equations with constant coefficients: three equations of motion of the center of gravity and rotation of the aircraft as a solid body, and a combination of equations for the flexible oscillations of an elastic fuselage in the plane of longitudinal symmetry. It is assumed that the autopilot acts on the flaps in changing the pitch and attack angles, the generalized coordinates characterizing the bending oscillations of the fuselage, and the nose controlling surface, as well as in changing the slope of the trajectory.

Author (GRA)

N73-16029# Lockheed Missiles and Space Co., Sunnyvale, Calif. Ground Vehicle Systems.

HIGH PERFORMANCE HELICOPTER HOIST PROGRAM Final Report

Louis J. Lawson, J. H. Duddy, R. R. Gilbert, M. R. Helvey, E. H. Jacobsen, R. Ruth, and W. T. Wada Aug. 1972 169 p refs (Contract DAAD05-72-C-0099)

(AD-751217; LMSC-D267477; LWL-CR-02M72) Avail: NTIS CSCL 01/3

The report presents a feasibility study on a flywheel powered personnel rescue hoist for helicopters. It includes investigations of flywheel configurations, materials, and associated equipment including bearings, seals, and pumps. Also included are discussions of human factors considerations and design considerations affecting component selection, hoist configuration, and hoist installation. Particular attention is given to the capability of a 13.5-lb. 73.5 w-hr flywheel to provide the short duration high power required to affect rescue hoisting speed as high as 500 ft per min. without overtaxing the helicopter's limited accessory power capacity. Author (GRA)

N73-16215 Texas Univ., Austin.

THEORETICAL EFFECTS OF POROSITY AND ANGLE OF ATTACK ON JET STRETCHER PERFORMANCE Ph.D. Thesis

Ben Russell Eppright, Jr. 1971 117 p
Avail: Univ. Microfilms Order No. 72-11341

Two methods of improving the usefulness of a jet stretcher are investigated. Both methods attempt to make possible the use of a jet stretcher designed for a body at zero angle of attack with the same body at small angles of attack. The two methods are: (1) making the jet stretcher walls porous, and (2) placing the jet stretcher at an angle of attack. The above methods are investigated theoretically by solving the supersonic, three-dimensional flow field about the body with the jet stretcher and without the jet stretcher. The solutions are obtained numerically using the Method of Characteristics for an ideal, inviscid gas. The derivation of the finite difference equations is included. The results are first compared to experimental data to establish the accuracy of the solution. It is found that the solution is very accurate. The solutions for the body with the jet stretcher are then compared to the solutions for the body without the jet stretcher. Dissert. Abstr.

N73-16216 Stanford Univ., Calif.

MODELING OF A SATELLITE AIRPORT SYSTEM FOR LARGE METROPOLITAN AREAS: A SYSTEMS ANALYSIS Ph.D. Thesis

Inder Kumar Sud 1971 195 p
Avail: Univ. Microfilms Order No. 72-11674

The satellite airport system is presented as a possible solution to the growing congestion problem at the major metropolitan airports. The system visualizes a large airport as the hub of a ring of satellites around it. The satellite airport system includes conventional take-off and landing (CTOL) airports, short take-off and landing (STOL) ports, and collection-ports linked to the main airport by means of transportation links. It is proposed that the short-haul and some of the medium-haul passengers would be handled by the satellite airports and the remaining passengers would enter the system at one of the satellite collection-ports, and then would be transported to the main airport. A system approach is proposed to analyze the satellite airport concept for large metropolitan areas. Various socioeconomic factors that influence the airport location are considered. A mathematical model formulates the problem as a fixed charge selection-allocation problem. Dissert. Abstr.

N73-16222# Landing Aids Experiment Station, Arcata, Calif.

THERMAL FOG DISPERSAL MANUAL

Dec. 1972 76 p refs Reprinted Sponsored by AF, Navy, Civil Aeron. Admin., CAB, Air Trans. Assoc., and Air Line Pilots Assoc.

(Contract C13cA-136)

(FAA-RD-72-138) Avail: NTIS HC \$6.00

The requirements, basic principles of design, construction, operation, and maintenance of a thermal fog dispersal system are described. The recommended installation is a high pressure

system wherein fuel is pumped to the burner lines at pressures over 1000 p.s.i., atomized by passing through an orifice plate in the burner head, and automatically ignited. Atmospheric heat requirements for the dissipation of fog, the effect of winds on system design, and the interface between aircraft and fog dispersal system operations are analyzed. Author

N73-16226# Massachusetts Inst. of Tech., Cambridge. Engineering Projects Lab.

NONLINEAR AND FINITE PAD LENGTH PERFORMANCE OF VEHICLE AIR CUSHION SUSPENSIONS

D. N. Wormley, D. P. Garg, and A. B. Boghani Feb. 1972 130 p refs

(Contract DOT-FR-10007)

(PB-212705; EPL-72-72966-1; FRA-RT-73-6) Avail: NTIS HC \$3.00 CSCL 13B

Nonlinear and small perturbation linear models for the one-dimensional heave motion of a basic flexible-skirted air cushion suspension are formulated. A study of linear and nonlinear model characteristics under transient guideway and external force inputs is conducted to determine over what range of cushion configurations, operating conditions, and input disturbance levels a linear model provides a good approximation to the nonlinear cushion model. The performance of a finite pad length suspension on a guideway containing random irregularities is determined. To illustrate the design information resulting from the transient performance and finite pad length study, the prototype designs of suspensions for intraurban and intercity vehicles are discussed. Author (GRA)

N73-16229# Naval Postgraduate School, Monterey, Calif.

IMPLEMENTATION OF A FIXED BASE SPIN SIMULATOR M.S. Thesis

Bruce Holladay Kenton Sep. 1972 139 p refs
(AD-751644) Avail: NTIS CSCL 14/2

The report discusses the design and implementation of a fixed-based spin simulator and the results derived from conducting preliminary spin tests on the simulator. The central piece of equipment in the simulator was a hybrid computer in which the analog computer solved the equations of motion while the digital computer performed the tasks of program control and aerodynamic data storage. The visual display consisted of a computer-drawn picture on a graphics terminal, while pilot control was obtained by use of a simulated cockpit situated in front of the graphics terminal. Author (GRA)

N73-16247*# National Aeronautics and Space Administration. Flight Research Center, Edwards, Calif.

DESIGN AND FLIGHT TESTING OF A NULLABLE COMPRESSOR FACE RAKE

Jon K. Holzman and Gordon A. Payne Washington Jan. 1973 17 p refs

(NASA-TN-D-7162; H-733) Avail: NTIS HC \$3.00 CSCL 20D

A compressor face rake with an internal valve arrangement to permit nulling was designed, constructed, and tested in the laboratory and in flight at the NASA Flight Research Center. When actuated by the pilot in flight, the nullable rake allowed the transducer zero shifts to be determined and then subsequently removed during data reduction. Design details, the fabrication technique, the principle of operation, brief descriptions of associated digital zero-correction programs and the qualification tests, and test results are included. Sample flight data show that the zero shifts were large and unpredictable but could be measured in flight with the rake. The rake functioned reliably and as expected during 25 hours of operation under flight environmental conditions and temperatures from 230 K (-46 F) to greater than 430 K (314 F). The rake was nulled approximately 1000 times. The in-flight zero-shift measurement technique, as well as the rake design, was successful and should be useful in future applications, particularly where accurate measurements of both steady-state and dynamic pressures are required under adverse environmental conditions. Author

N73-16274# ARO, Inc., Arnold Air Force Station, Tenn.
SIMULATION OF A HIGH DISC LOADING FREE PROPELLER IN A CROSS FLOW BY THE VORTEX-LATTICE METHOD
 Final Report, 10 Nov. 1969 - 30 Jun. 1971
 R. L. Parker, Jr. and F. L. Heltsley AEDC Nov. 1972 102 p refs
 (Contract F40600-73-C-0004; AF Proj. 69BT; ARO Proj. 8D5026)
 (AD-751463; ARO-OMD-TR-72-98; AEDC-TR-72-139) Avail: NTIS CSCL 01/3

A study was conducted to develop an analytical model for the investigation of flow fields about intermediate disc loading lift devices for VTOL applications. Classical vortex-lattice theory was used in conjunction with experimental data for representing a free propeller in a crossflow. The jet phenomena to be simulated by the method are discussed. A number of previous attempts at vortex-lattice modeling are presented. Analytical stream lines and field vectors are compared with available experimental data. The results are evaluated and recommendations are made for further model development. Author (GRA)

N73-16283# Douglas Aircraft Co., Inc., Long Beach, Calif.
A NEW FAMILY OF AIRFOILS BASED ON THE JET-FLAP PRINCIPLE Technical Report, Apr. 1971 - Apr. 1972
 Andrew B. Bauer Sep. 1972 63 p refs
 (Contract N00014-71-C-0250; NR Proj. 215-189)
 (AD-751075; MDC-J5713) Avail: NTIS CSCL 20/4

A new family of airfoils is based largely on the utilization of the jet flap principle and termed power profiles. Several unique features associated with this new concept, and the applicability of existing experimental data and theoretical methods to its evaluation, design and development are described. This technology is used to develop a configuration suitable for wind tunnel testing, and the report concludes with a discussion of some outstanding aerodynamic problems for which analytical and experimental research is required. GRA

N73-16466# Institute for Defense Analyses, Arlington, Va. Jason Div.
STRATOSPHERIC NITRIC OXIDE PRODUCTION FROM PAST NUCLEAR EXPLOSIONS AND ITS RELEVANCE TO PROJECTED SST POLLUTION
 H. M. Foley and M. A. Ruderman Aug. 1972 34 p refs
 (AD-751295; P-894; IDA/HQ-72-14452) Avail: NTIS CSCL 04/1

It is shown that during certain years of intense nuclear testing, high-yield nuclear explosions seem to have injected into the stratosphere a few times 10 to the 34th power nitric oxide molecules. This is very similar to upper estimates for NO generation from 500 SSTs flying for a year. Large catalytic ozone reduction from such NO injection was not observed in worldwide or local total ozone measurements. Author (GRA)

N73-16483* National Aeronautics and Space Administration, Washington, D.C.
SYSTEM FOR INDICATING DIRECTION OF INTRUDER AIRCRAFT Patent

Anne W. Story, inventor (to NASA) Issued 2 Jan. 1973 8 p
 Filed 16 Mar. 1971 Continuation-in-part of abandoned US Patent Appl. SN-808822, filed 20 Mar. 1969
 (NASA-Case-ERC-10226-1; US-Patent-3,708,671;
 US-Patent-Appl-SN-124909; US-Patent-Class-250-209;
 US-Patent-Class-250-215; US-Patent-Class-250-217;
 US-Patent-Class-315-153; US-Patent-Class-340-25;
 US-Patent-Class-340-27R; US-Patent-Appl-SN-808822) Avail: US Patent Office CSCL 14B

A pilot warning indicator system consisting of a flashing beacon, a detector, and an indicating panel is described. The detector responds to radiant energy from another aircraft's beacon by energizing particular signal lamps positioned in the periphery of the pilot's normal field of view. Since the positions of the energized lamps are related to the direction from which radiant energy is received by the detector, the pilot is apprised of the relative position of an intruder aircraft without any shift in visual fixation. Official Gazette of the U.S. Patent Office

N73-16514# Army Aviation Systems Test Activity, Edwards, AFB, Calif.

A PORTABLE INSTRUMENTATION KIT FEASIBILITY STUDY
 Report for 22 May 1970 - Nov. 1971

Robert P. Jefferis and William T. Rivers Jun. 1972 46 p refs
 (USAAVSCOM Proj. 70-17)
 (AD-751188; USAASTA-70-17) Avail: NTIS CSCL 14/2

The purpose of this study was to investigate the feasibility of developing an airborne instrumentation kit that could be easily transported and quickly installed. The system would need to be compatible with anticipated US Army vehicle and test requirements. Results show that a system can be developed which will meet the requirements for all but the most extensive testing. The system will also interface with existing instrumentation and data processing systems. The weight of the system is estimated to be 30 pounds with dimensions of 12 by 15 by 9 inches. The cost is expected to be approximately \$90,000.

Author (GRA)

N73-16524*# Pratt and Whitney Aircraft, East Hartford, Conn.
LABYRINTH SEAL TESTING FOR LIFT FAN ENGINES

L. J. Dobek Feb. 1973 78 p refs

(Contract NAS3-14409)

(NASA-CR-121131; PWA-TM-4593) Avail: NTIS HC \$6.00 CSCL 11A

An abradable buffered labyrinth seal for the control of turbine gas path leakage in a tri-turbine driven lift fan was designed, tested, and analyzed. The seal configuration was not designed to operate in any specific location but was sized to be evaluated in an existing test rig. The final sealing diameter selected was 28 inches. Results of testing indicate that the flow equations predicted seal air flows consistent with measured values. Excellent sealing characteristics of the abradable coating on the stator land were demonstrated when a substantial seal penetration of .030 inch into the land surface was encountered without appreciable wear on the labyrinth knife edges. Author

N73-16576*# Scientific Translation Service, Santa Barbara, Calif.
USE OF COMPOSITE MATERIALS IN AIRCRAFT STRUCTURES

A. S. Volmir, V. F. Pavlenko, and A. T. Ponomarev Washington
 NASA Jan. 1973 17 p refs Transl. into ENGLISH from Mekhan. Polimerov, Akad. Nauk Latv. SSR (Riga), Jan. - Feb. 1972 p 105-112

(Contract NASw-2483)

(NASA-TT-F-14648) Avail: NTIS HC \$3.00 CSCL 11D

The applicability of a group of composite boron and carbon plastic fiber materials in aircraft structural component and engine designs is evaluated as an approach to the damping of aircraft reactions to dynamic and impact forces. The properties of some well-developed composites are compared with those of conventional materials. Examples are given for some aircraft applications of composites. Author

N73-16597 National Lending Library for Science and Technology, Boston Spa (England).

[VISIBILITY MEASUREMENTS FROM THE GROUND AND AN AERODROME]

[1972] 64 p refs Transl. into ENGLISH from Met. Nat. (Paris), no. 76

(NLL-M-20785-(5828.4F)) Avail: Natl. Lending Library, Boston Spa, Engl.: 6 NLL photocopy coupons

Articles on the observation, measurement, and the automatic calculation of runway visibility are presented.

N73-16598 National Lending Library for Science and Technology, Boston Spa (England).

OBSERVATION AND MEASUREMENT OF VISIBILITY AT THE GROUND

C. PerrinDeBrichambaut In its Visibility Measurements from the Ground and an Aerodrome [1972] p 2-38

The determination of visibility on an airport is discussed. Definitions of daylight and night visibilities, meteorological optical range, runway visual range, quantities and fundamental units are presented. Visibility measuring instruments which depend on measuring the opacity of the atmosphere, or the mean coefficient of extinction discussed include telephotometric instruments, extinction instruments, and photoelectric transmission instruments. The orientation and calibration of equipment is discussed along with the standardization of measuring procedures. F.O.S.

N73-16599 National Lending Library for Science and Technology, Boston Spa (England).

AUTOMATIC CALCULATION OF RUNWAY VISUAL RANGE ON AN AERODROME

A. Bettan *In its* Visibility Measurements from the Ground and an Aerodrome [1972] p 39-61

The use of a LYNX controlled transmissometer is discussed for rapid measurement and continuous dissemination of visibility to aircraft on final approach, or takeoff. The general principles used to calculate horizontal visibilities are reviewed, and the collection and dissemination of visibilities by the transmissometer are described along with the LYNX computer programming. F.O.S.

N73-16612# Transportation Systems Center, Cambridge, Mass. **CLIMATIC IMPACT ASSESSMENT PROGRAM. PROCEEDINGS OF THE SURVEY CONFERENCE**

A. E. Barrington Sep. 1972 289 p refs Conf. held at Cambridge, Mass.; 15-16 Feb. 1972

(Contract DOT-OS-320)

(PB-212427; DOT-TSC-OST-72-13) Avail: NTIS HC \$3.00 CSCL 04A

The report contains the proceedings of a survey conference, concerning the impact of climatic changes which might result from perturbation of the upper atmosphere by the exhaust effluent of a world high altitude aircraft fleet, as projected to 1990. The reports deal with the general categories of engine emissions, the natural stratospheric perturbations, and risk/benefit analysis. All but one of the talks are included in the volume, each followed by an abbreviated version of the ensuing open discussion. GRA

N73-16628# Cornell Aeronautical Lab., Inc., Buffalo, N.Y. **INVESTIGATIONS OF MLS CONVENTIONAL AND DOPPLER SCANNING BEAM TECHNIQUES** Final Report, Jun. 1971 - Sep. 1972

J. Beneke, C. W. Wightman, H. D. Becker, and C. E. Kassel Sep. 1972 182 p refs

(Contract DOT-FA71WA-2592)

(AG-5011-B-1; FAA-RD-72-124) Avail: NTIS HC \$11.25

The results of analytical and experimental investigations carried out in support of the Microwave Landing System (MLS) program of the Federal Aviation Administration are summarized. The experimental program consisted of a simulation of the MLS signals that would be received in an aircraft. The systems simulated included conventional scanning beams with frequency and pulse angle coding, step-scan beams with frequency and time interval coding and the Doppler scan technique. Angle measurement errors were determined for a wide range of signal parameters. Errors were measured in the presence of a single multipath of variable characteristics. Conclusions were drawn concerning the capability of the several signal formats to meet certain accuracy requirements. The need for special processing techniques to reduce the effects of multipath is discussed. Author

N73-16629# IIT Research Inst., Annapolis, Md. **AIR TRAFFIC CONTROL SYSTEMS INTERFERENCE CONSIDERATIONS** Final Report

F. Tabor and J. Shields Mar. 1972 53 p refs

(Contract DOT-FA70WAI-175; FAA Proj. 213-516-035)

(ECAC-PR-72-008; FAA-RD-72-20) Avail: NTIS HC \$4.75

The FAA Air Traffic Control Navigation/Communications system is examined to identify areas within the system that are particularly susceptible to radio frequency interference effects. The identified areas are investigated in the light of known past and present analyses, and recommendations for further studies

are made. The report concludes that the cosite aspects of the FAA VHF communications system requires further study in order to derive a practical means for achieving electromagnetic compatibility in the future. Author

N73-16630# IIT Research Inst., Annapolis, Md. **ATCRBS PERFORMANCE ANALYSIS FOR NEW YORK AIR ROUTE TRAFFIC CONTROL CENTER** Final Report

Charles A. Gettier Jul. 1972 47 p refs

(Contract DOT-FA70WAI-175; FAA Proj. 213-503-015)

(ECAC-PR-72-031; FAA-RD-72-35) Avail: NTIS HC \$4.50

The occurrence of excessive interrogation signals (hot spots) within air traffic control sectors supervised by the Air Traffic Control Beacon System (ATCRBS) of the Federal Aviation Administration is evaluated. On-site observations of air traffic displays are discussed, and the analyses of the air traffic electromagnetic environments using performance prediction model techniques are described. Each of the studies evaluates the possibility of hot spots affecting one of the following ATCRBS Air Route Traffic Control Centers: Jacksonville, Washington, New York, Kansas City, and Los Angeles. Author

N73-16632# German Air Traffic Controller's Association, Langenhagen (West Germany).

AIR TRAFFIC CONTROL PROBLEMS FROM THE CONTROLLER'S POINT OF VIEW [FLUGSICHERUNGSPROBLEME AUS DER SICHT DER FLUGLOTSEN]

Wolfgang Kassebohm 1972 7 p In GERMAN Presented at the DGLB Symp. on Flugbetrieb, Cologne, 15 Sep. 1972

(DGLR-Paper-72-038) Avail: NTIS HC \$3.00

The problems of air traffic control due to the increasing volume of air traffic are discussed. A solution is suggested which consists of a basic reform of air traffic law, and a central government authority responsible for all safety regulations. Author (ESRO)

N73-16634# Mitre Corp., Bedford, Mass. **UNDERSTANDING KALMAN FILTERING AND ITS APPLICATION IN REAL TIME TRACKING SYSTEMS**

J. J. Burke Jul. 1972 70 p refs

(Contract F19628-71-C-0002; AF Proj. 4510)

(AD-751485; MTR-2417; ESD-TR-72-312) Avail: NTIS CSCL 17/7

The theory and applications of Kalman filtering have now been under development for over a decade. Kalman filtering is currently being used operationally in numerous applications such as satellite tracking systems, aircraft navigational systems and aircraft tracking systems. Because Kalman filtering is a statistical concept that is typically described in terms of state-space notation, project managers and engineers must frequently accept an abstruse set of equations while feeling insufficiently qualified to appreciate their significance or applicability. In spite of the obscure terminology and associated matrix notation that typically accompanies any discussion of Kalman filtering, the salient features of the theory are relatively straightforward and can be presented in a manner that appeals to intuition. The paper represents such an attempt with emphasis on applications to real time tracking systems. Author (GRA)

N73-16635# Human Factors Research, Inc., Santa Barbara, Calif.

THE LANDING SIGNAL OFFICER: DISPLAY REQUIREMENTS FOR ACLS RECOVERIES Final Technical Report

Albert Harabedian, Gail J. Borden, and Gene R. Kelley Sep. 1972 85 p refs

(Contract N00014-71-C-0258; NR Proj. 215-190)

(AD-751076; Rept-1720-F) Avail: NTIS CSCL 17/7

A description of a study to determine the information displays required by LSOs to effectively control aircraft in the Automatic Carrier Landing System environment is presented. Dangerous and safe approaches were flown in an F-4B aircraft simulator. Displays of selected information about the aircraft's performance during the approaches were produced with a computer and recorded on motion picture film. The information

displays were integrated Glide-Slope and Line-Up deviations. Range, Airspeed, Power, Angle of Attack, and Sink-Rate. Groups of LSOs viewed the different display combinations. The LSO's task was to wave-off the aircraft if he judged the approach to be dangerous.

Author

N73-16651# Ultrasytems, Inc., Newport Beach, Calif.
THE EFFECTS OF LOCAL METEOROLOGICAL FACTORS UPON AIRCRAFT NOISE MEASUREMENTS Final Report, Aug. - Nov. 1972

D. C. Wooten and R. L. Eidemiller 12 Nov. 1972 47 p refs
 (Contract DOT-FA73WI-0382-1)
 (FAA-RD-72-145) Avail: NTIS HC \$4.50

Aircraft noise measurements from the Boeing 737, made at Orange County Airport, Santa Ana, California, during operational conditions, are statistically correlated with the local meteorological factors including wind force and direction, temperature, humidity, barometric pressure, ceiling and visibility. The correlation was carried out using regression techniques and indicated that there is a significant inverse correlation between temperature and noise level. Wind speed appeared to be of significance in one calculation that included wind speeds up to 25 knots, but was not significant when the range of wind speeds was 15 knots and below.

Author

N73-16654*# National Aeronautics and Space Administration, Lewis Research Center, Cleveland, Ohio.

NEW ASPECTS OF SUBSONIC AERODYNAMIC NOISE THEORY

Marvin E. Goldstein and Walton L. Howes Washington Feb. 1973 40 p refs

(NASA-TN-D-7158; E-7047) Avail: NTIS HC \$3.00 CSCL 20A

A theory of aerodynamic noise is presented which differs from Lighthill's theory primarily in the way in which convection of the noise sources is treated. The sound directivity pattern obtained from the present theory agrees better with jet-noise directivity data than does that obtained from Lighthill's theory. The results imply that the shear-noise contribution to jet noise is smaller than previously expected.

Author

N73-16655*# National Aeronautics and Space Administration, Lewis Research Center, Cleveland, Ohio.

THE EFFECT OF NOZZLE INLET SHAPE, LIP THICKNESS, AND EXIT SHAPE AND SIZE ON SUBSONIC JET NOISE

W. A. Olsen, O. A. Gutierrez, and R. G. Dorsch 1973 28 p refs Presented at 11th Aerospace Sci. Meeting, Washington, D. C., 10-12 Jan. 1973; sponsored by Am. Inst. of Aeron. and Astronaut.

(NASA-TM-X-68182; E-7289) Avail: NTIS HC \$3.50 CSCL 20A

Far field noise data were taken for convergent nozzles of various shapes and sizes at subsonic velocities exceeding 400 feet per second. For a circular nozzle, the nozzle inlet shape and lip thickness had no effect on the noise level, directivity, or spectra when compared at the same nozzle exit diameter and peak exhaust velocity. A sharp edged orifice was one exception to this statement. Coannular nozzles can produce additional high frequency noise. Blunt ended centerbodies, where there is significant base drag, also generate significant additional noise. The total noise power generation was essentially the same for circular, slot, and plug nozzles of good aerodynamic shape. The noise radiation patterns were essentially the same for these nozzle shapes except near the nozzle exhaust axis.

Author

N73-16658# Institut Franco-Allemand de Recherches, St. Louis (France).

STUDY OF THE SENSITIVITY OF NITROGLYCERIN TO WEAK SHOCK WAVES (SUPERSONIC AIRCRAFT BANGS) (UNTERSUCHUNG DER EMPFINDLICHKEIT VON NITROGLYCERIN GEGEN SCHWACHE STOSSWELLEN (FLUGZ-EUGKNALL))

H. W. Koch, I. Bischoff, and L. Philipp 27 Apr. 1972 19 p refs In GERMAN

(ISL-14/72) Avail: NTIS HC \$3.00

The resistance of nitroglycerin to weak shock waves corresponding to the sonic boom caused by aircraft was examined. Tests were carried out in a sonic boom generator which produced shock waves with pressure gradients up to 50 mbar and a duration of 345 ms in order to investigate detonation risk under the sonic boom effect. Nitroglycerin samples in layers 6 mm thick, placed in a bowl covered with a thin plastic layer, were exposed to incident frontal waves. No detonation was observed either during these tests or during the same tests carried out with other primers.

ESRO

N73-16748# Honeywell, Inc., Bloomington, Minn. Corporate Research Center.

PROPERTIES AND LIMITATIONS OF LIQUID CRYSTALS FOR AIRCRAFT DISPLAYS Final Technical Report, 1 Feb. 1971 - 30 May 1972

Ulrich Bonne and John P. Cummings Oct. 1972 185 p refs
 (Contract N00014-71-C-0262; NR Proj: 215-173)

(AD-751667; HR-72-285:4-35) Avail: NTIS CSCL 07/4

The objectives of the study were to determine the feasibility of using nematic liquid crystals as media for aircraft displays from the viewpoint of their temperature range, response time, grey scale and color control. These parameters were determined experimentally for various liquid crystal systems (pure compounds as well as mixtures), at various temperatures and under various operating conditions (AC and DC drive voltage, cell thickness, reflective and transmissive modes). Mathematical modeling of the temperature range achievable through formation of multiple eutectic mixtures, of response times (delay rise, and fall times), of the voltage dependent brightness of reflective and transmissive displays, and of the properties of LC color displays via the forced alignment technique matched the experimental data and was used to define the conditions (material, cell construction, and operating parameters) under which a temperature range of -54 to 71°C, a 1 microsecond response time, a 10-step grey scale (in steps of 2 in conjunction with a display brightness and a viewing angle range close to those accepted for paper-and-ink displays) and a full color display can be achieved.

Author (GRA)

N73-16758# Lincoln Lab., Mass. Inst. of Tech., Lexington.
ADVANCED ELECTRONIC TECHNOLOGY Quarterly Technical Summary, 1 May - 31 Jul. 1972

Melvin A. Herlin, Herbert G. Weiss, and Alan L. McWhorter 15 Aug. 1972 30 p refs
 (Contract F19628-73-C-0002; AF Proj. 649L)

(AD-751308; ESD-TR-72-210) Avail: NTIS CSCL 20/12

Contents: Integrated circuit processing; Photolithographic interconnection of plastic-embedded semiconductor chips; Testing and mask design; Applications and circuit design; Communications, navigation, and identification (CNI) studies; Approach and landing systems; Airborne traffic situation display (ATSD); Solid state device research; Quantum electronics; Materials research; Physics of solids; Microelectronics.

GRA

N73-16771*# National Aeronautics and Space Administration, Lewis Research Center, Cleveland, Ohio.

COMPARISON OF COMBUSTION CHARACTERISTICS OF ASTM A-1, PROPANE, AND NATURAL-GAS FUELS IN AN ANNULAR TURBOJET COMBUSTOR

Jerrold D. Wear and Robert E. Jones Washington Jan. 1973 23 p refs

(NASA-TN-D-7135; E-7078) Avail: NTIS HC \$3.00 CSCL 21D

The performance of an annular turbojet combustor using natural-gas fuel is compared with that obtained using ASTM A-1 and propane fuels. Propane gas was used to simulate operation with vaporized kerosene fuels. The results obtained at severe operating conditions and altitude reight conditions show that natural gas is inferior to both ASTM A-1 and propane fuels. Combustion efficiencies were significantly lower and combustor pressures for reight were higher with natural-gas fuel than with the other fuels. The inferior performance of natural gas is shown to be caused by the chemical stability of the methane molecule.

Author

N73-16772# National Aviation Facilities Experimental Center, Atlantic City, N.J.

THE FEASIBILITY OF BURNER-CAN BURN-THROUGH THERMAL DETECTION PRIOR TO ENGINE CASE RUPTURE

Final Report, Jan. - Sep. 1972

Richard Hill Jan. 1973 36 p ref

(FAA Proj. 181-522-01X)

(FAA-NA-72-92; FAA-RD-72-134) Avail: NTIS HC \$4.00

Full-scale tests simulating engine combustion section thermal failures (burn-through) were conducted using a J57 engine (cowed and uncowed) to determine the feasibility of detecting a burn-through prior to its occurrence by monitoring engine skin temperature. Results of the tests indicated that as few as four thermocouples, located 90 degrees apart around the diffuser case and/or burner can case, could detect a burn-through prior to engine case rupture. Author

N73-16773# National Aeronautics and Space Administration, Lewis Research Center, Cleveland, Ohio.

EXPERIMENTAL PERFORMANCE OF CASCADE THRUST REVERSERS AT FORWARD VELOCITY

Donald A. Dietrich and Roger W. Luidens Washington 1973 22 p refs

(NASA-TM-X-2665; E-7125) Avail: NTIS HC \$3.00 CSCL 21E

A series of static and wind tunnel tests were performed on four cowl cascade thrust reverser configurations which had various reversed jet emission patterns applicable to an externally blown flap STOL aircraft. The work was performed using a model fan which was 14.0 cm in diameter and passed a fan mass flow of 2.49 kg/sec at an approximate fan pressure ratio of 1.22 and fan corrected rotational speed of 35,800 rpm. The tests demonstrated that the reingestion of fan flow significantly reduced the reverser efficiency and that the thrust reverser efficiency was improved by reducing the reversed jet azimuthal emission angle. The reverser efficiency at STOL landing speeds was as high as 0.95; however, configurations with lateral emission were adversely affected by yawing the nacelle at forward velocity. Measurements of the internal static pressure at the stator exit showed significant increases in the local static pressure for configurations with reduced jet emission angles. Author

N73-16776# National Aeronautics and Space Administration, Lewis Research Center, Cleveland, Ohio.

EFFECT OF A REDUCTION IN BLADE THICKNESS ON PERFORMANCE OF A SINGLE STAGE 20.32 CENTIMETER MEAN DIAMETER TURBINE

William J. Nusbaum and Milton G. Kofskey Washington Feb. 1973 26 p refs

(NASA-TN-D-7128; E-7029) Avail: NTIS HC \$3.00 CSCL 21E

As part of a program to reduce the manufacturing costs of a small gas-turbine engine, the turbine blading was reduced in thickness to facilitate coining. Tests were made to determine the effect of this modification on turbine performance. The working fluid was air at nominal inlet total conditions of 535 deg F and 20.0 psia. Performance results are presented and compared for four stator-rotor combinations in terms of equivalent torque, mass flow, and efficiency at equivalent design speed and at inlet-total to exit-static pressure ratios of 1.8 to 3.8. Author

N73-16778# General Electric Co., Cincinnati, Ohio.

HIGHLY LOADED MULTI-STAGE FAN DRIVE TURBINE-CASCADE TEST PROGRAM

D. G. Cherry, T. K. Staley, and M. W. Thomas Washington NASA Jan. 1973 153 p refs

(Contract NAS3-14304)

(NASA-CR-2171; Rept-72AEG268) Avail: NTIS HC \$3.00 CSCL 21E

Test results are presented for 19 cascades involving five plain and two tandem blade sections. High camber and/or negative reaction is associated with six of the sections. Exit Mach numbers range up to slightly above sonic. Cascade efficiency, exit flow

angle and static pressure, and blade surface pressure data are reported with incidence angle, Mach number, solidity, and relative position of the tandem blades as independent variables. Author

N73-16781# Air Force Aero Propulsion Lab., Wright-Patterson AFB, Ohio. Ramjet Applications Branch.

SUBSONIC PERFORMANCE POTENTIAL OF RAMJETS AND EJECTOR RAMJETS Technical Report, Dec. 1970 - Sep. 1971

William E. Supp, John H. Miller, and Kenneth A. Watson May 1972 99 p refs

(AF Proj. 3012)

(AD-751317; AFAPL-TR-72-7) Avail: NTIS CSCL 21/5

A method for analyzing the performance of a ramjet engine at subsonic flight speeds is presented. The absence of a known choked point ($M=1$) in the engine necessitates an iterative solution. A modified ideal gas analysis is utilized. Considered are the conventional ramjet with liquid fuel injection and an ejector ramjet using vaporized fuel injected into the engine at supersonic velocities. In the latter case, the fuel's momentum is significant and the ejector action draws additional air mass into the engine, which must be considered in the analysis. The method presented compares the two engine cycles at several subsonic flight speeds for both JP-4 and propane fuel. The effects of several levels of component efficiencies are considered. Author (GRA)

N73-16783# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.

DESIGN PRINCIPLES OF AIRCRAFT ENGINES, CHAPTERS 1-5

E. L. Feldman, G. I. Danileiko, and L. N. Kapustin 6 Jul. 1972 192 p Transl. into ENGLISH of the publ. "Osnovy Konstruktsii Aviatsonnykh Dvigatelyey" Moscow, Izd-vo Transport, 1970 p 1-123

(AD-751510; FTD-MT-24-1903-71) Avail: NTIS CSCL 21/5

In the book, general questions of design of gas-turbine engines (with mention of piston engines) are presented, their design diagrams are analyzed, the purpose, arrangement, and service conditions of units, assemblies and systems are described, as well as the loads experienced by them and also the materials used, the requirements imposed on structural elements and systems, and the simplest structural designs are set forth. The book is intended as a text for students in technical schools and schools of civil aviation. It can be used by technical-engineering and flight crews of civil aviation. Author (GRA)

N73-16784# Rohr Corp., Chula Vista, Calif.

ANALYTICAL STUDY OF INFLIGHT THRUST REVERSERS, VOLUME 1 Final Technical Report, 25 Jan. 1971 - 25 May 1972

Tirumalesa Duvvuri, Hai-Yain Chang, and Barry W. Prior Jul. 1972 353 p refs

(Contract F33615-71-C-1208; AF Proj. 1478)

(AD-751525; RHR-72-365-1; AFFDL-TR-72-85-Vol-1) Avail: NTIS CSCL 21/5

Mathematical models are developed for predicting the flow fields within and external to a thrust reverser when it is deployed in flight, and the forces and moments induced on the aircraft by virtue of these flow fields. The method used are largely two-dimensional in nature, but contain empirical corrections to account for three-dimensionality. Although no testing was accomplished under this contract, the analytical predictions are compared with existing test data. A method of evaluating stowed reverser losses is given, twin-jet and unsteady flow effects are discussed and a test/analytical program is outlined which is aimed at further improving and verifying the results of the study. This volume contains the technical discussion and results of the analytical effort. Author (GRA)

N73-16785# Rohr Corp., Chula Vista, Calif.

ANALYTICAL STUDY OF INFLIGHT THRUST REVERSERS, VOLUME 2: USER'S MANUAL AND SOURCE LISTINGS

FOR COMPUTER PROGRAMS

Tirumalesa Duvvuri, Hai-Yain Chang, Barry W. Prior, and Miriam J. Alcala Jul. 1972 235 p refs
(Contract F33615-71-C-1208; AF Proj. 1478)
(AD-751526; RHR-72-365-2; AFFDL-TR-72-85-Vol-2) Avail:
NTIS CSCL 21/5

Fifteen computer programs have been developed to solve problems for the analytical study of inflight thrust reversers. User instructions for all 15 programs are presented in this Volume, including a brief theoretical background, the function, input and output of each program. Lists of sample input and output are also included. Listings of all computer programs are included in the Appendix. The detailed descriptions of all theoretical developments are given in Volume I of the report.

Author (GRA)

N73-16896# Advisory Group for Aerospace Research and Development, Paris (France).

SYMPOSIUM ON RANDOM LOAD FATIGUE

Oct. 1972 237 p refs Symp. held at 34th meeting of the AGARD Struct. and Mater. Panel, Lyngby, Denmark, 13 Apr. 1972; sponsored by Struct. and Mater. Panel
(AGARD-CP-118) Avail: NTIS HC \$14.00

Physical aspects of fatigue damage accumulation and the significance of theories for the calculation of fatigue damage accumulation are reviewed. Influence of test frequencies on crack propagation rates, measurements of residual stresses in notched specimens, etc. are reported.

N73-16897 Societe Nationale Industrielle Aerospatiale, Paris (France).

A SHORT SURVEY ON POSSIBILITIES OF FATIGUE LIFE ASSESSMENT OF AIRCRAFT STRUCTURES BASED ON RANDOM OR PROGRAMMED FATIGUE TESTS

W. Barrois /in AGARD Symp. on Random Load Fatigue Oct. 1972 21 p refs

After considering designers' needs and detailing the various physical parameters that are significant in the fatigue behavior of specimens and structures, several types of fatigue tests are reviewed. Prediction methods of structure fatigue life from fatigue tests of components, assemblies and structures undergoing constant amplitude loadings are surveyed. After considering fatigue tests under programmed loadings, the case of random loadings is briefly discussed. It is concluded that describing random loadings by their root mean squares is not sufficient to predict the fatigue lives of structures even when the shape of the load power spectrum is known, except in cases of comparative prediction where the only change is the general intensity of the spectrum. The possibility of test acceleration by increasing the general loading intensity is considered.

Author

N73-16898 Royal Aircraft Establishment, Farnborough (England). Structures Dept.

SOME EFFECTS OF CHANGE IN SPECTRUM SEVERITY AND SPECTRUM SHAPE ON FATIGUE BEHAVIOUR UNDER RANDOM LOADING

W. T. Kirkby /in AGARD Symp. on Random Load Fatigue Oct. 1972 19 p refs

The problem of reassessing the fatigue life of an aircraft structure is considered, when it is found that the spectrum of loads experienced in service differs from the load spectrum applied in test. Results obtained during fatigue tests on structural elements under random load spectra are used to illustrate some of the important considerations involved. It is shown that the use of an improved method of life prediction will generally lead to improved accuracy in reassessing life.

Author

N73-16899 National Aerospace Lab., Amsterdam (Netherlands). **THE ACCUMULATION OF FATIGUE DAMAGE IN AIRCRAFT MATERIALS AND STRUCTURES**

J. Schijve /in AGARD Symp. on Random Load Fatigue Oct. 1972 120 p refs

Physical aspects of fatigue damage accumulation are discussed, including interaction and sequence effects. Empirical trends observed in variable-amplitude tests are summarized including the effects of a high preload, periodical high loads, ground-to-air cycles, and the variables pertaining to program loading, random loading, and flight simulation loading. This also includes results from full scale fatigue test series. Various theories on fatigue damage accumulation are recapitulated. The significance of these theories for explaining empirical trends as well as for estimating fatigue properties as a design problem is evaluated.

Author

N73-16900 National Aerospace Lab., Amsterdam (Netherlands). **EFFECTS OF TEST FREQUENCY ON FATIGUE CRACK PROPAGATION UNDER FLIGHT-SIMULATION LOADING**

J. Schijve /in AGARD Symp. on Random Load Fatigue Oct. 1972 17 p refs

Fatigue crack propagation in 2024-T3 and 7075-T6 sheet material was studied at three test frequencies, viz. 10, 1, and 0.1 cycles per second. The flight simulation loading was based on a gust spectrum. The design stress level was adopted as a second variable. Differences between the crack propagation rates at the three test frequencies were small and unsystematic. The propagation was much slower than predicted from constant amplitude test data. Moreover, the macro-cracking behavior appeared to be different.

Author

N73-16901 Air Force Systems Command, Wright-Patterson AFB, Ohio.

CORRELATION BETWEEN LABORATORY TESTS AND SERVICE EXPERIENCE

W. B. Miller and Holland B. Lowndes /in AGARD Symp. on Random Load Fatigue Oct. 1972 16 p refs

Direct comparisons are made between full scale fatigue test failures and actual service failures for several military aircraft. The correlations are discussed in relation to the basic fatigue test procedures and spectra used. Some methods used to force correlation where apparent correlation is lacking are discussed. The improvements in fatigue testing evolved over the past 25 years are summarized.

Author

N73-16902 Technical Univ. of Denmark, Lyngby. Dept. of Solid Mechanics.

ON RESIDUAL STRESSES DURING RANDOM LOAD FATIGUE

Find Rotvel /in AGARD Symp. on Random Load Fatigue Oct. 1972 14 p refs

Data are presented from random fatigue tests on normalized carbon steel with 0.7% carbon. In notched specimens, a preload beyond the yield stress induced residual stresses around the notch. The residual stresses were measured with an X-ray measuring technique at intervals during the fatigue loading. Results from broadband and narrowband stochastic loading tests are compared with constant amplitude sinusoidal tests.

Author

N73-16903 Industrieanlagen-Betriebsgesellschaft m.b.H., Otto-brunn (West Germany).

THE FATIGUE LIFE UNDER THREE DIFFERENT LOAD SPECTRA - TESTS AND CALCULATIONS

Walter Schuetz /in AGARD Symp. on Random Load Fatigue Oct. 1972 10 p refs

One of the more important problems in the fatigue life prediction of military airplanes is caused by the difference between the load spectrum used in the full scale fatigue test and the load spectrum in service. Complex flight-by-flight tests with two types of notched specimens and a bolted joint simulating a skin fitting joint were carried out under three different load spectra occurring in service of a German military airplane. It is shown that Miner's rule can be used as a transfer function (relative Miner rule) to calculate the lives with high accuracy for the notched specimens and with less accuracy for the bolted specimens.

Author

N73-16904 Laboratorium fuer Betriebsfestigkeit, Darmstadt (West Germany).

A RELATION BETWEEN MEASURED CENTER OF GRAVITY VERTICAL ACCELERATIONS AND THE LOADS AT THE T-TAIL OF A MILITARY AIRPLANE c02

Otto Buxbaum In AGARD Symp. on Random Load Fatigue Oct. 1972 16 p refs

An engineering solution is presented for correlating two different random loads - time histories, based on measurements of C.G. vertical accelerations and loads at the tailplane of an aircraft. The choice of instrumentation for a fleet airplane is described, and the measurements of operational loads are related to C.G. acceleration countings. Author

N73-16905* National Aeronautics and Space Administration, Langley Research Center, Langley Station, Va.

EVALUATION OF AN AEROELASTIC MODEL TECHNIQUE FOR PREDICTING AIRPLANE BUFFET LOADS

Perry W. Hanson Washington Feb. 1973 62 p refs

(NASA-TN-D-7066; L-8460) Avail: NTIS HC \$3.00 CSCL 01C

A wind-tunnel technique which makes use of a dynamically scaled aeroelastic model to predict full-scale airplane buffet loads during buffet boundary penetration is evaluated. A 1/8-scale flutter model of a fighter airplane with remotely controllable variable-sweep wings and trimming surfaces was used for the evaluation. The model was flown on a cable-mount system which permitted high lift forces comparable to those in maneuvering flight. Bending moments and accelerations due to buffet were measured on the flutter model and compared with those measured on the full-scale airplane in an independent flight buffet research study. It is concluded that the technique can provide valuable information on airplane buffet load characteristics not available from any other source except flight test. Author

N73-16929* National Aeronautics and Space Administration, Lewis Research Center, Cleveland, Ohio.

HIGH-PRESSURE COMBUSTOR EXHAUST EMISSIONS WITH IMPROVED AIR-ATOMIZING AND CONVENTIONAL PRESSURE-ATOMIZING FUEL NOZZLES

Robert D. Ingebo and Carl T. Norgren Washington Feb. 1973 24 p refs

(NASA-TN-D-7154; E-7148) Avail: NTIS HC \$3.00 CSCL 21B

A high-pressure combustor segment 0.456 meter (18 in.) long with a maximum cross section of 0.153 by 0.305 meter (6 by 12 in.) was tested with specially designed air-atomizing and conventional pressure-atomizing fuel nozzles at inlet-air temperatures of 340 to 755 K (610 deg to 1360 R), reference velocities of 12.4 to 26.1 meters per second (41 to 86 ft/sec), and fuel-air ratios of 0.008 to 0.020. Increasing inlet-air pressure from 4 to 20 atmospheres generally increased smoke number and nitric oxide, but decreased carbon monoxide and unburned hydrocarbon concentrations with air-atomizing and pressure-atomizing nozzles. Emission indexes for carbon monoxide and unburned hydrocarbons were lower at 4, 10, and 20 atmospheres, and nitric oxide emission indexes were lower at 10 and 20 atmospheres with air-atomizing than with pressure-atomizing nozzles. Author

N73-16943* Aeronautical Research Labs., Melbourne (Australia). [AERONAUTICAL RESEARCH AND DEVELOPMENT] Annual Report, 1971 - 1972

1972 90 p refs Original contains color illustrations Avail: NTIS HC \$6.50

Aeronautical research is reported for 1971-1972. Work in the following areas is discussed: aircraft materials, defect detection, aircraft structures, aerodynamic, propulsion, high temperature, turbine blades, human factors, instrumentation, testing, damage assessment, and life of aircraft engines.

F. O. S.

N73-16978* Parsons-Brinckerhoff-Tudor-Bechtel, San Francisco, Calif.

SAN FRANCISCO AIRPORT ACCESS PROJECT

May 1972 40 p Prepared in cooperation with Smith (Wilbur) and Associates, San Francisco, Calif. and Kirker, Chapman Consultants, San Francisco, Calif.

(Contract DOT-UT-262)

(PB-212456; UMTA-CA-09-0012-72-1) Avail: NTIS HC \$3.00 CSCL 13B

An earlier study of the feasibility of extending the Bay Area Rapid Transit (BART) system to serve San Francisco International Airport is summarized. This summary was prepared to answer several basic questions about the proposed BART extensions: (1) how can such transit help? (2) how soon is it needed? (3) what will it be like? (4) how might the cost be shared? (5) will it be built? A proposed route description and various financing alternatives are discussed. GRA

N73-16981* Aeronautical Research Labs., Melbourne (Australia). **A SIDE MOUNTED SUPERSONIC INTAKE AND THE PROBLEM OF THREE DIMENSIONAL BOUNDARY LAYER SEPARATION**

Murdoch Culley Jun. 1972 49 p refs

(ARL/ME-137; ISBN-642-97744-5) Avail: NTIS HC \$4.50

As part of a program to study integrated supersonic intakes and their associated interference problems, a model has been constructed consisting of a half-conical intake mounted on the side of a fuselage. The flow field around this model has been qualitatively examined using schlieren and surface flow techniques. A strong three dimensional separation of the fuselage boundary layer has been observed; the location of the separation line is sensitive to the condition of the fuselage boundary layer and to the intake static pressure field. As a result of three dimensional flow over the shock cone, the intake has a weaker pressure field than an equivalent axisymmetric intake. Consequently the observed separation occurs under the combined influence of the normal and cone shocks, and thus the location of the separation line is sensitive to the position of the normal shock. The separation gives rise to an unsteady shock wave, and this indicates, despite the finely detailed flow patterns obtained, that the separation is unsteady. This boundary layer shock generates a Mach number gradient and thus modifies the intake shock system. Author

N73-16982* Northrop Corporate Labs., Hawthorne, Calif. **ANALYSIS OF HIGH-ASPECT-RATIO JET-FLAP WINGS OF ARBITRARY GEOMETRY**

Peter B. S. Lissaman Washington NASA Feb. 1973 58 p refs

(Contract NAS1-10627)

(NASA-CR-2179) Avail: NTIS HC \$3.00 CSCL 01A

An analytical technique to compute the performance of an arbitrary jet-flapped wing is developed. The solution technique is based on the method of Maskell and Spence in which the well-known lifting-line approach is coupled with an auxiliary equation providing the extra function needed in jet-flap theory. The present method is generalized to handle straight, uncambered wings of arbitrary planform, twist, and blowing (including unsymmetrical cases). An analytical procedure is developed for continuous variations in the above geometric data with special functions to exactly treat discontinuities in any of the geometric and blowing data. A rational theory for the effect of finite wing thickness is introduced as well as simplified concepts of effective aspect ratio for rapid estimation of performance. Author

N73-16983* National Aeronautics and Space Administration, Ames Research Center, Moffett Field, Calif.

GENERALIZE AERODYNAMIC COEFFICIENT TABLE STORAGE, CHECKOUT AND INTERPOLATION FOR AIRCRAFT SIMULATION

Frank Neuman and Neil Warner Jan. 1973 107 p

(NASA-TM-X-62229) Avail: NTIS HC \$7.50 CSCL 01A

The set of programs described has been used for rapidly introducing, checking out and very efficiently using aerodynamic tables in complex aircraft simulations on the IBM 360. The

preprocessor program reads in tables with different names and dimensions and stores them on disc storage according to the specified dimensions. The tables are read in from IBM cards in a format which is convenient to reduce the data from the original graphs. During table processing, new auxiliary tables are generated which are required for table cataloging and for efficient interpolation. In addition, DIMENSION statements for the tables as well as READ statements are punched so that they may be used in other programs for readout of the data from disc without chance of programming errors. A quick data checking graphical output for all tables is provided in a separate program. Author

N73-16984# Aeronautical Research Inst. of Sweden, Stockholm. BOUNDARY LAYER STUDIES ON A TWO DIMENSIONAL HIGH LIFT WING

Bjoern L. G. Ljungstrom* 1972 110 p refs
(FAA-AU-862) Avail: NTIS HC \$7.50

Wind tunnel tests were carried out with a 2-dimensional wing model equipped with a leading edge slat and a trailing edge flap. The objectives of the investigation have been the following: (1) to increase general understanding of the viscous and inviscid flow phenomena on a high lift wing and significance to the high lift performance. And (2) to investigate the significance of Reynolds number effects for high lift wings by an attempt to simulate higher Reynolds number boundary layers. The model was equipped with two suction slots at a distance of 30 slot widths from the trailing edges of the leading edge slat and the main wing. The different amounts of suction applied resulted in a reduced boundary layer thickness at the trailing edge of the leading edge slat and the main wing, respectively. The various suction configurations have been tested for two leading edge slat gaps. The pressure distributions and the complete boundary layer velocity profiles have been mapped at a few angles of attack. Author

N73-16985# Aeronautical Research Inst. of Sweden, Stockholm. A COMPUTER PROGRAM FOR THE PREDICTION OF AERODYNAMIC CHARACTERISTICS OF WING-BODY-TAIL COMBINATIONS AT SUBSONIC AND SUPERSONIC SPEEDS, PART 2

S. Anders and L. Gustavsson 1972 120 p refs
(FAA-AU-835-Pr-2) Avail: NTIS HC \$8.00

A computer program for calculating the aerodynamic characteristics of wing-body combinations at subsonic and supersonic speeds is described. The aerodynamic theory is outlined and several calculated examples with comparisons to experimental results are shown. A description of the computer program is provided together with a user's manual. The results indicate that the method is a valuable tool for analysis and design purposes. Author

N73-16986*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

ANALYTICAL STUDY ON A TWO-DIMENSIONAL PLANE OF THE OFF-DESIGN FLOW PROPERTIES OF TANDEM-BLADED COMPRESSOR STATORS

Nelson L. Sanger Washington Mar. 1973 43 p refs
(NASA-TM-X-2734; E-7031) Avail: NTIS HC \$3.00 CSCI 20D

The flow characteristics of several tandem bladed compressor stators were analytically evaluated over a range of inlet incidence angles. The ratios of rear-segment to front-segment chord and camber were varied. Results were also compared to the analytical performance of a reference solid blade section. All tandem blade sections exhibited lower calculated losses than the solid stator. But no one geometric configuration exhibited clearly superior characteristics. The front segment accepts the major effect of overall incidence angle change. Rear- to front-segment camber ratios of 4 and greater appeared to be limited by boundary-layer separation from the pressure surface of the rear segment. Author

N73-16987 California Univ., Los Angeles. AERODYNAMIC AND STRUCTURAL DESIGN CONSIDERATIONS FOR HIGH LIFT BIPLANE WING SYSTEMS Ph.D.

Thesis

Robert Briand Addoms 1971 172 p
Avail: Univ. Microfilms Order No. 72-13586

Modern theoretical methods and computer technology are applied to the design of biplane wing systems. Biplane aerodynamics are discussed, with emphasis on the stall matching and induced camber effects which make the biplane different from the monoplane. The theoretical basis of a method for designing biplane airfoils is presented. The method uses three-dimensional potential flow theory, combined with two-dimensional thin airfoil theory. The application of this method to an actual design is described in detail. It is shown that for virtually any biplane configuration of practical interest, it is possible to design a biplane wing system which sacrifices nothing in maximum usable lift coefficient without flaps to monoplanes, and next to nothing with flaps. Such a wing system has approximately half the weight per unit area of a well-designed monoplane wing.

Dissert. Abstr.

N73-16988*# California Univ., Davis. Dept. of Mechanical Engineering.

EQUATIONS OF MOTION FOR THE X-14 AIRCRAFT, PHASE 2 STUDY Quarterly Status Report, 1 Jul. - 31 Dec. 1972

Myron A. Hoffman, Walter V. Loscutoff, and J. A. Jørgensen Dec. 1972 73 p refs

(Grant NGR-05-004-051)
(NASA-CR-130760; QSR-7) Avail: NTIS HC \$5.75 CSCI 01C

A study of the control and power requirements of the X-14 VTOL aircraft is presented. The complete equations of motion for X-14 are derived. The fundamental assumption is that the aircraft is a single rigid body. The equations of motion are derived with respect to a set of axes fixed to the aircraft. Additional assumptions used are that any wind disturbances are irrotational and that the twin engines used on the aircraft rotate in the same direction at the same speed and that the engine exhaust is diverted by means of vanes to provide a direction varying thrust vector. The equations obtained are subsequently linearized about various reference conditions and numerical values for the trim parameters and the stability derivatives at these conditions are tabulated. Author

N73-16989# Advisory Group for Aerospace Research and Development, Paris (France).

STABILITY AND CONTROL

Nov. 1972 305 p refs Proceedings of the 40th Meeting of the Flight Mech. Panel of AGARD, Braunschweig West Germany, 10-13 Apr. 1972

(AGARD-CP-119) Avail: NTIS HC \$17.25

Summaries of papers presented at conferences concerning aircraft stability, control, maneuverability and design are reported.

Author

N73-16990 National Aerospace Lab., Amsterdam (Netherlands). SUMMARY OF AGARD MEETING ON PROBLEMS OF THE COCKPIT ENVIRONMENT, NOVEMBER 1968 IN AMSTERDAM, NETHERLANDS

J. J. P. Moelker In AGARD Stability and Control Nov. 1972 9 p refs

Problems related to the process of man-machine communication are discussed with emphasis on cockpit information-generation, display, and transfer. Techniques for the evaluation of cockpit geometry, display systems and cockpit workload are summarized together with the associated anthropometrical data and types of display systems. Author

N73-16991 Centre d'Essais en Vol, Bretigny-sur-Orge (France). AEROELASTIC EFFECTS FROM A FLIGHT MECHANICS STAND POINT

J. F. Renaudie In AGARD Stability and Control Nov. 1972 17 p In FRENCH

Methods for calculating the effects of aeroelasticity on aircraft flight are discussed. Data cover aerodynamics of flexible rotors,

flight dynamics of flexible aircraft, experimental determination of flexibility for flexible aircraft, stability augmentation systems, and problems of determining influence of aerodynamic forces on flexible aircraft. Transl. by E.H.W.

N73-16992 British Aircraft Corp., Preston (England). Military Aircraft Div.
SUMMARY PAPER ON SIMULATION MEETING, SPRING 1970 AT NASA RESEARCH CENTER
A. G. Barnes *In AGARD Stability and Control* Nov. 1972 5 p ref

The conference on flight simulation is summarized. Topics discussed include: simulation objectives, simulator characteristics, design of experiments, simulation results, and analysis. F.O.S.

N73-16993 Air Force Flight Dynamics Lab., Wright-Patterson AFB, Ohio.
HANDLING QUALITIES CRITERIA AND REQUIREMENTS
William E. Lamar and Terry L. Neighbor *In AGARD Stability and Control* Nov. 1972 19 p refs

Summaries of papers presented at the conference on flight qualities are presented. Topics discussed include: flying qualities for conventional and V/STOL aircraft, man-machine research, and the establishment of criteria. F.O.S.

N73-16994* National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.
CONSIDERATIONS FOR STABILITY AND CONTROL OF V/STOL AIRCRAFT: A REVIEW OF AGARD REPORT 577
Seth B. Anderson and Laurel G. Schroers (Army Mobility R and D Lab.) *In AGARD Stability and Control* Nov. 1972 10 p refs
CSSL 01B

Revisions which have been made to previous V/STOL handling qualities requirements based on criteria are discussed. A discussion of the pilot's desire for a particular characteristic is given. In addition, data and reference material are provided to back up the proposed criteria to permit the user to understand the limitations of the data on which the criteria are based. A review is included of several controversial areas including pitch control sensitivity, static longitudinal stability, roll control power, roll-yaw cross coupling, and vertical flight path control. Author

N73-16995 Air Force Flight Dynamics Lab., Wright-Patterson AFB, Ohio.
MISSION EFFECTS ON STABILITY AND MANEUVERABILITY
Charles B. Westbrook *In AGARD Stability and Control* Nov. 1972 13 p refs

The relationship between the mission requirements of a piloted aircraft and its stability and maneuverability are defined. The framework utilized in current U.S. Air Force handling qualities requirements, i.e., classification of aircraft, flight phases, levels, states, etc., is described. Examples of various aircraft designed for one mission and then utilized for other missions are given. A discussion is presented of the problems encountered when the detailed mission requirements are not clear, such as with V/STOL aircraft, reentry vehicles, etc. Problems encountered with off-design conditions and operation at the limits of the flight envelope are discussed with examples. The various methods open to the designer for achieving the proper compromises in design of an aircraft are outlined. Author

N73-16996 British Aircraft Corp., Preston (England). Military Aircraft Div.
DESIGN CONSIDERATIONS FOR THE SATISFACTORY STABILITY AND CONTROL OF MILITARY COMBAT AEROPLANES
B. R. A. Burns *In AGARD Stability and Control* Nov. 1972 28 p refs

Design criteria for achieving satisfactory stability and control for military aircraft are reviewed along with official requirements.

Some of the difficulties of designing to meet the standards of these criteria are considered. Topics discussed include longitudinal stability and control, and lateral stability and control. Author

N73-16997 Technische Hochschule, Darmstadt (West Germany).
THE EFFECTS OF THRUST CHARACTERISTICS ON LONGITUDINAL STABILITY IN SUPERSONIC FLIGHT
G. Sachs *In AGARD Stability and Control* Nov. 1972 15 p refs

The influence of the variation of thrust with speed and height on the dynamic stability of the longitudinal motion in supersonic flight is shown. The effects directly related to thrust changes are described along with the effects due to pitching moments which, associated with thrust characteristics, depend on speed and height. The thrust influence on two methods of artificial stabilization of long-term modes is also investigated. Author

N73-16998 Societe Nationale Industrielle Aerospatiale, Paris (France). Departement Recherche.
INFLUENCE OF THE MASS AND MASS DISTRIBUTION ON FLYING QUALITIES [INFLUENCE DE LA MASSE ET DE LA REPARTITION DE LA MASSE SUR LES QUALITES DE VOL]
Marc Mesniere *In AGARD Stability and Control* Nov. 1972 9 p refs *In FRENCH*

Several techniques pertinent to determining the influence of mass and mass distribution on the handling qualities of aircraft are presented. Particular attention was given to lateral and longitudinal maneuverability and the influence of inertia on the principle axis tilt angle. Several examples using a Corvett aircraft are given. Transl. by E.H.W.

N73-16999 Royal Aircraft Establishment, Bedford (England). Aerodynamics Dept.
THE ROLE OF THEORY AND CALCULATIONS IN THE REFINEMENT OF FLYING QUALITIES
W. J. G. Pinsker *In AGARD Stability and Control* Nov. 1972 13 p refs

The present state of the art in handling qualities research and design is broadly surveyed with particular emphasis on the role of theory and paper studies in this field. The significance and scope of handling criteria is critically discussed as setting targets for flying qualities design. The capabilities and limitations of theory are then considered in such areas as derivative prediction, rigid-body stability and response calculations, predictions of stability under partial constraint and under active pilot control. Finally some general consideration is given to novel flying qualities problems associated with the introduction of stability and control augmentation systems. Author

N73-17000 Royal Netherlands Aircraft Factories Fokker, Schiphol-Oost. Aerodynamics Dept.
ADJUSTMENT OF FLYING QUALITIES BY WIND TUNNEL TESTING
Tj. Schuringa *In AGARD Stability and Control* Nov. 1972 7 p

Two examples of the wind tunnel approach to the flying qualities of the Fokker F28 Fellowship aircraft are described, one dealing with the development of the elevator surface, and the other with the development of stall characteristics. Author

N73-17001 Naval Air Systems Command, Washington, D.C. Advanced Technology Section.
FLIGHT SIMULATION: A SIGNIFICANT AID IN AIRCRAFT DESIGN
Ralph C. AHarrah *In AGARD Stability and Control* Nov. 1972 17 p refs

The role of flight simulation in the development of the S-3 and F-14 aircraft is described along with the facilities used. An appraisal is included of simulation technology as applied to aircraft design. Author

N73-17002 Royal Aircraft Establishment, Bedford (England). Aerodynamics Dept.

THE ROLE OF FREE-FLIGHT MODELS IN AIRCRAFT RESEARCH AND DEVELOPMENT.

R. Fail *In* AGARD Stability and Control Nov. 1972 14 p refs

The special features of free-flight models are discussed. Two examples are given of tests in the field of flight mechanics. Preparations are described for a program of tests which is about to start at RAE to investigate the low-speed stall and post-stall dynamics of aircraft. Attention is concentrated on the planning of the tests and the instrumentation and control system in the model. Some details are given of the model handling and retrieval systems. Author

N73-17003 British Aircraft Corp., Preston (England). Commercial Aircraft Div.

THE EFFECT OF ENGINE FAILURE AT SUPERSONIC SPEEDS ON A SLENDER AIRCRAFT: PREDICTED AND ACTUAL

C. S. Leyman and R. L. Scotland *In* AGARD Stability and Control Nov. 1972 8 p

The effect of engine failure on the aerodynamic characteristics of a supersonic aircraft were studied. Topics discussed include: prediction of aircraft stability derivatives, prediction of forces and moments due to engine failure, preflight simulation experience, and flight test results. F.O.S.

N73-17004 Aerospatiale Usines de Toulouse (France). **CALCULATION OF INDUCED LOAD BY VARIATION IN COURSE DURING ANY MANEUVER [CALCUL DES CHARGES INDUITES PAR LA CLEXIBILITE AU COURS D'UNE MANOEUVRE QUELCONQUE]**

A. Marsan *In* AGARD Stability and Control Nov. 1972 9 p *In* FRENCH

A general formula for calculating load influence on aircraft flexibility is presented along with illustrations. A comparison was made of the load effects in rigid and transverse flexible aircraft. Three maneuvers, - lifting moments and forces, checked pitching, and checked rolling - were used for the analysis.

Transl. by E.H.W.

N73-17005* National Aeronautics and Space Administration. Langley Research Center, Langley Station, Va.

ACTIVE CONTROL OF AEROELASTIC RESPONSE

A. Gerald Rainey, Charles L. Ruhlin, and Maynard C. Sandford *In* AGARD Stability and Control Nov. 1972 8 p refs

Conceptual and wind-tunnel programs leading to the development of technology for applying active controls to the suppression of flutter were studied to provide a powerful tool for required safety margins for flutter in future high-performance supersonic aircraft. The nature of flutter considerations in the design of the U.S. SST prototype aircraft is described as an example of the type of application where active flutter suppression shows promise. Author

N73-17006 Aeronautical Systems Div., Wright-Patterson AFB, Ohio. B-1 Airframe Div.

PREDICTION OF AEROELASTIC HINGE MOMENT EFFECTS ON STABILITY AND CONTROLLABILITY

John W. Carlson *In* AGARD Stability and Control Nov. 1972 5 p

The effect of aeroelastic deflections on the stability and control characteristics are studied. Some examples of difficulties are shown that have resulted in control problems and aircraft limitations. Methods of predicting hinge moments are reviewed and some of the problems that arise by the use of these methods are discussed. A program for the analysis of structural deformations is described which may be used to analyze many aeroelastic problems. Author

N73-17007 Aeritalia, Turin (Italy).

CONSIDERATIONS ON THE MANUAL FLIGHT CONTROL DESIGN OF A MILITARY TRANSPORT AIRCRAFT

Antonio Filisetti and Giuseppe Ferretti *In* AGARD Stability and Control Nov. 1972 20 p refs

Criteria for designing manual control systems for military transport aircraft are presented including a guide to the choice of the manual control parameter. Practical problems concerning the nonlinear hinge moments behavior and the control force scatter with the flight conditions are discussed. Aspects of matching manual operated ailerons with hydraulically driven spoilers are emphasized along with practical methods for designing spring-tab control surfaces. Author

N73-17008 Messerschmitt-Boelkow-Blohm G.m.b.H., Ottobrunn (West Germany).

POWERED CONTROLS, INFLUENCE ON STABILITY AND MANEUVERABILITY

Gerhard K. Kissel *In* AGARD Stability and Control Nov. 1972 13 p

The influence is discussed of powered controls on the dynamic and static behavior of modern high performance aircraft. The possibilities of improving the stability and maneuverability by interconnections in the various axes are considered, and an example for a modern fighter type aircraft is demonstrated. Author

N73-17009 Boeing Co., Seattle, Wash.

FLY-BY-WIRE AND ARTIFICIAL STABILIZATION DESIGN

R. L. Schoenman *In* AGARD Stability and Control Nov. 1972 13 p

The implementation of artificial stabilization to correct serious stability and control deficiencies is discussed for meeting the performance demands for aircraft which operate over a broad flight envelope such as VTOL, STOL, and SST. For this class of aircraft safety-of-flight is dependent on the integrity of these systems, and has resulted in the development of redundant system designs. The conventional SAS design approach is compared to that recommended for those vehicles which require augmentation for safety-of-flight. The impact of system redundancy on maintainability and operating costs is also discussed. A system is proposed which features integration of critical flight functions, and the use of digital computation to simplify system complexity. Author

N73-17010 Royal Aircraft Establishment, Farnborough (England). Human Engineering Div.

PILOT WORKLOAD: A CONCEPTUAL MODEL

R. G. Thorne *In* AGARD Stability and Control Nov. 1972 6 p

A conceptual model is presented for the study of the situations when, some of the crew, some of the time are unable to complete satisfactorily some of their tasks. A more realistic simulation of the difficult tasks is recommended. Author

N73-17011 Royal Aircraft Establishment, Farnborough (England). Aerodynamics Dept.

THE ROLE OF THEORETICAL STUDIES OF FLIGHT DYNAMICS IN RELATION TO FLIGHT TESTING

H. H. B. M. Thomas *In* AGARD Stability and Control Nov. 1972 13 p refs

It is argued that calculations have an important role to play in the planning of, the conduct of, and the analysis of flight tests. This is especially true of those areas of flight testing which involve maneuvers near limiting flight conditions in which preflight calculations are invaluable in arriving at a clearer definition of the objective of a test. Provided the aerodynamic forces acting on the aircraft can be adequately and reliably represented, there is inherent difficulty about undertaking the solution of the equations of motion in an appropriate number of degrees of freedom with the aid of available digital computers. The real problem, therefore, lies in reducing to a manageable form the output of such computer studies and thereby achieving a deeper understanding of and a more ready interpretation of the results. As an illustrative example, the longitudinal motion of an aircraft involving an extended angle-of-attack range is considered. Author

N73-17012* National Aeronautics and Space Administration. Flight Research Center, Edwards, Calif.

FLIGHT TEST EXPERIENCE IN AIRCRAFT PARAMETER IDENTIFICATION

Chester H. Wolowicz, Kenneth W. Iloff, and Glenn B. Gilyard /
 AGARD Stability and Control Nov. 1972 13 p refs

An automatic method for determining stability and control derivatives from flight data is presented. The technique, a modification of the Newton-Raphson method for derivative extraction, has a priori provision that makes use of initial estimates of the derivatives and provides a means of checking the validity of the results. Recommendations for applications of the method are included. Author

N73-17013 Aerospatiale Usines de Toulouse (France).
UTILIZATION OF BLACK BOXES FOR IMPROVING THE CHARACTERISTICS OF PILOTAGE DURING THE AIRCRAFT DEVELOPMENT PHASE [UTILISATION DES BOITES NOIRES POUR AMELIORER LES CARACTERISTIQUES DE PILOTAGE DURANT LA PHASE DE DEVELOPPEMENT D'UN AVION]

R. Deque /
 AGARD Stability and Control Nov. 1972 12 p
 In FRENCH

Problems encountered while trying to modify the flight control system of the Concorde aircraft during the development phase are reported. They are: (1) tendency of pilot engine to pump in a lateral direction during supersonic flight, (2) consecutive skid with motor breakdown at supersonic speed, and (3) control of the aircraft after cut off of the piloting gear. The modifications made to correct these problems are given. Transl. by E.H.W.

N73-17014* National Aeronautics and Space Administration.
 Ames Research Center, Moffett Field, Calif.
STUDY OF BUOYANCY SYSTEMS FOR FLIGHT VEHICLES
 C. Dewey Havill and Louis J. Williams Washington Dec. 1972
 62 p refs
 (NASA-TM-X-62168) Avail: NTIS HC \$5.25 CSCL 018

The performance potential of buoyant systems and flexible structures used in air vehicles for short-haul passenger transportation is discussed. The study was intended only to determine if sufficient performance potential existed, and to provide a focus for a more extensive design study, if such a study appeared desirable. A relatively conventional helium system was examined along with a more unusual configuration employing hot-air as the buoyant fluid. Both configurations were examined in the VTOL and STOL modes of operation. The helium system appears to have some superiority in the VTOL mode, while the hot-air system has a superiority in the STOL mode. Both configurations exhibit sufficient performance potential to suggest that a much more extensive design study might well be undertaken. Author

N73-17015* National Aeronautics and Space Administration.
 Ames Research Center, Moffett Field, Calif.
A PILOTTED SIMULATION STUDY OF THE EFFECTS OF CONTROLLER FORCE GRADIENT IN VTOL HOVERING FLIGHT

Emmett B. Fry, Ronald M. Gerdes, and Laurel G. Schroers Jan. 1973 35 p refs Prepared in cooperation with Army Air Mobility Res. and Develop. Lab., Moffett Field, Calif.

(NASA-TM-X-62230) Avail: NTIS HC \$3.75 CSCL 018

A study of the effect of control force gradient on the VTOL visual hovering task was conducted on the NASA-Ames Research Center Six-Degree-of-Freedom Motion Simulator. Lateral control force-gradient characteristics were evaluated in combination with three different types of stabilization systems: An unstabilized (acceleration) system, a rate-stabilized system, and two attitude-stabilized systems. The effects of gust disturbances were included in the control force evaluation for the attitude systems. A force gradient of 1.0 lb/in was within the optimum range for all control systems and conditions evaluated in this study. Author

N73-17016* National Aeronautics and Space Administration.
 Ames Research Center, Moffett Field, Calif.
APPLICATION OF MODERN CONTROL THEORY TO THE DESIGN OF OPTIMUM AIRCRAFT CONTROLLERS
 Leo J. Power Jan. 1973 12 p refs
 (NASA-TM-X-62208) Avail: NTIS HC \$3.00 CSCL 018

The synthesis procedure presented is based on the solution of the output regulator problem of linear optimal control theory

for time-invariant systems. By this technique, solution of the matrix Riccati equation leads to a constant linear feedback control law for an output regulator which will maintain a plant in a particular equilibrium condition in the presence of impulse disturbances. Two simple algorithms are presented that can be used in an automatic synthesis procedure for the design of maneuverable output regulators requiring only selected state variables for feedback. The first algorithm is for the construction of optimal feedforward control laws that can be superimposed upon a Kalman output regulator and that will drive the output of a plant to a desired constant value on command. The second algorithm is for the construction of optimal Luenberger observers that can be used to obtain feedback control laws for the output regulator requiring measurement of only part of the state vector. This algorithm constructs observers which have minimum response time under the constraint that the magnitude of the gains in the observer filter be less than some arbitrary limit. Author

N73-17017* Massachusetts Inst. of Tech., Cambridge.
 Aeroelastic and Structures Research Lab.

THE NONLINEAR INSTABILITY IN FLAP-LAG OF ROTOR BLADES IN FORWARD FLIGHT

Pin Tong Oct. 1971 67 p refs

(Contract NAS2-6175)

(NASA-CR-114524; ASRL-TR-166-2) Avail: NTIS HC \$5.50
 CSCL 01C

The nonlinear flap-lag coupled oscillation of torsionally rigid rotor blades in forward flight is examined using a set of consistently derived equations by the asymptotic expansion procedure of multiple time scales. The regions of stability and limit cycle oscillation are presented. The roles of parametric excitation, nonlinear oscillation, and forced excitation played in the response of the blade are determined. Author

N73-17018* National Transportation Safety Board, Washington, D.C.

AIRCRAFT ACCIDENT REPORT. PAN ALASKA AIRWAYS, LTD., CESSNA 310C, N1812H MISSING BETWEEN ANCHORAGE AND JUNEAU, ALASKA, 16 OCTOBER 1972

31 Jan. 1973 26 p refs

(NTSB-AAR-73-1) Avail: NTIS HC \$3.50

A Cessna 310C disappeared on a flight from Anchorage to Juneau, Alaska, on October 16, 1972. In addition to the pilot, three passengers, including two U. S. Congressmen, were aboard the aircraft. After takeoff from Anchorage, the pilot filed a Visual Flight Rules flight plan for the flight to Juneau. The weather conditions along the proposed route were not conducive to flight under Visual Flight Rules criteria. An extensive air, sea, and land search was conducted during the 39 day period following October 16, 1972. Nothing was found that could be identified with either the aircraft or its occupants. The probable cause of this accident, from the evidence presently available, is undetermined. Author

N73-17019* Cranfield Inst. of Technology (England). Coll. of Aeronautics.

AEROPLANE DESIGN STUDY STOL AIRLINER (A71). PART 1: CONFIGURATION DESCRIPTION AND DATA

D. Howe and R. E. Ward Jun. 1972 32 p refs

(Cranfield-Aero-12-Pt-1) Avail: NTIS HC \$3.75

The proposed design of a short takeoff and landing aircraft for short haul passenger operation is presented. The low speed lift and control problems of a short takeoff aircraft are investigated. The aerodynamic configurations and predicted performance of the aircraft are described. Author

N73-17020* National Aeronautics and Space Administration.
 Ames Research Center, Moffett Field, Calif.

VERTICAL MOTION REQUIREMENTS FOR LANDING SIMULATION

Richard S. Bray Feb. 1973 24 p

(NASA-TM-X-62236) Avail: NTIS HC \$3.25 CSCL 01B

Tests were conducted to determine the significance of vertical acceleration cues in the simulation of the visual approach and landing maneuver. Landing performance measures were

obtained for four subject pilots operating a visual landing simulation device which provides up to plus or minus 40 feet of vertical motion. Test results indicate that vertical motion cues are utilized in the landing task, and that they are particularly important in the simulation of aircraft with marginal longitudinal handling qualities. To assure vertical motion cues of the desired fidelity in the landing tasks, it appears that a simulator must have excursion capabilities of at least plus or minus 20 feet.

Author

N73-17021* Air Force Flight Dynamics Lab., Wright-Patterson AFB, Ohio.

THE DESIGN OF STABILITY AUGMENTATION SYSTEMS FOR DECOUPLING AIRCRAFT RESPONSES Ph.D. Thesis - Purdue Univ. Final Report, Jan. 1970 - Dec. 1971 Rhall E. Pope Jun. 1972 154 p refs Sponsored in part by NASA

(AF Proj. 8219)

(NASA-CR-130543; AD-747017; AFFDL-TR-72-63) Avail: NTIS HC \$9.75 CSCL 01/3

Tactical aircraft with STOL capability exhibit undesirable coupled response during the landing phase of flight. A simplified method for designing a stability augmentation system which eliminates the coupling effects is demonstrated. The method is based on Gilbert's decoupling theory which utilizes a feedback control law to obtain a set of single input, single output subsystems. The augmentation system can be designed to provide either command rate or command angle authority in the three rotational axes. Analyses is facilitated through the use of two computer programs, the first of which determines the class of control laws which will decouple a system. The second computer program determines, through transient response analysis, the values of the transfer function parameters required to satisfy response criteria. The results of a piloted simulation which analyzed several decoupled configurations is also presented.

Author (GRA)

N73-17023# Naval Air Engineering Center, Philadelphia, Pa. Engineering Dept.

ENVIRONMENTAL TEMPERATURE AND AIRCRAFT COMPATIBILITY STUDIES

G. Geaman and W. Goon Oct. 1972 78 p refs

(AD-752018; NAEC-ENG-7780) Avail: NTIS CSCL 01/3

A study of both landbased and shipboard tests of the F14A aircraft with the MK7 Jet Blast Deflector to investigate the effect of backflow of jet exhaust on the aircraft being launched and the resulting environmental temperature aft and alongside the JBD. Configuration for shipboard installation and desired mode of operation are recommended. Areas for further effort to achieve improved compatibility are also presented.

Author (GRA)

N73-17024# Aeronautical Systems Div., Wright-Patterson AFB, Ohio.

F-111 CRACK-PROPAGATION SENSITIVITY ANALYSES

Neil McManus and Troy T. King Mar. 1972 32 p refs

(AF Proj. 324A)

(AD-752223; ASD-TR-71-89) Avail: NTIS CSCL 01/3

The report presents the results of sensitivity analyses conducted on the F-111 aircraft. The objective of the investigation was to identify and assess those parameters which significantly affect the crack propagation characteristics of high strength steel and to relate these results to the F-111 aircraft. The study was done by parametric analyses, and the results are presented graphically in terms of subcritical crack growth interval versus the independent parameter. The analyses showed where emphasis should be placed to control the parametric variables and to minimize a structural failure caused by a pre-existing flaw. In particular, the greatest variation in crack growth interval was a function of initial flaw size.

Author (GRA)

N73-17025# Technology, Inc., Dayton, Ohio.

T-38 STRUCTURAL FLIGHT LOADS DATA FOR JUNE 1970 - DECEMBER 1971 Final Report, 1 Jun. 1970 - 31 Mar. 1972

Larry E. Clay and Ronald I. Rockafellow Wright-Patterson AFB, Ohio ASD Jun. 1972 149 p refs

(Contracts F33657-70-D-1161; F33657-71-C-0662)

(AD-751968; ASD-TR-72-54) Avail: NTIS CSCL 01/3

In a fifth part of a continuing T-38 Service Loads Recording Program to cover the period from 1 June 1970 through 31 December 1971, 4265 hours of VGH data were recorded by A/A24U-10 magnetic tape recording systems installed in twenty-eight T-37 aircraft: 22 fleet and 6 lead-the-force T-38's operating from Williams, Reese, and Moody Air Force Bases. As in previous reports, the data presentation includes curves showing normal load factor (nz) exceedances above each nz level per thousand flight hours. Only one (nz) exceeded 7.8 (design limit is 7.33), and the comparison of the exceedance curves for the current and previous programs substantiated that the T-38 (nz) spectrum had remained unchanged during the T-38 SLRP.

Author (GRA)

N73-17026# Hughes Aircraft Co., Culver City, Calif. Engineering Equipment Div.

STUDY OF A HIGHLY RELIABLE PILOT'S VERTICAL DISPLAY SYSTEM Final Report, 8 Jun. 1970 - 8 Jul. 1972 J. L. Heard, H. L. Bjelland, and E. Streeter Oct. 1972 185 p refs

(Contract N62269-71-C-0510)

(AD-752510; HAC-P72-104R) Avail: NTIS CSCL 01/3

The study develops the requirements for a highly reliable cathode ray tube type of Vertical Display Systems (VDS) for use in Advanced Navy All-Weather Aircraft of the 1980's. First the operational requirements study identified the detailed information required for the VDS. The performance requirements section converts the general operational requirements into specific mechanization requirements. Mechanization tradeoffs then evaluate specific candidate designs and selects the optimum design mechanization for the VDS. A reliability analysis is also performed and aids in making the hardware tradeoffs. A TV type (resonant) indicator is selected to be optimum for the VDS application along with an in-raster or digital television symbol generator. Also two candidate digital scan converter PPI to TV mechanizations are recommended for further evaluation.

Author (GRA)

N73-17027# Naval Air Development Center, Warminster, Pa. Air Vehicle Technology Dept.

TEST PLAN FOR NON-DESTRUCTIVE INSPECTION INVESTIGATION OF THE CATAPULT AND ARRESTED LANDING CARRY-THROUGH STRUCTURE OF THE E-2 AIRCRAFT Progress Report

Louis Berman 15 Jul. 1972 11 p

(AD-752492) Avail: NTIS CSCL 01/3

Non-destructive inspection techniques, for utilization by the NAVAIWORKFAC (Naval Air Rework Facility), are required to inspect the catapult and arrested landing carry-through structure of the E-2 airplane. This program proposes an NDI investigation to be performed during the E-2 fatigue tests.

Author (GRA)

N73-17028# Naval Air Development Center, Warminster, Pa. Air Vehicle Technology Dept.

TEST PLAN REPORT FOR CATAPULT FATIGUE TEST OF THE MODEL C-2A AIRPLANE

Edward F. Kautz 6 Oct. 1972 19 p refs

(AD-752493; NADC-72197-VT) Avail: NTIS CSCL 01/3

A laboratory fatigue test will be performed on a C-2 airframe to determine whether the airframe will sustain the effects of 3000 catapult launches without structural failure.

Author (GRA)

N73-17029# Forest Products Lab., Madison, Wis.

DESIGN PARAMETERS FOR TORSION OF SANDWICH STRIPS HAVING TRAPEZOIDAL RECTANGULAR, AND TRIANGULAR CROSS SECTIONS

H. M. Montrey and Edward W. Kuenzi 1972 41 p refs Sponsored by Air Force and FAA

(AD-752619; FSRP-FPL-156) Avail: NTIS CSCL 01/3

Solutions for the elastic torsion of sandwich strips having triangular, rectangular, or trapezoidal cross sections are presented analytically in terms of suitable design parameters. Data obtained

from resulting expressions are presented in a series of design curves for normalized values of torsional stiffness and maximum facing and core shear stresses. The analysis is based on the Saint Venant theory of torsion. The sandwich facings are idealized as identical, thin, isotropic membranes, while the core's elastic behavior is characterized by a single transverse modulus of rigidity. Author (GRA)

N73-17030# Air Force Flight Dynamics Lab., Wright-Patterson AFB, Ohio.

BI-NORMAL COORDINATES IN DISCRETE SYSTEMS WITH APPLICATION TO AN AIRCRAFT SHIMMY PROBLEM

Lynn C. Rogers Jun. 1972 265 p refs
(AF Proj. 1367)

(AD-752548; AFFDL-TR-72-79) Avail: NTIS CSCL 01/3

The use of bi-normal coordinate theory in the analysis of practical discrete systems provides the substantial benefits of conceptual value/physical insight, computational utility, and enhanced redesign capability. These benefits are explained and demonstrated in the present effort with attention to practical considerations. Section 1 extends the theory and presents the new material together with some previously available results in a coordinated manner. In particular, the nature of response in a single homogenous phasor mode is described in detail. Also, an expression for the derivative of an eigenvalue is developed and explained. Section 2 reports the analysis of an aircraft nosegear shimmy problem using bi-normal coordinate methods. Stability boundaries, mode shapes, and sensitivities to parameter changes are presented. Derivatives of eigenvalues are used in Section 3 to illustrate automated minimum weight design for a shimmy-free nosegear. Recommendations for further research are made. Author (GRA)

N73-17031# Boeing Co., Philadelphia, Pa. Vertol Div.
AN INVESTIGATION OF HELICOPTER TRANSMISSION NOISE REDUCTION BY VIBRATION ABSORBERS AND DAMPING Final Report

H. Sternfeld, J. Schairer, and R. Spencer Ft. Eustis, Va. Army Air Mobility Res. and Develop. Lab. Aug. 1972 163 p refs
(Contract DAAJ02-71-C-0020; DA Proj. 1F1-62204-A-142)
(AD-752579; USAAMRDL-TR-72-34) Avail: NTIS CSCL 01/3

A test program was conducted to evaluate the effect of dynamic absorbers and damping on the noise generated by a CH-47 rotor transmission. Comparison was made between predicted and measured results, and a method for comparing the efficiency of various methods of transmission noise reduction was developed. Gear damping was achieved by filling the gear shafts with Viton, and by a ring of Viton on the spiral bevel ring gear. Constrained layer damping was also used on the outside of the planetary ring gear. Author (GRA)

N73-17032# Massachusetts Inst. of Tech., Cambridge. Aerophysics Lab.

HELICOPTER ROTOR WAKE GEOMETRY AND AIRLOADS AND HELICOPTER ROTOR WAKES Final Scientific Technical Report, 6 Jun. 1971 - 6 Jun. 1972

M. P. Scully and J. P. Sullivan Aug. 1972 67 p refs
(Contract N00019-71-C-0220; MIT Proj. DSR-73032)
(AD-752628; TR-179) Avail: NTIS CSCL 14/2

Computer programs have been developed for the calculation of helicopter rotor tip vortex geometry in hover and forward flight and for the calculation of helicopter rotor harmonic airloads in forward flight. Calculated forward flight tip vortex geometries compare well in general with experimental smoke studies although there are differences in detail. The hovering tip vortex geometry agrees qualitatively with experiment but does not move downward fast enough. Airloads were computed using both the classical rigid wake assumption and the distorted tip vortex geometry obtained from the computer program. When compared with experimental airloads measurements the rigid wake airloads give better results than the distorted wake airloads. Author (GRA)

N73-17033# Northrop Corp., Hawthorne, Calif. Aircraft Div.
V/STOL AIRCRAFT AERODYNAMIC PREDICTION METHODS INVESTIGATION. VOLUME 1: THEORETICAL DEVELOPMENT OF PREDICTION METHODS Final Report, 1 May 1969 - 31 Jan. 1972

Peter T. Wooler, Hsiao C. Kao, Myles F. Schwendemann, Howard R. Wasson, and Henry Ziegler Jan. 1972 238 p refs
(Contract F33615-69-C-1602; AF Proj. 6988T)
(AD-752557; NOR-72-9-Vol-1; AFFDL-TR-72-26-Vol-1) Avail: NTIS CSCL 01/3

Analytical engineering methods are developed for use in predicting the static and dynamic stability and control derivatives and force and moment coefficients of lift-jet, lift-fan, and vectored thrust V/STOL aircraft in the hover and transition flight regimes. The methods take into account the strong power effects, large variations in angle of attack and sideslip, and changes in aircraft geometry that are associated with high disk loaded V/STOL aircraft operating in the aforementioned flight regimes. The theoretical development of the prediction methods is presented in this volume. Author (GRA)

N73-17034# Northrop Corp., Hawthorne, Calif. Aircraft Div.
V/STOL AIRCRAFT AERODYNAMIC PREDICTION METHODS INVESTIGATION. VOLUME 2: APPLICATION OF PREDICTION METHODS Final Report, 1 May 1969 - 31 Jan. 1972

Peter T. Wooler, Hsiao C. Kao, Myles F. Schwendemann, Howard R. Wasson, and Henry Ziegler Jan. 1972 249 p refs
(Contract F33615-69-C-1602; AF Proj. 6988T)
(AD-752558; NOR-72-9-Vol-2; AFFDL-TR-72-26-Vol-2) Avail: NTIS CSCL 01/3

Analytical engineering methods are developed for use in predicting the static and dynamic stability and control derivatives and force and moment coefficients of lift-jet, lift-fan, and vectored thrust V/STOL aircraft in the hover and transition flight regimes. The aircraft configurations studied have a conventional wing, fuselage and empennage. The prediction methods are applied to a number of V/STOL configurations in this volume. Author (GRA)

N73-17035# Northrop Corp., Hawthorne, Calif. Aircraft Div.
V/STOL AIRCRAFT AERODYNAMIC PREDICTION METHODS INVESTIGATION. VOLUME 3: MANUAL FOR COMPUTER PROGRAMS Final Report, 1 May 1969 - 31 Jan. 1972

Peter T. Wooler, Hsiao C. Kao, Myles F. Schwendemann, Howard R. Wasson, and Henry Ziegler Jan. 1972 207 p
(Contract F33615-69-C-1602; AF Proj. 6988T)
(AD-752559; NOR-72-9-Vol-3; AFFDL-TR-72-26-Vol-3) Avail: NTIS CSCL 01/3

Analytical engineering methods are developed for use in predicting the static and dynamic stability and control derivatives and force and moment coefficients of lift-jet, lift-fan, and vectored thrust V/STOL aircraft in the hover and transition flight regimes. The aircraft configurations studies have a conventional wing, fuselage and empennage. The prediction methods are suitable for use by design personnel during the preliminary design and evaluation of V/STOL aircraft of the type previously mentioned. Details and listings of the computer programs associated with the prediction methods are given in the volume. Author (GRA)

N73-17036# Northrop Corp., Hawthorne, Calif. Aircraft Div.
V/STOL AIRCRAFT AERODYNAMIC PREDICTION METHODS INVESTIGATION. VOLUME 4: LITERATURE SURVEY Final Report, 1 May 1969 - 31 Jan. 1972

Peter T. Wooler, Hsiao C. Kao, Myles F. Schwendemann, Howard R. Wasson, and Henry Ziegler Jan. 1972 79 p refs
(Contract F33615-69-C-1602; AF Proj. 6988T)
(AD-752563; NOR-72-9-Vol-4; AFFDL-TR-72-26-Vol-4) Avail: NTIS CSCL 01/3

Analytical engineering methods are developed for use in predicting the static and dynamic stability and control derivatives and force and moment coefficients of lift-jet, lift-fan, and vectored thrust V/STOL aircraft in the hover and transition flight

regimes. The prediction methods are suitable for use by design personnel during the preliminary design and evaluation of V/STOL aircraft of the type previously mentioned. The results of a literature survey are presented in this volume. Author (GRA)

N73-17039* National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.
EFFECT OF REDUCING ROTOR BLADE INLET DIAMETER ON THE PERFORMANCE OF A 11.66-CENTIMETER RADIAL-INFLOW TURBINE
 Milton G. Kofskey and Jeffrey E. Haas Washington Mar. 1973 20 p refs Prepared in cooperation with Army Air Mobility R and D Lab., Cleveland, Ohio
 (NASA-TM-X-2730; E-7119) Avail: NTIS HC \$3.00 CSCL 21E

The effect of increased rotor blade loading on turbine performance was investigated by reducing rotor blade inlet diameter. The reduction was made in four stages. Each modification was tested with the same stator using cold air as the working fluid. Results are presented in terms of equivalent mass flow and efficiency at equivalent design rotative speed and over a range of pressure ratios. Internal flow characteristics are shown in terms of stator exit static pressure and the radial variation of local loss and rotor-exit flow angle with radius ratio. Included are velocity diagrams calculated from the experimental results. Author

N73-17046* Garrett Corp., Phoenix, Ariz. AiResearch Manufacturing Div.
A SECONDARY POWER SYSTEM STUDY FOR ADVANCED ROTARY-WING AIRCRAFT Final Technical Report, 1 Jun. 1970 - 31 May 1971
 Bernard H. Nicholls Aug. 1972 335 p
 (Contract DAAJ02-70-C-0048; DA Proj. 1G1-82203-D-144)
 (AD-751854; SY-6103-R; USAAMRD-TR-72-13) Avail: NTIS CSCL 10/2

A study was performed to define and evaluate secondary power systems for an advanced Army rotary-wing aircraft, using existing technology and two advanced technology levels. The basic aircraft mission, performance penalty parameters, and system components are defined. From a total of 162 candidate systems, 36 were selected for detailed comparisons. Evaluation parameters included incremental takeoff gross weight, system weight, volume, reliability, maintainability, availability, power APU that drives into the aircraft accessory gearbox with two electrical generators and two hydraulic pumps. Main engines are started pneumatically by bleed air from the APU. Cockpit cooling was an optional addition, and an air-cycle system was selected. Author (GRA)

N73-17059* National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.
MACHINING OF LOW PERCENTAGE BERYLLIUM COPPER ALLOYS
 John G. Habermeyer In: Proc. of the Ann. Conf. of NASA Clinic Directors, Environ. Health Off. and Med. Program Advisors 1969 p 117-120
 CSCL 06T

Airborne beryllium sampling during machining of low percentage beryllium-copper alloys shows that normal dry machining creates 45.2 microgram/cu m of airborne beryllium in the casting operators breathing zone and 2.3 microgram/cu m in an adjacent machine working area. A small vacuum system placed over the tool effectively removes airborne beryllium in the breathing zone sample to 0.2 microgram/cu m. G.G.

N73-17163* Federal Aviation Administration, Washington, D.C.
ENGINEERING AND DEVELOPMENT PROGRAM PLAN: AIR TRAFFIC CONTROL SURVEILLANCE RADAR
 Harry C. Moses Dec. 1972 65 p refs
 (FAA-ED-02-1) Avail: NTIS HC \$5.25

The role of the primary radar system in air traffic control operations is discussed. Emphasis is placed on the performance deficiencies and the technical development programs undertaken to eliminate the deficiencies. The compliance of the radar with the air traffic control surveillance requirements is analyzed.

Author

N73-17168* Colorado Univ., Boulder.
FLIGHT SAFETY ASPECTS OF PRECISION RADAR NEAR AIR BASES IN BIRD-AIRCRAFT COLLISION AVOIDANCE
 Technical Report, 18 Jun. 1970 - 1 Feb. 1972
 Warren L. Flock Kirtland AFB, N. Mex. AFWL Oct. 1972. 67 p refs
 (Contract F29601-70-C-0076)
 (AD-751985; AFWL-TR-72-25) Avail: NTIS CSCL 17/9

The utility of a GEC-AEI No. 654 radar for warning of bird hazards at airfields has been evaluated at Gunbarrel Hill and Valmont Reservoir, near Boulder, Colorado, from 16 March to 19 December 1971. Morning and evening flights of Mallards, Canada Geese, etc., provide good test radar targets at these locations. The 654 radar is useful as it is, but improvements are recommended to allow detection of birds at greater ranges. Some Doppler radar signature data were also taken with a CW radar at Baller Lake in spring 1971. Experience with this radar provides a basis for recommending further development of signature capability. Such capability should allow determining quickly if a target is caused by birds or not, the type or size of bird, and whether the echo is from one or a small or large number of birds. Author (GRA)

N73-17170* Lincoln Lab., Mass. Inst. of Tech., Lexington.
A THEORY FOR OPTIMAL MOVING TARGET INDICATOR (MTI) DIGITAL SIGNAL PROCESSING, SUPPLEMENT 1
 Robert J. McAulay 31 Oct. 1972 22 p refs
 (Contract F19628-73-C-0002; AF Proj. 649L)
 (AD-751923; TN-1972-14-Suppl-1; ESD-TR-72-243-Suppl-1) Avail: NTIS CSCL 17/9

In the report, A Theory for Optimal MTI Digital Signal Processing. Part I. Receiver Synthesis, (1), the problem of eliminating scanning ground clutter from an aircraft surveillance radar was examined from a statistical decision theoretical point of view. An optimum processor was derived which could be approximated by a clutter filter followed by a discrete Fourier transform (DFT). In the report, additional numerical work is documented that compares the performance of the pulse cancellers with feedback and the DFT with that of the optimum processor. The issue of coherent vs incoherent integration gain is considered by comparing the filters only on their ability to reject clutter. A clutter rejection improvement factor is defined and used to compare the various filters. It is shown that the pulse cancellers can be quite effective in rejecting clutter provided the input clutter power is not too large and that additional gains are possible using the DFT. Author (GRA)

N73-17178* Lincoln Lab., Mass. Inst. of Tech., Lexington.
DIVERSITY TECHNIQUES FOR AIRBORNE COMMUNICATIONS IN THE PRESENCE OF GROUND REFLECTION MULTIPATH
 Henry Berger and James E. Evans Sep. 1972 151 p refs
 (Contract F19628-73-C-0002; AF Proj. 649)
 (AD-752249; TN-1972-27; ESD-TR-72-216) Avail: NTIS CSCL 17/2

The signal power reduction due to multipath fading is an important design consideration in the development of air-air and ground-air communications links at L-band. A first order mathematical model of ground reflection multipath is used to predict the relationship between the depth of fading and environmental parameters such as surface roughness and the terminal positions relative to earth. The model is then used to investigate two techniques for reducing the loss in received signal power: frequency diversity and antenna height diversity. A measurement program to experimentally evaluate the applicability of antenna height diversity is outlined. Author (GRA)

N73-17221# Systems Technology Center, Los Angeles, Calif.
STUDY OF CAPABILITIES, NECESSARY CHARACTERISTICS AND EFFECTIVENESS OF PILOT GROUND TRAINERS.
VOLUME 1: MAIN TEXT Final Report, Jul. 1970 - Jun. 1971

Peter Stanek Jan. 1973 261 p refs
 (Contract DOT-FA70NA-506; Proj. 502-103-10X)
 (FAA-NA-72-102-Vol-1; STC-16001-Vol-1) Avail: NTIS HC \$15.25

An experiment was conducted to test the capabilities, necessary characteristics, and effectiveness of pilot ground trainers in developing primary aeronautical skills, those maneuvers and procedures limited to aircraft, single-engine, land. During the first phase of the experiment, 30 subjects were trained to proficiency, fifteen in aircraft only and fifteen in combined ground trainer and aircraft. During the next phase, 20 of the original 30 were trained to proficiency, 10 in each group. A third phase of the experiment tested additional subjects in various procedures with varying levels of simulator capability. The results of the experiment show which maneuvers and procedures may be taught effectively and efficiently in a ground trainer. Author

N73-17222# Systems Technology Center, Los Angeles, Calif.
STUDY OF CAPABILITIES, NECESSARY CHARACTERISTICS AND EFFECTIVENESS OF PILOT GROUND TRAINERS.
VOLUME 2: ADDENDUM, SUMMARY OF FLIGHT INSTRUCTORS VIEWS Final Report, Jul. 1970 - Jun. 1971
 Peter Stanek Jan. 1973 40 p refs
 (Contract DOT-FA70NA-506; Proj. 502-103-10X)
 (FAA-NA-72-102-Vol-2-Add; STC-16001-Vol-2-Add) Avail: NTIS HC \$4.00

N73-17223*# National Aeronautics and Space Administration, Ames Research Center, Moffett Field, Calif.
A STUDY ON AIRCRAFT MAP DISPLAY LOCATION AND ORIENTATION
 D. Baty, T. Wempe, and E. Huff Jan. 1973 88 p refs
 (NASA-TM-X-62198) Avail: NTIS HC \$6.50 CSCL 14B

Six airline pilots participated in a fixed-based simulator study to determine the effects of two horizontal situation display (HSD/map) panel locations relative to the vertical situation display (VSD), and of three map orientations on manual piloting performance. Pilot comments and opinions were formally obtained. Significant performance differences were found between wind conditions and among pilots but not between map locations and orientations. The results also illustrate the potential tracking accuracy of such a display. Recommendations concerning display location and map orientation are made. Author

N73-17233# Army Engineer Waterways Experiment Station, Vicksburg, Miss.
EVALUATION OF HARVEY ALUMINUM 1-BY 12-FT EXTRUDED LIGHT DUTY LANDING MAT WITH SYMMETRICAL BUTT TYPE END CONNECTORS Final Report
 Hugh L. Green Oct. 1972 70 p refs Sponsored in part by AFWL
 (DA Proj. 1G6-64717-D-H01; AF Proj. 6111A)
 (AD-752079; AEWES-Misc-Paper-S-72-38) Avail: NTIS CSCL 01/5

The investigation reported herein was conducted to evaluate an extruded aluminum alloy landing mat. The 1-by 12-ft mat is a one-piece hollow extrusion fabricated from 6063 aluminum alloy artificially aged to the T6 condition and weights 2.81 lb per square foot of placing area. The mat panels are interlocked along the sides by means of a hinge-type connector, the components of which are integral parts of the basic extrusion. End connectors, which are composed of 6061-T6 extruded aluminum connectors with integral inserts welded to the basic panel using the electron beam welding method, consist of symmetrical butt-type sections that are secured by a locking bar after individual panels have been joined together. The

investigation consisted of laboratory, traffic, and skid tests to obtain information for use in evaluating Harvey mat for potential use as a light-duty landing mat. Author (GRA)

N73-17235# Massachusetts Inst. of Tech., Cambridge. Flight Transportation Lab.
THE DEVELOPMENT OF A WIND TUNNEL FACILITY FOR THE STUDY OF V/STOL NOISE
 Paul Bauer and Sheila Widnall Aug. 1972 29 p refs
 (Contract DAHCO4-69-C-0086)
 (AD-751857; FTL-R72-6; AROD-8713-2-E) Avail: NTIS CSCL 14/2

An open-jet wind tunnel operating within an anechoic chamber was developed for the purpose of the study of V/STOL noise mechanisms. An existing low-speed conventional hardwalled wind tunnel was modified to operate as an open-jet tunnel; an anechoic chamber was then constructed around the test section. The resulting aerodynamic and acoustic characteristics of the tunnel are discussed. Author (GRA)

N73-17247# Carleton Univ., Ottawa (Ontario). Div. of Aerothermodynamics.
AIRCRAFT TRAILING VORTICES: A SURVEY OF THE PROBLEM

Z. El-Ramly Nov. 1972 195 p refs
 (ME/A-72-1) Avail: NTIS HC \$11.75

A survey of aircraft trailing vortices is presented. Only vortices shed from high aspect ratio straight or sweptback wings are considered. A brief description of the formation and behavior of vortex systems is provided. The stability of a trailing vortex pair is analyzed. The effects of buoyancy on the motion of wing tip vortices and the vortex breakdown phenomenon are discussed. Author

N73-17252 ARO, Inc., Arnold Air Force Station, Tenn.
EJECTOR DESIGN FOR A VARIETY OF APPLICATIONS
 Delbert Taylor In AGARD Supersonic Ejectors Nov. 1972 p 103-163 refs
 (Contract F40600-69-C-0001)

Methods and techniques developed to improve the performance and applications of various ejector designs are examined. Data cover fixed value simple design and variable area/variable pressure ejectors. E.H.W.

N73-17258*# Lockheed-California Co., Burbank.
RESEARCH ON UNSTEADY TRANSONIC FLOW THEORY
 James D. Revell Feb. 1973 108 p refs
 (Contract NAS1-11566)
 (NASA-CR-112114) Avail: NTIS HC \$7.50 CSCL 20D

A two-dimensional theory is considered for the unsteady flow disturbances caused by aeroelastic deformations of a thick wing at high subsonic freestream Mach numbers, having a single, internally embedded supercritical (locally supersonic) steady flow region adjacent to the low pressure side of the wing. The theory develops a matrix of unsteady aerodynamic influence coefficients (AICs) suitable as a strip theory for aeroelastic analysis of large aspect ratio thick wings of moderate sweep, typical of a wide class of current and future aircraft. The theory derives the linearized unsteady flow solutions separately for both the subcritical and supercritical regions. These solutions are coupled together to give the requisite (wing pressure-downwash) AICs by the intermediate step of defining flow disturbances on the sonic line, and at the shock wave; these intermediate quantities are then algebraically eliminated by expressing them in terms of the wing surface downwash. Author

N73-17259*# Scientific Translation Service, Santa Barbara, Calif.
PROBLEM OF UNIFORM JET FLOW AROUND AN AIRFOIL
 E. G. Shifrin Washington NASA 22 Feb. 1973 12 p refs
 Transl. into ENGLISH from Izv. Akad. Nauk SSSR, Mekh. Zhidk. Gaza (USSR), Jul. - Aug. 1972 p 162-165

(Contract NASw-2483)

(NASA-TT-F-14813) Avail: NTIS HC \$3.00 CSCL 20D

A uniform jet flowing around an airfoil with a separated shock wave is examined for a case of low supersonic velocities, of the incident flow where entropy changes at the shock wave may be neglected. Shapes of minimal regions of influence of the mixed flow are examined for both convex and concave profiles.

Author

N73-17266# Air Force Flight Dynamics Lab., Wright-Patterson AFB, Ohio.

THE INFLUENCE OF AERODYNAMIC DECELERATORS ON SUPERSONIC WAKES: WITH AN APPLICATION OF THE GAS HYDRAULIC ANALOGY Final Technical Report, Apr. 1965 - Dec. 1969

Charles A. Babish, III Aug. 1972 105 p refs

(AD-751982; AFFDL-TR-72-54) Avail: NTIS CSCL 01/3

Two-body performance characteristics can be predicted with a reasonable degree of accuracy for deployable aerodynamic decelerators operating in conventional supersonic wakes. However, under certain geometric and flight conditions, the decelerator can modify the base flow region of the forebody, thus invalidating the performance prediction techniques. A literature review, supplementary wind tunnel tests, and a large number of shallow water tow table tests were performed to obtain a description of the process of wake modification and identify those parameters that influence the process.

Author (GRA)

N73-17270# Naval Postgraduate School, Monterey, Calif.
SMOKE AND HELIUM BUBBLE VISUALIZATION STUDIES OF INCOMPRESSIBLE FLOW PAST A JET-FLAP AIRFOIL M.S. Thesis

John Patrick Costello, II Jun. 1972 58 p refs

(AD-752012) Avail: NTIS CSCL 14/2

An exploratory low speed visualization study was performed in the wind tunnel on a jet-flapped airfoil to evaluate a test facility for future work and to compare an old and a relatively new flow visualization technique. These techniques are smoke flow and helium bubble flow. The study was conducted using various tunnel speeds and blowing rates for the jet flap. The varying of these parameters and the complexity of the jet flap flow allowed for the evaluation. As a result of many photographs taken, a comparison was made between predicted jet stream deflection and the deflections measured on photographs.

Author (GRA)

N73-17271# Aerospace Research Labs., Wright-Patterson AFB, Ohio. Fluid Dynamics Facilities Research Lab.

SHOCK DETACHMENT FROM THE LEADING EDGE OF DELTA WINGS Final Scientific Report

Kenneth F. Stetson and Norman E. Scaggs May 1972 20 p refs

(AF Proj. 7065)

(AD-752208; ARL-72-0079) Avail: NTIS CSCL 20/4

Angles of attack for shock wave detachment from the sharp leading edge of five delta wing models with flat compression surfaces were determined experimentally and the results are compared with analytical prediction methods. The wind tunnel experiments were performed at a free stream Mach number of 14.2 and a free stream Reynolds number per foot of 62,000. The angle of attack for shock wave detachment was experimentally determined by observing the flow of oil from the compression side of the model around the leading edge.

Author (GRA)

N73-17278# Applicazioni e Ricerche Scientifiche, Milan (Italy).
MODELS FOR GAS SURFACE INTERACTIONS AND COMPUTATION OF AERODYNAMIC COEFFICIENTS Interim Scientific Report, 1 Aug. 1971 - 31 Jul. 1972

Carlo Cercignani 31 Jul. 1972 25 p refs

(Contract F44620-71-C-0121; AF Proj. 9783)

(AD-752245; AFOSR-72-2202TR) Avail: NTIS CSCL 20/4

The report is devoted to summarizing the research work carried out on models for gas surface interaction, and computation of aerodynamic coefficient for some simple geometrical shapes and high Mach number flow past thin, almost specularly reflecting airfoils.

Author (GRA)

N73-17279# Naval Ordnance Lab., White Oak, Md.
DISTORTION OF NEAR-SONIC SHOCKS BY WEAKLY TURBULENT LAYERS

Leonard S. Taylor and Ralph E. Phinney 21 Sep. 1972 26 p refs

(NOL Proj. 324/FAA)

(AD-752472; NOLTR-72-225) Avail: NTIS CSCL 20/1

The focusing effects of turbulence in the propagation medium upon near-sonic shocks are studied by extending the theory of shock dynamics to a medium with random temperature and pressure variations. A perturbation procedure is used to solve the resulting nonlinear partial differential equation. The results are applied in a discussion of sonic boom distortion in the terrestrial boundary layer.

Author (GRA)

N73-17562# Air Force Avionics Lab., Wright-Patterson AFB, Ohio.

LIGHTNING AND STATIC ELECTRICITY CONFERENCE

Dec. 1972 694 p refs Conf. held at Las Vegas, Nev., 12-15 Dec. 1972; sponsored by AFAL and SAE

(AD-752551; AFAL-TR-72-325) Avail: NTIS CSCL 01/2

The document contains the text of unclassified papers presented at the 1972 Conference on Lightning and Static Electricity, held 12-15 December 1972. The papers document the discussion of the theoretical aspects of both lightning and atmospheric electrification. In addition, the practical control of adverse effects is addressed relative to aerospace vehicles and installations. Sessions include fundamental aspects, missiles and spacecraft, aircraft, advanced composites, fuels, and lightning simulation.

Author (GRA)

N73-17570# Cranfield Inst. of Technology (England). Coll. of Aeronautics.

A COMPARATIVE ASSESSMENT OF THREE METHODS OF MEASUREMENT OF PRESSURE ERROR CORRECTIONS

M. E. Eshelby Jun. 1972 25 p refs

(Cranfield-Aero-11) Avail: NTIS HC \$3.25

Three methods of evaluating the pressure error of an aircraft pitot-static system are described, and the relative merits of each method are compared. The determination of static pressure error by a trailing cone is considered as a method suitable for use on light aircraft, and comparisons are made between the pressure error measured by the cone and other methods.

Author

N73-17592# Boeing Commercial Airplane Co., Seattle, Wash.
DEVELOPMENT AND TESTING OF IMPROVED POLYIMIDE ACTUATOR ROD SEALS AT HIGHER TEMPERATURES FOR USE IN ADVANCED AIRCRAFT HYDRAULIC SYSTEMS

E. D. Robinson, A. W. Waterman, and W. G. Nelson 28 Feb. 1972 39 p refs

(Contract NAS3-16733)

(NASA-CR-121124; D6-41114) Avail: NTIS HC \$4.00 CSCL 11A

Polyimide second stage rod seals were evaluated to determine their suitability for application in advanced aircraft systems. The configurations of the seals are described. The conditions of the life cycle tests are provided. It was determined that external rod seal leakage was within prescribed limits and that the seals showed no signs of structural degradation.

Author

N73-17654# Royal Aircraft Establishment, Farnborough (England).

FABRIC PROPERTIES AND THE WEAR OF HOVERCRAFT FINGERS

J. E. Swallow, J. H. Cadwell, and M. Webb Oct. 1971 27 p refs

(RAE-TR-71210; BR-27693) Avail: NTIS HC \$3.50

The wear of fingers made from 16 types of coated fabric was studied on an SRN 5 hovercraft. Laboratory determinations of a number of fabric properties were made, and the results correlated with wear behavior, using correlation and factor analysis techniques. The extent to which the laboratory tests enable wear to be predicted was also investigated. ESRO

N73-17681# Naval Air Development Center, Warminster, Pa. Air Vehicle Technology Dept.
INVESTIGATION OF THE EFFECTS OF LIQUID OXYGEN ON CHEMICALLY TREATED SURFACES OF ALUMINUM TUBING

M. Perlman and J. F. Danovich 18 Oct. 1972 11 p refs
 (AD-752030; NADC-72201-VT) Avail: NTIS CSCL 11/3

The report describes the effects of liquid oxygen on chemically treated (chromic acid anodized and chromate conversion coated) surfaces of aluminum tubing used in aviators' breathing systems. Tests were conducted to detect residual deposits, gaseous contamination and changes in surface structure. Author (GRA)

N73-17676# Finnish Meteorological Inst., Helsinki.
AN INVESTIGATION INTO WIND SHEAR AT HELSINKI AIRPORT

Eero Immonen Jun. 1972 40 p refs
 (TR-3) Avail: NTIS HC \$4.25

Vertical wind shear measurements were made using a balloon rising with the average rate of 180 m/min and optical theodolites to measure the angle at 10 sec intervals and to check the rate of ascent. Weather permitting, soundings were carried out on three days of the week at four synoptic times from the beginning of April 1967 through March 1968. The annual, seasonal, and diurnal distributions are discussed and are graphed. N.E.N.

N73-17694# Sierra Research Corp., Boulder, Colo. Environmental Systems Group.

FIELD TEST OF WARM FOG DISPERSAL SYSTEM TO SUPPORT MARINE CORPS HELICOPTER OPERATIONS

Ralph Papania, Jr. 20 Jun. 1972 76 p refs
 (Contract M00264-72-C-0094)
 (AD-752046) Avail: NTIS CSCL 04/2

Warm fog dispersal techniques using helicopter downwash mixing and hygroscopic seeding were successfully tested to a limited degree on fog and low stratus. The equipment, procedures and nomograms for helicopter application of hygroscopic seeding materials are described as they were developed in three field tests. Weather conditions suitable for dispersal operations occurred on only one day, during which a useable clearing was created in low stratus, 650 feet thick. Results show that the effectiveness of fog dispersal by helicopter downwash was considerably enhanced when the fog or stratus layer was treated with hygroscopic seeding agent (unsized urea in these particular tests). Some quantitative data and photographic coverage is presented. Author (GRA)

N73-17708# Toronto Univ. (Ontario). Inst. for Aerospace Studies.
AIRCRAFT TRANSITION ALGORITHM FOR CONFLICT PREDICTION, WITH SPECIFIC REFERENCE TO THE NORTH ATLANTIC AIR TRAFFIC CONTROL SYSTEM

D. J. Mohr Jan. 1973 131 p refs
 (UTIAS-TN-183) Avail: NTIS HC \$8.75

The development of digital fast-time air traffic control conflict prediction simulation models is discussed. A simulation algorithm was designed for compatibility with the Gander Automated Air Traffic System. The algorithm is applied to multiple aircraft strategically controlled environments and functions to search, detect, and resolve conflict situations during enroute aircraft transitioning. The simulation model includes meteorological data, route structure, flight trajectory construction, and a conflict resolution option. Author

N73-17710*# Kanner (Leo) Associates, Redwood City, Calif.
VISUAL CONSIDERATIONS CONCERNING APPROACH LIGHTS

N. Iwataki and H. Kansaku Washington NASA Jan. 1973 26 p refs Transl. into ENGLISH from Iijitsu Hokoku (Japan), v. 7, no. 2, Oct. 1966 p 98-107
 (Contract NASw-2481)

(NASA-TT-F-14667) Avail: NTIS HC \$3.50 CSCL 17G

Approach lights serve the pilot, landing at night or in bad weather, as visual aids to his spatial judgment. Desirable properties of approach lights such as color, intensity, configuration, etc., are discussed from the viewpoint of visual perception with data from published, fundamental research and investigations. The color red is most desirable as an approach light considering visibility in several weather conditions, darkness adaptation, advance-retreat and swelling-contracting phenomenon, ability to discriminate from other lights at the airfield, and transmissivity of light through the atmosphere. The optimal intensity of light is related to the color of the light and the amount of glare. Stroboscopic light is effective for increased conspicuousness. Visual approach slope line indicator systems and a few others were determined to be superior to other configurations. Author

N73-17803# Esso Research and Engineering Co., Linden, N.J. Government Research Lab.

FUEL MODIFICATION FOR ABATEMENT OF AIRCRAFT TURBINE ENGINE OXIDES OF NITROGEN EMISSIONS
 Final Report, 26 Apr. 1971 - 31 May 1972

Henry Shaw Oct. 1972 134 p refs
 (Contract F33615-71-C-1575; AF Proj. 3066)
 (AD-752581; GRU.1GDJA.72; AFAPL-TR-72-80) Avail: NTIS CSCL 21/4

The report describes a broad experimental program that was undertaken to assess the feasibility of reducing NO(x) from aircraft gas turbine engines by fuel modification. The Esso High Pressure Cannular Combustor was used to simulate the characteristic emissions of gas turbines at full power operation. Over 70 fuel modifications were tested using Jet A as the base fuel. Soluble compounds of cobalt, iron, magnesium, and copper reduce NO(x) by as much as 30% when added to the fuel at a treat rate of up to 0.5% (w). None of the investigated additives were fully acceptable because of the relatively low NO(x) reduction that was obtained even with high additive treat rates. A simple expression was derived which is useful in estimating NO levels in gas turbine combustors when equilibrium NO(x) concentrations and temperature are known. Author (GRA)

N73-17809*# AiResearch Mfg. Co., Torrance, Calif.
ANALYTICAL INVESTIGATION OF CHORD SIZE AND COOLING METHODS ON TURBINE BLADE COOLING REQUIREMENTS. BOOK 1: SECTIONS 1 THROUGH 8 AND APPENDICES A THROUGH I

F. E. Faulkner Aug. 1971 378 p refs
 (Contract NAS3-13205)

(NASA-CR-120882-Bk-1; AiResearch-71-7487-Bk-1) Avail: NTIS HC \$21.00 CSCL 21E

A study was conducted to determine the effect of chord size on air cooled turbine blades. In the preliminary design phase, eight turbine blade cooling configurations in 0.75-in., 1.0-in., and 1.5-in. chord sizes were analyzed to determine the maximum turbine inlet temperature capabilities. A pin fin convection cooled configuration and a film-impingement cooled configuration were selected for a final design analysis in which the maximum turbine inlet temperature was determined as a function of the cooling air inlet temperature and the turbine inlet total pressure for each of the three chord sizes. The cooling air flow requirements were also determined for a varying cooling air inlet temperature with a constant turbine inlet temperature. It was determined that allowable turbine inlet temperature increases with increasing chord for the convection cooled and transpiration cooled designs, however, the film-convection cooled designs did not have a significant change in turbine inlet temperature with chord. Author

N73-17810* AiResearch Mfg. Co., Torrance, Calif.
ANALYTICAL INVESTIGATION OF CHORD SIZE AND COOLING METHODS ON TURBINE BLADE COOLING REQUIREMENTS. BOOK 2: APPENDIXES J THROUGH M
 F. E. Faulkner Aug. 1971 334 p refs
 (Contract NAS3-13205)
 (NASA-CR-120882; AiResearch-71-7487-Bk-2) Avail: NTIS HC \$18.75 CSCL 21E

N73-17814* National Aeronautics and Space Administration.
 Lewis Research Center, Cleveland, Ohio.
TWO-DIMENSIONAL CASCADE TEST OF A HIGHLY LOADED, LOW-SOLIDITY, TANDEM AIRFOIL TURBINE ROTOR BLADE
 John F. Kline and Roy G. Stabe Washington Mar. 1973 19 p refs
 (NASA-TM-X-2729; E-7216) Avail: NTIS HC \$3.00 CSCL 21E

A tip region section of a low-solidity tandem airfoil blade for a turbine rotor was tested in a two-dimensional cascade tunnel at solidities of 0.736 and 0.912. Blade surface static pressures and blade exit total and static pressure and flow angle were surveyed. Blade surface velocities, wake shapes, and kinetic energy losses were analyzed and compared with values for 1.852 solidity tandem airfoil blading. Author

N73-17815* National Aeronautics and Space Administration.
 Lewis Research Center, Cleveland, Ohio.
EXPERIMENTAL INVESTIGATION OF AERODYNAMIC PERFORMANCE OF COOLED TURBINE VANES AT GAS-TO COLLANT-TEMPERATURE RATIOS UP TO 2.75
 Roy G. Stabe and Robert P. Dengler Washington Mar. 1973 33 p refs
 (NASA-TM-X-2733; E-7183) Avail: NTIS HC \$3.00 CSCL 21E

The results of an experimental investigation of the aerodynamic performance of two geometrically similar turbine vanes with different cooling designs are presented. The test vanes were a convection-film-cooled vanes and a transpiration-cooled vane. A solid uncooled vane with the same aerodynamic profile as the cooled vane was also tested. Four vanes of each type were tested in an annular sector cascade. The cooled vanes were tested at primary to coolant temperature ratios of 1.0, 1.75, and 2.75 and a coolant to primary pressure ratios of 1.0, 1.2, and 1.5. This resulted in coolant flows up to about 10 percent of the primary flow. The principal measurements were surveys of vane exit total pressure, total temperature, and static pressure. The report includes a brief description of the test facility and the design of the test vanes. The test results presented include weight flow and efficiency data for the uncooled vanes and coolant flow, primary flow, and efficiency data as functions of the cooling variables for the cooled vanes. Author

N73-17817* National Aeronautics and Space Administration.
 Lewis Research Center, Cleveland, Ohio.
PERFORMANCE COMPARISON OF THREE NORMAL-SHOCK POSITION SENSORS FOR MIXED-COMPRESSION INLETS
 Miles O. Dustin and Gary L. Cole Washington Mar. 1973 29 p refs
 (NASA-TM-X-2739; E-7197) Avail: NTIS HC \$3.00 CSCL 21E

The performance of three types of normal shock position sensors for supersonic inlets is described. All three sensors determined the shock position from the presence of the large pressure gradient at the normal shock location. The logic means for the three sensors were: (1) electronic, using pressure transducers, (2) fluidic, and (3) direct-coupled pressure switches. The sensors were evaluated in a two-dimensional, Mach 2.7, supersonic inlet having 30-percent internal supersonic area contraction. Both dynamic (from 1 to 80 Hz) and static tests were conducted. Author

N73-17822* Bendix Corp., South Bend, Ind. Energy Controls Div.
ULTRASONIC TRANSMISSION INVESTIGATIONS FOR TURBINE INLET GAS TEMPERATURE MEASUREMENT
 Final Report, Jan. 1971 - Jun. 1972
 C. J. Ahern, C. S. Longstreet, B. R. Teitelbaum, and W. E. Werts Sep. 1972 291 p refs
 (Contract F33615-71-C-1184; AF Proj. 3086)
 (AD-752602; ECD-863-18249-R; AFAPL-TR-72-75) Avail: NTIS CSCL 21/5

For advanced turbine engine propulsion systems, the need for an accurate, fast response turbine inlet gas temperature measurement is becoming more acute. One of the potentially promising techniques is the ultrasonic gas gap approach which utilizes the transit time of a high-frequency acoustic pulse to determine the average gas temperature along a path through the sound supporting medium. The objective of this Air Force sponsored research and development effort was to ascertain the potential and limitations of such an approach. Based on engine noise tests conducted on a J85-7 turbojet engine and both bench and burner rig evaluations of candidate transmission approaches, a matched piezoelectric transmitter/receiver pair operating in a gated RF mode within the carrier frequency range of 200 to 500 kHz was selected as a prototype engine sensor.

Author (GRA)

N73-17892* National Aeronautics and Space Administration.
 Washington, D.C.
THE NASTRAN PROGRAMMER'S MANUAL
 1972 2309 p
 (NASA-SP-223(01)) Avail: Computer Software Management and Information Center, Barrows Hall, University of Georgia, Athens, Georgia 30601 \$27.50 CSCL 20K

The computer programmer manual for NASTRAN is presented. The subjects discussed are: (1) NASTRAN programming fundamentals, (2) data block and table description, (3) subroutine descriptions, (4) module functional descriptions, (5) NASTRAN-operating systems interfaces, (6) modifications and additions to NASTRAN, and (7) NASTRAN support program. Author

N73-17900* Boeing Commercial Airplane Co., Seattle, Wash.
RESIDUAL STRESS ALLEVIATION OF AIRCRAFT METAL STRUCTURES REINFORCED WITH FILAMENTARY COMPOSITES Technical Report, Jul. 1971 - Mar. 1972
 J. B. Kelly and R. R. June Jan. 1973 95 p refs
 (Contract NAS1-8858)
 (NASA-CR-112207; D6-60136-4) Avail: NTIS HC \$6.75 CSCL 20K

Methods to eliminate or reduce residual stresses in aircraft metal structures reinforced by filamentary composites are discussed. Residual stress level reductions were achieved by modifying the manufacturing procedures used during adhesive bonding. The residual stress alleviation techniques involved various forms of mechanical constraint which were applied to the components during bonding. Nine methods were evaluated, covering a wide range in complexity. All methods investigated during the program affected the residual stress level. In general, residual stresses were reduced by 70 percent or more from the stress level produced by conventional adhesive bonding procedures. Author

N73-17916* Pratt and Whitney Aircraft, West Palm Beach, Fla. Research and Development Center.
EFFECT OF FUEL ZONING AND FUEL NOZZLE DESIGN ON POLLUTION EMISSIONS AT GROUND IDLE CONDITIONS FOR A DOUBLE-ANNULAR RAM-INDUCTION COMBUSTOR Final Report
 T. R. Clements Feb. 1973 61 p refs
 (Contract NAS3-11159)
 (NASA-CR-121094; FR-5295) Avail: NTIS HC \$5.25 CSCL 21B

An exhaust emission survey was conducted on a double-annular ram induction combustor at simulated ground idle conditions. The combustor was designed for a large augmented

turbofan engine capable of sustained flight speeds up to Mach 3.0. The emission levels of total hydrocarbon (THC), carbon monoxide, carbon dioxide, and nitric oxide were measured. The effects of fuel zoning, fuel nozzle design, and operating conditions (inlet temperature and reference Mach number) on the level of these emissions were determined. At an overall combustor fuel/air ratio of 0.007, fuel zoning reduced THC emissions by a factor of 5 to 1. The reduction in THC emissions is attributed to the increase in local fuel/air ratio provided by the fuel zoning. An alternative method of increasing fuel/air ratio would be to operate with larger-than-normal compressor overboard bleed; however, analysis on this method indicated an increase in idle fuel consumption of 20 percent. The use of air-atomizing nozzles reduced the THC emissions by 2 to 1. Author

N73-17921*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

MEASUREMENT OF GASEOUS EMISSIONS FROM AN AFTERBURNING TURBOJET ENGINE AT SIMULATED ALTITUDE CONDITIONS

Larry A. Diehl Washington Mar. 1973 20 p refs
(NASA-TM-X-2726; E-7238) Avail: NTIS HC \$3.00 CSCL 21B

Gaseous emissions from a J85-GE-13 turbojet engine were measured over a range of fuel-air ratios from idle to full afterburning and simulated altitudes from near sea-level to 12,800 meters (42,000 ft). Without afterburning, carbon monoxide and unburned hydrocarbon emissions were highest at idle and lowest at takeoff; oxides of nitrogen exhibited the reverse trend. With afterburning, carbon monoxide and unburned hydrocarbon emissions were greater than for military power. Carbon monoxide emissions were altitude dependent. Oxides of nitrogen emissions were less at minimum afterburning than at military power. For power levels above minimum afterburning, the oxides of nitrogen emissions were both power level and altitude dependent.

Author

N73-17991*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

NORTHWEST PASSAGE: TRADE ROUTE FOR LARGE AIR CUSHION VEHICLES

John L. Anderson Washington Mar. 1973 38 p refs
(NASA-TM-X-2684; E-7211) Avail: NTIS HC \$3.00 CSCL 01C


A conceptual vehicle and powerplant (10,000-ton) nuclear-powered air-cushion vehicle (ACV) that could open the Northwest Passage and other Arctic passages to commercial traffic is identified. The report contains a description of the conceptual vehicle, including the powerplant and operations, an assessment of technical feasibility, estimates of capital and operating costs, and identification of eligible cargo and markets. A comparison of the nuclear ACV freighter with nuclear container ships shows that for containerized or roll-on/roll-off cargo the ACV would provide greatly reduced transit time between North Atlantic and North Pacific ports at a competitive cost. Author

SUBJECT INDEX

AERONAUTICAL ENGINEERING / A Special Bibliography (Suppl. 31)

MAY 1973

Typical Subject Index Listing



The subject heading is a key to the subject content of the document. The Notation of Content (NOC), rather than the title of the document, is usually used to provide a more exact description of the subject matter. (In some cases AIAA uses the title in lieu of an NOC.) The report number helps to indicate the type of document cited (e.g., NASA report, translation, NASA contractor report). The accession number is located beneath and to the right of the Notation of Content, e.g., N73-11019. Under any one subject heading, the accession numbers are arranged in sequence with the /AA accession numbers appearing first.

A

AC GENERATORS

Superconducting a.c. machines - An approach to development. A73-20407

Aircraft power supply alternators with superconductive field windings, calculating specific weights and performance characteristics A73-20408

ACCELERATED LIFE TESTS

Fatigue tests to determine service life of catapult structure on C-2 aircraft [AD-752493] N73-17028

Evaluation of polyimide second stage rod seals at high temperatures to determine suitability for application to aircraft systems [NASA-CR-121124] N73-17592

ACCELERATION (PHYSICS)

Accelerations of points on a flight vehicle during short-period motion A73-20095

Relation between measured C.G. vertical accelerations and loads at T-tail of military aircraft N73-16904

ACOUSTIC MEASUREMENTS

Sound pressure level spectra measurements for four- and three-engine jet transport during concrete and grassy surface runup and flyover [SAE AIR 1216] A73-20693

Effect of sound absorbing exhaust duct on rear quadrant noise of J-65 engine and contributions of internal and jet components [NASA-TM-X-2718] N73-16011

Measurement of noise levels produced by Boeing 737 aircraft and correlation with local meteorological parameters including wind force and direction, temperature, and atmospheric pressure [FAA-RD-72-145] N73-16651

Development of theory of aerodynamic noise to analyze jet noise directivity and shear-noise contribution to overall jet noise [NASA-TN-D-7158] N73-16654

ACOUSTIC PROPAGATION

Analysis of internally generated sound in continuous materials. III - The momentum potential field description of fluctuating fluid motion as a basis for a unified theory of internally generated sound. A73-19097

ACOUSTIC PROPERTIES

Effect of sound absorbing exhaust duct on rear quadrant noise of J-65 engine and contributions of internal and jet components [NASA-TM-X-2718] N73-16011

Development of theory of aerodynamic noise to analyze jet noise directivity and shear-noise contribution to overall jet noise [NASA-TN-D-7158] N73-16654

ADAPTIVE CONTROL

Development of aircraft control systems based on operator performance, adaptive displays, and coupling of manual with automatic control [AD-751306] N73-16026

AERIAL PHOTOGRAPHY

The utility of a low flying aircraft or helicopter when collecting ground data for regional resource surveys. A73-21710

AERIAL RECONNAISSANCE

Image formation radiometers for blind landing, aerial reconnaissance over land and sea, horizon detection and detection of obstacles at sea A73-21087

AERODYNAMIC BRAKES

Performance prediction for deployable aerodynamic decelerators operating in supersonic wakes using gas dynamics analogy [AD-751982] N73-17266

AERODYNAMIC CHARACTERISTICS

The effect of the degree of turbulence on the aerodynamic characteristics of planar decelerating cascades A73-19197

Calculation of the aerodynamic characteristics of a rectangular wing with tip plates moving at a low subsonic speed in the proximity of a screen A73-20094

Aerodynamic characteristics of thin asymmetric wing profiles in supersonic flow A73-20487

Aerodynamic experimental investigation of annular cascade of gas turbine nozzle blade in subsonic and supersonic flow. A73-20939

Method for estimating aerodynamic characteristics of airfoils in compressible inviscid flow based on thickness and camber line parameters [ESDU-72024] N73-15981

Development of nonlinearized solution for aerodynamic characteristics of jet flap lifting surface with span-wise slot near trailing edge [NASA-CR-2190] N73-15986

Aerodynamic configurations and characteristics of airfoils designed to reduce formation of shock waves during supersonic flight [NASA-TT-F-749] N73-15987

Effects of various leading edge slat devices on static aerodynamic characteristics of twin-jet, swept wing fighter model [NASA-TN-D-6921] N73-15988

Method for estimating changes in lift curve, drag, tail lift, and downwash from wing of aircraft due to ground effect in incompressible flow [ESDU-72023] N73-15993

Numerical analysis of characteristics of rotary wing aircraft when considered as two coupled rigid bodies representing rotor and fuselage N73-15994

Development and application of computer programs for evaluating performance of powered-lift STOL aircraft to include static, takeoff, and landing performance [NASA-TM-X-62217] N73-16007

AERODYNAMIC COEFFICIENTS

SUBJECT INDEX

- Technique for defining aircraft performance model from limited flight test data and predicted aerodynamic and propulsion system characteristics [NASA-TN-D-7137] N73-16008
- Wind tunnel tests of full scale model of light aircraft to determine effects of configuration changes on aerodynamic characteristics [NASA-TN-D-6896] N73-16012
- Development of dynamic helicopter performance and control model based on force and rotor aerodynamic equations [AD-751460] N73-16022
- Development of analytical technique for computing performance of arbitrary jet-flapped wing with compensations for variations in wing geometry [NASA-CR-2179] N73-16982
- Wind tunnel tests of two dimensional wing model with leading edge slat and trailing edge flap [FAA-AU-862] N73-16984
- Computer program and users manual for calculating aerodynamic characteristics of wing-body combinations at subsonic and supersonic speeds [FFA-AU-635-PT-2] N73-16985
- Aerodynamic characteristics of biplane wing systems with emphasis on stall matching and induced camber effects which differ from monoplane wing N73-16987
- Conference on flight handling qualities and requirements N73-16993
- Revisions to V/STOL handling qualities based on criteria N73-16994
- Role of theory and calculations in refinement of flying qualities N73-16999
- Predicting flying qualities by wind tunnel tests N73-17000
- Effect of engine failure on aerodynamic characteristics of supersonic aircraft N73-17003
- Analysis of performance potential of buoyant systems and flexible structures for use with short haul passenger transport aircraft [NASA-TM-X-62168] N73-17014
- Development of methods for predicting performance characteristics of V/STOL aircraft - Vol. 1 [AD-752557] N73-17033
- Analytical techniques for predicting static and dynamic stability, control derivatives, and force and moment coefficients for V/STOL aircraft - Vol. 2 [AD-752558] N73-17034
- Computer program manual for analytical techniques to predict performance of V/STOL aircraft - Vol. 3 [AD-752559] N73-17035
- Literature survey of techniques for predicting performance of V/STOL aircraft - Vol. 4 [AD-752563] N73-17036
- Experimental determination of aerodynamic performance of cooled turbine vanes at gas to coolant temperature ratios up to 2.75 [NASA-TM-X-2733] N73-17815
- AERODYNAMIC COEFFICIENTS**
- German monograph - The steady and unsteady aerodynamic coefficients for the rolling motion of slender wings. A73-19578
- Multiple element airfoils optimized for maximum lift coefficient. A73-19956
- Procedure for determining rolling moment derivatives of aircraft due to rolling, yawing, and sideslip [ESDU-AIRCRAFT-06.01.00] N73-15978
- Contribution of straight-tapered swept wing to rolling moment derivative due to yawing under conditions where flow remains fully attached to surface [ESDU-72021] N73-15980
- Method for estimating aerodynamic characteristics of airfoils in compressible inviscid flow based on thickness and camber line parameters [ESDU-72024] N73-15981
- Effects of thickness and viscosity considerations on accuracy of aerodynamic coefficients determined for thin wings in inviscid flow conditions [ESDU-70011-AMEND-A] N73-15982
- Computerized aircraft simulation using aerodynamic coefficient table storage, checkout, and interpolation routines [NASA-TM-X-62229] N73-16983
- Mathematical models for gas surface interactions and calculating aerodynamic coefficients for simple geometric shapes and high Mach number flow past thin airfoils [AD-752245] N73-17278
- AERODYNAMIC CONFIGURATIONS**
- Contribution of straight-tapered swept wing to rolling moment derivative due to yawing under conditions where flow remains fully attached to surface [ESDU-72021] N73-15980
- Design modifications to improve static performance and lateral-directional dynamic stability of light aircraft N73-15996
- Optimized design of supersonic aircraft wing based on linear combination of weight of wing and aerodynamic drag minimization N73-15997
- Wind tunnel tests of full scale model of light aircraft to determine effects of configuration changes on aerodynamic characteristics [NASA-TN-D-6896] N73-16012
- Computer program and users manual for calculating aerodynamic characteristics of wing-body combinations at subsonic and supersonic speeds [FFA-AU-635-PT-2] N73-16985
- Aerodynamic characteristics of biplane wing systems with emphasis on stall matching and induced camber effects which differ from monoplane wing N73-16987
- Aerodynamic configuration and predicted performance of short takeoff aircraft for short haul passenger transportation [CRANFIELD-AERO-12-PT-1] N73-17019
- Analytical techniques for predicting static and dynamic stability, control derivatives, and force and moment coefficients for V/STOL aircraft - Vol. 2 [AD-752558] N73-17034
- Computer program manual for analytical techniques to predict performance of V/STOL aircraft - Vol. 3 [AD-752559] N73-17035
- Literature survey of techniques for predicting performance of V/STOL aircraft - Vol. 4 [AD-752563] N73-17036
- Concept of nuclear powered ground effect machine for commercial operations in Arctic regions [NASA-TM-X-2684] N73-17991
- AERODYNAMIC DRAG**
- Reduction of transonic drag for high performance aircraft by injecting air in rear of aircraft to alter transonic flow distribution on aft section [AD-751269] N73-15991
- AERODYNAMIC FORCES**
- A linearised theory of parachute opening dynamics. A73-21692
- AERODYNAMIC HEAT TRANSFER**
- Investigation of the heat transfer between the gas and casing in the area of the apertures between the nozzle diaphragm blades and guide vanes of turbines A73-20086
- AERODYNAMIC LOADS**
- Relation between measured C.G. vertical accelerations and loads at T-tail of military aircraft N73-16904
- Calculation of induced load effects on controllability of rigid and flexible aircraft N73-17004
- Acquisition and recording of structural flight load data for T-38 aircraft during normal training flights [AD-751968] N73-17025

SUBJECT INDEX

AIR TRAFFIC CONTROL

- Development of computer programs to calculate helicopter rotor tip vortex geometry in hover and forward flight to include calculation of rotor harmonic air loads
[AD-752628] N73-17032
- AERODYNAMIC NOISE**
Analysis of internally generated sound in continuous materials. III - The momentum potential field description of fluctuating fluid motion as a basis for a unified theory of internally generated sound. A73-19097
- The effect of nozzle inlet shape, lip thickness, and exit shape and size on subsonic jet noise. [AIAA PAPER 73-187] A73-20465
- Ducts, nacelles, power source components and cabin noise sources identified for aircraft noise control research, considering prerequisites for quiet operations [SAE AIR 1079] A73-20698
- Development of theory of aerodynamic noise to analyze jet noise directivity and shear-noise contribution to overall jet noise [NASA-TN-D-7158] N73-16654
- AERODYNAMIC STABILITY**
Nonlinear instability in flap-lag of rotor blades in forward flight [NASA-CR-114524] N73-17017
- AERODYNAMIC STALLING**
Wind tunnel tests to determine aircraft post-stall characteristics and to define boundaries for maintaining controlled aircraft flight [AD-751461] N73-16023
- AERODYNAMICS**
Mathematical model of nonstationary linear aeroautoelasticity A73-19468
- Role of theoretical studies of flight dynamics in relation to flight testing N73-17011
- AEROELASTICITY**
Mathematical model of nonstationary linear aeroautoelasticity A73-19468
- A computerized flutter solution procedure. A73-20214
- A summary of wind tunnel research on tilt-rotors from hover to cruise flight. [ONERA, TP NO. 1133] A73-21683
- Book - Aircraft structures for engineering students. A73-21839
- Influence of aeroelasticity on flight mechanics of flexible aircraft N73-16991
- Prediction of aeroelastic hinge moment effects on stability and control N73-17006
- Development of two dimensional theory for unsteady flow disturbances caused by aeroelastic deformation of thick wing at high subsonic speeds [NASA-CR-112114] N73-17258
- AERONAUTICAL ENGINEERING**
Wind tunnel facilities in India for subsonic, transonic and supersonic aeronautical R and D, describing design layouts, power requirements, operational functions and instrumentation A73-20249
- Technology advancement effects on military and commercial transport aircraft development and production costs, considering airframes, engines and avionics A73-20394
- Aeronautical research for 1971-1972 N73-16943
- AERONOMY**
Climatic changes resulting from upper atmosphere perturbation by supersonic aircraft exhausts [PB-212427] N73-16612
- AIR COOLING**
Analysis of effect of chord size and cooling methods on cooling requirements for air cooled turbine blades - Vol. 1 [NASA-CR-120882-BR-1] N73-17809
- Analysis of effect of chord size and cooling methods on cooling requirements for air cooled turbine blades - Vol. 2 [NASA-CR-120882] N73-17810
- AIR FLOW**
Performance tests to determine effects of increased rotor blade loading on gas turbine operation by reduction of rotor blade inlet diameter [NASA-TM-X-2730] N73-17039
- AIR JETS**
Wing tip vortex modification by tip-mounted upstream and downstream directed air jets, discussing wind tunnel test results A73-19193
- Turbulent intensity induced by wakes near secondary air jet inlet to gas turbine engine flame tube A73-19625
- AIR NAVIGATION**
Air traffic control by programmed navigation. A73-19349
- Air navigation development review covering air traffic, civil jet aircraft event, electronics progress and semiconductor revolution A73-21088
- Analysis of military helicopter formation flight techniques with emphasis on station keeping based on nominal point coordinate system [AD-751459] N73-16021
- Survey of Air Traffic Control Beacon System to determine occurrence of excessive interrogation signals within New York air control sector - Final Report [ECAC-PB-72-031] N73-16630
- AIR POLLUTION**
Climatic changes resulting from upper atmosphere perturbation by supersonic aircraft exhausts [PB-212427] N73-16612
- AIR TRAFFIC**
Air traffic volume prediction by 1985, determining passenger growth factors for terminal pairs A73-19348
- The capacity of a single-runway S.T.O.L./R.T.O.L. airport. A73-19352
- Air navigation development review covering air traffic, civil jet aircraft event, electronics progress and semiconductor revolution A73-21088
- AIR TRAFFIC CONTROL**
Systems for collision avoidance. A73-18899
- Ground based and airborne collision avoidance systems comparison, discussing interrogator/transponder concept, pilot warning indicator, and air traffic handling capacity and economics A73-18900
- The Aeronautical Satellite Programme - ATC aspects. A73-19141
- Collection and processing of data for the establishment of route charges. A73-19182
- Two-level computer system with main and display processors as scale working model for semiautomatic digital ATC en route control A73-19183
- Automated radar terminal systems /ARTS/. A73-19184
- Air traffic control by programmed navigation. A73-19349
- A precision position and time service for the air traffic of the future. A73-19350
- Area navigation systems integration with terminal ATC approach procedures, considering computerized data linkage with aircraft navigation system A73-19351
- Distributed ATC with traffic information in cockpit, noting potential for cost and risk reduction and capacity increase based on system performance evaluation A73-20600
- Survey of air traffic control system to determine areas within system susceptible to radio frequency interference effects [ECAC-PB-72-008] N73-16629

AIR TRANSPORTATION

SUBJECT INDEX

- Survey of Air Traffic Control Beacon System to determine occurrence of excessive interrogation signals within New York air control sector - Final Report
[ECAC-PR-72-031] N73-16630
- Problems of flight safety in air traffic control with increased volume of traffic
[DGLR-PAPER-72-038] N73-16632
- Theory of Kalman filtering and applications to real time tracking systems for air traffic control, satellite observation, and aircraft navigation
[AD-751485] N73-16634
- Research and development in advance electronics including applications to digital computers, air traffic control, and solid state physics
[AD-751308] N73-16758
- Operation and characteristics of primary radar system for air traffic control surveillance
[FAA-ED-02-1] N73-17163
- Receiver synthesis for air traffic moving target indicator with digital signal processing
[AD-751923] N73-17170
- Development of digital fast-time air traffic control conflict prediction models and application to specific air route traffic control situations
[UTIAS-TN-183] N73-17708
- AIR TRANSPORTATION**
- Air-terminal queues under time-dependent conditions.
A73-20375
- Russian book on passenger aircraft and air transport design covering technical and economic efficiency, airbus concept, weight and size problems and aft-mounted engine design
A73-20377
- Monograph - System analysis of the air-ground transportation interface problem at Bangkok International Airport.
A73-20382
- Mass air transportation development in Sweden, discussing flight scheduling, fare structure and quiet STOL aircraft introduction in 1980s
A73-20618
- Benefit-cost analysis of delay reduction with STOL.
[ASCE PREPRINT 1507] A73-21000
- AIRBORNE EQUIPMENT**
- Ground based and airborne collision avoidance systems comparison, discussing interrogator/transponder concept, pilot warning indicator, and air traffic handling capacity and economics
A73-18900
- Minimum performance standards - Airborne distance measuring equipment /DME/ operating within the radio-frequency range of 960-1215 megahertz.
A73-19575
- AIRBORNE/SPACEBORNE COMPUTERS**
- Computer-controlled software diagnosis of an airborne computer.
A73-20677
- AIRCRAFT**
- Pilot warning indicator system of intruder aircraft
[NASA-CASE-ERC-10226-1] N73-16483
- Computerized aircraft simulation using aerodynamic coefficient table storage, checkout, and interpolation routines
[NASA-TN-X-62229] N73-16983
- Laser scattering from curved aluminum and titanium aircraft surfaces in clear atmosphere
N73-17159
- AIRCRAFT ACCIDENTS**
- Crash of DC-8 aircraft during takeoff from Anchorage International Airport, Alaska on 27 Nov. 1970
[NTSB-AAR-72-12] N73-15999
- Incident involving collision of Boeing 727 aircraft with landing light system at Atlanta International Airport, Georgia on 21 Dec. 1971
[NTSB-AAR-72-22] N73-16000
- Bibliography of aircraft accident reports for US civil aviation operations during calendar year 1971
[NTSB-BA-72-6] N73-16001
- Bibliography of aircraft accident reports for US civil aviation operations during calendar year 1971
[NTSB-BA-72-7] N73-16002
- Aircraft accident involving DH-114 aircraft during attempted landing at Mercedita Airport, Puerto Rico on 24 June, 1972
[NTSB-AAR-72-34] N73-16004
- Aircraft accident involving DC-9 aircraft landing at Port Lauderdale, Florida airport in marginal weather conditions on 18 May, 1972
[NTSB-AAR-72-31] N73-16005
- Aircraft accident involving Beechcraft 18 aircraft on air taxi flight from Cleveland, Ohio airport on 22 June, 1972
[NTSB-AAR-72-33] N73-16006
- Investigation of disappearance of Cessna 310 aircraft on flight between Anchorage and Juneau, Alaska on 16 Oct. 1972
[NTSB-AAR-73-1] N73-17018
- AIRCRAFT BRAKES**
- Aircraft brake design and materials, considering thermal, mechanical, friction and wear characteristics of Be, steel, graphite and carbon composites
A73-21688
- AIRCRAFT CARRIERS**
- Analysis of simulated aircraft landing approach to aircraft carrier to determine display system requirements and to evaluate dangerous conditions
[AD-751076] N73-16635
- AIRCRAFT COMMUNICATION**
- The Aeronautical Satellite Programme - ATC aspects.
A73-19141
- Diversity techniques for airborne communications in presence of ground reflection multipath
[AD-752249] N73-17178
- AIRCRAFT CONTROL**
- A flight control system for STOL aircraft.
A73-20171
- Russian book - Control of aircraft and helicopter flight.
A73-20381
- Recent advances and applications in the prediction of pilot acceptance of aircraft flying qualities.
A73-20586
- Nonlinear programming in design of control systems with specified handling qualities.
A73-20588
- Analysis of controllability and steady-state response of parallel-redundant flight control systems
[NASA-CR-130354] N73-15998
- Development of aircraft control systems based on operator performance, adaptive displays, and coupling of manual with automatic control
[AD-751306] N73-16026
- Summaries of papers presented to conference concerning aircraft stability and control
[AGARD-CP-119] N73-16989
- Design criteria for satisfactory stability and control of military aircraft
N73-16996
- Influence of load and wing load distribution on lateral and longitudinal maneuverability of aircraft
N73-16998
- Prediction of aeroelastic hinge moment effects on stability and control
N73-17006
- Criteria for designing manual control system for military transport aircraft
N73-17007
- Influence of powered controls on stability and maneuverability
N73-17008
- Automatic method for determining stability and control derivatives from flight data
N73-17012
- Effect of control force gradient on VTOL visual hovering task
[NASA-TN-X-62230] N73-17015
- Application of modern control theory to design of optimum aircraft controllers
[NASA-TN-X-62208] N73-17016
- AIRCRAFT DESIGN**
- Russian book on passenger aircraft and air transport design covering technical and economic efficiency, airbus concept, weight and size problems and aft-mounted engine design
A73-20377

SUBJECT INDEX

AIRCRAFT PARTS

- Optimisation in construction of the Jaguar and other military aircraft. A73-20947
- A proposed design for the construction of a VTOL simulator A73-21249
- L-1011 TriStar - Design development. A73-21574
- Formula-one air racing history, aircraft designs and characteristics and low cost amateur constructions A73-21689
- Design modifications to improve static performance and lateral-directional dynamic stability of light aircraft N73-15996
- Optimized design of supersonic aircraft wing based on linear combination of weight of wing and aerodynamic drag minimization N73-15997
- Development of optimized aircraft structures based on vibratory strain energy distribution using damped forced response [AD-751809] N73-16027
- Aerodynamic characteristics of biplane wing systems with emphasis on stall matching and induced camber effects which differ from monoplane wing N73-16987
- Design criteria for satisfactory stability and control of military aircraft N73-16996
- Role of theory and calculations in refinement of flying qualities N73-16999
- Role of flight simulation in development of S-3 and P-14 aircraft N73-17001
- Criteria for designing manual control system for military transport aircraft N73-17007
- AIRCRAFT ENGINES**
- Development trends in aircraft-engine compressor design methods. III A73-19605
- Aircraft and land vehicle electric generators and motors, noting semiconductor application and cooling systems A73-20124
- TP-34 turbofan engines for S-3A and AX aircraft respectively, discussing technological development, and components and characteristic features A73-20350
- Technology and operation of Olympus engine cycle on Concorde aircraft, discussing chemical and noise pollution and economic factors A73-21687
- AIRCRAFT EQUIPMENT**
- Aircraft power supply alternators with superconductive field windings, calculating specific weights and performance characteristics A73-20408
- Analysis of aircraft fire warning system performance and procedures for eliminating false fire warning indications [AD-751346] N73-16025
- Design, development, and evaluation of flywheel powered hoist for personnel rescue missions conducted by helicopters [AD-751217] N73-16029
- Feasibility determination of using nematic liquid crystals for aircraft displays [AD-751667] N73-16748
- Simulation of flight in Concorde for improving characteristic of flight control system N73-17013
- AIRCRAFT FUELS**
- Vapor pressure of supersonic aircraft fuels A73-20014
- AIRCRAFT HAZARDS**
- Bibliography of aircraft accident reports for US civil aviation operations during calendar year 1971 [NTSB-BA-72-6] N73-16001
- Aircraft accident involving Beechcraft Queen Air aircraft on takeoff from Albuquerque, New Mexico airport on 19 May, 1972 [NTSB-AAR-72-32] N73-16003
- Doppler effect continuous wave radar for bird hazard detection and aircraft collision avoidance near airfields [AD-751985] N73-17168
- AIRCRAFT HYDRAULIC SYSTEMS**
- Hydraulic drive and control systems used for landing gear retraction and extension on Piper Cherokee Arrow and for main wheel braking on P-111 A73-19604
- AIRCRAFT INSTRUMENTS**
- Basic specification research for the main instruments of light aircraft A73-20248
- Russian book on onboard distance measuring systems for flight vehicles covering design of cw and pulsed devices, modulators, error analysis, noise, logic elements, etc A73-20378
- Development and characteristics of cathode ray tube vertical display system for use in all-weather air navigation aircraft [AD-752510] N73-17026
- AIRCRAFT LANDING**
- Incident involving collision of Boeing 727 aircraft with landing light system at Atlanta International Airport, Georgia on 21 Dec. 1971 [NTSB-AAR-72-22] N73-16000
- Aircraft accident involving DH-114 aircraft during attempted landing at Mercedita Airport, Puerto Rico on 24 June, 1972 [NTSB-AAR-72-34] N73-16004
- Aircraft accident involving DC-9 aircraft landing at Fort Lauderdale, Florida airport in marginal weather conditions on 18 May, 1972 [NTSB-AAR-72-31] N73-16005
- Flight simulator evaluations of flight control, flight path, and airspeed for approach and landing of powered lift jet short takeoff aircraft [NASA-TM-X-62203] N73-16014
- Bibliography of data on aircraft landings, instrument landings, approach control, glide path systems, display devices, and terminal facilities [AD-751800] N73-16024
- Analysis of simulated aircraft landing approach to aircraft carrier to determine display system requirements and to evaluate dangerous conditions [AD-751076] N73-16635
- Measurement of pilot performance during aircraft landing simulation to determine significance of vertical acceleration cues during approach and landing maneuver [NASA-TM-X-62236] N73-17020
- Design and development of stability augmentation system to eliminate coupling effects during landing of short takeoff aircraft [NASA-CR-130543] N73-17021
- Approach light properties for visual discrimination in pilot landing environment [NASA-TT-F-14667] N73-17710
- AIRCRAFT MAINTENANCE**
- Some UK military views on the development and procurement of AIDS, BIT and ATE for avionics. A73-20679
- AIRCRAFT MODELS**
- Role of free-flight models in aircraft research and development N73-17002
- AIRCRAFT NOISE**
- Ducts, nacelles, power source components and cabin noise sources identified for aircraft noise control research, considering prerequisites for quiet operations [SAE AIR 1079] A73-20698
- Effect of nozzle inlet shape, lip thickness, and exit shape and size on subsonic jet noise [NASA-TM-X-68182] N73-16655
- Open jet, wind tunnel operating within anechoic chamber for studying V/STOL noise mechanisms [AD-751857] N73-17235
- AIRCRAFT PARTS**
- Aircraft components solid film lubrication problems, discussing surface pretreatment, contamination susceptibility, corrosion prevention and aerosol applicability A73-19554
- Icing testing in the large Modane wind-tunnel on full-scale and reduced scale models A73-20244

AIRCRAFT PERFORMANCE

SUBJECT INDEX

Nondestructive inspection techniques for examining catapult and arresting gear structures on E-2 aircraft
[AD-752492] N73-17027

AIRCRAFT PERFORMANCE
L-1011 TriStar - Design development. A73-21574

Formula-one air racing history, aircraft designs and characteristics and low cost amateur constructions A73-21689

Procedure for determining rolling moment derivatives of aircraft due to rolling, yawing, and sideslip
[ESDU-AIRCRAFT-06.01.00] N73-15978

Method for estimating changes in lift curve, drag, tail lift, and downwash from wing of aircraft due to ground effect in incompressible flow
[ESDU-72023] N73-15993

Design modifications to improve static performance and lateral-directional dynamic stability of light aircraft N73-15996

Analysis of controllability and steady-state response of parallel-redundant flight control systems
[NASA-CR-130354] N73-15998

Development and application of computer programs for evaluating performance of powered-lift STOL aircraft to include static, takeoff, and landing performance
[NASA-TN-X-62217] N73-16007

Technique for defining aircraft performance model from limited flight test data and predicted aerodynamic and propulsion system characteristics
[NASA-TN-D-7137] N73-16008

Time vector technique for determining stability and control derivatives by simultaneous analysis of two maneuvers which differ by dependent control input
[NASA-TN-X-2722] N73-16010

Wind tunnel tests to determine aircraft post-stall characteristics and to define boundaries for maintaining controlled aircraft flight
[AD-751461] N73-16023

Analysis of control and power requirements for X-14 aircraft based on equations of motion with respect to set of axes fixed to aircraft
[NASA-CR-130760] N73-16988

Conference on flight handling qualities and requirements N73-16993

Performance tests of F-14 aircraft with jet blast deflector to determine effects of backflow of jet exhaust on aircraft launch operation
[AD-752018] N73-17023

Acquisition and recording of structural flight load data for T-38 aircraft during normal training flights
[AD-751968] N73-17025

Development of methods for predicting performance characteristics of V/STOL aircraft -Vol. 1
[AD-752557] N73-17033

AIRCRAFT RELIABILITY
The corrosion problem in aircraft structures. A73-20452

Book - Aircraft structures for engineering students. A73-21839

Influence of aircraft reliability regulations on STOL takeoff and landing performance
[NBB-UH-13-72-0] N73-16018

AIRCRAFT SAFETY
Systems for collision avoidance. A73-18899

Distributed ATC with traffic information in cockpit, noting potential for cost and risk reduction and capacity increase based on system performance evaluation A73-20600

AIRCRAFT SPECIFICATIONS
Basic specification research for the main instruments of light aircraft A73-20248

Formula-one air racing history, aircraft designs and characteristics and low cost amateur constructions A73-21689

AIRCRAFT STABILITY
Procedure for determining rolling moment derivatives of aircraft due to rolling, yawing, and sideslip
[ESDU-AIRCRAFT-06.01.00] N73-15978

Design modifications to improve static performance and lateral-directional dynamic stability of light aircraft N73-15996

Digital simulation language for flight dynamic tests, exemplified by Fiat G-91 and Dornier Do-31 aircraft
[BMVG-PBWT-72-21] N73-16019

Wind tunnel tests to determine aircraft post-stall characteristics and to define boundaries for maintaining controlled aircraft flight
[AD-751461] N73-16023

Development of automatic system for controlling aircraft under turbulent atmospheric conditions to provide pitch stabilization
[AD-751148] N73-16028

Analysis of control and power requirements for X-14 aircraft based on equations of motion with respect to set of axes fixed to aircraft
[NASA-CR-130760] N73-16988

Summaries of papers presented to conference concerning aircraft stability and control
[AGARD-CP-119] N73-16989

Relationship between mission requirements of piloted aircraft stability and maneuverability N73-16995

Design criteria for satisfactory stability and control of military aircraft N73-16996

Prediction of aeroelastic hinge moment effects on stability and control N73-17006

Influence of powered controls on stability and maneuverability N73-17008

Artificial stabilization to correct control deficiencies for high performance aircraft N73-17009

Automatic method for determining stability and control derivatives from flight data N73-17012

Design and development of stability augmentation system to eliminate coupling effects during landing of short takeoff aircraft
[NASA-CR-130543] N73-17021

AIRCRAFT STRUCTURES
The status of engineering knowledge concerning the damping of built-up structures. A73-19099

Second derivatives of the flutter velocity and the optimization of aircraft structures. A73-19952

Fatigue life of aircraft structures A73-20246

Russian book - Methods and equipment for in-flight aircraft strength tests. A73-20376

The corrosion problem in aircraft structures. A73-20452

Optimisation in construction of the Jaquar and other military aircraft. A73-20947

Book - Aircraft structures for engineering students. A73-21839

Applicability of composite materials in aircraft structure and engine design
[NASA-TT-P-14648] N73-16576

Random load fatigue of aircraft structures
[AGARD-CP-118] N73-16896

Fatigue life assessment of aircraft structures based on random or programmed fatigue tests and loadings N73-16897

Physical aspects of fatigue damage accumulation, including interaction and sequence effects N73-16899

AIRCRAFT WAKES
Analysis of aircraft trailing vortices to show formation and breakdown for various aircraft wing configurations
[HE/A-72-1] N73-17247

SUBJECT INDEX

APPROACH CONTROL

AIRFOIL PROFILES

Conformal mapping of two airfoil profiles symmetric with respect to real axis onto circles, using rational function power series
A73-20200

Pressure distribution measurement at surface of aerodynamic body by pneumatically activated inductive sensor
A73-21180

Aerodynamic configurations and characteristics of airfoils designed to reduce formation of shock waves during supersonic flight
[NASA-TT-P-749]
N73-15987

AIRFOILS

Conformal mapping for potential flow about airfoils with attached flap.
A73-19192

Flow in the wake of a cascade of oscillating airfoils.
A73-19954

Multiple element airfoils optimized for maximum lift coefficient.
A73-19956

Method for estimating aerodynamic characteristics of airfoils in compressible inviscid flow based on thickness and camber line parameters
[ESDU-72024]
N73-15981

Short takeoff aircraft lift augmentation and prevention of airflow separation on cambered elliptical airfoil section using circulation control
[AD-751045]
N73-15992

Air foils based on utilization of jet flap principle
[AD-751075]
N73-16283

Analysis of uniform jet flow around airfoil with separated shock wave at low supersonic velocities of incident flow
[NASA-TT-P-14813]
N73-17259

Two dimensional cascade test of highly loaded, low solidity, tandem airfoil turbine rotor blade
[NASA-TM-X-2729]
N73-17814

AIRFRAME MATERIALS

Welding airframe structures in titanium alloys using tensile loading as a means of overcoming distortion.
A73-21240

Crack growth characteristics of steel and structural failure of F-111 aircraft frame
[AD-752223]
N73-17024

AIRFRAMES

Development of optimized aircraft structures based on vibratory strain energy distribution using damped forced response
[AD-751809]
N73-16027

Nondestructive inspection techniques for examining catapult and arresting gear structures on E-2 aircraft
[AD-752492]
N73-17027

Fatigue tests to determine service life of catapult structure on C-2 aircraft
[AD-752493]
N73-17028

Design parameters for torsion of airframe sandwich strips having trapezoidal, rectangular, and triangular cross sections
[AD-752619]
N73-17029

Procedures for reducing residual stresses in aircraft metal structures reinforced by filamentary composites
[NASA-CR-112207]
N73-17900

AIRLINE OPERATIONS

Mass air transportation development in Sweden, discussing flight scheduling, fare structure and quiet STOL aircraft introduction in 1980s
A73-20618

Benefit-cost analysis of delay reduction with STOL.
[ASCE PREPRINT 1507]
A73-21000

Technical documentation to support V/STOL aircraft implementation and utilization based on short haul air transportation requirements - Vol. 2
[NASA-CR-114518]
N73-16009

Analysis of factors affecting development and operation of satellite airport system as method for relieving congestion at metropolitan airports
N73-16216

AIRPLANE PRODUCTION COSTS

Technology advancement effects on military and commercial transport aircraft development and production costs, considering airframes, engines and avionics
A73-20394

AIRPORT LIGHTS

Incident involving collision of Boeing 727 aircraft with landing light system at Atlanta International Airport, Georgia on 21 Dec. 1971
[NTSB-AAR-72-22]
N73-16000

AIRPORT PLANNING

The capacity of a single-runway S.T.O.L./R.T.O.L. airport.
A73-19352

Monograph - System analysis of the air-ground transportation interface problem at Bangkok International Airport.
A73-20382

Analysis of factors affecting development and operation of satellite airport system as method for relieving congestion at metropolitan airports
N73-16216

Economic feasibility analysis on San Francisco rapid transit system extension to serve airport
[PB-212456]
N73-16978

AIRPORTS

Requirements, basic principles of operation, design, construction, and maintenance of thermal fog dispersal system for airport applications
[FAA-RD-72-138]
N73-16222

ALASKA

Investigation of disappearance of Cessna 310 aircraft on flight between Anchorage and Juneau, Alaska on 16 Oct. 1972
[NTSB-AAR-73-1]
N73-17018

ALGORITHMS

Flight vehicle equations of motion with variable information, noting flight control algorithm for random variable with given probability
A73-20077

Development of digital fast-time air traffic control conflict prediction models and application to specific air route traffic control situations
[UTIAS-TN-183]
N73-17708

ALIGNMENT

The pre-flight handling of inertial navigation systems.
A73-19347

ALL-WEATHER AIR NAVIGATION

Development and characteristics of cathode ray tube vertical display system for use in all-weather air navigation aircraft
[AD-752510]
N73-17026

ALPHA PARTICLES

Predicting light flashes due to alpha-particle flux on SST planes.
A73-20157

ALUMINUM ALLOYS

Evaluation of aluminum 1 by 12 ft extruded light-duty landing mat with symmetrical butt-type end connectors
[AD-752079]
N73-17233

ANECHOIC CHAMBERS

French project of anechoic chamber with wind tunnel for studying jets, turbojets blowers, helicopter rotors and V/STOL aircraft
A73-21529

ANGLE OF ATTACK

A flight control system for STOL aircraft.
A73-20171

ANGULAR VELOCITY

System for in-flight recording of the rotational speed of the turbine of a jet engine
A73-20546

ANNULAR NOZZLES

Calculation of the potential flow about axisymmetrical fuselages, annular profiles, and propulsion system inlets
A73-19205

Aerodynamic experimental investigation of annular cascade of gas turbine nozzle blade in subsonic and supersonic flow.
A73-20939

APPROACH CONTROL

A precision position and time service for the air traffic of the future.
A73-19350

APPROACH INDICATORS

- Area navigation systems integration with terminal ATC approach procedures, considering computerized data linkage with aircraft navigation system A73-19351
- A flight control system for STOL aircraft. A73-20171
- Incident involving collision of Boeing 727 aircraft with landing light system at Atlanta International Airport, Georgia on 21 Dec. 1971 [NTSB-AAR-72-22] N73-16000
- Flight simulator evaluations of flight control, flight path, and airspeed for approach and landing of powered lift jet short takeoff aircraft [NASA-TM-X-62203] N73-16014
- Bibliography of data on aircraft landings, instrument landings, approach control, glide path systems, display devices, and terminal facilities [AD-751800] N73-16024
- Analysis of simulated aircraft landing approach to aircraft carrier to determine display system requirements and to evaluate dangerous conditions [AD-751076] N73-16635
- Measurement of pilot performance during aircraft landing simulation to determine significance of vertical acceleration cues during approach and landing maneuver [NASA-TM-X-62236] N73-17020
- APPROACH INDICATORS**
- Approach light properties for visual discrimination in pilot landing environment [NASA-TT-F-14667] N73-17710
- AREA NAVIGATION**
- A precision position and time service for the air traffic of the future. A73-19350
- Area navigation systems integration with terminal ATC approach procedures, considering computerized data linkage with aircraft navigation system A73-19351
- ATMOSPHERIC TURBULENCE**
- Development of automatic system for controlling aircraft under turbulent atmospheric conditions to provide pitch stabilization [AD-751148] N73-16028
- AUTOMATIC CONTROL**
- Two-level computer system with main and display processors as scale working model for semiautomatic digital ATC en route control A73-19183
- Automated radar terminal systems /ARTS/. A73-19184
- Mathematical model of nonstationary linear aeroautoelasticity A73-19468
- Computer-controlled software diagnosis of an airborne computer. A73-20677
- Automatic calculation of runway visual range on airdromes N73-16599
- AUTOMATIC FLIGHT CONTROL**
- Russian book - Control of aircraft and helicopter flight. A73-20381
- AUTOMATIC PILOTS**
- Accelerations of points on a flight vehicle during short-period motion A73-20095
- Development of automatic system for controlling aircraft under turbulent atmospheric conditions to provide pitch stabilization [AD-751148] N73-16028
- AUTOMATIC TEST EQUIPMENT**
- Russian book - Methods and equipment for in-flight aircraft strength tests. A73-20376
- Some UK military views on the development and procurement of AIDS, BIT and ATE for avionics. A73-20679
- AUTOMATE** - A self-contained automatic test system. A73-20680
- Test techniques for advanced avionics displays. A73-20683

SUBJECT INDEX

- Automatic test equipment support software definition and development, describing language, translator and operating system as elements of closed loop ATE system A73-20687
- Test programs design for versatile avionics shop test system /VAST/, discussing compiler problems alleviation by on-station program patching capability A73-20688
- AUXILIARY POWER SOURCES**
- Performance of auxiliary power systems for advanced Army rotary wing aircraft [AD-751854] N73-17046
- AVIONICS**
- Calculation of the reliability of electronic components in an 'aeronautics' environment shaped by the operational service routines of onboard equipment devices used by Air France A73-19403
- Some UK military views on the development and procurement of AIDS, BIT and ATE for avionics. A73-20679
- AUTOMATE** - A self-contained automatic test system. A73-20680
- Test techniques for advanced avionics displays. A73-20683
- Test programs design for versatile avionics shop test system /VAST/, discussing compiler problems alleviation by on-station program patching capability A73-20688
- Air navigation development review covering air traffic, civil jet aircraft event, electronics progress and semiconductor revolution A73-21088
- AXISYMMETRIC BODIES**
- Calculation of the potential flow about axisymmetrical fuselages, annular profiles, and propulsion system inlets A73-19205
- B**
- BASE PRESSURE**
- Reduction of transonic drag for high performance aircraft by injecting air in rear of aircraft to alter transonic flow distribution on aft section [AD-751269] N73-15991
- BEAMS (SUPPORTS)**
- The status of engineering knowledge concerning the damping of built-up structures. A73-19099
- BEECHCRAFT AIRCRAFT**
- Aircraft accident involving Beechcraft Queen Air aircraft on takeoff from Albuquerque, New Mexico airport on 19 May, 1972 [NTSB-AAR-72-32] N73-16003
- BEECHCRAFT 18 AIRCRAFT**
- Aircraft accident involving Beechcraft 18 aircraft on air taxi flight from Cleveland, Ohio airport on 22 June, 1972 [NTSB-AAR-72-33] N73-16006
- BIBLIOGRAPHIES**
- Bibliography of aircraft accident reports for US civil aviation operations during calendar year 1971 [NTSB-BA-72-7] N73-16002
- BIPLANES**
- Aerodynamic characteristics of biplane wing systems with emphasis on stall matching and induced camber effects which differ from monoplane wing A73-16987
- BIRDS**
- Doppler effect continuous wave radar for bird hazard detection and aircraft collision avoidance near airfields [AD-751985] N73-17168
- BLAST DEFLECTORS**
- Performance tests of F-14 aircraft with jet blast deflector to determine effects of backflow of jet exhaust on aircraft launch operation [AD-752018] N73-17023
- BLIND LANDING**
- Image formation radiometers for blind landing, aerial reconnaissance over land and sea, horizon detection and detection of obstacles at sea A73-21087

SUBJECT INDEX

COLLISION AVOIDANCE

BLOWING

Acoustic results obtained with upper-surface-blowing lift-augmentation systems.
A73-20458

BODY-WING CONFIGURATIONS

Computer program and users manual for calculating aerodynamic characteristics of wing-body combinations at subsonic and supersonic speeds [FPA-AU-635-PT-2]
N73-16985

BOEING 727 AIRCRAFT

Incident involving collision of Boeing 727 aircraft with landing light system at Atlanta International Airport, Georgia on 21 Dec. 1971 [NTSB-AAR-72-22]
N73-16000

BOEING 737 AIRCRAFT

Measurement of noise levels produced by Boeing 737 aircraft and correlation with local meteorological parameters including wind force and direction, temperature, and atmospheric pressure [FAA-RD-72-145]
N73-16651

BONDING

Procedures for reducing residual stresses in aircraft metal structures reinforced by filamentary composites [NASA-CR-112207]
N73-17900

BOUNDARY LAYER FLOW

The effect of the degree of turbulence on the aerodynamic characteristics of planar decelerating cascades
A73-19197

Short takeoff aircraft lift augmentation and prevention of airflow separation on cambered elliptical airfoil section using circulation control [AD-751045]
N73-15992

BOUNDARY LAYER SEPARATION

Boundary-layer separation on rotating blades in forward flight.
A73-19955

Three dimensional boundary layer separation and shock wave generation in flow field of supersonic conical intake mounted on fuselage side [ARL/HE-137]
N73-16981

BREATHING APPARATUS

Influence of liquid oxygen on chromate coated aluminum tubing of breathing apparatus [AD-752030]
N73-17661

BUFFETING

Wind tunnel tests to predict full scale aircraft buffet loads during buffet boundary penetration using scale flutter model of fighter aircraft with variable sweep wings [NASA-TN-D-7066]
N73-16905

C

C-2 AIRCRAFT

Fatigue tests to determine service life of catapult structure on C-2 aircraft [AD-752493]
N73-17028

C-160 AIRCRAFT

Statistical evaluation of meteorological ice formation parameters: free moisture content, drop diameters, and temperature, obtained from Transall C-160 flights [HBB-UH-11-72-0]
N73-16016

CAMBERED WINGS

Conically cambered triangular wings with reflex spanwise curvature.
A73-20938

CARBON MONOXIDE

Analysis of gaseous emissions from J-85 engine at various fuel-air ratios, engine speeds, and simulated altitude conditions [NASA-TN-X-2726]
N73-17921

CARBON STEELS

Random fatigue tests on normalized carbon steel with 0.7 percent carbon
N73-16902

CASCADE FLOW

The effect of the degree of turbulence on the aerodynamic characteristics of planar decelerating cascades
A73-19197

Flow in the wake of a cascade of oscillating airfoils.
A73-19954

Aerodynamic experimental investigation of annular cascade of gas turbine nozzle blade in subsonic and supersonic flow.
A73-20939

Static and wind tunnel tests to determine performance of four cowl cascade thrust reverser configurations at forward velocity [NASA-TN-X-2665]
N73-16773

CASCADE WIND TUNNELS

Cascade tests of highly loaded multistage fan drive turbine configurations [NASA-CR-21711]
N73-16778

Two dimensional cascade test of highly loaded, low solidity, tandem airfoil turbine rotor blade [NASA-TN-X-2729]
N73-17814

CATHODE RAY TUBES

Development and characteristics of cathode ray tube vertical display system for use in all-weather air navigation aircraft [AD-752510]
N73-17026

CENTRAL PROCESSING UNITS

Two-level computer system with main and display processors as scale working model for semiautomatic digital ATC en route control
A73-19183

CENTRIFUGAL COMPRESSORS

Development trends in aircraft-engine compressor design methods. III
A73-19605

CESSNA AIRCRAFT

Investigation of disappearance of Cessna 310 aircraft on flight between Anchorage and Juneau, Alaska on 16 Oct. 1972 [NTSB-AAR-73-1]
N73-17018

CH-47 HELICOPTER

Effect of dynamic absorbers and damping on noise generated by CH-47 helicopter rotor transmission [AD-752579]
N73-17031

CHEMICAL REACTIONS

Analytical predictions of emissions from and within an Allison J-33 combustor.
A73-21670

CIVIL AVIATION

Formula-one air racing history, aircraft designs and characteristics and low cost amateur constructions
A73-21689

Book - Civil aviation development - A policy and operations analysis.
A73-21837

Bibliography of aircraft accident reports for US civil aviation operations during calendar year 1971 [NTSB-BA-72-6]
N73-16001

Bibliography of aircraft accident reports for US civil aviation operations during calendar year 1971 [NTSB-BA-72-7]
N73-16002

CLIMATOLOGY

Climatic changes resulting from upper atmosphere perturbation by supersonic aircraft exhausts [PB-212427]
N73-16612

CLIMBING FLIGHT

Glider soaring flight energy budget analysis, discussing rate of climb indicator error compensation
A73-21656

CLOUDS (METEOROLOGY)

Requirements, basic principles of operation, design, construction, and maintenance of thermal fog dispersal system for airport applications [FAA-RD-72-138]
N73-16222

COCKPIT SIMULATORS

Summary of conference on flight simulation
N73-16992

COCKPITS

Problems of cockpit environment
N73-16990

COLLISION AVOIDANCE

Systems for collision avoidance.
A73-18899

Ground based and airborne collision avoidance systems comparison, discussing interrogator/transponder concept, pilot warning indicator, and air traffic handling capacity and economics
A73-18900

COMBUSTION CHAMBERS

SUBJECT INDEX

- Doppler effect continuous wave radar for bird hazard detection and aircraft collision avoidance near airfields
[AD-751985] N73-17168
- COMBUSTION CHAMBERS**
- Emissions from and within an Allison J-33 combustor.
A73-20359
- Analytical predictions of emissions from and within an Allison J-33 combustor.
A73-21670
- Analysis of thermal failures in combustion chambers of J-57 jet engine and system for detecting burn-through prior to engine case rupture
[FAA-NA-72-92] N73-16772
- Tests of high pressure combustor exhaust emissions with improved air-atomizing and conventional pressure-atomizing fuel nozzle
[NASA-TN-D-7154] N73-16929
- Effect of fuel zoning and fuel nozzle design on exhaust pollution emissions at ground idle conditions for double-annular ram-induction combustor for turbofan engines
[NASA-CR-121094] N73-17916
- COMBUSTION EFFICIENCY**
- Comparison of combustion characteristics of ASTM A-1, propane, and natural gas fuels in annular turbojet combustor
[NASA-TN-D-7135] N73-16771
- COMBUSTION PRODUCTS**
- Emissions from and within an Allison J-33 combustor.
A73-20359
- Analytical predictions of emissions from and within an Allison J-33 combustor.
A73-21670
- Modification of jet engine fuels to reduce emissions of nitrogen oxides from jet aircraft turbine engines
[AD-752581] N73-17803
- Analysis of gaseous emissions from J-85 engine at various fuel-air ratios, engine speeds, and simulated altitude conditions
[NASA-TN-X-2726] N73-17921
- COMMERCIAL AIRCRAFT**
- Crew station lighting - Commercial aircraft.
[SAE ARP 1161] A73-20692
- Technical documentation to support V/STOL aircraft implementation and utilization based on short haul air transportation requirements - Vol. 2
[NASA-CR-114518] N73-16009
- Design principles of gas turbine and piston engines for commercial aircraft
[AD-751510] N73-16783
- COMMUNICATION SATELLITES**
- The Aeronautical Satellite Programme - ATC aspects.
A73-19141
- COMPETITION**
- Formula-one air racing history, aircraft designs and characteristics and low cost amateur constructions
A73-21689
- COMPONENT RELIABILITY**
- Calculation of the reliability of electronic components in an 'aeronautics' environment shaped by the operational service routines of onboard equipment devices used by Air France
A73-19403
- COMPOSITE STRUCTURES**
- Procedures for reducing residual stresses in aircraft metal structures reinforced by filamentary composites
[NASA-CR-112207] N73-17900
- COMPRESSIBLE FLOW**
- Method for estimating aerodynamic characteristics of airfoils in compressible inviscid flow based on thickness and camber line parameters
[ESDU-72024] N73-15981
- COMPRESSOR EFFICIENCY**
- Flow characteristics of tandem bladed compressor stators at various inlet incidence angles
[NASA-TN-X-2734] N73-16986
- COMPUTER PROGRAMMING**
- Computerized aircraft simulation using aerodynamic coefficient table storage, checkout, and interpolation routines
[NASA-TN-X-62229] N73-16983
- COMPUTER PROGRAMS**
- Air traffic control by programmed navigation.
A73-19349
- Recent advances and applications in the prediction of pilot acceptance of aircraft flying qualities.
A73-20586
- Automatic test equipment support software definition and development, describing language, translator and operating system as elements of closed loop ATE system
A73-20687
- Test programs design for versatile avionics shop test system /VAST/, discussing compiler problems alleviation by on-station program patching capability
A73-20688
- Gas turbine engine transient performance presentation for digital computer programs.
[SAE ARP 1257] A73-20696
- Development and application of computer programs for evaluating performance of powered-lift STOL aircraft to include static, takeoff, and landing performance
[NASA-TN-X-62217] N73-16007
- Development of computer program for calculating flow field resulting from sonic boom focusing
[NASA-CR-2127] N73-16013
- User manual and source listings for computer programs to solve problems in analysis of in-flight thrust reversers
[AD-751526] N73-16785
- Computer programmer manual for NASA structural analysis program
[NASA-SP-223 (01)] N73-17892
- COMPUTER SYSTEMS PROGRAMS**
- Computer-controlled software diagnosis of an airborne computer.
A73-20677
- Automatic test equipment support software definition and development, describing language, translator and operating system as elements of closed loop ATE system
A73-20687
- Test programs design for versatile avionics shop test system /VAST/, discussing compiler problems alleviation by on-station program patching capability
A73-20688
- COMPUTER TECHNIQUES**
- Two-level computer system with main and display processors as scale working model for semiautomatic digital ATC en route control
A73-19183
- Automated radar terminal systems /ARTS/.
A73-19184
- Area navigation systems integration with terminal ATC approach procedures, considering computerized data linkage with aircraft navigation system
A73-19351
- A computerized flutter solution procedure.
A73-20214
- AUTOMATE - A self-contained automatic test system.**
A73-20680
- COMPUTERIZED DESIGN**
- Nonlinear programming in design of control systems with specified handling qualities.
A73-20588
- COMPUTERIZED SIMULATION**
- Computerized simulation of shrouded propeller low field in cross flow using vortex lattice models
[AD-751463] N73-16274
- Computerized aircraft simulation using aerodynamic coefficient table storage, checkout, and interpolation routines
[NASA-TN-X-62229] N73-16983
- CONCORDE AIRCRAFT**
- Technology and operation of Olympus engine cycle on Concorde aircraft, discussing chemical and noise pollution and economic factors
A73-21687
- Simulation of flight in Concorde for improving characteristic of flight control system
N73-17013
- CONFERENCES**
- Welding and fabrication of non-ferrous metals; Proceedings of the International Conference, Eastbourne, Sussex, England, May 2, 3, 1972. Volume 1.
A73-21235
- Random load fatigue of aircraft structures
[AGARD-CP-118] N73-16896

SUBJECT INDEX

DISPLAY DEVICES

Summaries of papers presented to conference concerning aircraft stability and control [AGARD-CP-119] N73-16989

Papers presented at conference on lightning and static electricity [AD-752551] N73-17552

CONFORMAL MAPPING

Conformal mapping for potential flow about airfoils with attached flap. A73-19192

Conformal mapping of two airfoil profiles symmetric with respect to real axis onto circles, using rational function power series A73-20200

CONICAL CAMBER

Conically cambered triangular wings with reflex spanwise curvature. A73-20938

CONSTRUCTION MATERIALS

Welding airframe structures in titanium alloys using tensile loading as a means of overcoming distortion. A73-21240

CONTINUOUS WAVE RADAR

Doppler effect continuous wave radar for bird hazard detection and aircraft collision avoidance near airfields [AD-751985] N73-17168

CONTRACT MANAGEMENT

Statistical expectation application to risk density functions and fee/incentive-element relationships for contract incentive structuring, considering C-5A procurement. A73-20958

CONTROL THEORY

Development of aircraft control systems based on operator performance, adaptive displays, and coupling of manual with automatic control [AD-751306] N73-16026

Application of modern control theory to design of optimum aircraft controllers [NASA-TN-X-62208] N73-17016

CONTROLLABILITY

Nonlinear programming in design of control systems with specified handling qualities. A73-20588

Calculation of induced load effects on controllability of rigid and flexible aircraft N73-17004

CONVERGENT NOZZLES

The effect of nozzle inlet shape, lip thickness, and exit shape and size on subsonic jet noise. [AIAA PAPER 73-187] A73-20465

COOLING SYSTEMS

Aircraft and land vehicle electric generators and motors, noting semiconductor application and cooling systems A73-20124

Experimental determination of aerodynamic performance of cooled turbine vanes at gas to coolant temperature ratios up to 2.75 [NASA-TN-X-2733] N73-17815

CORROSION PREVENTION

Aircraft components solid film lubrication problems, discussing surface pretreatment, contamination susceptibility, corrosion prevention and aerosol applicability A73-19554

CORROSION RESISTANCE

The corrosion problem in aircraft structures. A73-20452

COST ANALYSIS

Benefit-cost analysis of delay reduction with STOL. [ASCE PREPRINT 1507] A73-21000

COST REDUCTION

A description of two low cost turbo-compressors built for powered lift research. A73-19942

Distributed ATC with traffic information in cockpit, noting potential for cost and risk reduction and capacity increase based on system performance evaluation A73-20600

CRACK PROPAGATION

Crack growth study and effects of change in spectrum severity and shape on fatigue behavior under random loading N73-16898

Fatigue crack propagation under flight simulation loading at 10, 1, and 0.1 cycles per second N73-16900

Crack growth characteristics of steel and structural failure of F-111 aircraft frame [AD-752223] N73-17024

CRACKING (FRACTURING)

Aircraft accident involving Beechcraft 18 aircraft on air taxi flight from Cleveland, Ohio airport on 22 June, 1972 [NTSB-AAR-72-33] N73-16006

CRUISING FLIGHT

Hypersonic flows in large-scale inlet models. A73-19189

D

DAMPING TESTS

Applicability of composite materials in aircraft structure and engine design [NASA-TT-P-14648] N73-16576

DATA PROCESSING

Collection and processing of data for the establishment of route charges. A73-19182

DC 8 AIRCRAFT

Crash of DC-8 aircraft during takeoff from Anchorage International Airport, Alaska on 27 Nov. 1970 [NTSB-AAR-72-12] N73-15999

DC 9 AIRCRAFT

Aircraft accident involving DC-9 aircraft landing at Fort Lauderdale, Florida airport in marginal weather conditions on 18 May, 1972 [NTSB-AAR-72-31] N73-16005

DE HAVILLAND AIRCRAFT

Aircraft accident involving DH-114 aircraft during attempted landing at Mercedita Airport, Puerto Rico on 24 June, 1972 [NTSB-AAR-72-34] N73-16004

DELTA WINGS

Conically cambered triangular wings with reflex spanwise curvature. A73-20938

Angles of attack for shock wave detachment from sharp leading edge of five delta wing models with flat compression surfaces [AD-752206] N73-17271

DETONATION

Sonic boom nitroglycerin resistance noting shock simulation and sonic boom effect on detonation [ISL-14/72] N73-16658

DIAGNOSIS

Computer-controlled software diagnosis of an airborne computer. A73-20677

DIGITAL COMPUTERS

Research and development in advance electronics including applications to digital computers, air traffic control, and solid state physics [AD-751308] N73-16758

DIGITAL RADAR SYSTEMS

Receiver synthesis for air traffic moving target indicator with digital signal processing [AD-751923] N73-17170

DIGITAL SIMULATION

Digital simulation language for flight dynamic tests, exemplified by Fiat G-91 and Dornier Do-31 aircraft [BNVG-PBWT-72-21] N73-16019

DISPLAY DEVICES

Two-level computer system with main and display processors as scale working model for semiautomatic digital ATC en route control A73-19183

Automated radar terminal systems /ARTS/. A73-19184

Moving radiography for photographic recording and display of transient or cyclic motion, emphasizing application to aircraft gas turbines under dynamic conditions A73-20451

Test techniques for advanced avionics displays. A73-20683

Development of aircraft control systems based on operator performance, adaptive displays, and coupling of manual with automatic control [AD-751306] N73-16026

DISTANCE MEASURING EQUIPMENT

- Feasibility determination of using nematic liquid crystals for aircraft displays
[AD-751667] N73-16748
- Development and characteristics of cathode ray tube vertical display system for use in all-weather air navigation aircraft
[AD-752510] N73-17026
- Analysis of fixed base simulator tests to determine effects of two horizontal display panel locations and three map orientations on manual piloting performance
[NASA-TN-X-62198] N73-17223
- ### DISTANCE MEASURING EQUIPMENT
- Minimum performance standards - Airborne distance measuring equipment /DME/ operating within the radio-frequency range of 960-1215 megahertz.
A73-19575
- Russian book on onboard distance measuring systems for flight vehicles covering design of cw and pulsed devices, modulators, error analysis, noise, logic elements, etc
A73-20378
- ### DISTORTION
- Focusing effects of distortion of near sonic shocks by weakly turbulent layers with random temperature and pressure variations
[AD-752472] N73-17279
- ### DRAG REDUCTION
- Reduction of transonic drag for high performance aircraft by injecting air in rear of aircraft to alter transonic flow distribution on aft section
[AD-751269] N73-15991
- ### DYNAMIC RESPONSE
- Moving radiography for photographic recording and display of transient or cyclic motion, emphasizing application to aircraft gas turbines under dynamic conditions
A73-20451
- Mathematical model for tracked air cushion vehicle and guideway to determine vertical dynamic response of vehicle and guideway system to high speed vehicle passage
N73-15995
- ### DYNAMIC STRUCTURAL ANALYSIS
- Crack growth characteristics of steel and structural failure of F-111 aircraft frame
[AD-752223] N73-17024

E

- ### E-2 AIRCRAFT
- Nondestructive inspection techniques for examining catapult and arresting gear structures on E-2 aircraft
[AD-752492] N73-17027
- ### EARTH RESOURCES SURVEY AIRCRAFT
- The utility of a low flying aircraft or helicopter when collecting ground data for regional resource surveys.
A73-21710
- ### ECONOMIC ANALYSIS
- Air traffic volume prediction by 1985, determining passenger growth factors for terminal pairs
A73-19348
- ### ECONOMIC FACTORS
- Technology advancement effects on military and commercial transport aircraft development and production costs, considering airframes, engines and avionics
A73-20394
- Mass air transportation development in Sweden, discussing flight scheduling, fare structure and quiet STOL aircraft introduction in 1980s
A73-20618
- Technology and operation of Olympus engine cycle on Concorde aircraft, discussing chemical and noise pollution and economic factors
A73-21687
- Economic feasibility analysis on San Francisco rapid transit system extension to serve airport
[PB-212456] N73-16978
- ### EJECTORS
- Semiempirical methods for designing ejectors for various applications
N73-17252
- ### ELASTIC DAMPING
- Damping configurations that have a stabilizing influence on nonconservative systems.
A73-19088

SUBJECT INDEX

- ### ELECTRIC GENERATORS
- Aircraft and land vehicle electric generators and motors, noting semiconductors application and cooling systems
A73-20124
- ### ELECTRIC MOTORS
- Aircraft and land vehicle electric generators and motors, noting semiconductors application and cooling systems
A73-20124
- ### ELECTRONIC EQUIPMENT TESTS
- Test programs design for versatile avionics shop test system /VAST/, discussing compiler problems alleviation by on-station program patching capability
A73-20688
- ### ENERGY BUDGETS
- Glider soaring flight energy budget analysis, discussing rate of climb indicator error compensation
A73-21656
- ### ENGINE DESIGN
- Lubricants thermophysical properties effects on gas turbine engine design, considering thermal stability, vapor pressure, autoignition, load capacity and bearing life
A73-19563
- Development trends in aircraft-engine compressor design methods. III
A73-19605
- A description of two low cost turbo-compressors, built for powered lift research.
A73-19942
- TF-34 turbofan engines for S-3A and AX aircraft respectively, discussing technological development, and components and characteristic features
A73-20350
- Designing turbomachine blades for forced vibrations under various excitation conditions
A73-20503
- Applicability of composite materials in aircraft structure and engine design
[NASA-TT-P-14648] N73-16576
- Performance tests to determine effects of reducing turbine blade thickness on turbine engine performance
[NASA-TN-D-7128] N73-16776
- Design principles of gas turbine and piston engines for commercial aircraft
[AD-751510] N73-16783
- ### ENGINE FAILURE
- Effect of engine failure on aerodynamic characteristics of supersonic aircraft
N73-17003
- ### ENGINE NOISE
- Ducts, nacelles, power source components and cabin noise sources identified for aircraft noise control research, considering prerequisites for quiet operations
[SAE AIR 1079] A73-20698
- Effect of sound absorbing exhaust duct on rear quadrant noise of J-65 engine and contributions of internal and jet components
[NASA-TN-X-2718] N73-16011
- ### ENGINE PARTS
- TF-34 turbofan engines for S-3A and AX aircraft respectively, discussing technological development, and components and characteristic features
A73-20350
- Probability theory for vibrational strength of turbomachine parts, calculating statistical maximum stress for given stress distribution conditions
A73-20502
- ### ENGINE TESTS
- Sound pressure level spectra measurements for four- and three-engine jet transport during concrete and grassy surface runup and flyover
[SAE AIR 1216] A73-20693
- ### ENVIRONMENTAL TESTS
- Evaluation of polyimide second stage rod seals at high temperatures to determine suitability for application to aircraft systems
[NASA-CR-121124] N73-17592

EQUATIONS OF MOTION

Flight vehicle equations of motion with variable information, noting flight control algorithm for random variable with given probability A73-20077

Application of equations of motion to investigate effects of mode shape and coning angle on stability boundaries of hingeless helicopter rotor blades [NASA-CR-114525] N73-16015

Analysis of control and power requirements for X-14 aircraft based on equations of motion with respect to set of axes fixed to aircraft [NASA-CR-130760] N73-16988

EQUIPMENT SPECIFICATIONS

Basic specification research for the main instruments of light aircraft A73-20248

Crew station lighting - Commercial aircraft. [SAE ARP 1161] A73-20692

General requirements for aerospace powered mobile ground support equipment. [SAE ARP 1247] A73-20694

EULER-LAGRANGE EQUATION

Numerical analysis of characteristics of rotary wing aircraft when considered as two coupled rigid bodies representing rotor and fuselage N73-15994

EUROPEAN AIRBUS

Russian book on passenger aircraft and air transport design covering technical and economic efficiency, airbus concept, weight and size problems and aft-mounted engine design A73-20377

EXHAUST GASES

Emissions from and within an Allison J-33 combustor. A73-20359

Tests of high pressure combustor exhaust emissions with improved air-atomizing and conventional pressure-atomizing fuel nozzle [NASA-TN-D-7154] N73-16929

Modification of jet engine fuels to reduce emissions of nitrogen oxides from jet aircraft turbine engines [AD-752581] N73-17803

Effect of fuel zoning and fuel nozzle design on exhaust pollution emissions at ground idle conditions for double-annular ram-induction combustor for turbofan engines [NASA-CR-121094] N73-17916

Analysis of gaseous emissions from J-85 engine at various fuel-air ratios, engine speeds, and simulated altitude conditions [NASA-TN-X-2726] N73-17921

EXPECTATION

Statistical expectation application to risk density functions and fee/incentive-element relationships for contract incentive structuring, considering C-5A procurement A73-20958

EXTERNALLY BLOWN FLAPS

Comparison of mechanical high lift flaps with externally blown flaps for STOL aircraft [NBB-UH-12-72-0] N73-16017

F**F-14 AIRCRAFT**

Role of flight simulation in development of S-3 and F-14 aircraft N73-17001

Performance tests of F-14 aircraft with jet blast deflector to determine effects of backflow of jet exhaust on aircraft launch operation [AD-752018] N73-17023

FABRICATION

Welding and fabrication of non-ferrous metals; Proceedings of the International Conference, Eastbourne, Sussex, England, May 2, 3, 1972. Volume 1. A73-21235

FABRICS

Correlation of wear behavior and properties of coated fabric hovercraft fingers [BAE-TR-71210] N73-17654

FAILURE ANALYSIS

Analysis of aircraft fire warning system performance and procedures for eliminating false fire warning indications [AD-751346] N73-16025

Correlation between full scale fatigue test failures and actual service failures for several military aircraft N73-16901

FAR FIELDS

Acoustic results obtained with upper-surface-blowing lift-augmentation systems. A73-20458

The effect of nozzle inlet shape, lip thickness, and exit shape and size on subsonic jet noise. [AIAA PAPER 73-187] A73-20465

FATIGUE (MATERIALS)

Physical aspects of fatigue damage accumulation, including interaction and sequence effects N73-16899

Fatigue crack propagation under flight simulation loading at 10, 1, and 0.1 cycles per second N73-16900

Random fatigue tests on normalized carbon steel with 0.7 percent carbon N73-16902

FATIGUE LIFE

Fatigue life of aircraft structures A73-20246

Random load fatigue of aircraft structures [AGARD-CP-118] N73-16896

Fatigue life assessment of aircraft structures based on random or programmed fatigue tests and loadings N73-16897

Crack growth study and effects of change in spectrum severity and shape on fatigue behavior under random loading N73-16898

Fatigue life prediction of military aircraft under three different load spectra N73-16903

FATIGUE TESTS

Fatigue tests to determine service life of catapult structure on C-2 aircraft [AD-752493] N73-17028

FEASIBILITY ANALYSIS

Economic feasibility analysis on San Francisco rapid transit system extension to serve airport [PB-212456] N73-16978

FEEDBACK CONTROL

A computerized flutter solution procedure. A73-20214

FIELD COILS

Aircraft power supply alternators with superconductive field windings, calculating specific weights and performance characteristics A73-20408

FIGHTER AIRCRAFT

Nonlinear programming in design of control systems with specified handling qualities. A73-20588

Effects of various leading edge slat devices on static aerodynamic characteristics of twin-jet, swept wing fighter model [NASA-TN-D-6921] N73-15988

Wind tunnel tests to predict full scale aircraft buffet loads during buffet boundary penetration using scale flutter model of fighter aircraft with variable sweep wings [NASA-TN-D-7066] N73-16905

FILM THICKNESS

Aircraft components solid film lubrication problems, discussing surface pretreatment, contamination susceptibility, corrosion prevention and aerosol applicability A73-19554

FINANCIAL MANAGEMENT

Collection and processing of data for the establishment of route charges. A73-19182

FINLAND

Vertical wind shear measurements at Helsinki Airport - Apr. 1967 through Mar. 1968 [TR-3] N73-17676

FIRE PREVENTION

FIRE PREVENTION

Analysis of aircraft fire warning system performance and procedures for eliminating false fire warning indications
[AD-751346] N73-16025

FIBES

Analysis of aircraft fire warning system performance and procedures for eliminating false fire warning indications
[AD-751346] N73-16025

FLAPPING

Model tests on unsteady rotor wake effects.
A73-19191

FLAPS (CONTROL SURFACES)

Conformal mapping for potential flow about airfoils with attached flap.
A73-19192

FLEXIBLE BODIES

Analysis of performance potential of buoyant systems and flexible structures for use with short haul passenger transport aircraft
[NASA-TM-X-62168] N73-17014

FLEXIBLE WINGS

Influence of aeroelasticity on flight mechanics of flexible aircraft
N73-16991

Calculation of induced load effects on controllability of rigid and flexible aircraft
N73-17004

FLIGHT

Fatigue crack propagation under flight simulation loading at 10, 1, and 0.1 cycles per second
N73-16900

FLIGHT CHARACTERISTICS

Recent advances and applications in the prediction of pilot acceptance of aircraft flying qualities.
A73-20586

Simulation of flight in Concorde for improving characteristic of flight control system
N73-17013

FLIGHT CONDITIONS

Nonlinear programming in design of control systems with specified handling qualities.
A73-20588

FLIGHT CONTROL

Flight vehicle equations of motion with variable information, noting flight control algorithm for random variable with given probability
A73-20077

A flight control system for STOL aircraft.
A73-20171

Analysis of controllability and steady-state response of parallel-redundant flight control systems
[NASA-CR-130354] N73-15998

Time vector technique for determining stability and control derivatives by simultaneous analysis of two maneuvers which differ by dependent control input
[NASA-TM-X-2722] N73-16010

Simulation of flight in Concorde for improving characteristic of flight control system
N73-17013

Design and development of stability augmentation system to eliminate coupling effects during landing of short takeoff aircraft
[NASA-CR-130543] N73-17021

FLIGHT HAZARDS

Crash of DC-8 aircraft during takeoff from Anchorage International Airport, Alaska on 27 Nov. 1970
[NTSB-AAR-72-12] N73-15999

Bibliography of aircraft accident reports for US civil aviation operations during calendar year 1971
[NTSB-BA-72-7] N73-16002

Aircraft accident involving DH-114 aircraft during attempted landing at Mercedita Airport, Puerto Rico on 24 June, 1972
[NTSB-AAR-72-34] N73-16004

Aircraft accident involving DC-9 aircraft landing at Port Lauderdale, Florida airport in marginal weather conditions on 18 May, 1972
[NTSB-AAR-72-31] N73-16005

FLIGHT INSTRUMENTS

Basic specification research for the main instruments of light aircraft
A73-20248

SUBJECT INDEX

FLIGHT LOAD RECORDERS

Acquisition and recording of structural flight load data for T-38 aircraft during normal training flights
[AD-751968] N73-17025

FLIGHT MECHANICS

Digital simulation language for flight dynamic tests, exemplified by Fiat G-91 and Dornier Do-31 aircraft
[BNVG-FBWT-72-21] N73-16019

Influence of aeroelasticity on flight mechanics of flexible aircraft
N73-16991

FLIGHT PATHS

Flight simulator evaluations of flight control, flight path, and airspeed for approach and landing of powered lift jet short takeoff aircraft
[NASA-TM-X-62203] N73-16014

Analysis of military helicopter formation flight techniques with emphasis on station keeping based on nominal point coordinate system
[AD-751459] N73-16021

FLIGHT PLANS

Collection and processing of data for the establishment of route charges.
A73-19182

Air traffic control by programmed navigation.
A73-19349

FLIGHT RECORDERS

System for in-flight recording of the rotational speed of the turbine of a jet engine
A73-20546

FLIGHT SAFETY

Bibliography of aircraft accident reports for US civil aviation operations during calendar year 1971
[NTSB-BA-72-6] N73-16001

Survey of Air Traffic Control Beacon System to determine occurrence of excessive interrogation signals within New York air control sector - Final Report
[ECAC-PR-72-031] N73-16630

Problems of flight safety in air traffic control with increased volume of traffic
[DGLR-PAPER-72-038] N73-16632

Development of digital fast-time air traffic control conflict prediction models and application to specific air route traffic control situations
[UTIAS-TN-183] N73-17708

FLIGHT SIMULATION

Summary of conference on flight simulation
N73-16992

Role of flight simulation in development of S-3 and F-14 aircraft
N73-17001

Simulation of flight in Concorde for improving characteristic of flight control system
N73-17013

Measurement of pilot performance during aircraft landing simulation to determine significance of vertical acceleration cues during approach and landing maneuver
[NASA-TM-X-62236] N73-17020

FLIGHT SIMULATORS

A proposed design for the construction of a VTOL simulator
A73-21249

Flight simulator evaluations of flight control, flight path, and airspeed for approach and landing of powered lift jet short takeoff aircraft
[NASA-TM-X-62203] N73-16014

Design and implementation of fixed-based spin simulator, and spin test results
[AD-751644] N73-16229

Analysis of simulated aircraft landing approach to aircraft carrier to determine display system requirements and to evaluate dangerous conditions
[AD-751076] N73-16635

Analysis of capabilities, characteristics, and effectiveness of flight simulators for developing primary aeronautical skills in single-engine, land aircraft - Vol. 1
[FAA-WA-72-102-VOL-1] N73-17221

Analysis of capabilities, characteristics, and effectiveness of flight simulators for developing primary aeronautical skills in pilots of single-engine, land aircraft Vol. 2
[FAA-WA-72-102-VOL-2-ADD] N73-17222

SUBJECT INDEX

GAS FLOW

- Analysis of fixed base simulator tests to determine effects of two horizontal display panel locations and three map orientations on manual piloting performance
[NASA-TN-X-62198] N73-17223
- FLIGHT TESTS**
- Russian book - Methods and equipment for in-flight aircraft strength tests. A73-20376
- Role of theoretical studies of flight dynamics in relation to flight testing N73-17011
- Automatic method for determining stability and control derivatives from flight data N73-17012
- FLIGHT TRAINING**
- Analysis of capabilities, characteristics, and effectiveness of flight simulators for developing primary aeronautical skills in single-engine, land aircraft - Vol. 1 [PAA-NA-72-102-VOL-1] N73-17221
- Analysis of capabilities, characteristics, and effectiveness of flight simulators for developing primary aeronautical skills in pilots of single-engine, land aircraft Vol. 2 [PAA-NA-72-102-VOL-2-ADD] N73-17222
- FLIGHT VEHICLES**
- Flight vehicle equations of motion with variable information, noting flight control algorithm for random variable with given probability A73-20077
- Accelerations of points on a flight vehicle during short-period motion A73-20095
- FLOW CHARACTERISTICS**
- Effects of thickness and viscosity considerations on accuracy of aerodynamic coefficients determined for thin wings in inviscid flow conditions [ESDU-70011-AMEND-A] N73-15982
- Flow characteristics of tandem bladed compressor stators at various inlet incidence angles [NASA-TN-X-2734] N73-16986
- Analysis of uniform jet flow around airfoil with separated shock wave at low supersonic velocities of incident flow [NASA-TT-P-148113] N73-17259
- FLOW DISTRIBUTION**
- Application of unsteady airfoil theory to determine pressure and lift fluctuations on rotor blades of turbomachinery N73-15983
- Reduction of transonic drag for high performance aircraft by injecting air in rear of aircraft to alter transonic flow distribution on aft section [AD-751269] N73-15991
- Development of computer program for calculating flow field resulting from sonic boom focusing [NASA-CR-2127] N73-16013
- Analysis of supersonic, three-dimensional flow characteristics to determine effects of material porosity and angle of attack on jet stretcher performance N73-16215
- Computerized simulation of shrouded propeller low field in cross flow using vortex lattice models [AD-751463] N73-16274
- Mathematical models for predicting flow fields within and external to thrust reverser deployed in flight including forces and moments induced on aircraft by flow fields [AD-751525] N73-16784
- Analysis of uniform jet flow around airfoil with separated shock wave at low supersonic velocities of incident flow [NASA-TT-P-148113] N73-17259
- FLOW THEORY**
- Analysis of internally generated sound in continuous materials. III - The momentum potential field description of fluctuating fluid motion as a basis for a unified theory of internally generated sound. A73-19097
- A correction to 'lifting-line theory as a singular perturbation problem.' A73-19964
- Effects of thickness and viscosity considerations on accuracy of aerodynamic coefficients determined for thin wings in inviscid flow conditions [ESDU-70011-AMEND-A] N73-15982
- Development of two dimensional theory for unsteady flow disturbances caused by aeroelastic deformation of thick wing at high subsonic speeds [NASA-CR-112114] N73-17258
- FLOW VELOCITY**
- Second derivatives of the flutter velocity and the optimization of aircraft structures. A73-19952
- Discrete vortex scheme of a wing of finite span A73-21611
- FLOW VISUALIZATION**
- Smoke and helium bubble visualization studies of incompressible flow past jet flap airfoil [AD-752012] N73-17270
- FLUTTER**
- Application of active controls to suppression of flutter for supersonic aircraft N73-17005
- FLUTTER ANALYSIS**
- Damping configurations that have a stabilizing influence on nonconservative systems. A73-19088
- Second derivatives of the flutter velocity and the optimization of aircraft structures. A73-19952
- A computerized flutter solution procedure. A73-20214
- FLY BY WIRE CONTROL**
- Artificial stabilization to correct control deficiencies for high performance aircraft N73-17009
- FLYWHEELS**
- Design, development, and evaluation of flywheel powered hoist for personnel rescue missions conducted by helicopters [AD-751217] N73-16029
- FOG**
- Field test of warm fog dispersal using helicopter downwash and hygroscopic seeding [AD-752046] N73-17694
- FORCED VIBRATION**
- Designing turbomachine blades for forced vibrations under various excitation conditions A73-20503
- FRAGMENTATION**
- Approximate analysis of containment/deflection ring responses to engine rotor fragment impact. A73-19188
- FREE FLIGHT**
- Role of free-flight models in aircraft research and development N73-17002
- FUEL INJECTION**
- Tests of high pressure combustor exhaust emissions with improved air-atomizing and conventional pressure-atomizing fuel nozzle [NASA-TN-D-7154] N73-16929
- FUEL TESTS**
- Vapor pressure of supersonic aircraft fuels A73-20014
- Comparison of combustion characteristics of ASTM A-1, propane, and natural gas fuels in annular turbojet combustor [NASA-TN-D-7135] N73-16771
- FULL SCALE TESTS**
- Icing testing in the large Modane wind-tunnel on full-scale and reduced scale models A73-20244

G

- GAS ANALYSIS**
- Analysis of gaseous emissions from J-85 engine at various fuel-air ratios, engine speeds, and simulated altitude conditions [NASA-TN-X-2726] N73-17921
- GAS FLOW**
- Discrete vortex scheme of a wing of finite span A73-21611
- Mathematical models for gas surface interactions and calculating aerodynamic coefficients for simple geometric shapes and high Mach number flow past thin airfoils [AD-752245] N73-17278

GAS TEMPERATURE

GAS TEMPERATURE

Emissions from and within an Allison J-33 combustor.
A73-20359

Turbine inlet gas temperature measurement by
ultrasonic impedance
[AD-752602] N73-17822

GAS TURBINE ENGINES

Lubricants thermophysical properties effects on
gas turbine engine design, considering thermal
stability, vapor pressure, autoignition, load
capacity and bearing life
A73-19563

Turbulent intensity induced by wakes near
secondary air jet inlet to gas turbine engine
flame tube
A73-19625

Moving radiography for photographic recording and
display of transient or cyclic motion,
emphasizing application to aircraft gas turbines
under dynamic conditions
A73-20451

Gas turbine engine transient performance
presentation for digital computer programs.
[SAE ARP 1257] A73-20696

Design principles of gas turbine and piston
engines for commercial aircraft
[AD-751510] N73-16783

GAS TURBINES

Investigation of the heat transfer between the gas
and casing in the area of the apertures between
the nozzle diaphragm blades and guide vanes of
turbines
A73-20086

Aerodynamic experimental investigation of annular
cascade of gas turbine nozzle blade in subsonic
and supersonic flow.
A73-20939

Performance tests to determine effects of
increased rotor blade loading on gas turbine
operation by reduction of rotor blade inlet
diameter
[NASA-TN-X-2730] N73-17039

GASES

Ab radable buffered labyrinth seal for control of
gas path leakage in tip-turbine driven lift fan
[NASA-CR-121131] N73-16524

GENERAL AVIATION AIRCRAFT

Bibliography of aircraft accident reports for US
civil aviation operations during calendar year
1971
[NTSB-BA-72-6] N73-16001

Bibliography of aircraft accident reports for US
civil aviation operations during calendar year
1971
[NTSB-BA-72-7] N73-16002

Aircraft accident involving Beechcraft Queen Air
aircraft on takeoff from Albuquerque, New Mexico
airport on 19 May, 1972
[NTSB-BA-72-32] N73-16003

Aircraft accident involving Beechcraft 18 aircraft
on air taxi flight from Cleveland, Ohio airport
on 22 June, 1972
[NTSB-BA-72-33] N73-16006

GLANDS (SEALS)

Evaluation of polyimide second stage rod seals at
high temperatures to determine suitability for
application to aircraft systems
[NASA-CR-121124] N73-17592

GLIDE PATHS

Bibliography of data on aircraft landings,
instrument landings, approach control, glide
path systems, display devices, and terminal
facilities
[AD-751800] N73-16024

GLIDERS

Glider soaring flight energy budget analysis,
discussing rate of climb indicator error
compensation
A73-21656

GOVERNMENT/INDUSTRY RELATIONS

Book - Civil aviation development - A policy and
operations analysis.
A73-21837

SUBJECT INDEX

GROUND BASED CONTROL

Ground based and airborne collision avoidance
systems comparison, discussing
interrogator/transponder concept, pilot warning
indicator, and air traffic handling capacity and
economics
A73-18900

GROUND EFFECT

Method for estimating changes in lift curve, drag,
tail lift, and downwash from wing of aircraft
due to ground effect in incompressible flow
[ESDU-72023] N73-15993

GROUND EFFECT MACHINES

Mathematical model for tracked air cushion vehicle
and guideway to determine vertical dynamic
response of vehicle and guideway system to high
speed vehicle passage
N73-15995

Nonlinear and small perturbation linear models for
one dimensional heave motion of flexible
skirted, air cushion suspension
[PB-212705] N73-16226

Concept of nuclear powered ground effect machine
for commercial operations in Arctic regions
[NASA-TN-X-2684] N73-17991

GROUND SUPPORT EQUIPMENT

General requirements for aerospace powered mobile
ground support equipment.
[SAE ARP 1247] A73-20694

Requirements, basic principles of operation,
design, construction, and maintenance of thermal
fog dispersal system for airport applications
[FAA-RD-72-138] N73-16222

GROUND TRUTH

The utility of a low flying aircraft or helicopter
when collecting ground data for regional
resource surveys.
A73-21710

GUIDANCE (NOTION)

Mathematical model for tracked air cushion vehicle
and guideway to determine vertical dynamic
response of vehicle and guideway system to high
speed vehicle passage
N73-15995

GUST LOADS

Development of automatic system for controlling
aircraft under turbulent atmospheric conditions
to provide pitch stabilization
[AD-751148] N73-16028

Wind tunnel tests to predict full scale aircraft
buffet loads during buffet boundary penetration
using scale flutter model of fighter aircraft
with variable sweep wings
[NASA-TN-D-7066] N73-16905

H

HEAT TRANSFER COEFFICIENTS

Investigation of the heat transfer between the gas
and casing in the area of the apertures between
the nozzle diaphragm blades and guide vanes of
turbines
A73-20086

HEATING EQUIPMENT

Requirements, basic principles of operation,
design, construction, and maintenance of thermal
fog dispersal system for airport applications
[FAA-RD-72-138] N73-16222

HELICOPTER CONTROL

Russian book - Control of aircraft and helicopter
flight.
A73-20381

Numerical analysis of characteristics of rotary
wing aircraft when considered as two coupled
rigid bodies representing rotor and fuselage
N73-15994

HELICOPTER PERFORMANCE

Application of equations of motion to investigate
effects of mode shape and coning angle on
stability boundaries of hingeless helicopter
rotor blades
[NASA-CR-114525] N73-16015

Development of dynamic helicopter performance and
control model based on force and rotor
aerodynamic equations
[AD-751460] N73-16022

SUBJECT INDEX

INSTRUMENT LANDING SYSTEMS

HELICOPTER PROPELLER DRIVE

Effect of dynamic absorbers and damping on noise generated by CH-47 helicopter rotor transmission
[AD-752579] N73-17031

HELICOPTER WAKES

Field test of warm fog dispersal using helicopter downwash and hygroscopic seeding
[AD-752046] N73-17694

HELICOPTERS

Russian book - Methods and equipment for in-flight aircraft strength tests. A73-20376

The utility of a low flying aircraft or helicopter when collecting ground data for regional resource surveys. A73-21710

Development of dynamic helicopter performance and control model based on force and rotor aerodynamic equations
[AD-751460] N73-16022

Design, development, and evaluation of flywheel powered hoist for personnel rescue missions conducted by helicopters
[AD-751217] N73-16029

Nonlinear instability in flap-lag of rotor blades in forward flight
[NASA-CR-114524] N73-17017

Development of computer programs to calculate helicopter rotor tip vortex geometry in hover and forward flight to include calculation of rotor harmonic air loads
[AD-752628] N73-17032

HORIZON SCANNERS

Image formation radiometers for blind landing, aerial reconnaissance over land and sea, horizon detection and detection of obstacles at sea
A73-21087

HOVERING

A summary of wind tunnel research on tilt-rotors from hover to cruise flight.
[ONERA, TP NO. 1133] A73-21683

Development of computer programs to calculate helicopter rotor tip vortex geometry in hover and forward flight to include calculation of rotor harmonic air loads
[AD-752628] N73-17032

HUMAN FACTORS ENGINEERING

Conceptual model for pilot workload
N73-17010

Analysis of fixed base simulator tests to determine effects of two horizontal display panel locations and three map orientations on manual piloting performance
[NASA-TM-X-62198] N73-17223

Approach light properties for visual discrimination in pilot landing environment
[NASA-TT-P-14667] N73-17710

HYDRAULIC CONTROL

Hydraulic drive and control systems used for landing gear retraction and extension on Piper Cherokee Arrow and for main wheel braking on P-111
A73-19604

HYDROCARBONS

Analysis of gaseous emissions from J-85 engine at various fuel-air ratios, engine speeds, and simulated altitude conditions
[NASA-TM-X-2726] N73-17921

HYPERSONIC FLOW

Hypersonic flows in large-scale inlet models.
A73-19189

HYPERVELOCITY WIND TUNNELS

Hypersonic flows in large-scale inlet models.
A73-19189

ICE FORMATION

Icing testing in the large Modane wind-tunnel on full-scale and reduced scale models
A73-20244

Statistical evaluation of meteorological ice formation parameters: free moisture content, drop diameters, and temperature, obtained from Transall C-160 flights
[NBS-ON-11-72-0] N73-16016

IMPACT DAMAGE

Approximate analysis of containment/deflection ring responses to engine rotor fragment impact.
A73-19188

IN-FLIGHT MONITORING

Russian book - Methods and equipment for in-flight aircraft strength tests. A73-20376

System for in-flight recording of the rotational speed of the turbine of a jet engine
A73-20546

In-flight tests and operational reliability of jet aircraft nullable compressor face rake
[NASA-TM-D-7162] N73-16247

User manual and source listings for computer programs to solve problems in analysis of in-flight thrust reversers
[AD-751526] N73-16785

INCENTIVES

Statistical expectation application to risk density functions and fee/incentive-element relationships for contract incentive structuring, considering C-5A procurement
A73-20958

INCOMPRESSIBLE FLOW

A correction to 'lifting-line theory as a singular perturbation problem.'
A73-19964

Method for estimating changes in lift curve, drag, tail lift, and downwash from wing of aircraft due to ground effect in incompressible flow
[ESDU-72023] N73-15993

INCOMPRESSIBLE FLUIDS

Three dimensional steady flow of incompressible viscous fluid near thin wing trailing edge, using Stewartson-Williams triple layer method
A73-21495

Discrete vortex scheme of a wing of finite span
A73-21611

INERTIAL NAVIGATION

The pre-flight handling of inertial navigation systems.
A73-19347

INFLATABLE STRUCTURES

A linearised theory of parachute opening dynamics.
A73-21692

Analysis of performance potential of buoyant systems and flexible structures for use with short haul passenger transport aircraft
[NASA-TM-X-62168] N73-17014

INLET FLOW

Hypersonic flows in large-scale inlet models.
A73-19189

Turbulent intensity induced by wakes near secondary air jet inlet to gas turbine engine flame tube
A73-19625

The effect of nozzle inlet shape, lip thickness, and exit shape and size on subsonic jet noise.
[AIAA PAPER 73-187] A73-20465

Flow characteristics of tandem bladed compressor stators at various inlet incidence angles
[NASA-TM-X-2734] N73-16986

Turbine inlet gas temperature measurement by ultrasonic impedance
[AD-752602] N73-17822

INLET NOZZLES

Calculation of the potential flow about axisymmetrical fuselages, annular profiles, and propulsion system inlets
A73-19205

INSPECTION

Nondestructive inspection techniques for examining catapult and arresting gear structures on E-2 aircraft
[AD-752492] N73-17027

INSTRUMENT ERRORS

Russian book on onboard distance measuring systems for flight vehicles covering design of cw and pulsed devices, modulators, error analysis, noise, logic elements, etc
A73-20378

Comparative assessment of three methods of measurement of pressure error corrections for aircraft pitot-static systems
[CHAMFIELD-AERO-11] N73-17570

INSTRUMENT LANDING SYSTEMS

Bibliography of data on aircraft landings, instrument landings, approach control, glide path systems, display devices, and terminal facilities
[AD-751800] N73-16024

INSTRUMENT ORIENTATION

SUBJECT INDEX

Analysis of Microwave Landing System performance to determine signal formats and to reduce effects of multipath transmission
[AG-5011-B-1] N73-16628

INSTRUMENT ORIENTATION
The pre-flight handling of inertial navigation systems.
A73-19347

INSTRUMENTS

Portable instrumentation kit feasibility study
[AD-751188] N73-16514

INTEGRATED CIRCUITS

Research and development in advance electronics including applications to digital computers, air traffic control, and solid state physics
[AD-751308] N73-16758

INVISCID FLOW

A correction to 'lifting-line theory as a singular perturbation problem.'
A73-19964

Discrete vortex scheme of a wing of finite span
A73-21611

Method for estimating aerodynamic characteristics of airfoils in compressible inviscid flow based on thickness and camber line parameters
[ESDU-72024] N73-15981

Effects of thickness and viscosity considerations on accuracy of aerodynamic coefficients determined for thin wings in inviscid flow conditions
[ESDU-70011-AMEND-A] N73-15982

J-33 ENGINE

Emissions from and within an Allison J-33 combustor.
A73-20359

Analytical predictions of emissions from and within an Allison J-33 combustor.
A73-21670

J-57 ENGINE

Analysis of thermal failures in combustion chambers of J-57 jet engine and system for detecting burn-through prior to engine case rupture
[FAA-NA-72-92] N73-16772

J-65 ENGINE

Effect of sound absorbing exhaust duct on rear quadrant noise of J-65 engine and contributions of internal and jet components
[NASA-TM-X-2718] N73-16011

J-85 ENGINE

Analysis of gaseous emissions from J-85 engine at various fuel-air ratios, engine speeds, and simulated altitude conditions
[NASA-TM-X-2726] N73-17921

JAGUAR AIRCRAFT

Optimisation in construction of the Jaguar and other military aircraft.
A73-20947

JET AIRCRAFT

In-flight tests and operational reliability of jet aircraft nullable compressor face rake
[NASA-TM-D-7162] N73-16247

Mathematical models for predicting flow fields within and external to thrust reverser deployed in flight including forces and moments induced on aircraft by flow fields
[AD-751525] N73-16784

User manual and source listings for computer programs to solve problems in analysis of in-flight thrust reversers
[AD-751526] N73-16785

JET AIRCRAFT NOISE

Analysis of internally generated sound in continuous materials. III - The momentum potential field description of fluctuating fluid motion as a basis for a unified theory of internally generated sound.
A73-19097

Acoustic results obtained with upper-surface-blowing lift-augmentation systems.
A73-20458

Sound pressure level spectra measurements for four- and three-engine jet transport during concrete and grassy surface runup and flyover
[SAE AIR 1216] A73-20693

Measurement of noise levels produced by Boeing 737 aircraft and correlation with local meteorological parameters including wind force and direction, temperature, and atmospheric pressure
[FAA-ED-72-145] N73-16651

Development of theory of aerodynamic noise to analyze jet noise directivity and shear-noise contribution to overall jet noise
[NASA-TM-D-7158] N73-16654

JET ENGINE FUELS

Vapor pressure of supersonic aircraft fuels
A73-20014

Modification of jet engine fuels to reduce emissions of nitrogen oxides from jet aircraft turbine engines
[AD-752581] N73-17803

JET ENGINES

System for in-flight recording of the rotational speed of the turbine of a jet engine
A73-20546

JET EXHAUST

Performance tests of F-14 aircraft with jet blast deflector to determine effects of backflow of jet exhaust on aircraft launch operation
[AD-752018] N73-17023

JET FLAPS

Development of nonlinearized solution for aerodynamic characteristics of jet flap lifting surface with span-wise slot near trailing edge
[NASA-CR-2190] N73-15986

Air foils based on utilization of jet flap principle
[AD-751075] N73-16283

Development of analytical technique for computing performance of arbitrary jet-flapped wing with compensations for variations in wing geometry
[NASA-CR-2179] N73-16982

Smoke and helium bubble visualization studies of incompressible flow past jet flap airfoil
[AD-752012] N73-17270

JET NOZZLES

Acoustic results obtained with upper-surface-blowing lift-augmentation systems.
A73-20458

JOINTS (JUNCTIONS)

The status of engineering knowledge concerning the damping of built-up structures.
A73-19099

K

KALMAN FILTERS

Theory of Kalman filtering and applications to real time tracking systems for air traffic control, satellite observation, and aircraft navigation
[AD-751485] N73-16634

L

L-1011 AIRCRAFT

L-1011 TriStar - Design development.
A73-21574

LAMINAR BOUNDARY LAYER

Boundary-layer separation on rotating blades in forward flight.
A73-19955

LANDING AIDS

Incident involving collision of Boeing 727 aircraft with landing light system at Atlanta International Airport, Georgia on 21 Dec. 1971
[NTSB-AAR-72-22] N73-16000

Bibliography of data on aircraft landings, instrument landings, approach control, glide path systems, display devices, and terminal facilities
[AD-751800] N73-16024

Analysis of Microwave Landing System performance to determine signal formats and to reduce effects of multipath transmission
[AG-5011-B-1] N73-16628

LANDING GEAR

Hydraulic drive and control systems used for landing gear retraction and extension on Piper Cherokee Arrow and for main wheel braking on F-111
A73-19604

SUBJECT INDEX

MECHANICAL DRIVES

LASERS
Laser scattering from curved aluminum and titanium aircraft surfaces in clear atmosphere N73-17159

LATERAL CONTROL
Influence of load and wing load distribution on lateral and longitudinal maneuverability of aircraft N73-16998

LEADING EDGE SLATS
Effects of various leading edge slat devices on static aerodynamic characteristics of twin-jet, swept wing fighter model [NASA-TN-D-6921] N73-15988
Wind tunnel tests of two dimensional wing model with leading edge slat and trailing edge flap [PAA-AU-862] N73-16984

LEADING EDGES
Angles of attack for shock wave detachment from sharp leading edge of five delta wing models with flat compression surfaces [AD-752206] N73-17271

LEAKAGE
Abradable buffered labyrinth seal for control of gas path leakage in tip-turbine driven lift fan [NASA-CR-121131] N73-16524

LIFT
Multiple element airfoils optimized for maximum lift coefficient. A73-19956
A correction to 'lifting-line theory as a singular perturbation problem.' A73-19964

LIFT AUGMENTATION
Acoustic results obtained with upper-surface-blowing lift-augmentation systems. A73-20458
Development of nonlinearized solution for aerodynamic characteristics of jet flap lifting surface with span-wise slot near trailing edge [NASA-CR-2190] N73-15986
Short takeoff aircraft lift augmentation and prevention of airflow separation on cambered elliptical airfoil section using circulation control [AD-751045] N73-15992
Development of analytical technique for computing performance of arbitrary jet-flapped wing with compensations for variations in wing geometry [NASA-CR-2179] N73-16982

LIFT DEVICES
Comparison of mechanical high lift flaps with externally blown flaps for STOL aircraft [NBB-UH-12-72-0] N73-16017

LIFT PANS
Abradable buffered labyrinth seal for control of gas path leakage in tip-turbine driven lift fan [NASA-CR-121131] N73-16524

LIGHT AIRCRAFT
Basic specification research for the main instruments of light aircraft A73-20248
Design modifications to improve static performance and lateral-directional dynamic stability of light aircraft N73-15996
Wind tunnel tests of full scale model of light aircraft to determine effects of configuration changes on aerodynamic characteristics [NASA-TN-D-6896] N73-16012

LIGHT SCATTERING
Laser scattering from curved aluminum and titanium aircraft surfaces in clear atmosphere N73-17159

LIGHTING EQUIPMENT
Crew station lighting - Commercial aircraft. [SAE ARP 1161] A73-20692

LIGHTNING
Papers presented at conference on lightning and static electricity [AD-752551] N73-17552

LIQUID CRYSTALS
Feasibility determination of using nematic liquid crystals for aircraft displays [AD-751667] N73-16748

LIQUID OXYGEN
Influence of liquid oxygen on chromate coated aluminum tubing of breathing apparatus [AD-752030] N73-17661

LOAD DISTRIBUTION (FORCES)
Nonstationary load distribution on an arbitrary-planform wing in supersonic motion A73-21725

LONGITUDINAL CONTROL
Influence of load and wing load distribution on lateral and longitudinal maneuverability of aircraft N73-16998

LONGITUDINAL STABILITY
Development of automatic system for controlling aircraft under turbulent atmospheric conditions to provide pitch stabilization [AD-751148] N73-16028
Effects of thrust characteristics on longitudinal stability in supersonic flight N73-16997

LOMAN C
A precision position and time service for the air traffic of the future. A73-19350

LUBRICANTS
Lubricants thermophysical properties effects on gas turbine engine design, considering thermal stability, vapor pressure, autoignition, load capacity and bearing life A73-19563

M

HALFUNCTIONS
Computer-controlled software diagnosis of an airborne computer. A73-20677

MAN MACHINE SYSTEMS
Problems of cockpit environment N73-16990

MANEUVERABILITY
Relationship between mission requirements of piloted aircraft stability and maneuverability N73-16995
Influence of load and wing load distribution on lateral and longitudinal maneuverability of aircraft N73-16998
Influence of powered controls on stability and maneuverability N73-17008

MANUAL CONTROL
Criteria for designing manual control system for military transport aircraft N73-17007

MATERIALS SCIENCE
Aircraft brake design and materials, considering thermal, mechanical, friction and wear characteristics of Be, steel, graphite and carbon composites A73-21688

MATHEMATICAL MODELS
Mathematical model of nonstationary linear aeroautoelasticity A73-19468
Benefit-cost analysis of delay reduction with STOL. [ASCE PREPRINT 1507] A73-21000
Analytical predictions of emissions from and within an Allison J-33 combustor. A73-21670
Mathematical models for predicting flow fields within and external to thrust reverser deployed in flight including forces and moments induced on aircraft by flow fields [AD-751525] N73-16784
Mathematical models for gas surface interactions and calculating aerodynamic coefficients for simple geometric shapes and high Mach number flow past thin airfoils [AD-752245] N73-17278

MECHANICAL DEVICES
Design, development, and evaluation of flywheel powered hoist for personnel rescue missions conducted by helicopters [AD-751217] N73-16029

MECHANICAL DRIVES
Effect of dynamic absorbers and damping on noise generated by CH-47 helicopter rotor transmission [AD-752579] N73-17031

METAL SURFACES

METAL SURFACES

Laser scattering from curved aluminum and titanium aircraft surfaces in clear atmosphere N73-17159

METEOROLOGICAL INSTRUMENTS

Observation, measurement, and automatic calculation of runway visibilities [NLL-M-20785-(5828.4P)] N73-16597
Observation and measurement of visibility at ground N73-16598
Automatic calculation of runway visual range on airdromes N73-16599

METEOROLOGICAL PARAMETERS

Measurement of noise levels produced by Boeing 737 aircraft and correlation with local meteorological parameters including wind force and direction, temperature, and atmospheric pressure [FAA-RD-72-145] N73-16651

MICROMETEOROLOGY

Vertical wind shear measurements at Helsinki Airport - Apr. 1967 through Mar. 1968 [TR-3] N73-17676

MICROWAVE EQUIPMENT

Analysis of Microwave Landing System performance to determine signal formats and to reduce effects of multipath transmission [AG-5011-B-1] N73-16628

MICROWAVE FREQUENCIES

Diversity techniques for airborne communications in presence of ground reflection multipath [AD-752249] N73-17178

MILITARY AIR FACILITIES

Evaluation of aluminum 1 by 12 ft extruded light-duty landing mat with symmetrical butt-type end connectors [AD-752079] N73-17233

MILITARY AIRCRAFT

Portable instrumentation kit feasibility study [AD-751188] N73-16514
Correlation between full scale fatigue test failures and actual service failures for several military aircraft N73-16901

Fatigue life prediction of military aircraft under three different load spectra N73-16903

Relation between measured C.G. vertical accelerations and loads at T-tail of military aircraft N73-16904

Design criteria for satisfactory stability and control of military aircraft N73-16996

Performance of auxiliary power systems for advanced Army rotary wing aircraft [AD-751854] N73-17046

MILITARY HELICOPTERS

Analysis of military helicopter formation flight techniques with emphasis on station keeping based on nominal point coordinate system [AD-751459] N73-16021

MILITARY TECHNOLOGY

Optimisation in construction of the Jaguar and other military aircraft. A73-20947

Performance of auxiliary power systems for advanced Army rotary wing aircraft [AD-751854] N73-17046

MISSION PLANNING

Relationship between mission requirements of piloted aircraft stability and maneuverability N73-16995

MODULATORS

Russian book on onboard distance measuring systems for flight vehicles covering design of cw and pulsed devices, modulators, error analysis, noise, logic elements, etc. A73-20378

MOMENTUM TRANSFER

Analysis of internally generated sound in continuous materials. III - The momentum potential field description of fluctuating fluid motion as a basis for a unified theory of internally generated sound. A73-19097

SUBJECT INDEX

MOTION PICTURES

Moving radiography for photographic recording and display of transient or cyclic motion, emphasizing application to aircraft gas turbines under dynamic conditions A73-20451

MOVING TARGET INDICATORS

Receiver synthesis for air traffic moving target indicator with digital signal processing [AD-751923] N73-17170

MULTIPATH TRANSMISSION

Diversity techniques for airborne communications in presence of ground reflection multipath [AD-752249] N73-17178

MULTIPLEXING

Analysis of Microwave Landing System performance to determine signal formats and to reduce effects of multipath transmission [AG-5011-B-1] N73-16628

MUONS

Predicting light flashes due to alpha-particle flux on SST planes. A73-20157

N

NAVIGATION AIDS

Image formation radiometers for blind landing, aerial reconnaissance over land and sea, horizon detection and detection of obstacles at sea A73-21087

NITRIC OXIDE

Stratospheric nitric oxide production from past nuclear explosions and its relevance to projected SST pollution [AD-751295] N73-16466

NITROGEN OXIDES

Modification of jet engine fuels to reduce emissions of nitrogen oxides from jet aircraft turbine engines [AD-752581] N73-17803

NITROGLYCERIN

Sonic boom nitroglycerin resistance noting shock simulation and sonic boom effect on detonation [ISL-14/72] N73-16658

NOISE INTENSITY

Sound pressure level spectra measurements for four- and three-engine jet transport during concrete and grassy surface runup and flyover [SAE AIR 1216] A73-20693

NOISE POLLUTION

Technology and operation of Olympus engine cycle on Concorde aircraft, discussing chemical and noise pollution and economic factors A73-21687

NOISE REDUCTION

Ducts, nacelles, power source components and cabin noise sources identified for aircraft noise control research, considering prerequisites for quiet operations [SAE AIR 1079] A73-20698

Effect of nozzle inlet shape, lip thickness, and exit shape and size on subsonic jet noise [NASA-TN-X-68182] N73-16655

Effect of dynamic absorbers and damping on noise generated by CH-47 helicopter rotor transmission [AD-752579] N73-17031

NOISE SPECTRA

Sound pressure level spectra measurements for four- and three-engine jet transport during concrete and grassy surface runup and flyover [SAE AIR 1216] A73-20693

NONCONSERVATIVE FORCES

Damping configurations that have a stabilizing influence on nonconservative systems. A73-19088

NONDESTRUCTIVE TESTS

Nondestructive inspection techniques for examining catapult and arresting gear structures on E-2 aircraft [AD-752492] N73-17027

NONFERROUS METALS

Welding and fabrication of non-ferrous metals; Proceedings of the International Conference, Eastbourne, Sussex, England, May 2, 3, 1972. Volume 1. A73-21235

SUBJECT INDEX

PILOT PERFORMANCE

- NONLINEAR PROGRAMMING**
Nonlinear programming in design of control systems with specified handling qualities. A73-20588
- NORMAL SHOCK WAVES**
Performance comparison of three normal-shock position sensors for supersonic mixed compression inlets [NASA-TN-X-2739] N73-17817
- NOSE WHEELS**
Bi-normal coordinates in discrete systems with application to aircraft shimmy problem [AD-752548] N73-17030
- NOZZLE DESIGN**
Investigation of the heat transfer between the gas and casing in the area of the apertures between the nozzle diaphragm blades and guide vanes of turbines A73-20086
Effect of fuel zoning and fuel nozzle design on exhaust pollution emissions at ground idle conditions for double-annular ram-induction combustor for turbofan engines [NASA-CR-121094] N73-17916
- NOZZLE EFFICIENCY**
Tests of high pressure combustor exhaust emissions with improved air-atomizing and conventional pressure-atomizing fuel nozzle [NASA-TN-D-7154] N73-16929
- NOZZLE FLOW**
Hypersonic flows in large-scale inlet models. A73-19189
The effect of nozzle inlet shape, lip thickness, and exit shape and size on subsonic jet noise. [AIAA PAPER 73-187] A73-20465
- NOZZLE GEOMETRY**
Effect of nozzle inlet shape, lip thickness, and exit shape and size on subsonic jet noise [NASA-TN-X-68182] N73-16655
- NUCLEAR EXPLOSIONS**
Stratospheric nitric oxide production from past nuclear explosions and its relevance to projected SST pollution [AD-751295] N73-16466
- NUCLEAR PROPULSION**
Concept of nuclear powered ground effect machine for commercial operations in Arctic regions [NASA-TN-X-2684] N73-17991
- NUMERICAL CONTROL**
AUTOMATE - A self-contained automatic test system. A73-20680
- ONBOARD EQUIPMENT**
Russian book on onboard distance measuring systems for flight vehicles covering design of cw and pulsed devices, modulators, error analysis, noise, logic elements, etc A73-20378
Crew station lighting - Commercial aircraft. [SAE ARP 1161] A73-20692
- OPERATIONS RESEARCH**
Book - Civil aviation development - A policy and operations analysis. A73-21837
- OPERATOR PERFORMANCE**
Development of aircraft control systems based on operator performance, adaptive displays, and coupling of manual with automatic control [AD-751306] N73-16026
- OPTIMAL CONTROL**
Recent advances and applications in the prediction of pilot acceptance of aircraft flying qualities. A73-20586
Application of modern control theory to design of optimum aircraft controllers [NASA-TN-X-62208] N73-17016
- OPTIMIZATION**
Second derivatives of the flutter velocity and the optimization of aircraft structures. A73-19952
Multiple element airfoils optimized for maximum lift coefficient. A73-19956
Optimization in construction of the Jaguar and other military aircraft. A73-20947
- OSCILLATING FLOW**
Unsteady thin-airfoil theory for subsonic flow. A73-20718
- OSCILLATIONS**
Flow in the wake of a cascade of oscillating airfoils. A73-19954
- P**
- PACKINGS (SEALS)**
Evaluation of polyimide second stage rod seals at high temperatures to determine suitability for application to aircraft systems [NASA-CR-121124] N73-17592
- PARACHUTE DESCENT**
A linearised theory of parachute opening dynamics. A73-21692
- PASSENGER AIRCRAFT**
Russian book on passenger aircraft and air transport design covering technical and economic efficiency, airbus concept, weight and size problems and aft-mounted engine design A73-20377
- PERFORMANCE PREDICTION**
Recent advances and applications in the prediction of pilot acceptance of aircraft flying qualities. A73-20586
Technique for defining aircraft performance model from limited flight test data and predicted aerodynamic and propulsion system characteristics [NASA-TN-D-7137] N73-16008
Predicting flying qualities by wind tunnel tests N73-17000
Prediction of aeroelastic hinge moment effects on stability and control N73-17006
Performance prediction for deployable aerodynamic decelerators operating in supersonic wakes using gas dynamics analogy [AD-751982] N73-17266
- PERFORMANCE TESTS**
Minimum performance standards - Airborne distance measuring equipment /DME/ operating within the radio-frequency range of 960-1215 megahertz. A73-19575
A summary of wind tunnel research on tilt-rotors from hover to cruise flight. [ONERA, TP NO. 1133] A73-21683
Design and implementation of fixed-based spin simulator, and spin test results [AD-751644] N73-16229
Performance tests to determine effects of reducing turbine blade thickness on turbine engine performance [NASA-TN-D-7128] N73-16776
Performance tests to determine effects of increased rotor blade loading on gas turbine operation by reduction of rotor blade inlet diameter [NASA-TN-X-2730] N73-17039
- PERTURBATION**
Nonlinear and small perturbation linear models for one dimensional heave motion of flexible skirted, air cushion suspension [PB-212705] N73-16226
- PHOTOGRAPHIC RECORDING**
Moving radiography for photographic recording and display of transient or cyclic motion, emphasizing application to aircraft gas turbines under dynamic conditions A73-20451
- PHOTOINTERPRETATION**
The utility of a low flying aircraft or helicopter when collecting ground data for regional resource surveys. A73-21710
- PIEZOELECTRIC TRANSDUCERS**
Turbine inlet gas temperature measurement by ultrasonic impedance [AD-752602] N73-17822
- PILOT PERFORMANCE**
Recent advances and applications in the prediction of pilot acceptance of aircraft flying qualities. A73-20586
Conceptual model for pilot workload N73-17010

PILOT TRAINING

SUBJECT INDEX

- Measurement of pilot performance during aircraft landing simulation to determine significance of vertical acceleration cues during approach and landing maneuver
[NASA-TM-X-62236] N73-17020
- Analysis of fixed base simulator tests to determine effects of two horizontal display panel locations and three map orientations on manual piloting performance
[NASA-TM-X-62198] N73-17223
- PILOT TRAINING**
- Analysis of capabilities, characteristics, and effectiveness of flight simulators for developing primary aeronautical skills in single-engine, land aircraft - Vol. 1
[FAA-NA-72-102-VOL-1] N73-17221
- Analysis of capabilities, characteristics, and effectiveness of flight simulators for developing primary aeronautical skills in pilots of single-engine, land aircraft Vol. 2
[FAA-NA-72-102-VOL-2-ADD] N73-17222
- PILOTS (PERSONNEL)**
- Pilot warning indicators and collision avoidance systems
[PB-212496] N73-16020
- Pilot warning indicator system of intruder aircraft
[NASA-CASE-ERC-10226-1] N73-16483
- PIPES (TUBES)**
- Influence of liquid oxygen on chromate coated aluminum tubing of breathing apparatus
[AD-752030] N73-17661
- PISTON ENGINES**
- Design principles of gas turbine and piston engines for commercial aircraft
[AD-751510] N73-16783
- PITCH (INCLINATION)**
- Accelerations of points on a flight vehicle during short-period motion
A73-20095
- PITCHING MOMENTS**
- Development of automatic system for controlling aircraft under turbulent atmospheric conditions to provide pitch stabilization
[AD-751148] N73-16028
- PITOT TUBES**
- Comparative assessment of three methods of measurement of pressure error corrections for aircraft pitot-static systems
[CRANFIELD-AERO-11] N73-17570
- POLICIES**
- Book - Civil aviation development - A policy and operations analysis.
A73-21837
- POLLUTION**
- Effect of fuel zoning and fuel nozzle design on exhaust pollution emissions at ground idle conditions for double-annular ram-induction combustor for turbofan engines
[NASA-CR-121094] N73-17916
- POLYIMIDES**
- Evaluation of polyimide second stage rod seals at high temperatures to determine suitability for application to aircraft systems
[NASA-CR-121124] N73-17592
- POROUS MATERIALS**
- Analysis of supersonic, three-dimensional flow characteristics to determine effects of material porosity and angle of attack on jet stretcher performance
N73-16215
- PORTABLE EQUIPMENT**
- Portable instrumentation kit feasibility study
[AD-751188] N73-16514
- POTENTIAL FIELDS**
- Analysis of internally generated sound in continuous materials. III - The momentum potential field description of fluctuating fluid motion as a basis for a unified theory of internally generated sound.
A73-19097
- POTENTIAL FLOW**
- Conformal mapping for potential flow about airfoils with attached flap.
A73-19192
- Calculation of the potential flow about axisymmetrical fuselages, annular profiles, and propulsion system inlets
A73-19205
- POWER SERIES**
- Conformal mapping of two airfoil profiles symmetric with respect to real axis onto circles, using rational function power series
A73-20200
- POWER SUPPLIES**
- Aircraft power supply alternators with superconductive field windings, calculating specific weights and performance characteristics
A73-20408
- PREDICTION ANALYSIS TECHNIQUES**
- Air traffic volume prediction by 1985, determining passenger growth factors for terminal pairs
A73-19348
- PREFLIGHT OPERATIONS**
- The pre-flight handling of inertial navigation systems.
A73-19347
- PRESSURE DISTRIBUTION**
- Pressure distribution measurement at surface of aerodynamic body by pneumatically activated inductive sensor
A73-21180
- Application of unsteady airfoil theory to determine pressure and lift fluctuations on rotor blades of turbomachinery
N73-15983
- PRESSURE MEASUREMENTS**
- Pressure distribution measurement at surface of aerodynamic body by pneumatically activated inductive sensor
A73-21180
- PRESSURE SENSORS**
- Pressure distribution measurement at surface of aerodynamic body by pneumatically activated inductive sensor
A73-21180
- In-flight tests and operational reliability of jet aircraft nullable compressor face rake
[NASA-TM-D-7162] N73-16247
- Performance comparison of three normal-shock position sensors for supersonic mixed compression inlets
[NASA-TM-X-2739] N73-17817
- PRIMARY COSMIC RAYS**
- Predicting light flashes due to alpha-particle flux on SST planes.
A73-20157
- PROBABILITY THEORY**
- Flight vehicle equations of motion with variable information, noting flight control algorithms for random variable with given probability
A73-20077
- Probability theory for vibrational strength of turbomachine parts, calculating statistical maximum stress for given stress distribution conditions
A73-20502
- PROBLEM SOLVING**
- Development of digital fast-time air traffic control conflict prediction models and application to specific air route traffic control situations
[UTIAS-TN-183] N73-17708
- PROCUREMENT POLICY**
- Statistical expectation application to risk density functions and fee/incentive-element relationships for contract incentive structuring, considering C-5A procurement
A73-20958
- PROGRAMMING LANGUAGES**
- Digital simulation language for flight dynamic tests, exemplified by Fiat G-91 and Dornier Do-31 aircraft
[BNVG-FBWT-72-21] N73-16019
- PROPULSION SYSTEM CONFIGURATIONS**
- Concept of nuclear powered ground effect machine for commercial operations in Arctic regions
[NASA-TM-X-2684] N73-17991
- PROPULSION SYSTEM PERFORMANCE**
- Gas turbine engine transient performance presentation for digital computer programs.
[SAE ARP 1257] A73-20696
- Technique for defining aircraft performance model from limited flight test data and predicted aerodynamic and propulsion system characteristics
[NASA-TM-D-7137] N73-16008

SUBJECT INDEX

RESEARCH AND DEVELOPMENT

Subsonic performance potential of ramjets and ejector ramjets
[AD-751317] N73-16781

Performance of auxiliary power systems for advanced Army rotary wing aircraft
[AD-751854] N73-17046

PROTECTIVE COATINGS
Influence of liquid oxygen on chromate coated aluminum tubing of breathing apparatus
[AD-752030] N73-17661

Q

QUEUEING THEORY
Air-terminal queues under time-dependent conditions.
A73-20375

R

RADAR BEACONS
Automated radar terminal systems /ARTS/.
A73-19184

Survey of Air Traffic Control Beacon System to determine occurrence of excessive interrogation signals within New York air control sector - Final Report
[ECAC-PR-72-031] N73-16630

RADAR EQUIPMENT
Minimum performance standards - Airborne distance measuring equipment /DME/ operating within the radio-frequency range of 960-1215 megahertz.
A73-19575

Operation and characteristics of primary radar system for air traffic control surveillance
[FAA-ED-02-1] N73-17163

RADAR IMAGERY
Doppler effect continuous wave radar for bird hazard detection and aircraft collision avoidance near airfields
[AD-751985] N73-17168

RADAR RECEIVERS
Receiver synthesis for air traffic moving target indicator with digital signal processing
[AD-751923] N73-17170

RADAR TRACKING
Theory of Kalman filtering and applications to real time tracking systems for air traffic control, satellite observation, and aircraft navigation
[AD-751485] N73-16634

RADIAL FLOW
Performance tests to determine effects of increased rotor blade loading on gas turbine operation by reduction of rotor blade inlet diameter
[NASA-TN-X-2730] N73-17039

RADIO COMMUNICATION
Survey of air traffic control system to determine areas within system susceptible to radio frequency interference effects
[ECAC-PR-72-008] N73-16629

RADIO FREQUENCY INTERFERENCE
Survey of air traffic control system to determine areas within system susceptible to radio frequency interference effects
[ECAC-PR-72-008] N73-16629

RADIOGRAPHY
Moving radiography for photographic recording and display of transient or cyclic motion, emphasizing application to aircraft gas turbines under dynamic conditions
A73-20451

Nondestructive inspection techniques for examining catapult and arresting gear structures on E-2 aircraft
[AD-752492] N73-17027

RADIOMETERS
Image formation radiometers for blind landing, aerial reconnaissance over land and sea, horizon detection and detection of obstacles at sea
A73-21087

RAMJET ENGINES
Subsonic performance potential of ramjets and ejector ramjets
[AD-751317] N73-16781

RANDOM VARIABLES
Flight vehicle equations of motion with variable information, noting flight control algorithms for random variable with given probability
A73-20077

RAPID TRANSIT SYSTEMS
Economic feasibility analysis on San Francisco rapid transit system extension to serve airport
[PB-212456] N73-16978

RATE OF CLIMB INDICATORS
Glider soaring flight energy budget analysis, discussing rate of climb indicator error compensation
A73-21656

RATIONAL FUNCTIONS
Conformal mapping of two airfoil profiles symmetric with respect to real axis onto circles, using rational function power series
A73-20200

REACTION KINETICS
Analytical predictions of emissions from and within an Allison J-33 combustor.
A73-21670

REAL TIME OPERATION
Theory of Kalman filtering and applications to real time tracking systems for air traffic control, satellite observation, and aircraft navigation
[AD-751485] N73-16634

RECTANGULAR WINGS
Calculation of the aerodynamic characteristics of a rectangular wing with tip plates moving at a low subsonic speed in the proximity of a screen
A73-20094

REDUNDANT COMPONENTS
Analysis of controllability and steady-state response of parallel-redundant flight control systems
[NASA-CR-130354] N73-15998

REFERENCE SYSTEMS
A precision position and time service for the air traffic of the future.
A73-19350

REGULATIONS
Influence of aircraft reliability regulations on STOL takeoff and landing performance
[MBB-UH-13-72-0] N73-16018

REINFORCEMENT (STRUCTURES)
Procedures for reducing residual stresses in aircraft metal structures reinforced by filamentary composites
[NASA-CR-112207] N73-17900

REINFORCING FIBERS
Procedures for reducing residual stresses in aircraft metal structures reinforced by filamentary composites
[NASA-CR-112207] N73-17900

RELIABILITY ANALYSIS
Calculation of the reliability of electronic components in an 'aeronautics' environment shaped by the operational service routines of onboard equipment devices used by Air France
A73-19403

RELIABILITY ENGINEERING
In-flight tests and operational reliability of jet aircraft nullable compressor face rake
[NASA-TN-D-7162] N73-16247

REQUIREMENTS
General requirements for aerospace powered mobile ground support equipment.
[SAE ARP 1247] A73-20694

RESCUE OPERATIONS
Design, development, and evaluation of flywheel powered hoist for personnel rescue missions conducted by helicopters
[AD-751217] N73-16029

RESEARCH AND DEVELOPMENT
Ducts, nacelles, power source components and cabin noise sources identified for aircraft noise control research, considering prerequisites for quiet operations
[SAE AIR 1079] A73-20698

Book - Civil aviation development - A policy and operations analysis.
A73-21837

Aeronautical research for 1971-1972
N73-16943

RESEARCH FACILITIES

- Role of free-flight models in aircraft research and development
N73-17002
- RESEARCH FACILITIES**
Wind tunnel facilities in India for subsonic, transonic and supersonic aeronautical R and D, describing design layouts, power requirements, operational functions and instrumentation
A73-20249
- RESEARCH MANAGEMENT**
Book - Civil aviation development - A policy and operations analysis.
A73-21837
- RETINAL IMAGES**
Predicting light flashes due to alpha-particle flux on SST planes.
A73-20157
- RIGID ROTORS**
Application of equations of motion to investigate effects of mode shape and coning angle on stability boundaries of hingeless helicopter rotor blades
[NASA-CR-114525]
N73-16015
- RIGID WINGS**
Calculation of induced load effects on controllability of rigid and flexible aircraft
N73-17004
- RING WINGS**
Calculation of the potential flow about axisymmetrical fuselages, annular profiles, and propulsion system inlets
A73-19205
- ROLLING MOMENTS**
German monograph - The steady and unsteady aerodynamic coefficients for the rolling motion of slender wings.
A73-19578
- Procedure for determining rolling moment derivatives of aircraft due to rolling, yawing, and sideslip
[ESDU-AIRCRAFT-06.01.00]
N73-15978
- ROTARY WING AIRCRAFT**
Performance of auxiliary power systems for advanced Army rotary wing aircraft
[AD-751854]
N73-17046
- ROTARY WINGS**
Boundary-layer separation on rotating blades in forward flight.
A73-19955
- Numerical analysis of characteristics of rotary wing aircraft when considered as two coupled rigid bodies representing rotor and fuselage
N73-15994
- Application of equations of motion to investigate effects of mode shape and coning angle on stability boundaries of hingeless helicopter rotor blades
[NASA-CR-114525]
N73-16015
- Development of dynamic helicopter performance and control model based on force and rotor aerodynamic equations
[AD-751460]
N73-16022
- Effect of dynamic absorbers and damping on noise generated by CH-47 helicopter rotor transmission
[AD-752579]
N73-17031
- Development of computer programs to calculate helicopter rotor tip vortex geometry in hover and forward flight to include calculation of rotor harmonic air loads
[AD-752628]
N73-17032
- ROTATING ELECTRICAL MACHINES**
Superconducting a.c. machines - An approach to development.
A73-20407
- ROTOR AERODYNAMICS**
Model tests on unsteady rotor wake effects.
A73-19191
- Nonlinear instability in flap-lag of rotor blades in forward flight
[NASA-CR-114524]
N73-17017
- ROTOR BLADES**
Nonlinear instability in flap-lag of rotor blades in forward flight
[NASA-CR-114524]
N73-17017
- ROTOR BLADES (TURBOMACHINERY)**
Approximate analysis of containment/deflection ring responses to engine rotor fragment impact.
A73-19188

SUBJECT INDEX

- Designing turbomachine blades for forced vibrations under various excitation conditions
A73-20503
- Application of unsteady airfoil theory to determine pressure and lift fluctuations on rotor blades of turbomachinery
N73-15993
- Two dimensional cascade test of highly loaded, low solidity, tandem airfoil turbine rotor blade
[NASA-TN-X-2729]
N73-17814
- ROUTES**
Collection and processing of data for the establishment of route charges.
A73-19182
- RUNWAYS**
The capacity of a single-runway S.T.O.L./R.T.O.L. airport.
A73-19352
- Observation, measurement, and automatic calculation of runway visibilities
[NLL-M-20785-(5828.4P)]
N73-16597
- Evaluation of aluminum 1 by 12 ft extruded light-duty landing mat with symmetrical butt-type end connectors
[AD-752079]
N73-17233
- S**
- S-3 AIRCRAFT**
Role of flight simulation in development of S-3 and P-14 aircraft
N73-17001
- SANDWICH STRUCTURES**
Design parameters for torsion of airframe sandwich strips having trapezoidal, rectangular, and triangular cross sections
[AD-752619]
N73-17029
- SCALE MODELS**
Hypersonic flows in large-scale inlet models.
A73-19189
- Icing testing in the large Modane wind-tunnel on full-scale and reduced scale models
A73-20244
- SCREEN EFFECT**
Calculation of the aerodynamic characteristics of a rectangular wing with tip plates moving at a low subsonic speed in the proximity of a screen
A73-20094
- SEALS (STOPPERS)**
Abradable buffered labyrinth seal for control of gas path leakage in tip-turbine driven lift fan
[NASA-CR-121131]
N73-16524
- SECONDARY INJECTION**
Turbulent intensity induced by wakes near secondary air jet inlet to gas turbine engine flame tube
A73-19625
- SEMICONDUCTORS (MATERIALS)**
Aircraft and land vehicle electric generators and motors, noting semiconductors application and cooling systems
A73-20124
- SEMIEMPIRICAL EQUATIONS**
Semiempirical methods for designing ejectors for various applications
N73-17252
- SHOCK RESISTANCE**
Sonic boom nitroglycerin resistance noting shock simulation and sonic boom effect on detonation
[ISL-14/72]
N73-16658
- SHOCK WAVES**
Aerodynamic configurations and characteristics of airfoils designed to reduce formation of shock waves during supersonic flight
[NASA-TT-P-749]
N73-15987
- Analysis of uniform jet flow around airfoil with separated shock wave at low supersonic velocities of incident flow
[NASA-TT-P-14813]
N73-17259
- Angles of attack for shock wave detachment from sharp leading edge of five delta wing models with flat compression surfaces
[AD-752206]
N73-17271
- Focusing effects of distortion of near sonic shocks by weakly turbulent layers with random temperature and pressure variations
[AD-752472]
N73-17279

SUBJECT INDEX

STATIC ELECTRICITY

SHORT HAUL AIRCRAFT

Technical documentation to support V/STOL aircraft implementation and utilization based on short haul air transportation requirements - Vol. 2 [NASA-CR-114518] N73-16009
Analysis of factors affecting development and operation of satellite airport system as method for relieving congestion at metropolitan airports N73-16216

Analysis of performance potential of buoyant systems and flexible structures for use with short haul passenger transport aircraft [NASA-TM-X-62168] N73-17014

Aerodynamic configuration and predicted performance of short takeoff aircraft for short haul passenger transportation [CRANFIELD-AERO-12-PT-1] N73-17019

SHORT TAKEOFF AIRCRAFT

The capacity of a single-runway S.T.O.L./R.T.O.L. airport. A73-19352

A flight control system for STOL aircraft. A73-20171

Acoustic results obtained with upper-surface-blowing lift-augmentation systems. A73-20458

Mass air transportation development in Sweden; discussing flight scheduling, fare structure and quiet STOL aircraft introduction in 1980s A73-20618

Benefit-cost analysis of delay reduction with STOL. [ASCE PREPRINT 1507] A73-21000

Short takeoff aircraft lift augmentation and prevention of airflow separation on cambered elliptical airfoil section using circulation control [AD-751045] N73-15992

Development and application of computer programs for evaluating performance of powered-lift STOL aircraft to include static, takeoff, and landing performance [NASA-TM-X-62217] N73-16007

Flight simulator evaluations of flight control, flight path, and airspeed for approach and landing of powered lift jet short takeoff aircraft [NASA-TM-X-62203] N73-16014

Comparison of mechanical high lift flaps with externally blown flaps for STOL aircraft [NBB-UH-12-72-0] N73-16017

Influence of aircraft reliability regulations on STOL takeoff and landing performance [NBB-UH-13-72-0] N73-16018

Aerodynamic configuration and predicted performance of short takeoff aircraft for short haul passenger transportation [CRANFIELD-AERO-12-PT-1] N73-17019

Design and development of stability augmentation system to eliminate coupling effects during landing of short takeoff aircraft [NASA-CR-130543] N73-17021

SHROUDED PROPELLERS

Computerized simulation of shrouded propeller low field in cross flow using vortex lattice models [AD-751463] N73-16274

SIDE INLETS

Three dimensional boundary layer separation and shock wave generation in flow field of supersonic conical intake mounted on fuselage side [ABL/ME-137] N73-16981

SIGNAL RECEPTION

Analysis of Microwave Landing System performance to determine signal formats and to reduce effects of multipath transmission [AG-5011-B-1] N73-16628

SIGNAL TRANSMISSION

Analysis of Microwave Landing System performance to determine signal formats and to reduce effects of multipath transmission [AG-5011-B-1] N73-16628

SIMULATORS

Development of digital fast-time air traffic control conflict prediction models and application to specific air route traffic control situations [UTIAS-TN-183] N73-17708

SKIN (STRUCTURAL MEMBER)

The status of engineering knowledge concerning the damping of built-up structures. A73-19099

SKIN TEMPERATURE (NON-BIOLOGICAL)

Analysis of thermal failures in combustion chambers of J-57 jet engine and system for detecting burn-through prior to engine case rupture [FAA-NA-72-92] N73-16772

SLENDER WINGS

German monograph - The steady and unsteady aerodynamic coefficients for the rolling motion of slender wings. A73-19578

A correction to 'lifting-line theory as a singular perturbation problem.' A73-19964

SMALL PERTURBATION FLOW

A correction to 'lifting-line theory as a singular perturbation problem.' A73-19964

SOARING

Glider soaring flight energy budget analysis, discussing rate of climb indicator error compensation A73-21656

SOLID LUBRICANTS

Aircraft components solid film lubrication problems, discussing surface pretreatment, contamination susceptibility, corrosion prevention and aerosol applicability A73-19554

SOLID STATE PHYSICS

Research and development in advance electronics including applications to digital computers, air traffic control, and solid state physics [AD-751308] N73-16758

SONIC BOOMS

Development of computer program for calculating flow field resulting from sonic boom focusing [NASA-CR-2127] N73-16013

Sonic boom nitroglycerin resistance noting shock simulation and sonic boom effect on detonation [ISL-14/72] N73-16658

Focusing effects of distortion of near sonic shocks by weakly turbulent layers with random temperature and pressure variations [AD-752472] N73-17279

SOUND PRESSURE

Sound pressure level spectra measurements for four- and three-engine jet transport during concrete and grassy surface runup and flyover [SAE AIR 1216] A73-20693

SOUND TRANSMISSION

Effect of sound absorbing exhaust duct on rear quadrant noise of J-65 engine and contributions of internal and jet components [NASA-TM-X-2718] N73-16011

SPACECRAFT INSTRUMENTS

Crew station lighting - Commercial aircraft. [SAE ARP 1161] A73-20692

SPACECRAFT STRUCTURES

Computer programmer manual for NASA structural analysis program [NASA-SP-223 (01)] N73-17892

SPEED INDICATORS

Comparative assessment of three methods of measurement of pressure error corrections for aircraft pitot-static systems [CRANFIELD-AERO-11] N73-17570

STABILITY DERIVATIVES

Time vector technique for determining stability and control derivatives by simultaneous analysis of two maneuvers which differ by dependent control input [NASA-TM-X-2722] N73-16010

Application of equations of motion to investigate effects of mode shape and coning angle on stability boundaries of hingeless helicopter rotor blades [NASA-CR-114525] N73-16015

STANDARDS

Minimum performance standards - Airborne distance measuring equipment /DME/ operating within the radio-frequency range of 960-1215 megahertz. A73-19575

Crew station lighting - Commercial aircraft. [SAE ARP 1161] A73-20692

STATIC ELECTRICITY

Papers presented at conference on lightning and static electricity [AD-752551] N73-17552

STATIC TESTS

STATIC TESTS

Static and wind tunnel tests to determine performance of four cowl cascade thrust reverser configurations at forward velocity
[NASA-TN-X-2665] N73-16773

STATIONKEEPING

Analysis of military helicopter formation flight techniques with emphasis on station keeping based on nominal point coordinate system
[AD-751459] N73-16021

STATISTICAL ANALYSIS

Statistical expectation application to risk density functions and fee/incentive-element relationships for contract incentive structuring, considering C-5A procurement
A73-20958

STATOR BLADES

Flow characteristics of tandem bladed compressor stators at various inlet incidence angles
[NASA-TN-X-2734] N73-16986

STEADY FLOW

Three dimensional steady flow of incompressible viscous fluid near thin wing trailing edge, using Stewartson-Williams triple layer method
A73-21495

STEELS

Crack growth characteristics of steel and structural failure of F-111 aircraft frame
[AD-752223] N73-17024

STOCHASTIC PROCESSES

Air-terminal queues under time-dependent conditions.
A73-20375

STRATOSPHERE

Stratospheric nitric oxide production from past nuclear explosions and its relevance to projected SST pollution
[AD-751295] N73-16466

STRESS CONCENTRATION

Probability theory for vibrational strength of turbomachine parts, calculating statistical maximum stress for given stress distribution conditions
A73-20502

STRESS RELIEVING

Procedures for reducing residual stresses in aircraft metal structures reinforced by filamentary composites
[NASA-CR-112207] N73-17900

STRUCTURAL ANALYSIS

Book - Aircraft structures for engineering students.
A73-21839
Fatigue tests to determine service life of catapult structure on C-2 aircraft
[AD-752493] N73-17028
Computer programmer manual for NASA structural analysis program
[NASA-SP-223(01)] N73-17892

STRUCTURAL DESIGN

Optimisation in construction of the Jaguar and other military aircraft.
A73-20947

STRUCTURAL ENGINEERING

Development of optimized aircraft structures based on vibratory strain energy distribution using damped forced response
[AD-751809] N73-16027

STRUCTURAL FAILURE

Approximate analysis of containment/deflection ring responses to engine rotor fragment impact.
A73-19188
Aircraft accident involving Beechcraft 18 aircraft on air taxi flight from Cleveland, Ohio airport on 22 June, 1972
[NTSB-AAR-72-33] N73-16006

STRUCTURAL RELIABILITY

Fatigue life of aircraft structures
A73-20246

STRUCTURAL STABILITY

Damping configurations that have a stabilizing influence on nonconservative systems.
A73-19088
A computerized flutter solution procedure.
A73-20214
Fatigue tests to determine service life of catapult structure on C-2 aircraft
[AD-752493] N73-17028

SUBJECT INDEX

STRUCTURAL VIBRATION

The status of engineering knowledge concerning the damping of built-up structures.
A73-19099

Designing turbomachine blades for forced vibrations under various excitation conditions
A73-20503

SUBSONIC FLOW

Unsteady thin-airfoil theory for subsonic flow.
A73-20718

SUBSONIC SPEED

Calculation of the aerodynamic characteristics of a rectangular wing with tip plates moving at a low subsonic speed in the proximity of a screen
A73-20094
Subsonic performance potential of ramjets and ejector ramjets
[AD-751317] N73-16781

Development of two dimensional theory for unsteady flow disturbances caused by aeroelastic deformation of thick wing at high subsonic speeds
[NASA-CR-112114] N73-17258

SUPERCONDUCTIVITY

Aircraft power supply alternators with superconductive field windings, calculating specific weights and performance characteristics
A73-20408

SUPERCONDUCTORS

Superconducting a.c. machines - An approach to development.
A73-20407

SUPERSONIC AIRCRAFT

Vapor pressure of supersonic aircraft fuels
A73-20014
Reduction of transonic drag for high performance aircraft by injecting air in rear of aircraft to alter transonic flow distribution on aft section
[AD-751269] N73-15991
Optimized design of supersonic aircraft wing based on linear combination of weight of wing and aerodynamic drag minimization
N73-15997

Climatic changes resulting from upper atmosphere perturbation by supersonic aircraft exhausts
[PB-212427] N73-16612
Effect of engine failure on aerodynamic characteristics of supersonic aircraft
N73-17003

Application of active controls to suppression of flutter for supersonic aircraft
N73-17005
Artificial stabilization to correct control deficiencies for high performance aircraft
N73-17009

SUPERSONIC FLIGHT

Nonstationary load distribution on an arbitrary-planform wing in supersonic motion
A73-21725
Effects of thrust characteristics on longitudinal stability in supersonic flight
N73-16997

SUPERSONIC FLOW

Aerodynamic characteristics of thin asymmetric wing profiles in supersonic flow
A73-20487
Analysis of uniform jet flow around airfoil with separated shock wave at low supersonic velocities of incident flow
[NASA-TT-P-14813] N73-17259

SUPERSONIC INLETS

Three dimensional boundary layer separation and shock wave generation in flow field of supersonic conical intake mounted on fuselage side
[ARL/ME-137] N73-16981
Performance comparison of three normal-shock position sensors for supersonic mixed compression inlets
[NASA-TN-X-2739] N73-17817

SUPERSONIC SPEEDS

Aerodynamic configurations and characteristics of airfoils designed to reduce formation of shock waves during supersonic flight
[NASA-TT-P-749] N73-15987
Development of computer program for calculating flow field resulting from sonic boom focusing
[NASA-CR-2127] N73-16013

SUBJECT INDEX

THIN WINGS

SUPERSONIC TRANSPORTS

Predicting light flashes due to alpha-particle flux on SST planes.

A73-20157

SUPERSONIC WAKES

Performance prediction for deployable aerodynamic decelerators operating in supersonic wakes using gas dynamics analogy
[AD-751982]

N73-17266

SURFACE REACTIONS

Mathematical models for gas surface interactions and calculating aerodynamic coefficients for simple geometric shapes and high Mach number flow past thin airfoils
[AD-752245]

N73-17278

Influence of liquid oxygen on chromate coated aluminum tubing of breathing apparatus
[AD-752030]

N73-17661

SURFACE ROUGHNESS EFFECTS

Laser scattering from curved aluminum and titanium aircraft surfaces in clear atmosphere

N73-17159

SURVEILLANCE RADAR

Operation and characteristics of primary radar system for air traffic control surveillance
[FAA-ED-02-1]

N73-17163

SWEEP WINGS

Contribution of straight-tapered swept wing to rolling moment derivative due to yawing under conditions where flow remains fully attached to surface
[ESDU-72021]

N73-15980

Effects of various leading edge slat devices on static aerodynamic characteristics of twin-jet, swept wing fighter model
[NASA-TN-D-6921]

N73-15988

SYSTEM EFFECTIVENESS

Distributed ATC with traffic information in cockpit, noting potential for cost and risk reduction and capacity increase based on system performance evaluation

A73-20600

SYSTEMS ANALYSIS

Monograph - System analysis of the air-ground transportation interface problem at Bangkok International Airport.

A73-20382

SYSTEMS ENGINEERING

Two-level computer system with main and display processors as scale working model for semiautomatic digital ATC en route control

A73-19183

Lubricants thermophysical properties effects on gas turbine engine design, considering thermal stability, vapor pressure, autoignition, load capacity and bearing life

A73-19563

Operation and characteristics of primary radar system for air traffic control surveillance
[FAA-ED-02-1]

N73-17163

Semiempirical methods for designing ejectors for various applications

N73-17252

T

T-38 AIRCRAFT

Acquisition and recording of structural flight load data for T-38 aircraft during normal training flights
[AD-751968]

N73-17025

TACHOMETERS

System for in-flight recording of the rotational speed of the turbine of a jet engine

A73-20546

TAKEOFF

Crash of DC-8 aircraft during takeoff from Anchorage International Airport, Alaska on 27 Nov. 1970
[NTSB-AAB-72-12]

N73-15999

Aircraft accident involving Beechcraft Queen Air aircraft on takeoff from Albuquerque, New Mexico airport on 19 May, 1972
[NTSB-AAB-72-32]

N73-16003

TECHNOLOGY ASSESSMENT

TP-34 turbofan engines for S-3A and AX aircraft respectively, discussing technological development, and components and characteristic features

A73-20350

Technology advancement effects on military and commercial transport aircraft development and production costs, considering airframes, engines and avionics

A73-20394

Distributed ATC with traffic information in cockpit, noting potential for cost and risk reduction and capacity increase based on system performance evaluation

A73-20600

Technology and operation of Olympus engine cycle on Concorde aircraft, discussing chemical and noise pollution and economic factors

A73-21687

TEMPERATURE CONTROL

Analysis of effect of chord size and cooling methods on cooling requirements for air cooled turbine blades - Vol. 1
[NASA-CR-120882-BK-1]

N73-17809

Analysis of effect of chord size and cooling methods on cooling requirements for air cooled turbine blades - Vol. 2
[NASA-CR-120882]

N73-17810

TENSILE DEFORMATION

Welding airframe structures in titanium alloys using tensile loading as a means of overcoming distortion.

A73-21240

TERMINAL FACILITIES

Air-terminal queues under time-dependent conditions.

A73-20375

Monograph - System analysis of the air-ground transportation interface problem at Bangkok International Airport.

A73-20382

Analysis of factors affecting development and operation of satellite airport system as method for relieving congestion at metropolitan airports

N73-16216

TERMINAL GUIDANCE

Area navigation systems integration with terminal ATC approach procedures, considering computerized data linkage with aircraft navigation system

A73-19351

TP-34 ENGINE

TP-34 turbofan engines for S-3A and AX aircraft respectively, discussing technological development, and components and characteristic features

A73-20350

THERMAL STRESSES

Analysis of thermal failures in combustion chambers of J-57 jet engine and system for detecting burn-through prior to engine case rupture
[FAA-NA-72-92]

N73-16772

THERMOPHYSICAL PROPERTIES

Lubricants thermophysical properties effects on gas turbine engine design, considering thermal stability, vapor pressure, autoignition, load capacity and bearing life

A73-19563

THIN AIRFOILS

Unsteady thin-airfoil theory for subsonic flow.

A73-20718

Mathematical models for gas surface interactions and calculating aerodynamic coefficients for simple geometric shapes and high Mach number flow past thin airfoils
[AD-752245]

N73-17278

THIN WINGS

Aerodynamic characteristics of thin asymmetric wing profiles in supersonic flow

A73-20487

Three dimensional steady flow of incompressible viscous fluid near thin wing trailing edge, using Stewartson-Williams triple layer method

A73-21495

THREE DIMENSIONAL FLOW

SUBJECT INDEX

- Effects of thickness and viscosity considerations on accuracy of aerodynamic coefficients determined for thin wings in inviscid flow conditions
[ESDU-70011-AMEND-A] N73-15982
- THREE DIMENSIONAL FLOW**
Boundary-layer separation on rotating blades in forward flight. A73-19955
- Aerodynamic characteristics of thin asymmetric wing profiles in supersonic flow A73-20487
- Three dimensional steady flow of incompressible viscous fluid near thin wing trailing edge, using Stewartson-Williams triple layer method A73-21495
- Analysis of supersonic, three-dimensional flow characteristics to determine effects of material porosity and angle of attack on jet stretcher performance N73-16215
- Three dimensional boundary layer separation and shock wave generation in flow field of supersonic conical intake mounted on fuselage side [ARL/ME-137] N73-16981
- THRUST REVERSAL**
Static and wind tunnel tests to determine performance of four cowl cascade thrust reverser configurations at forward velocity [NASA-TM-X-2665] N73-16773
- Mathematical models for predicting flow fields within and external to thrust reverser deployed in flight including forces and moments induced on aircraft by flow fields [AD-751525] N73-16784
- User manual and source listings for computer programs to solve problems in analysis of in-flight thrust reversers [AD-751526] N73-16785
- TILTING ROTORS**
A summary of wind tunnel research on tilt-rotors from hover to cruise flight. [ONERA, TP NO. 1133] A73-21683
- TIME DEPENDENCE**
Air-terminal queues under time-dependent conditions. A73-20375
- TIME RESPONSE**
A linearised theory of parachute opening dynamics. A73-21692
- TITANIUM ALLOYS**
Welding airframe structures in titanium alloys using tensile loading as a means of overcoming distortion. A73-21240
- TORSION**
Design parameters for torsion of airframe sandwich strips having trapezoidal, rectangular, and triangular cross sections [AD-752619] N73-17029
- TRACKING RADAR**
Automated radar terminal systems /ARTS/. A73-19184
- TRAILING EDGES**
Three dimensional steady flow of incompressible viscous fluid near thin wing trailing edge, using Stewartson-Williams triple layer method. A73-21495
- TRAILING-EDGE FLAPS**
Wind tunnel tests of two dimensional wing model with leading edge slat and trailing edge flap [FAA-AU-862] N73-16984
- TRAINING SIMULATORS**
Analysis of capabilities, characteristics, and effectiveness of flight simulators for developing primary aeronautical skills in single-engine, land aircraft - Vol. 1 [FAA-NA-72-102-VOL-1] N73-17221
- Analysis of capabilities, characteristics, and effectiveness of flight simulators for developing primary aeronautical skills in pilots of single-engine, land aircraft Vol. 2 [FAA-NA-72-102-VOL-2-ADD] N73-17222
- TRANSIENT RESPONSE**
Approximate analysis of containment/deflection ring responses to engine rotor fragment impact. A73-19188
- Gas turbine engine transient performance presentation for digital computer programs. [SAE ARP 1257] A73-20696
- TRANSITION PROBABILITIES**
Air-terminal queues under time-dependent conditions. A73-20375
- TRANSOCEANIC COMMUNICATION**
The Aeronautical Satellite Programme - ATC aspects. A73-19141
- TRANSONIC SPEED**
Reduction of transonic drag for high performance aircraft by injecting air in rear of aircraft to alter transonic flow distribution on aft section [AD-751269] N73-15991
- TRANSPONDERS**
Ground based and airborne collision avoidance systems comparison, discussing interrogator/transponder concept, pilot warning indicator, and air traffic handling capacity and economics A73-18900
- TROPOSPHERE**
Vertical wind shear measurements at Helsinki Airport - Apr. 1967 through Mar. 1968 [TR-3] N73-17676
- TURBINE BLADES**
Investigation of the heat transfer between the gas and casing in the area of the apertures between the nozzle diaphragm blades and guide vanes of turbines A73-20086
- Aerodynamic experimental investigation of annular cascade of gas turbine nozzle blade in subsonic and supersonic flow. A73-20939
- Performance tests to determine effects of reducing turbine blade thickness on turbine engine performance [NASA-TM-D-7128] N73-16776
- Cascade tests of highly loaded multistage fan drive turbine configurations [NASA-CR-2171] N73-16778
- Performance tests to determine effects of increased rotor blade loading on gas turbine operation by reduction of rotor blade inlet diameter [NASA-TM-X-2730] N73-17039
- Analysis of effect of chord size and cooling methods on cooling requirements for air cooled turbine blades - Vol. 1 [NASA-CR-120882-BK-1] N73-17809
- Analysis of effect of chord size and cooling methods on cooling requirements for air cooled turbine blades - Vol. 2 [NASA-CR-120882] N73-17810
- Experimental determination of aerodynamic performance of cooled turbine vanes at gas to coolant temperature ratios up to 2.75 [NASA-TM-X-2733] N73-17815
- TURBINE ENGINES**
System for in-flight recording of the rotational speed of the turbine of a jet engine A73-20546
- Abordable buffered labyrinth seal for control of gas path leakage in tip-turbine driven lift fan [NASA-CR-121131] N73-16524
- Performance tests to determine effects of reducing turbine blade thickness on turbine engine performance [NASA-TM-D-7128] N73-16776
- Analysis of effect of chord size and cooling methods on cooling requirements for air cooled turbine blades - Vol. 1 [NASA-CR-120882-BK-1] N73-17809
- Analysis of effect of chord size and cooling methods on cooling requirements for air cooled turbine blades - Vol. 2 [NASA-CR-120882] N73-17810
- TURBOCOMPRESSORS**
A description of two low cost turbo-compressors built for powered lift research. A73-19942
- TURBOFAN ENGINES**
TF-34 turbofan engines for S-3A and AX aircraft respectively, discussing technological development, and components and characteristic features A73-20350
- Cascade tests of highly loaded multistage fan drive turbine configurations [NASA-CR-2171] N73-16778

SUBJECT INDEX

VISIBILITY

TURBOJET ENGINES

- Comparison of combustion characteristics of ASTM A-1, propane, and natural gas fuels in annular turbojet combustor
[NASA-TN-D-7135] N73-16771
- Modification of jet engine fuels to reduce emissions of nitrogen oxides from jet aircraft turbine engines
[AD-752581] N73-17803
- Turbine inlet gas temperature measurement by ultrasonic impedance
[AD-752602] N73-17822

TURBOMACHINE BLADES

- The effect of the degree of turbulence on the aerodynamic characteristics of planar decelerating cascades
A73-19197

TURBOMACHINERY

- Probability theory for vibrational strength of turbomachine parts, calculating statistical maximum stress for given stress distribution conditions
A73-20502
- Application of unsteady airfoil theory to determine pressure and lift fluctuations on rotor blades of turbomachinery
N73-15983

TURBULENCE EFFECTS

- The effect of the degree of turbulence on the aerodynamic characteristics of planar decelerating cascades
A73-19197

- Development of automatic system for controlling aircraft under turbulent atmospheric conditions to provide pitch stabilization
[AD-751148] N73-16028

TURBULENT MIXING

- Analysis of aircraft trailing vortices to show formation and breakdown for various aircraft wing configurations
[ME/A-72-1] N73-17247

TURBULENT WAKES

- Turbulent intensity induced by wakes near secondary air jet inlet to gas turbine engine flame tube
A73-19625

- Analysis of aircraft trailing vortices to show formation and breakdown for various aircraft wing configurations
[ME/A-72-1] N73-17247

TURNING FLIGHT

- Analysis of military helicopter formation flight techniques with emphasis on station keeping based on nominal point coordinate system
[AD-751459] N73-16021

TWO DIMENSIONAL BODIES

- Unsteady thin-airfoil theory for subsonic flow.
A73-20718

TWO DIMENSIONAL FLOW

- Development of two dimensional theory for unsteady flow disturbances caused by aeroelastic deformation of thick wing at high subsonic speeds
[NASA-CR-112114] N73-17258

U

ULTRASONIC RADIATION

- Turbine inlet gas temperature measurement by ultrasonic impedance
[AD-752602] N73-17822

UNSTEADY FLOW

- Model tests on unsteady rotor wake effects.
A73-19191

UPWASH

- Unsteady thin-airfoil theory for subsonic flow.
A73-20718

URBAN TRANSPORTATION

- Benefit-cost analysis of delay reduction with STOL.
[ASCE PREPRINT 15071] A73-21000

V

V/STOL AIRCRAFT

- Technical documentation to support V/STOL aircraft implementation and utilization based on short haul air transportation requirements - Vol. 2
[NASA-CR-114518] N73-16009

- Development of optimized aircraft structures based on vibratory strain energy distribution using damped forced response
[AD-751809] N73-16027
- Revisions to V/STOL handling qualities based on criteria
N73-16994

- Development of methods for predicting performance characteristics of V/STOL aircraft - Vol. 1
[AD-752557] N73-17033

- Analytical techniques for predicting static and dynamic stability, control derivatives, and force and moment coefficients for V/STOL aircraft - Vol. 2
[AD-752558] N73-17034

- Computer program manual for analytical techniques to predict performance of V/STOL aircraft - Vol. 3
[AD-752559] N73-17035

- Literature survey of techniques for predicting performance of V/STOL aircraft - Vol. 4
[AD-752563] N73-17036

VANELESS DIFFUSERS

- Development trends in aircraft-engine compressor design methods. III
A73-19605

VAPOR PRESSURE

- Vapor pressure of supersonic aircraft fuels
A73-20014

VARIABLE SWEEP WINGS

- Wind tunnel tests to predict full scale aircraft buffet loads during buffet boundary penetration using scale flutter model of fighter aircraft with variable sweep wings
[NASA-TN-D-7066] N73-16905

VECTOR ANALYSIS

- Time vector technique for determining stability and control derivatives by simultaneous analysis of two maneuvers which differ by dependent control input
[NASA-TN-X-2722] N73-16010

VEHICULAR TRACKS

- Mathematical model for tracked air cushion vehicle and guideway to determine vertical dynamic response of vehicle and guideway system to high speed vehicle passage
N73-15995

VERTICAL DISTRIBUTION

- Vertical wind shear measurements at Helsinki Airport - Apr. 1967 through Mar. 1968
[TR-3] N73-17676

VERTICAL TAKEOFF AIRCRAFT

- A proposed design for the construction of a VTOL simulator
A73-21249

- Numerical analysis of characteristics of rotary wing aircraft when considered as two coupled rigid bodies representing rotor and fuselage
N73-15994

- Effect of control force gradient on VTOL visual hovering task
[NASA-TN-X-62230] N73-17015

VIBRATION

- Bi-normal coordinates in discrete systems with application to aircraft shimmy problem
[AD-752548] N73-17030

VIBRATION DAMPING

- The status of engineering knowledge concerning the damping of built-up structures.
A73-19099

VIBRATION MODE

- Designing turbomachine blades for forced vibrations under various excitation conditions
A73-20503

VIBRATIONAL STRESS

- Probability theory for vibrational strength of turbomachine parts, calculating statistical maximum stress for given stress distribution conditions
A73-20502

VISCIOUS FLUIDS

- Three dimensional steady flow of incompressible viscous fluid near thin wing trailing edge, using Stewartson-Williams triple layer method
A73-21495

VISIBILITY

- Observation, measurement, and automatic calculation of runway visibilities
[NLL-N-20785-(5828.4P)] N73-16597

VISUAL AIDS

Observation and measurement of visibility at ground
N73-16598
Automatic calculation of runway visual range on
airdromes
N73-16599

VISUAL AIDS

Approach light properties for visual
discrimination in pilot landing environment
[NASA-TT-P-14667] N73-17710

VISUAL FLIGHT RULES

Investigation of disappearance of Cessna 310
aircraft on flight between Anchorage and Juneau,
Alaska on 16 Oct. 1972
[NTSB-AAR-73-1] N73-17018

VORTEX SHEETS

Discrete vortex scheme of a wing of finite span
A73-21611

Analysis of aircraft trailing vortices to show
formation and breakdown for various aircraft
wing configurations
[HE/A-72-1] N73-17247

VORTICES

Wing tip vortex modification by tip-mounted
upstream and downstream directed air jets,
discussing wind tunnel test results
A73-19193

Development of computer programs to calculate
helicopter rotor tip vortex geometry in hover
and forward flight to include calculation of
rotor harmonic air loads
[AD-752628] N73-17032

Analysis of aircraft trailing vortices to show
formation and breakdown for various aircraft
wing configurations
[HE/A-72-1] N73-17247

W

WAKES

Model tests on unsteady rotor wake effects.
A73-19191

Flow in the wake of a cascade of oscillating
airfoils.
A73-19954

WARNING SYSTEMS

Ground based and airborne collision avoidance
systems comparison, discussing
interrogator/transponder concept, pilot warning
indicator, and air traffic handling capacity and
economics
A73-18900

Pilot warning indicators and collision avoidance
systems
[PB-212496] N73-16020

Analysis of aircraft fire warning system
performance and procedures for eliminating false
fire warning indications
[AD-751346] N73-16025

Pilot warning indicator system of intruder aircraft
[NASA-CASE-ERC-10226-1] N73-16483

WEAR TESTS

Correlation of wear behavior and properties of
coated fabric hovercraft fingers
[RAE-TR-71210] N73-17654

WEATHER

Aircraft accident involving DC-9 aircraft landing
at Fort Lauderdale, Florida airport in marginal
weather conditions on 18 May, 1972
[NTSB-AAR-72-31] N73-16005

WEATHER MODIFICATION

Field test of warm fog dispersal using helicopter
downwash and hygroscopic seeding
[AD-752046] N73-17694

WELDED STRUCTURES

Welding airframe structures in titanium alloys
using tensile loading as a means of overcoming
distortion.
A73-21240

WELDING

Welding and fabrication of non-ferrous metals;
Proceedings of the International Conference,
Eastbourne, Sussex, England, May 2, 3, 1972.
Volume 1.
A73-21235

WESTLAND GROUND EFFECT MACHINES

Correlation of wear behavior and properties of
coated fabric hovercraft fingers
[RAE-TR-71210] N73-17654

SUBJECT INDEX

WHEEL BRAKES

Hydraulic drive and control systems used for
landing gear retraction and extension on Piper
Cherokee Arrow and for main wheel braking on F-111
A73-19604

WINCHES

Design, development, and evaluation of flywheel
powered hoist for personnel rescue missions
conducted by helicopters
[AD-751217] N73-16029

WIND SHEAR

Vertical wind shear measurements at Helsinki
Airport - Apr. 1967 through Mar. 1968
[TR-3] N73-17676

WIND TUNNEL APPARATUS

Analysis of supersonic, three-dimensional flow
characteristics to determine effects of material
porosity and angle of attack on jet stretcher
performance
N73-16215

WIND TUNNEL MODELS

Icing testing in the large Modane wind-tunnel on
full-scale and reduced scale models.
A73-20244

A summary of wind tunnel research on tilt-rotors
from hover to cruise flight.
[ONERA, TP NO. 1133] A73-21683

Effects of various leading edge slat devices on
static aerodynamic characteristics of twin-jet,
swept wing fighter model
[NASA-TN-D-6921] N73-15988

Static and wind tunnel tests to determine
performance of four cowl cascade thrust reverser
configurations at forward velocity
[NASA-TN-X-2665] N73-16773

Wind tunnel tests to predict full scale aircraft
buffet loads during buffet boundary penetration
using scale flutter model of fighter aircraft
with variable sweep wings
[NASA-TN-D-7066] N73-16905

Wind tunnel tests of two dimensional wing model
with leading edge slat and trailing edge flap
[FAA-AU-862] N73-16984

WIND TUNNEL STABILITY TESTS

Wing tip vortex modification by tip-mounted
upstream and downstream directed air jets,
discussing wind tunnel test results
A73-19193

Wind tunnel tests of full scale model of light
aircraft to determine effects of configuration
changes on aerodynamic characteristics
[NASA-TN-D-6896] N73-16012

Wind tunnel tests to determine aircraft post-stall
characteristics and to define boundaries for
maintaining controlled aircraft flight
[AD-751461] N73-16023

WIND TUNNELS

Wind tunnel facilities in India for subsonic,
transonic and supersonic aeronautical R and D,
describing design layouts, power requirements,
operational functions and instrumentation
A73-20249

French project of anechoic chamber with wind
tunnel for studying jets, turbojets blowers,
helicopter rotors and V/STOL aircraft
A73-21529

Predicting flying qualities by wind tunnel tests
N73-17000

Open jet, wind tunnel operating within anechoic
chamber for studying V/STOL noise mechanisms
[AD-751857] N73-17235

WING CAMBER

Conically cambered triangular wings with reflex
spanwise curvature.
A73-20938

WING FLAPS

Comparison of mechanical high lift flaps with
externally blown flaps for STOL aircraft
[NBB-UH-12-72-0] N73-16017

WING LOADING

Nonstationary load distribution on an
arbitrary-planform wing in supersonic motion
A73-21725

Influence of load and wing load distribution on
lateral and longitudinal maneuverability of
aircraft
N73-16998

SUBJECT INDEX

YAWING MOMENTS

WING PANELS

Wind tunnel tests of two dimensional wing model
with leading edge slat and trailing edge flap
[FAA-AU-862] N73-16984

WING PLANFORMS

Nonstationary load distribution on an
arbitrary-planform wing in supersonic motion
A73-21725
Optimized design of supersonic aircraft wing based
on linear combination of weight of wing and
aerodynamic drag minimization N73-15997

Development of analytical technique for computing
performance of arbitrary jet-flapped wing with
compensations for variations in wing geometry
[NASA-CR-2179] N73-16982

WING PROFILES

Aerodynamic characteristics of thin asymmetric
wing profiles in supersonic flow
A73-20487
Discrete vortex scheme of a wing of finite span
A73-21611

WING SLOTS

Development of nonlinearized solution for
aerodynamic characteristics of jet flap lifting
surface with span-wise slot near trailing edge
[NASA-CR-2190] N73-15986

WING TIPS

Wing tip vortex modification by tip-mounted
upstream and downstream directed air jets,
discussing wind tunnel test results
A73-19193
Calculation of the aerodynamic characteristics of
a rectangular wing with tip plates moving at a
low subsonic speed in the proximity of a screen
A73-20094

X

X-14 AIRCRAFT

Analysis of control and power requirements for
X-14 aircraft based on equations of motion with
respect to set of axes fixed to aircraft
[NASA-CR-130760] N73-16988

Y

YAWING MOMENTS


Contribution of straight-tapered swept wing to
rolling moment derivative due to yawing under
conditions where flow remains fully attached to
surface
[ESDU-72021] N73-15980

PERSONAL AUTHOR INDEX

AERONAUTICAL ENGINEERING / A Special Bibliography (Suppl. 31)

MAY 1973

Typical Personal Author Index Listing



Listings in this index are arranged alphabetically by personal author. The title of the document provides the user with a brief description of the subject matter. The report number helps to indicate the type of document cited (e.g., NASA report, translation, NASA contractor report). The accession number is located beneath and to the right of the title, e.g., N73-11007. Under any one author's name the accession numbers are arranged in sequence with the /AA accession numbers appearing first.

A

- ADDONS, R. B.**
Aerodynamic and structural design considerations for high lift biplane wing systems
N73-16987
- ABARRAH, R. C.**
Flight simulation: A significant aid in aircraft design
N73-17001
- ABERN, C. J.**
Ultrasonic transmission investigations for turbine inlet gas temperature measurement
[AD-752602] N73-17822
- ALCALA, R. J.**
Analytical study of inflight thrust reversers. Volume 2: User's manual and source listings for computer programs
[AD-751526] N73-16785
- ALTRIKRICH, R. A.**
Emissions from and within an Allison J-33 combustor.
A73-20359
- ANDRES, S.**
A computer program for the prediction of aerodynamic characteristics of wing-body-tail combinations at subsonic and supersonic speeds, part 2
[PPA-AU-635-PT-2] N73-16985
- ANDRESON, J. L.**
Northwest passage: Trade route for large air cushion vehicles
[NASA-TN-X-2684] N73-17991
- ANDERSON, R. D.**
Emissions from and within an Allison J-33 combustor.
A73-20359
- ANDERSON, S. B.**
Considerations for stability and control of V/STOL aircraft: A review of AGARD report 577
N73-16994
- ANDROSKY, A.**
Study of V/STOL aircraft implementation. Volume 2: Appendices
[NASA-CR-114518] N73-16009
- ATTWOLL, V. W.**
The capacity of a single-runway S.T.O.L./B.T.O.L. airport.
A73-19352

B

- BABISH, C. A., III**
The influence of aerodynamic decelerators on supersonic wakes: With an application of the GaS hydraulic analogy
[AD-751982] N73-17266
- BARNES, A. G.**
Summary paper on Simulation Meeting, spring 1970 at NASA Research Center
N73-16992
- BARRIAGE, J. B.**
Benefit-cost analysis of delay reduction with STOL.
[ASCE PREPRINT 1507] A73-21000
- BARRINGTON, A. E.**
Climatic Impact Assessment Program. Proceedings of the Survey Conference
[PB-212427] N73-16612
- BARROIS, W.**
Fatigue life of aircraft structures
A73-20246
- BATY, D.**
A study on aircraft map display location and orientation
[NASA-TN-X-62198] N73-17223
- BAUER, A. B.**
A new family of airfoils based on the jet-flap principle
[AD-751075] N73-16283
- BAUER, P.**
The development of a wind tunnel facility for the study of V/STOL noise
[AD-751857] N73-17235
- BEACH, J. B.**
L-1011 TriStar - Design development.
A73-21574
- BECKER, R. D.**
Investigations of NLS conventional and Doppler scanning beam techniques
[AG-5011-B-1] N73-16628
- BELOTSEKOVSKII, S. M.**
Mathematical model of nonstationary linear aeroautoelasticity
A73-19468
- BENEKE, J.**
Investigations of NLS conventional and Doppler scanning beam techniques
[AG-5011-B-1] N73-16628
- BERGER, R.**
Diversity techniques for airborne communications in the presence of ground reflection multipath
[AD-752249] N73-17178
- BERRAN, L.**
Test plan for non-destructive inspection investigation of the catapult and arrested landing carry-through structure of the E-2 aircraft
[AD-752492] N73-17027
- BETAN, A.**
Automatic calculation of runway visual range on an aerodrome
N73-16599
- BHATIA, K. G.**
Second derivatives of the flutter velocity and the optimization of aircraft structures.
A73-19952

BIELEFELDT, E.

Comparison between STOL aircraft with mechanical high-lift systems and STOL aircraft with blown flap wings
[HBB-UH-12-72-0] N73-16017

BIGGERS, S. B., JR.

Dynamic interactions of high speed tracked air cushion vehicles with their guideways: A parametric study N73-15995

BISCHOPF, I.

Study of the sensitivity of nitroglycerin to weak shock waves (supersonic aircraft bangs)
[ISL-14/72] N73-16658

BJELLAND, H. L.

Study of a highly reliable pilot's vertical display system
[AD-752510] N73-17026

BODUNOV, M. N.

Investigation of the heat transfer between the gas and casing in the area of the apertures between the nozzle diaphragm blades and guide vanes of turbines A73-20086

BOGHABI, A. B.

Nonlinear and finite pad length performance of vehicle air cushion suspensions
[PB-212705] N73-16226

BOHNE, U.

Properties and limitations of liquid crystals for aircraft displays
[AD-751667] N73-16748

BORDEN, G. J.

The landing signal officer: Display requirements for ACLS recoveries
[AD-751076] N73-16635

BORE, G. J.

A dynamic helicopter performance and control model
[AD-751460] N73-16022

BOBODIN, V. T.

Control of aircraft and helicopter flight A73-20381

BRAY, R. S.

Vertical motion requirements for landing simulation
[NASA-TM-X-62236] N73-17020

BROWN, K. R.

The pre-flight handling of inertial navigation systems. A73-19347

BURKE, J. J.

Understanding Kalman filtering and its application in real time tracking systems
[AD-751485] N73-16634

BURNS, B. R. A.

Design considerations for the satisfactory stability and control of military combat aeroplanes N73-16996

BUXBAUM, O.

A relation between measured center of gravity vertical accelerations and the loads at the T-tail of a military airplane N73-16904

C

CADWELL, J. H.

Fabric properties and the wear of hovercraft fingers
[RAE-TR-71210] N73-17654

CARICO, D.

A dynamic helicopter performance and control model
[AD-751460] N73-16022

CARLSON, J. W.

Prediction of aeroelastic hinge moment effects on stability and controllability N73-17006

CARLSON, N. A.

PFI (Pilot Warning Indicators) systems survey
[PB-212496] N73-16020

CERCIGNANI, C.

Models for gas surface interactions and computation of aerodynamic coefficients
[AD-752245] N73-17278

CHANG, H.

Analytical study of inflight thrust reversers, volume 1
[AD-751525] N73-16784

Analytical study of inflight thrust reversers.

Volume 2: User's manual and source listings for computer programs
[AD-751526] N73-16785

CHARPIN, P.

Icing testing in the large Modane wind-tunnel on full-scale and reduced scale models A73-20244

CHEN, A. W.

Multiple element airfoils optimized for maximum lift coefficient. A73-19956

CHERANOVSKII, O. R.

Measurement of the pressure distribution at the surface of an aerodynamic body using a special interrogator. A73-21180

CHERRY, D. G.

Highly loaded multi-stage fan drive turbine-cascade test program
[NASA-CR-2171] N73-16778

CHERTKOV, I. A. B.

Vapor pressure of supersonic aircraft fuels A73-20014

CLAY, L. E.

T-38 structural flight loads data for June 1970 - December 1971
[AD-751968] N73-17025

CLEMENT, J. M.

Contribution to the study of the total energy. III A73-21656

CLEMENTS, T. R.

Effect of fuel zoning and fuel nozzle design on pollution emissions at ground idle conditions for a double-annular ram-induction combustor
[NASA-CR-121094] N73-17916

COLE, G. L.

Performance comparison of three normal-shock position sensors for mixed-compression inlets
[NASA-TM-X-2739] N73-17817

CONWAY, J. A.

A description of two low cost turbo-compressors built for powered lift research. A73-19942

COOK, W. L.

A summary of wind tunnel research on tilt-rotors from hover to cruise flight.
[ONERA, TP NO. 1133] A73-21683

COSTELLO, J. P., II

Smoke and helium bubble visualization studies of incompressible flow past a jet-flap airfoil
[AD-752012] N73-17270

CREWS, S. T.

Model tests on unsteady rotor wake effects. A73-19191

CULLEY, M.

A side mounted supersonic intake and the problem of three dimensional boundary layer separation
[ARL/NE-137] N73-16981

CUNNINGHAM, J. P.

Properties and limitations of liquid crystals for aircraft displays
[AD-751667] N73-16748

D

DANILEIKO, G. I.

Design principles of aircraft engines, chapters 1-5
[AD-751510] N73-16783

DANOVICH, J. P.

Investigation of the effects of liquid oxygen on chemically treated surfaces of aluminum tubing
[AD-752030] N73-17661

DEJESUS, C.

The effect of injection on base drag at transonic speed
[AD-751269] N73-15991

DELANEY, C.

Fire detection system performance in USAF aircraft
[AD-751346] N73-16025

DEGLER, R. P.

Experimental investigation of aerodynamic performance of cooled turbine vanes at gas- to coolant-temperature ratios up to 2.75
[NASA-TM-X-2733] N73-17815

PERSONAL AUTHOR INDEX

POMBOHNE, P.

- DEQUE, R.
Utilization of black boxes for improving the characteristics of pilotage during the aircraft development phase
N73-17013
- DEVRIESE, J.
Olympus in Concorde /Twenty-fifth Louis Bleriot Lecture/.
A73-21687
- DIEHL, L. A.
Measurement of gaseous emissions from an afterburning turbojet engine at simulated altitude conditions
[NASA-TN-X-2726]
N73-17921
- DIETRICH, D. A.
Experimental performance of cascade thrust reversers at forward velocity
[NASA-TN-X-2665]
N73-16773
- DOAK, P. E.
Analysis of internally generated sound in continuous materials. III - The momentum potential field description of fluctuating fluid motion as a basis for a unified theory of internally generated sound.
A73-19097
- DOBEK, L. J.
Labyrinth seal testing for lift fan engines
[NASA-CR-121131]
N73-16524
- DOE, G. T. S.
Damping configurations that have a stabilizing influence on nonconservative systems.
A73-19088
- DONHEISER, A. D.
Civil aviation development - A policy and operations analysis.
A73-21837
- DORSCH, R.
Acoustic results obtained with upper-surface-blowing lift-augmentation systems.
A73-20458
- DORSCH, R. G.
The effect of nozzle inlet shape, lip thickness, and exit shape and size on subsonic jet noise
[NASA-TN-X-68182]
N73-16655
- DUDDY, J. H.
High performance helicopter hoist program
[AD-751217]
N73-16029
- DUKES, T. A.
Helicopter station keeping
[AD-751459]
N73-16021
- DURBIN, E. J.
A dynamic helicopter performance and control model
[AD-751460]
N73-16022
- DUSTIN, M. O.
Performance comparison of three normal-shock position sensors for mixed-compression inlets
[NASA-TN-X-2739]
N73-17817
- DUVVURI, T.
Analytical study of inflight thrust reversers, volume 1
[AD-751525]
N73-16784
Analytical study of inflight thrust reversers. Volume 2: User's manual and source listings for computer programs
[AD-751526]
N73-16785
- EIDENMILLER, B. L.
The effects of local meteorological factors upon aircraft noise measurements
[FAA-RD-72-145]
N73-16651
- EL-RABLY, Z.
Aircraft trailing vortices: A survey of the problem
[HB/A-72-1]
N73-17247
- EMMIL, H. V.
An investigation of the intensity of turbulence in the region of the inflow of a jet of secondary air into the firing tube of a gas turbine engine chamber.
A73-19625
- EPFRIGHT, B. R., JR.
Theoretical effects of porosity and angle of attack on jet stretcher performance
N73-16215
- ERICKSON, R. E.
Ground based CAS versus Airborne CAS.
A73-18900
- ERMOLENKO, S. D.
Calculation of the aerodynamic characteristics of a rectangular wing with tip plates moving at a low subsonic speed in the proximity of a screen
A73-20094
- ESHELBY, M. E.
A comparative assessment of three methods of measurement of pressure error corrections
[CRANFIELD-AERO-11]
N73-17570
- EVANS, J. E.
Diversity techniques for airborne communications in the presence of ground reflection multipath
[AD-752249]
N73-17178
- F
- FAIL, R.
The role of free-flight models in aircraft research and development
N73-17002
- FASSO, G.
Icing testing in the large Modane wind-tunnel on full-scale and reduced scale models
A73-20244
- FAULKNER, F. E.
Analytical investigation of chord size and cooling methods on turbine blade cooling requirements. Book 1: Sections 1 through 8 and appendixes A through I
[NASA-CR-120882-BK-1]
N73-17809
Analytical investigation of chord size and cooling methods on turbine blade cooling requirements. Book 2: Appendixes J through M
[NASA-CR-120882]
N73-17810
- FEHLNER, L. F.
A precision position and time service for the air traffic of the future.
A73-19350
- FELDMAN, B. L.
Design principles of aircraft engines, chapters 1-5
[AD-751510]
N73-16783
- FERRETTI, G.
Considerations on the manual flight control design of a military transport aircraft
N73-17007
- FILIP, J.
Hydraulic systems of modern aircraft. II
A73-19604
- FILISSETTI, A.
Considerations on the manual flight control design of a military transport aircraft
N73-17007
- FINCHUM, J. A., JR.
Expectation of contract incentives.
A73-20958
- FINK, H. P.
The effects of configuration changes on the aerodynamic characteristics of a full-scale mockup of a light twin engine airplane
[NASA-TN-D-6896]
N73-16012
- FLANDERS, J. H.
PWI (Pilot Warning Indicators) systems survey
[PB-212496]
N73-16020
- FLAY, A. H.
Cost and economic factors in aerospace system development.
A73-20394
- FLOCK, W. L.
Flight safety aspects of precision radar near air bases in bird-aircraft collision avoidance
[AD-751985]
N73-17168
- FOLCHINI, A.
A proposed design for the construction of a VTOL simulator
A73-21249
- FOLEY, H. H.
Stratospheric nitric oxide production from past nuclear explosions and its relevance to projected SST pollution
[AD-751295]
N73-16466
- FOMBOHNE, P.
Evolution and actual aspect of air navigation
A73-21088

E

FRANKLIN, J. A.

PERSONAL AUTHOR INDEX

- FRANKLIN, J. A.
Pitch attitude, flight path, and airspeed control during approach and landing of a powered lift STOL aircraft
[NASA-TN-X-62203] N73-16014
- FRASER, R. C.
Civil aviation development - A policy and operations analysis. A73-21837
- FRIEDMANN, P.
Investigation of some parameters affecting the stability of a hingeless helicopter blade in hover
[NASA-CN-114525] N73-16015
- FRIEDRICH, H.
Study of flight dynamics using problem oriented program languages
[BMVG-FBWT-72-21] N73-16019
- FRY, R. B.
A piloted simulation study of the effects of controller force gradient in VTOL hovering flight
[NASA-TN-X-62230] N73-17015
- FUKUI, K.
Predicting light flashes due to alpha-particle flux on SST planes. A73-20157

G

- GABEL, B. K.
How practical are lab-oriented solid film lubricants. A73-19554
- GAEHMAN, G.
Environmental temperature and aircraft compatibility studies
[AD-752018] N73-17023
- GARG, D. P.
Nonlinear and finite pad length performance of vehicle air cushion suspensions
[PB-212705] N73-16226
- GEISSLER, W.
Calculation of the potential flow about axisymmetrical fuselages, annular profiles, and propulsion system inlets A73-19205
- GERDES, R. M.
A piloted simulation study of the effects of controller force gradient in VTOL hovering flight
[NASA-TN-X-62230] N73-17015
- GETTIER, C. A.
ATCRBS performance analysis for New York Air Route Traffic Control Center
[ECAC-PB-72-031] N73-16630
- GILBERT, R. R.
High performance helicopter hoist program
[AD-751217] N73-16029
- GILYARD, G. B.
Explicit determination of lateral-directional stability and control derivatives by simultaneous time vector analysis of two maneuvers
[NASA-TN-X-2722] N73-16010
Flight test experience in aircraft parameter identification N73-17012
- GOLDSTEIN, M. R.
New aspects of subsonic aerodynamic noise theory
[NASA-TN-D-7158] N73-16654
- GOON, W.
Environmental temperature and aircraft compatibility studies
[AD-752018] N73-17023
- GORBUNOV, G. M.
An investigation of the intensity of turbulence in the region of the inflow of a jet of secondary air into the firing tube of a gas turbine engine chamber. A73-19625
- GRANDE, M.
A proposed design for the construction of a VTOL simulator A73-21249
- GREEN, R. L.
Evaluation of Harvey aluminum 1- by 12-ft extruded light duty landing mat with symmetrical butt type end connectors
[AD-752079] N73-17233

- GREENWOOD, D. P.
The scattering from rough curved surfaces of a wave propagated through a random medium N73-17159
- GREER, H. D.
The effects of configuration changes on the aerodynamic characteristics of a full-scale mockup of a light twin engine airplane
[NASA-TN-D-6896] N73-16012
- GRUNDY, P. A.
PWI (Pilot Warning Indicators) systems survey
[PB-212496] N73-16020
- GUDKOV, A. I.
Methods and equipment for in-flight aircraft strength tests A73-20376
- GUIRAUD, J.-P.
Flow in the vicinity of a trailing edge A73-21495
- GUSTAVSSON, L.
A computer program for the prediction of aerodynamic characteristics of wing-body-tail combinations at subsonic and supersonic speeds, part 2
[PPA-AU-635-PT-2] N73-16985
- GUTIERREZ, O. A.
The effect of nozzle inlet shape, lip thickness, and exit shape and size on subsonic jet noise
[NASA-TN-X-68182] N73-16655

H

- HAAS, J. E.
Effect of reducing rotor blade inlet diameter on the performance of a 11.66-Centimeter radial-inflow turbine
[NASA-TN-X-2730] N73-17039
- HADLOW, H. E.
Superconducting a.c. machines - An approach to development. A73-20407
- HALL, W. B.
Computational methods for the synthesis of rotary wing VTOL aircraft control systems N73-15994
- HARMOND, D. C., JR.
Analytical predictions of emissions from and within an Allison J-33 combustor. A73-21670
- HANSON, P. W.
Evaluation of an aeroelastic model technique for predicting airplane buffet loads
[NASA-TN-D-7066] N73-16905
- HARABEDIAN, A.
The landing signal officer: Display requirements for ACLS recoveries
[AD-751076] N73-16635
- HARDY, R. J.
Formula one air racing. A73-21689
- HAVILL, C. D.
Study of buoyancy systems for flight vehicles
[NASA-TN-X-62168] N73-17014
- HAYDEN, J. T.
Superconducting generators for aircraft. A73-20408
- HAYFIELD, C. P.
The capacity of a single-runway S.T.O.L./R.T.O.L. airport. A73-19352
- HAZELHURST, R. H.
Welding airframe structures in titanium alloys using tensile loading as a means of overcoming distortion. A73-21240
- HEARD, J. L.
Study of a highly reliable pilot's vertical display system
[AD-752510] N73-17026
- HEINRICH, H. G.
A linearised theory of parachute opening dynamics. A73-21692
- HELTSLLEY, F. L.
Simulation of a high disc loading free propeller in a cross flow by the vortex-lattice method
[AD-751463] N73-16274

PERSONAL AUTHOR INDEX

KENTON, B. H.

- HELVEY, M. R.
High performance helicopter hoist program
[AD-751217] N73-16029
- HERLIN, H. A.
Advanced electronic technology
[AD-751308] N73-16758
- HEROLD, A. C.
A two-dimensional, iterative solution for the jet
flap
[NASA-CR-2190] N73-15986
- HILL, R.
The feasibility of burner-can burn-through thermal
detection prior to engine case rupture
[FAA-NA-72-92] N73-16772
- HOFFMAN, H. A.
Equations of motion for the X-14 Aircraft, phase 2
study
[NASA-CR-130760] N73-16988
- HOHENEMSER, K. H.
Model tests on unsteady rotor wake effects.
A73-19191
- HOLLA, V. S.
Conically cambered triangular wings with reflex
spanwise curvature.
A73-20938
- HOLLINGSWORTH, E. G.
Subsonic characteristics of a twin-jet swept-wing
fighter model with maneuvering devices
[NASA-TN-D-6921] N73-15988
- HOLLISTER, W. H.
Distributed control of air traffic.
A73-20600
- HOLT, D. J.
Circulation control by steady and pulsed blowing
for a cambered elliptical airfoil
[AD-751045] N73-15992
- HOLZMAN, J. K.
Design and flight testing of a nullable compressor
face rake
[NASA-TN-D-7162] N73-16247
- HOWE, D.
Aeroplane design study STOL airliner (A71). Part
1: Configuration description and data
[CRANFIELD-AERO-12-PT-1] N73-17019
- HOWES, W. L.
New aspects of subsonic aerodynamic noise theory
[NASA-TN-D-7158] N73-16654
- HOFF, E.
A study on aircraft map display location and
orientation
[NASA-TN-X-62198] N73-17223
- HUGGARD, R. P.
ATE support software system concept.
A73-20687
- HUGHES, W. H.
How can we use area navigation in the terminal area.
A73-19351
- HUMPHREYS, D. R.
Design for improvements to static performance and
lateral-directional dynamic stability of a
constant attitude light aircraft
N73-15996
- ILIFF, K. W.
Flight test experience in aircraft parameter
identification
N73-17012
- IMMONEN, E.
An investigation into wind shear at Helsinki Airport
[TR-3] N73-17676
- INGERO, B. D.
High-pressure combustor exhaust emissions with
improved air-atomizing and conventional
pressure-atomizing fuel nozzles
[NASA-TN-D-7154] N73-16929
- INNIS, R. C.
Pitch attitude, flight path, and airspeed control
during approach and landing of a powered lift
STOL aircraft
[NASA-TN-X-62203] N73-16014
- IWATAKI, H.
Visual considerations concerning approach lights
[NASA-TT-P-14667] N73-17710
- JACOBSEN, E. H.
High performance helicopter hoist program
[AD-751217] N73-16029
- JARVINEN, P. O.
Aircraft wing-tip vortex modification.
A73-19193
- JEFFERIS, R. P.
A portable instrumentation kit feasibility study
[AD-751188] N73-16514
- JONES, R. E.
Comparison of combustion characteristics of ASTM
A-1, propane, and natural-gas fuels in an
annular turbojet combustor
[NASA-TN-D-7135] N73-16771
- JONES, W. P.
Flow in the wake of a cascade of oscillating
airfoils.
A73-19954
- JOWITT, P. P.
The corrosion problem in aircraft structures.
A73-20452
- JUNE, R. B.
Residual stress alleviation of aircraft metal
structures reinforced with filamentary composites
[NASA-CR-112207] N73-17900
- KANSAKU, H.
Visual considerations concerning approach lights
[NASA-TT-P-14667] N73-17710
- KAO, H. C.
V/STOL aircraft aerodynamic prediction methods
investigation. Volume 1: Theoretical
development of prediction methods
[AD-752557] N73-17033
- V/STOL aircraft aerodynamic prediction methods
investigation. Volume 2: Application of
prediction methods
[AD-752558] N73-17034
- V/STOL aircraft aerodynamic prediction methods
investigation. Volume 3: Manual for computer
programs
[AD-752559] N73-17035
- V/STOL aircraft aerodynamic prediction methods
investigation. Volume 4: Literature survey
[AD-752563] N73-17036
- KAPUSTIN, L. N.
Design principles of aircraft engines, chapters 1-5
[AD-751510] N73-16783
- KARIMOVA, A. G.
Investigation of the heat transfer between the gas
and casing in the area of the apertures between
the nozzle diaphragm blades and guide vanes of
turbines
A73-20086
- KASSEBOHM, W.
Air traffic control problems from the controller's
point of view
[DGLR-PAPER-72-038] N73-16632
- KASSEL, C. E.
Investigations of MLS conventional and Doppler
scanning beam techniques
[AG-5011-B-1] N73-16628
- KAUTZ, R. P.
Test plan report for catapult fatigue test of the
model C-2a airplane
[AD-752493] N73-17028
- KELLEY, C. E.
Predictive and adaptive processes in the control
of Air Force systems
[AD-751306] N73-16026
- KELLEY, G. R.
The landing signal officer: Display requirements
for ACLS recoveries
[AD-751076] N73-16635
- KELLY, J. B.
Residual stress alleviation of aircraft metal
structures reinforced with filamentary composites
[NASA-CR-112207] N73-17900
- KEENEY, J. W.
Test techniques for advanced avionics displays.
A73-20683
- KENTON, B. H.
Implementation of a fixed base spin simulator
[AD-751644] N73-16229

KERNEY, K. P.

PERSONAL AUTHOR INDEX

KERNEY, K. P.

A correction to 'lifting-line theory as a singular perturbation problem.'

A73-19964

KERR, R. I.

Optimisation in construction of the Jaguar and other military aircraft.

A73-20947

KHALATOV, I. U. M.

A possible approach to the probabilistic estimation of the vibration strength of turbomachine components

A73-20502

KHRISTOPOROV, I. L.

An investigation of the intensity of turbulence in the region of the inflow of a jet of secondary air into the firing tube of a gas turbine engine chamber.

A73-19625

KING, T. T.

F-111 crack-propagation sensitivity analyses [AD-752223]

N73-17024

KIOCK, R.

The effect of the degree of turbulence on the aerodynamic characteristics of planar decelerating cascades

A73-19197

KIRKBY, W. T.

Some effects of change in spectrum severity and spectrum shape on fatigue behaviour under random loading

N73-16898

KISSEL, G. K.

Powered controls, influence on stability and maneuverability

N73-17008

KLEIN, A.

India's wind tunnels

A73-20249

KLEUTERS, W.

Recent studies on meteorological icing parameters [HBB-UH-11-72-0]

N73-16016

KLINE, J. P.

Two-dimensional cascade test of a highly loaded, low-solidity, tandem airfoil turbine rotor blade [NASA-TM-X-2729]

N73-17814

KLUG, H. G.

Influence of airworthiness regulations on takeoff and landing performance of QSTOL aircraft [HBB-UH-13-72-0]

N73-16018

KOCH, B. W.

Study of the sensitivity of nitroglycerin to weak shock waves (supersonic aircraft bangs) [ISL-14/72]

N73-16658

KOFSKEY, H. G.

Effect of a reduction in blade thickness on performance of a single stage 20.32 centimeter mean diameter turbine [NASA-TM-D-7128]

N73-16776

Effect of reducing rotor blade inlet diameter on the performance of a 11.66-Centimeter radial-inflow turbine [NASA-TM-X-2730]

N73-17039

KOHL, W.

Study of flight dynamics using problem oriented program languages [BHV-G-PBWT-72-21]

N73-16019

KOLOBOVA, P. M.

Vapor pressure of supersonic aircraft fuels

A73-20014

KOOPMAN, B. O.

Air-terminal queues under time-dependent conditions.

A73-20375

KORDZINSKI, W.

Development trends in aircraft-engine compressor design methods. III

A73-19605

KOSTICHEV, G. I.

Flight control with incomplete information.

A73-20077

KOZIN, C. H.

ATE support software system concept.

A73-20687

KOZLOVSKII, V. I.

Problems of passenger aircraft design

A73-20377

KRISHNASWAMY, T. N.

Conically cambered triangular wings with reflex spanwise curvature.

A73-20938

KUDELSKI, R.

System for in-flight recording of the rotational speed of the turbine of a jet engine

A73-20546

KUENZLI, E. W.

Design parameters for torsion of sandwich strips having trapezoidal, rectangular, and triangular cross sections [AD-752619]

N73-17029

L

LANAB, W. E.

Handling qualities criteria and requirements

N73-16993

LAUER, D. T.

The utility of a low flying aircraft or helicopter when collecting ground data for regional resource surveys.

A73-21710

LAWSON, L. J.

High performance helicopter hoist program [AD-751217]

N73-16029

LEMONON, C.

Applications of the infrared to navigation

A73-21087

LESHAKOV, P. S.

Methods and equipment for in-flight aircraft strength tests

A73-20376

LEVY, D.

Calculation of the reliability of electronic components in an 'aeronautics' environment shaped by the operational service routines of onboard equipment devices used by Air France

A73-19403

LEYMAN, C. S.

The effect of engine failure at supersonic speeds on a slender aircraft: Predicted and actual

N73-17003

LISSAMAN, P. B. S.

Analysis of high-aspect-ratio jet-flap wings of arbitrary geometry [NASA-CR-2179]

N73-16982

LJUNGSTROM, B. L. G.

Boundary layer studies on a two dimensional high lift wing [FAA-AU-862]

N73-16984

LJUNGSTROM, O.

Mass air travel is definitely possible

A73-20618

LOCKWOOD, K. A. J.

A description of two low cost turbo-compressors built for powered lift research.

A73-19942

LOKAI, V. I.

Investigation of the heat transfer between the gas and casing in the area of the apertures between the nozzle diaphragm blades and guide vanes of turbines

A73-20086

LOKSHANOV, E. A.

A possible approach to the probabilistic estimation of the vibration strength of turbomachine components

A73-20502

LONGSTREET, C. S.

Ultrasonic transmission investigations for turbine inlet gas temperature measurement [AD-752602]

N73-17822

LOSCUTOFF, W. V.

Equations of motion for the X-14 Aircraft, phase 2 study [NASA-CR-130760]

N73-16988

LOWNDES, E. B.

Correlation between laboratory tests and service experience

N73-16901

LUIDENS, R. W.

Experimental performance of cascade thrust reversers at forward velocity [NASA-TM-X-2665]

N73-16773

M

- MARSAN, A.
Calculation of induced load by variation in course during any maneuver. N73-17004
- MARSHALL, R. T.
Modeling of airplane performance from flight-test results and validation with an F-104G airplane [NASA-TN-D-7137] N73-16008
- MCAULAY, R. J.
A theory for optimal Moving Target Indicator (MTI) digital signal processing, supplement 1 [AD-751923] N73-17170
- MCCARTY, T. A.
A precision position and time service for the air traffic of the future. A73-19350
- MCKINLAY, W. H.
The pre-flight handling of inertial navigation systems. A73-19347
- MCHANUS, H.
P-111 crack-propagation sensitivity analyses [AD-752223] N73-17024
- MCWHORTER, A. L.
Advanced electronic technology [AD-751308] N73-16758
- MEDVEDEV, M. G.
Designing turbomachine blades for forced vibrations under various excitation conditions A73-20503
- MEGRILL, J. L.
The effects of configuration changes on the aerodynamic characteristics of a full-scale mockup of a light twin engine airplane [NASA-TN-D-6896] N73-16012
- MEGSON, T. H. G.
Aircraft structures for engineering students. A73-21839
- MELLOR, A. H.
Emissions from and within an Allison J-33 combustor. A73-20359
Analytical predictions of emissions from and within an Allison J-33 combustor. A73-21670
- MESNIERE, H.
Influence of the mass and mass distribution on flying qualities N73-16998
- METHLIE, J. B.
The influence of lubricants on turbine engine design. A73-19563
- MEZELUNIAN, B. A.
Nonstationary load distribution on an arbitrary-planform wing in supersonic motion A73-21725
- MILILLO, J. B.
Post-stall testing of aircraft with a wind tunnel captive system [AD-751461] N73-16023
- MILLER, J. H.
Subsonic performance potential of ramjets and ejector ramjets [AD-751317] N73-16781
- MILLER, S. C.
Study of V/STOL aircraft implementation. Volume 2: Appendices [NASA-CR-114518] N73-16009
- MILLER, T. G., JR.
Civil aviation development - A policy and operations analysis. A73-21837
- MILLER, W. B.
Correlation between laboratory tests and service experience N73-16901
- MILLER, W. D.
The experimental data processor. A73-19183
- MINNER, G. L.
Low-frequency rear quadrant noise of a turbojet engine with exhaust duct muffling [NASA-TN-X-2718] N73-16011

- MIURA, H.
An optimal configuration design of lifting surface type structures under dynamic constraints N73-15997
- MOELKER, J. J. P.
Summary of AGARD meeting on Problems of the Cockpit Environment, November 1968 in Amsterdam, Netherlands N73-16990
- MOHR, D. J.
Aircraft transition algorithm for conflict prediction, with specific reference to the North Atlantic air traffic control system [UTIAS-TN-183] N73-17708
- MONTREY, H. H.
Design parameters for torsion of sandwich strips having trapezoidal, rectangular, and triangular cross sections [AD-752619] N73-17029
- MOORE, J. A.
Flow in the wake of a cascade of oscillating airfoils. A73-19954
- MORIKAWA, Y.
Aerodynamic characteristics of thin asymmetric wing profiles in supersonic flow A73-20487
- MORISSET, J.
ONERA will put a large anechoic chamber with a wind tunnel in service in 1975 A73-21529
- MOSES, H. C.
Engineering and development program plan: Air traffic control surveillance radar [FAA-ED-02-1] N73-17163
- MUNSER, H.
Study of flight dynamics using problem oriented program languages [BMVG-PBWT-72-21] N73-16019
- MYER, D. P.
Circulation control by steady and pulsed blowing for a cambered elliptical airfoil [AD-751045] N73-15992
- N
- NAKABE, K.
Aerodynamic characteristics of thin asymmetric wing profiles in supersonic flow A73-20487
- NAKAMURA, K.
Aerodynamic characteristics of thin asymmetric wing profiles in supersonic flow A73-20487
- NAUMANN, H. G. W.
Unsteady airfoil theory applied to cambered blades and to blade rows of high solidity N73-15983
- NAYLOR, F. R.
Recent advances and applications in the prediction of pilot acceptance of aircraft flying qualities. A73-20586
- NEIGHBOR, T. L.
Handling qualities criteria and requirements N73-16993
- NEISS, J. A.
Study of V/STOL aircraft implementation. Volume 2: Appendices [NASA-CR-114518] N73-16009
- NELSON, W. G.
Development and testing of improved polyimide actuator rod seals at higher temperatures for use in advanced aircraft hydraulic systems [NASA-CR-121124] N73-17592
- NEUMAN, F.
Generalize aerodynamic coefficient table storage, checkout and interpolation for aircraft simulation [NASA-TN-X-62229] N73-16983
- NICHOLLS, B. H.
A secondary power system study for advanced rotary-wing aircraft [AD-751854] N73-17046
- HORGREN, C. T.
High-pressure combustor exhaust emissions with improved air-atomizing and conventional pressure-atomizing fuel nozzles [NASA-TN-D-7154] N73-16929

MUSBAUM, W. J.

PERSONAL AUTHOR INDEX

MUSBAUM, W. J.

Effect of a reduction in blade thickness on performance of a single stage 20.32 centimeter mean diameter turbine
[NASA-TN-D-7128] N73-16776

O'HAGAN, M.

The Aeronautical Satellite Programme - ATC aspects.
A73-19141

OLSEN, W. A.

The effect of nozzle inlet shape, lip thickness, and exit shape and size on subsonic jet noise
[NASA-TN-X-68182] N73-16655

ORNSBEE, A. I.

Multiple element airfoils optimized for maximum lift coefficient.
A73-19956

OSBORNE, C.

Unsteady thin-airfoil theory for subsonic flow.
A73-20718

P

PAPANIA, R., JR.

Field test of warm fog dispersal system to support Marine Corps helicopter operations
[AD-752046] N73-17694

PARKER, L. W.

Godunov method and computer program to determine the pressure and flow field associated with a sonic boom focus
[NASA-CR-2127] N73-16013

PARKER, R. L., JR.

Simulation of a high disc loading free propeller in a cross flow by the vortex-lattice method
[AD-751463] N73-16274

PAVLENKO, V. P.

Use of composite materials in aircraft structures
[NASA-TT-P-14648] N73-16576

PAYNE, G. A.

Design and flight testing of a nullable compressor face rake
[NASA-TN-D-7162] N73-16247

PERLMAN, M.

Investigation of the effects of liquid oxygen on chemically treated surfaces of aluminum tubing
[AD-752030] N73-17661

PERRINDEBRICHANBAUT, C.

Observation and measurement of visibility at the ground.
N73-16598

PESHKOV, A. V.

An investigation of the intensity of turbulence in the region of the inflow of a jet of secondary air into the firing tube of a gas turbine engine chamber.
A73-19625

PHILIPP, L.

Study of the sensitivity of nitroglycerin to weak shock waves (supersonic aircraft bangs)
[ISL-14/72] N73-16658

PHIBNEY, R. E.

Distortion of near-sonic shocks by weakly turbulent layers
[AD-752472] N73-17279

PHOA, Y. T.

A computerized flutter solution procedure.
A73-20214

PINSKE, W. J. G.

The role of theory and calculations in the refinement of flying qualities
N73-16999

PIVA, R.

The effect of injection on base drag at transonic speed
[AD-751269] N73-15991

PODGORNOV, V. A.

Investigation of the heat transfer between the gas and casing in the area of the apertures between the nozzle diaphragm blades and guide vanes of turbines
A73-20086

POISSON-QUINTON, PH.

A summary of wind tunnel research on tilt-rotors from hover to cruise flight.
[ONERA, TP NO. 1133] A73-21683

PONOMAREV, A. T.

Use of composite materials in aircraft structures
[NASA-TT-P-14648] N73-16576

POPE, R. E.

The design of stability augmentation systems for decoupling aircraft responses
[NASA-CR-130543] N73-17021

PORTENIER, W. J.

Study of V/STOL aircraft implementation. Volume 2: Appendices
[NASA-CR-114518] N73-16009

POST, S. E.

Computer programs for estimation of STOL takeoff, landing, and static performance
[NASA-TN-X-62217] N73-16007

POWER, L. J.

Application of modern control theory to the design of optimum aircraft controllers
[NASA-TN-X-62208] N73-17016

PRICE, S. P. E.

Benefit-cost analysis of delay reduction with STOL.
[ASCE PREPRINT 1507] A73-21000

PRIOR, B. W.

Analytical study of inflight thrust reversers, volume 1
[AD-751525] N73-16784

Analytical study of inflight thrust reversers. Volume 2: User's manual and source listings for computer programs
[AD-751526] N73-16785

PROSHAK, W. J.

On a particular case of conformal representation of multiconnected domains.
A73-20200

PUL'ER, I. U. M.

Onboard distance-measuring systems
A73-20378

PULLEN, D. A. W.

Moving radiography.
A73-20451

PUTZ, L.

Collection and processing of data for the establishment of route charges.
A73-19182

R

RAINEY, A. G.

Active control of aeroelastic response
N73-17005

RANACHANDRA, S. M.

Conically cambered triangular wings with reflex spanwise curvature.
A73-20938

RANSAYER, K.

Air traffic control by programmed navigation.
A73-19349

RAY, E. J.

Subsonic characteristics of a twin-jet swept-wing fighter model with maneuvering devices
[NASA-TN-D-6921] N73-15988

REED, J. E.

Systems for collision avoidance.
A73-18899

REHAUDIE, J. P.

Aeroelastic effects from a flight mechanics stand point
N73-16991

RESHOTKO, M.

Acoustic results obtained with upper-surface-blowing lift-augmentation systems.
A73-20458

REVELL, J. D.

Research on unsteady transonic flow theory
[NASA-CR-112114] N73-17258

RICKS, R. G.

Use of the finite element damped forced response strain energy distribution for vibration reduction
[AD-751809] N73-16027

RIDENOUR, A. E.

Automated radar terminal systems /ARTS/.
A73-19184

RIVERS, W. T.

A portable instrumentation kit feasibility study
[AD-751188] N73-16514

- ROBINSON, E. D.
Development and testing of improved polyimide actuator rod seals at higher temperatures for use in advanced aircraft hydraulic systems [NASA-CR-121124] N73-17592
- ROCKAFELLOW, R. I.
T-38 structural flight loads data for June 1970 - December 1971 [AD-751968] N73-17025
- ROGACHEV, G. V.
Calculation of the aerodynamic characteristics of a rectangular wing with tip plates moving at a low subsonic speed in the proximity of a screen A73-20094
- ROGERS, L. C.
Bi-normal coordinates in discrete systems with application to an aircraft shimmy problem [AD-752548] N73-17030
- ROGOSIN, I. A.
Calculation of the aerodynamic characteristics of a rectangular wing with tip plates moving at a low subsonic speed in the proximity of a screen A73-20094
- ROSSOW, V. J.
Conformal mapping for potential flow about airfoils with attached flap. A73-19192
- ROTHWELL, T. L.
AUTOMATE - A self-contained automatic test system. A73-20680
- ROTVEL, F.
On residual stresses during random load fatigue N73-16902
- RUDEMAN, M. A.
Stratospheric nitric oxide production from past nuclear explosions and its relevance to projected SST pollution [AD-751295] N73-16466
- RUDISILL, C. S.
Second derivatives of the flutter velocity and the optimization of aircraft structures. A73-19952
- RUHLIN, C. L.
Active control of aeroelastic response N73-17005
- RUSSELL, T. E.
The influence of lubricants on turbine engine design. A73-19563
- RUTH, R.
High performance helicopter hoist program [AD-751217] N73-16029
- RYL'SKII, G. I.
Control of aircraft and helicopter flight A73-20381
- S**
- SACHS, G.
The effects of thrust characteristics on longitudinal stability in supersonic flight N73-16997
- SANDFORD, M. C.
Active control of aeroelastic response N73-17005
- SANGER, H. L.
Analytical study on a two-dimensional plane of the off-design flow properties of tandem-bladed compressor stators [NASA-TN-X-2734] N73-16986
- SATO, J.
On peaky airfoil sections [NASA-TT-F-749] N73-15987
- SCAGGS, H. E.
Shock detachment from the leading edge of delta wings [AD-752206] N73-17271
- SCHAEFER, G.
A flight control system for STOL aircraft. A73-20171
- SCHAIERER, J.
An investigation of helicopter transmission noise reduction by vibration absorbers and damping [AD-752579] N73-17031
- SCHIJVE, J.
The accumulation of fatigue damage in aircraft materials and structures N73-16899
- Effects of test frequency on fatigue crack propagation under flight-simulation loading N73-16900
- SCHLOTTHANN, F.
The steady and unsteady aerodynamic coefficients for the rolling motion of slender wings A73-19578
- SCHOENHART, R. L.
Fly-by-wire and artificial stabilization design N73-17009
- SCHROERS, L. G.
Considerations for stability and control of V/STOL aircraft: A review of AGARD report 577 N73-16994
- A piloted simulation study of the effects of controller force gradient in VTOL hovering flight [NASA-TN-X-62230] N73-17015
- SCHUETZ, W.
The fatigue life under three different load spectra - Tests and calculations N73-16903
- SCHURINGA, T.
Adjustment of flying qualities by wind tunnel testing N73-17000
- SCHWEIKHARD, W. G.
Modeling of airplane performance from flight-test results and validation with an F-104G airplane [NASA-TN-D-7137] N73-16008
- SCHWENDEHANN, H. F.
V/STOL aircraft aerodynamic prediction methods investigation. Volume 1: Theoretical development of prediction methods [AD-752557] N73-17033
- V/STOL aircraft aerodynamic prediction methods investigation. Volume 2: Application of prediction methods [AD-752558] N73-17034
- V/STOL aircraft aerodynamic prediction methods investigation. Volume 3: Manual for computer programs [AD-752559] N73-17035
- V/STOL aircraft aerodynamic prediction methods investigation. Volume 4: Literature survey [AD-752563] N73-17036
- SCHY, A. A.
Nonlinear programming in design of control systems with specified handling qualities. A73-20588
- SCIARBA, J. J.
Use of the finite element damped forced response strain energy distribution for vibration reduction [AD-751809] N73-16027
- SCOTLAND, R. L.
The effect of engine failure at supersonic speeds on a slender aircraft: Predicted and actual N73-17003
- SCULLY, H. P.
Helicopter rotor wake geometry and airloads and helicopter rotor wakes [AD-752628] N73-17032
- SEEBAUER, W. E.
Hypersonic flows in large-scale inlet models. A73-19189
- SEEVERS, J. A.
Equations of motion for the X-14 Aircraft, phase 2 study [NASA-CR-130760] N73-16988
- SHAW, H.
Fuel modification for abatement of aircraft turbine engine oxides of nitrogen emissions [AD-752581] N73-17803
- SHEBIN, V. H.
Problems of passenger aircraft design A73-20377
- SHIELDS, J.
Air traffic control systems interference considerations [ECAC-PR-72-008] N73-16629
- SHIFRIN, E. G.
Problem of uniform jet flow around an airfoil [NASA-TT-F-14813] N73-17259
- SHIVERS, J. P.
The effects of configuration changes on the aerodynamic characteristics of a full-scale mockup of a light twin engine airplane [NASA-TN-D-6896] N73-16012

SHNAIDER, B. D.

PERSONAL AUTHOR INDEX

SHNAIDER, B. D.
Accelerations of points on a flight vehicle during short-period motion
A73-20095

SHORR, B. P.
A possible approach to the probabilistic estimation of the vibration strength of turbomachine components
A73-20502

SIMPSON, B. W.
Distributed control of air traffic.
A73-20600

SMALLY, R. D.
Computer-controlled software diagnosis of an airborne computer.
A73-20677

SOLOMONIAN, B. SH.
Nonstationary load distribution on an arbitrary-planform wing in supersonic motion
A73-21725

SPENCER, R.
An investigation of helicopter transmission noise reduction by vibration absorbers and damping
[AD-752579] N73-17031

SPEERLING, P.-G.
Advances in the design of electric three-phase machines for air and land vehicles
A73-20124

STABE, R. G.
Two-dimensional cascade test of a highly loaded, low-solidity, tandem airfoil turbine rotor blade
[NASA-TN-X-2729] N73-17814
Experimental investigation of aerodynamic performance of cooled turbine vanes at gas- to coolant-temperature ratios up to 2.75
[NASA-TN-X-2733] N73-17815

STALEY, T. K.
Highly loaded multi-stage fan drive turbine-cascade test program
[NASA-CR-2171] N73-16778

STANER, P.
Study of capabilities, necessary characteristics and effectiveness of pilot ground trainers.
Volume 1: Main text
[FAA-WA-72-102-VOL-1] N73-17221
Study of capabilities, necessary characteristics and effectiveness of pilot ground trainers.
Volume 2: Addendum, summary of flight instructors views
[FAA-WA-72-102-VOL-2-ADD] N73-17222

STANHOPE, A.
Welding airframe structures in titanium alloys using tensile loading as a means of overcoming distortion.
A73-21240

STENGEL, R. P.
Some effects of bias errors in redundant flight control systems
[NASA-CR-130354] N73-15998

STERNFELD, H.
An investigation of helicopter transmission noise reduction by vibration absorbers and damping
[AD-752579] N73-17031

STETSON, K. P.
Shock detachment from the leading edge of delta wings
[AD-752206] N73-17271

STONE, J. R.
Recent advances and applications in the prediction of pilot acceptance of aircraft flying qualities.
A73-20586

STORY, A. W.
System for indicating direction of intruder aircraft
[NASA-CASE-ERC-10226-1] N73-16483

STREETER, E.
Study of a highly reliable pilot's vertical display system
[AD-752510] N73-17026

SUD, I. K.
Modeling of a satellite airport system for large metropolitan areas: A systems analysis.
N73-16216

SULLIVAN, J. P.
Helicopter rotor wake geometry and airloads and helicopter rotor wakes
[AD-752628] N73-17032

SUPP, W. E.
Subsonic performance potential of ramjets and ejector ramjets
[AD-751317] N73-16781

SWALLOW, J. E.
Fabric properties and the wear of hovercraft fingers
[RAE-TR-71210] N73-17654

SWANN, B. M.
Welding airframe structures in titanium alloys using tensile loading as a means of overcoming distortion.
A73-21240

T
TABOR, F.
Air traffic control systems interference considerations
[ECAC-PR-72-008] N73-16629

TADA, S.
Aerodynamic characteristics of thin asymmetric wing profiles in supersonic flow
A73-20487

TATG, I. C.
Optimisation in construction of the Jaguar and other military aircraft.
A73-20947

TAYLOR, D.
Ejector design for a variety of applications
N73-17252

TAYLOR, L. S.
Distortion of near-sonic shocks by weakly turbulent layers
[AD-752472] N73-17279

TEITELBAUM, B. R.
Ultrasonic transmission investigations for turbine inlet gas temperature measurement
[AD-752602] N73-17822

THOMAS, H. H. B. H.
The role of theoretical studies of flight dynamics in relation to flight testing
N73-17011

THOMAS, M. W.
Highly loaded multi-stage fan drive turbine-cascade test program
[NASA-CR-2171] N73-16778

THORNE, R. G.
Pilot workload: A conceptual model
N73-17010

TIERCELIN, R.
Basic specification research for the main instruments of light aircraft
A73-20248

TONG, P.
The nonlinear instability in flap-lag of rotor blades in forward flight
[NASA-CR-114524] N73-17017

TUTTLE, J. H.
Emissions from and within an Allison J-33 combustor.
A73-20359

U

UDILOV, V. V.
Coordinate stabilization for a flexible aircraft during flight in a turbulent atmosphere
[AD-751148] N73-16028

UGGAR, E. E.
The status of engineering knowledge concerning the damping of built-up structures.
A73-19099

V

VOLBEIR, A. S.
Use of composite materials in aircraft structures
[NASA-TT-F-14648] N73-16576

VON GLAHN, U.
Acoustic results obtained with upper-surface-blowing lift-augmentation systems.
A73-20458

VOROB'EV, I. U. S.
Designing turbomachine blades for forced vibrations under various excitation conditions
A73-20503

VOROB'EV, N. F.
Discrete vortex scheme of a wing of finite span
A73-21611

W

WADA, W. T.
High performance helicopter hoist program
[AD-751217] N73-16029

WALSHAW, M. H.
Some UK military views on the development and
procurement of AIDS, BIT and ATE for avionics.
A73-20679

WALTERS, R. E.
Circulation control by steady and pulsed blowing
for a cambered elliptical airfoil
[AD-751045] N73-15992

WANG, C.-R.
System analysis of the air-ground transportation
interface problem at Bangkok International
Airport.
A73-20382

WARD, R. E.
Aeroplane design study STOL airliner (A71). Part
1: Configuration description and data
[CRANFIELD-AERO-12-PT-1] N73-17019

WARNE, D. P.
Superconducting a.c. machines - An approach to
development.
A73-20407

WARNER, N.
Generalize aerodynamic coefficient table storage,
checkout and interpolation for aircraft simulation
[NASA-TM-X-62229] N73-16983

WASSON, H. R.
V/STOL aircraft aerodynamic prediction methods
investigation. Volume 1: Theoretical
development of prediction methods
[AD-752557] N73-17033

V/STOL aircraft aerodynamic prediction methods
investigation. Volume 2: Application of
prediction methods
[AD-752558] N73-17034

V/STOL aircraft aerodynamic prediction methods
investigation. Volume 3: Manual for computer
programs
[AD-752559] N73-17035

V/STOL aircraft aerodynamic prediction methods
investigation. Volume 4: Literature survey
[AD-752563] N73-17036

WATERMAN, A. W.
Development and testing of improved polyimide
actuator rod seals at higher temperatures for
use in advanced aircraft hydraulic systems
[NASA-CR-121124] N73-17592

WATSON, K. A.
Subsonic performance potential of ramjets and
ejector ramjets
[AD-751317] N73-16781

WEAR, J. D.
Comparison of combustion characteristics of ASTM
A-1, propane, and natural-gas fuels in an
annular turbojet combustor
[NASA-TN-D-7135] N73-16771

WEAVER, J. V.
Advanced materials for aircraft brakes.
A73-21688

WEBB, H. H.
Study of V/STOL aircraft implementation. Volume
2: Appendices
[NASA-CR-114518] N73-16009

WEBB, H.
Fabric properties and the wear of hovercraft fingers
[BAE-TB-71210] N73-17654

WEISS, H. G.
Advanced electronic technology
[AD-751308] N73-16758

WEMPE, T.
A study on aircraft map display location and
orientation
[NASA-TM-X-62198] N73-17223

WEETS, W. E.
Ultrasonic transmission investigations for turbine
inlet gas temperature measurement
[AD-752602] N73-17822

WESTBROOK, C. B.
Mission effects on stability and maneuverability
N73-16995

WIDHALL, S.
The development of a wind tunnel facility for the
study of V/STOL noise
[AD-751857] N73-17235

WIGHTMAN, C. W.
Investigations of MLS conventional and Doppler
scanning beam techniques
[AG-5011-B-1] N73-16628

WILLIAMS, J. C.
Boundary-layer separation on rotating blades in
forward flight.
A73-19955

WILLIAMS, L. J.
Study of buoyancy systems for flight vehicles
[NASA-TM-X-62168] N73-17014

WITNER, E. A.
Approximate analysis of containment/deflection
ring responses to engine rotor fragment impact.
A73-19188

WOLOWICZ, C. H.
Flight test experience in aircraft parameter
identification
N73-17012

WOODWARD, R. P.
Low-frequency rear quadrant noise of a turbojet
engine with exhaust duct muffling
[NASA-TM-X-2718] N73-16011

WOOLER, P. T.
V/STOL aircraft aerodynamic prediction methods
investigation. Volume 1: Theoretical
development of prediction methods
[AD-752557] N73-17033

V/STOL aircraft aerodynamic prediction methods
investigation. Volume 2: Application of
prediction methods
[AD-752558] N73-17034

V/STOL aircraft aerodynamic prediction methods
investigation. Volume 3: Manual for computer
programs
[AD-752559] N73-17035

V/STOL aircraft aerodynamic prediction methods
investigation. Volume 4: Literature survey
[AD-752563] N73-17036

WOOTEN, D. C.
The effects of local meteorological factors upon
aircraft noise measurements
[FAA-RD-72-145] N73-16651

WORMLEY, D. H.
Nonlinear and finite pad length performance of
vehicle air cushion suspensions
[PB-212705] N73-16226

WU, R. W.-H.
Approximate analysis of containment/deflection
ring responses to engine rotor fragment impact.
A73-19188

Y

YADAO, K. L.
Aerodynamic experimental investigation of annular
cascade of gas turbine nozzle blade in subsonic
and supersonic flow.
A73-20939

YAPPEE, M. L.
Earlier programs spawned TP34.
A73-20350

YOUNG, P. H.
Olympus in Concorde /Twenty-fifth Louis Bleriot
Lecture/.
A73-21687

YOUNG, P. S.
Predicting light flashes due to alpha-particle
flux on SST planes.
A73-20157

YOUNG, W. H., JR.
Boundary-layer separation on rotating blades in
forward flight.
A73-19955

Z

ZALOSH, R. G.
Godunov method and computer program to determine
the pressure and flow field associated with a
sonic boom focus
[NASA-CR-2127] N73-16013

ZIEGLER, H.
V/STOL aircraft aerodynamic prediction methods
investigation. Volume 1: Theoretical
development of prediction methods
[AD-752557] N73-17033

ZINGG, D. J.

PERSONAL AUTHOR INDEX

V/STOL aircraft aerodynamic prediction methods
investigation. Volume 2: Application of
prediction methods
[AD-752558] N73-17034

V/STOL aircraft aerodynamic prediction methods
investigation. Volume 3: Manual for computer
programs
[AD-752559] N73-17035

V/STOL aircraft aerodynamic prediction methods
investigation. Volume 4: Literature survey
[AD-752563] N73-17036

ZINGG, D. J.

Extension of the VAST software system.
A73-20688

ZOZULIA, V. B.


Measurement of the pressure distribution at the
surface of an aerodynamic body using a special
interrogator.
A73-21180

CONTRACT NUMBER INDEX

AERONAUTICAL ENGINEERING / A Special Bibliography (Suppl. 31)

MAY 1973

Typical Contract Number Index Listing



Listings in this index are arranged alphanumerically by contract number. Under each contract number, the accession numbers denoting documents that have been produced as a result of research done under that contract are arranged in ascending order with the IAA accession numbers appearing first. The accession number denotes the number by which the citation is identified in either the IAA or STAR section.

AF PROJ. 69BT
N73-16274
AF PROJ. 324A
N73-17024
AF PROJ. 649
N73-17178
AF PROJ. 649L
N73-16758
N73-17170
AF PROJ. 698BT
N73-17033
N73-17034
N73-17035
N73-17036
AF PROJ. 1367
N73-17030
AF PROJ. 1476
N73-16784
N73-16785
AF PROJ. 3012
N73-16781
AF PROJ. 3066
N73-17803
N73-17822
AF PROJ. 4510
N73-16634
AF PROJ. 6111A
N73-17233
AF PROJ. 7065
N73-17271
AF PROJ. 8219
N73-17021
AF PROJ. 9778
N73-16026
AF PROJ. 9782
N73-15991
AF PROJ. 9783
N73-17278
AF-AFOSR-2167-72
N73-15991
ARO PROJ. BD5026
N73-16274
ARO PROJ. PW5284
N73-16023
C13CA-136
N73-16222
DA PROJ. 1F1-62204-A-142
N73-17031
DA PROJ. 1G1-62203-D-144
N73-17046
DA PROJ. 1G6-64717-D-H01
N73-17233
DA PROJ. 1H1-62202-A-219
N73-16021
N73-16022
DA-ARO (D) -31-124-71-G153
A73-19954
DA-28-043-AHC-02412 (B)
N73-16021
N73-16022
DAAD05-72-C-0099
N73-16029
DAAE07-69-C-0756
A73-20359
A73-21670
DAAJ02-69-C-0086
A73-19955

DAAJ02-70-C-0048
N73-17046
DAAJ02-71-C-0020
N73-17031
DAH04-69-C-0086
N73-17235
DAH04-71-C-0048
N73-16027
DOT-FA70NA-506
N73-17221
N73-17222
DOT-FA70WAI-175
N73-16629
N73-16630
DOT-FA71WA-2592
N73-16628
DOT-FA73WI-0382-1
N73-16651
DOT-FR-10007
N73-16226
DOT-OS-320
N73-16612
DOT-OS-00083
A73-21837
DOT-TSC-188
N73-16020
DOT-UT-262
N73-16978
EPA-68-04-0001
A73-20359
FAA PROJ. 181-522-01X
N73-16772
FAA PROJ. 213-503-015
N73-16630
FAA PROJ. 213-516-035
N73-16629
F19628-71-C-0002
N73-16634
F19628-73-C-0002
N73-16758
N73-17170
N73-17178
F29601-70-C-0076
N73-17168
F33615-69-C-1602
N73-17033
N73-17034
N73-17035
N73-17036
F33615-71-C-1184
N73-17822
F33615-71-C-1208
N73-16784
N73-16785
F33615-71-C-1575
N73-17803
F33615-71-C-1663
A73-19097
F33657-70-D-1161
N73-17025
F33657-71-C-0662
N73-17025
F40600-69-C-0001
N73-17252
F40600-73-C-0004
N73-16023
N73-16274
F44620-71-C-0121
N73-17278
F44620-72-C-0006
N73-16026

MIT PROJ. DSR-73032
N73-17032
N00264-72-C-0094
N73-17694
NASA ORDER R-03-038-002
A73-21710
NASW-2481
N73-17710
NASW-2483
N73-16576
N73-17259
NAS1-8858
N73-17900
NAS1-9557-17
A73-19099
NAS1-10276
N73-16013
NAS1-10627
N73-16982
NAS1-11566
N73-17258
NAS2-4151
A73-19191
NAS2-5052
A73-19189
NAS2-5719
A73-19189
NAS2-6175
N73-16015
N73-17017
NAS2-6473
N73-16009
NAS3-11159
N73-17916
NAS3-13205
N73-17809
N73-17810
NAS3-14304
N73-16778
NAS3-14409
N73-16524
NAS3-16733
N73-17592
NAS9-10268
N73-15998
NAVY TASK J-15090
A73-19964
NGL-48-002-010
N73-15986
NGR-05-004-051
N73-16988
NGR-14-005-144
A73-19956
NGR-22-009-339
A73-19188
NGR-41-001-027
A73-19952
NOL PROJ. 324/FAA
N73-17279
NR PROJ. 215-163
N73-15992
NR PROJ. 215-173
N73-16748
NR PROJ. 215-189
N73-16283
NR PROJ. 215-190
N73-16635
N00014-68-A-0512
N73-15992
N00014-71-C-0250
N73-16283
N00014-71-C-0258
N73-16635
N00014-71-C-0262
N73-16748
N00019-71-C-0220
N73-17032
N62269-71-C-0510
N73-17026
PROJ. 502-103-10X
N73-17221
N73-17222
USAAVSCOM PROJ. 70-17
N73-16514
136-13-08-00-24
N73-16008
501-04
N73-16011
N73-16654
501-22-04-01
N73-16905
501-24
N73-16771
N73-16773
N73-16776
N73-16929
N73-16986
N73-17814
N73-17815
N73-17817
N73-17921
N73-17991
501-26-01-00-24
N73-16010
501-98-01-00-24
N73-16247

503-35
N73-17039
721-04-00-01-00
N73-17015
760-60-01-01
N73-16012
760-61-02-81-23
N73-15986
760-74-04-02
N73-17020

1. Report No. NASA SP-7037 (31)		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle AERONAUTICAL ENGINEERING A Special Bibliography (Supplement 31)				5. Report Date May 1973	
				6. Performing Organization Code	
7. Author(s)				8. Performing Organization Report No.	
9. Performing Organization Name and Address National Aeronautics and Space Administration Washington, D.C. 20546				10. Work Unit No.	
				11. Contract or Grant No.	
12. Sponsoring Agency Name and Address				13. Type of Report and Period Covered	
				14. Sponsoring Agency Code	
15. Supplementary Notes					
16. Abstract <p>This special bibliography lists 307 reports, articles, and other documents introduced into the NASA scientific and technical information system in April 1973.</p>					
17. Key Words (Suggested by Author(s)) Aerodynamics Aeronautical Engineering Aeronautics Bibliographies				18. Distribution Statement Unclassified - Unlimited	
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		21. No. of Pages 99	
				22. Price* \$3.00	

* For sale by the National Technical Information Service, Springfield, Virginia 22151

PUBLIC COLLECTIONS OF NASA DOCUMENTS

DOMESTIC

NASA deposits its technical documents and bibliographic tools in eleven special regional libraries located in the organizations listed below. Each library is prepared to furnish the public such services as reference assistance, interlibrary loans, photocopy service, and assistance in obtaining copies of NASA documents for retention.

CALIFORNIA

University of California, Berkeley

COLORADO

University of Colorado, Boulder

DISTRICT OF COLUMBIA

Library of Congress

GEORGIA

Georgia Institute of Technology, Atlanta

ILLINOIS

The John Crerar Library, Chicago

MASSACHUSETTS

Massachusetts Institute of Technology, Cambridge

MISSOURI

Linda Hall Library, Kansas City

NEW YORK

Columbia University, New York

PENNSYLVANIA

Carnegie Library of Pittsburgh

WASHINGTON

University of Washington, Seattle

NASA publications (those indicated by an "*" following the accession number) are also received by the following public and free libraries:

CALIFORNIA

Los Angeles Public Library

San Diego Public Library

COLORADO

Denver Public Library

CONNECTICUT

Hartford Public Library

MARYLAND

Enoch Pratt Free Library, Baltimore

MASSACHUSETTS

Boston Public Library

MICHIGAN

Detroit Public Library

MINNESOTA

Minneapolis Public Library

MISSOURI

Kansas City Public Library

St. Louis Public Library

NEW JERSEY

Trenton Public Library

NEW YORK

Brooklyn Public Library

Buffalo and Erie County Public Library

Rochester Public Library

New York Public Library

OHIO

Akron Public Library

Cincinnati Public Library

Cleveland Public Library

Dayton Public Library

Toledo Public Library

OKLAHOMA

Oklahoma County Libraries, Oklahoma City

TENNESSEE

Memphis Public Library

TEXAS

Dallas Public Library

Fort Worth Public Library

WASHINGTON

Seattle Public Library

WISCONSIN

Milwaukee Public Library

An extensive collection of NASA and NASA-sponsored documents and aerospace publications available to the public for reference purposes is maintained by the American Institute of Aeronautics and Astronautics, Technical Information Service, 750 Third Avenue, New York, New York 10017.

EUROPEAN

An extensive collection of NASA and NASA-sponsored publications is maintained by the National Lending Library for Science and Technology, Boston Spa, Yorkshire, England. By virtue of arrangements other than with NASA, the National Lending Library also has available many of the non-NASA publications cited in *STAR*. European requesters may purchase facsimile copy or microfiche of NASA and NASA-sponsored documents, those identified by both the symbols "*" and "#", from: ESRO/ELDO Space Documentation Service, European Space Research Organization, 114, av. Charles de Gaulle, 92-Neuilly-sur-Seine, France.



POSTMASTER: If Undeliverable (Section 158
Postal Manual) Do Not Return

"The aeronautical and space activities of the United States shall be conducted so as to contribute . . . to the expansion of human knowledge of phenomena in the atmosphere and space. The Administration shall provide for the widest practicable and appropriate dissemination of information concerning its activities and the results thereof."

—NATIONAL AERONAUTICS AND SPACE ACT OF 1958

NASA SCIENTIFIC AND TECHNICAL PUBLICATIONS

TECHNICAL REPORTS: Scientific and technical information considered important, complete, and a lasting contribution to existing knowledge.

TECHNICAL NOTES: Information less broad in scope but nevertheless of importance as a contribution to existing knowledge.

TECHNICAL MEMORANDUMS: Information receiving limited distribution because of preliminary data, security classification, or other reasons. Also includes conference proceedings with either limited or unlimited distribution.

CONTRACTOR REPORTS: Scientific and technical information generated under a NASA contract or grant and considered an important contribution to existing knowledge.

TECHNICAL TRANSLATIONS: Information published in a foreign language considered to merit NASA distribution in English.

SPECIAL PUBLICATIONS: Information derived from or of value to NASA activities. Publications include final reports of major projects, monographs, data compilations, handbooks, sourcebooks, and special bibliographies.

TECHNOLOGY UTILIZATION PUBLICATIONS: Information on technology used by NASA that may be of particular interest in commercial and other non-aerospace applications. Publications include Tech Briefs, Technology Utilization Reports and Technology Surveys.

Details on the availability of these publications may be obtained from:

SCIENTIFIC AND TECHNICAL INFORMATION OFFICE

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
Washington, D.C. 20546